MICROCOPY RESOLUTION TEST CHART

NATIONAL BUREAU OF STANDARDS-1963-A

AD-A134 293

AVIATION OFFICER REQUIREMENTS STUDY

PHASE II: FINAL REPORT

This document has been approved
for public release and sale; its
distribution is unlimited.

DTIC

NOV 2 1983

A

83 10 31 016

■⌁ INFORMATION SPECTRUM, INC.

1745 S. JEFFERSON DAVIS HIGHWAY, ARLINGTON, VIRGINIA 22202   (703) 892-9000

AVIATION OFFICER REQUIREMENTS STUDY

PHASE II: FINAL REPORT

Contract No. N00014-81-C-0368

ISI Report No. V-83-2693-02
Project No. 1894

August 31, 1983

Prepared by:
Francis E. O'Connor
Reviewed by:
Alfred S. Rhode, Ph.D.

Prepared for:
Program Director, Operations Research
Mathematical & Information Sciences Division
Office of Naval Research
800 North Quincy Street
Arlington, Virginia 22217

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM	
1. REPORT NUMBER V-2693-02	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Aviation Officer Requirements Study PHASE II: FINAL REPORT		5. TYPE OF REPORT & PERIOD COVERED Final Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) F. E. O'Connor		8. CONTRACT OR GRANT NUMBER(s) N00014-81-C-0368
9. PERFORMING ORGANIZATION NAME AND ADDRESS Information Spectrum, Inc. 1745 Jefferson Davis Highway Arlington, Virginia 22202		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NR156-078
11. CONTROLLING OFFICE NAME AND ADDRESS Program Director, Operations Research Mathematical & Information Sciences Division Office of Naval Research 800 North Quincy St, Arlington, VA 22217		12. REPORT DATE 31 August 1982
		13. NUMBER OF PAGES 251
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Distribution of this document is unlimited. Reproduction in whole or in part is permitted for any purpose of the United States Government.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

Same

18. SUPPLEMENTARY NOTES

Supported by Office of Naval Research, Manpower R&D Program

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Officer Requirements
Retention
Career Path Analysis

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

A model is presented which develops Aviation Officer Requirements at the sub-community level within the constraints imposed by a network of permissible career paths specified by the user. The model is currently implemented in a WANG 2200 VS computer in a 'User-Friendly' interactive mode. The user can quickly make multiple runs, varying a number of parameters, to test the implications of various policy alternatives on Aviation Officer Requirements. Demonstration of model application and a model user's guide are included.

DD FORM 1473 EDITION OF 1 NOV 68 IS OBSOLETE
1 JAN 73
S/N 0102-LF-014-6601

CONTENTS

i

LIST OF TABLES

LIST OF FIGURES

I. INTRODUCTION

In spite of recent recruiting and retention success, Navy manpower managers face an increasingly difficult task in the next decade. A recovering economy will demand a greater share of the labor force. Demand will be particularly strong for personnel in those high technology skills which the Navy has the most difficulty in retaining. At the same time, the expansion of the fleet will require significant additional skilled manpower. The Navy's training establishment will be forced to expand to accommodate a larger Navy, and this will require additional increments of skilled manpower to staff the school system. Add to these considerations the decline in the 18-24 year old age group from which the Navy draws most new accessions, and the dimensions of the problem become apparent. It seems clear that frequent shortages of skilled manpower are likely to occur; that the cost of obtaining and retaining personnel is likely to rise; and that the process of Planning, Programming, and Budgeting for military manpower requirements and the management of the resulting inventory will be more complex and difficult than at any time in the past.

No group better exemplifies the scope of the problems identified above than Aviation Officers. Naval Aviator and Naval Flight Officer (NFO) retention is up. In addition to general economic conditions, the competitive effects of airline deregulation have had a direct impact on job opportunities for pilots. Airline mergers and a number of airline failures have inflated the rolls of furloughed pilots and created uncertainty regarding the degree of job security attached to a career as an airline pilot. In addition, a substantial Aviation Officer bonus has served as a positive inducement to young officers to remain in the Navy.

1

The improvements in Aviation Officer retention could not have come at a more fortuitous time. The force level expansion implied by a 600-ship Navy and the proliferation of ship types capable of supporting aircraft demand substantial increases in the number of Aviation Officers. At the same time, the large budget increments required to procure additional hardware and support for the expanded fleet militate against the added procurement required to replace and modernize an ageing training plant. In addition, recent increases in energy and manpower costs have dramatically raised the overall cost of providing Aviation Officers for the fleet. High retention reduces the number of new accessions required to replace officers who would otherwise leave the Navy. This, in turn, reduces training costs, relieving some of the fiscal stresses accompanying the force level expansion.

The benefits realized from the current high retention of Aviation Officers are not without a long term price. While force level expansion can be supported without any significant increase in training rates, the long term effect of this strategy is to distort the Aviation Officer inventory. In effect, relatively senior lieutenants (5-7 years of service) are being substituted for new accessions. In relative terms, a "hump" is being created at the senior lieutenant level, and a corresponding valley is being created in the more junior years of experience. While this distortion can be easily accommodated at the lieutenant level, it can be predicted that significant personnel management problems will arise as the inventory ages. As the hump and the following valley move through the senior command years, there first will be a surplus of officers eligible to fill senior positions, followed about five years later by a deficit.

2

In addition to the long term impact cited above, it should be recognized that current high levels of retention are unlikely to be sustained. As the economy improves, airline demand for pilots will revive. The revival is likely to be particularly robust as large numbers of senior pilots who entered airline service in the early 1950s reach mandatory retirement age. Thus the "valley" behind the current retention hump is likely to be deep--the result of low accessions compounded by low retention.

While the potential problems identified above are fundamentally personnel management issues, a great deal can be done to ameliorate the severity of their impact during the manpower planning process. Manpower planning defines requirements and identifies the course of action necessary to create an inventory to meet those requirements. Unfortunately, planners lack the analytic tools necessary to identify a preferred course of action. A large number of variables must be considered, the time available for manpower planning is short, and the number of planning iterations is likely to be large. The analytic procedures employed are rudimentary and are focused on near term requirements.

This report describes a more sophisticated tool that has been designed specifically to support the manpower planning process. In the following sections, the overall planning process will be described with particular emphasis on the difficulties faced by manpower planners. Following this, the general requirements for a manpower model suitable for the planning process will be identified. The specifics of the Aviation Officer Requirements Model will then be presented. Finally, the utility of the model will be demonstrated by presenting the results of a number of typical applications.

3

II. BACKGROUND - THE PLANNING PROCESS

It is logical to begin this discussion with a brief review of the essential elements of the planning process by which military manpower requirements in general, and Aviation Officer requirements in particular, are met. As with all resource requirements, manpower planning takes place within the context of the Defense Planning Programming and Budgeting System (PPBS). The fundamental objective of the PPBS is to produce the Five Year Defense Plan (FYDP), which is the basis for the resource requests for the Department of Defense contained in the President's annual budget submission to the Congress.

The PPBS process begins approximately 27 months prior to the beginning of the fiscal year corresponding to the first year of the FYDP which is the planning objective. (In the case of manpower, the first year is the only year actually authorized and funded.) Force levels drive manpower requirements. Therefore, manpower planners must constantly revise their plans in response to changes in force structure and adjustments to weapon system acquisition schedules. Such changes and adjustments are frequent during the planning process within DOD. In the subsequent authorization and appropriation process before the Congress, further changes occur. Ideally, the Military Personnel-Navy (MPN) Authorization and Budget should exactly support the fleet and shore establishment authorized by the Congress; that is, provision should be made for the skills and grade levels required to man and support the fleet. In reality, the result is only an approximation of requirements.

Manpower planners face a number of difficulties in establishing manpower requirements in the dynamic environment of the PPBS. Among these are the following:

- **The need to adjust requirements to constantly changing force level decisions.** This includes the adjustment of direct requirements and such indirect requirements as training staff, student billets, and other indirect support personnel. In addition, adjustments must be made within an overall end strength constraint.

- **The need to adjust certain requirements to meet current personnel deficiencies.** To the extent that current inventories fail to meet skill and grade level requirements, recruiting and training manpower resources must be provided to acquire and train additional increments of personnel.

- **The requirement to manage three different budgets simultaneously.** Because of the long planning lead time, manpower managers are constantly concerned with execution of the budget for the current fiscal year, defending the budget for the next fiscal year during the congressional budget process, and developing the budget for the following year. These three budgets are not independe t of one another. In general changes in one mandate changes to the r two.

- **The fact that the personnel inventory is created and s ined by accessions at the lowest skill and experience levels.** Thi ans that changes in manpower requirements at any skill or experienc vel must ultimately be reflected in accession requirements. C ently, almost any change in manpower requirements can have a ificant impact on a broad range of manpower and personnel management issues: promotion planning, skill conversion policy, specialized training requirements, and manning priorities, to name a few.

- **The existence of significant uncertainty regarding the future state of personnel inventories.** Direct manpower requirements are established by force levels. However, incremental requirements at a point in the future are a function of the difference between overall manpower requirements and the personnel inventory that will result from the ageing of the current inventory. The inventory ageing process is influenced by both endogenous factors associated with personnel management actions and exogenous factors relating to political, social, and economic forces operating at national and international levels. The determination of the impact of these factors on the parameters that describe the inventory ageing process--retention, attrition, and retirements--is an art, not a science.

In the face of the difficulties described above, the manpower planner necessarily has a multiplicity of planning objectives. These can be categorized in terms of the planning horizon in which they are operative:

- **In the short term**, defined by the planning process itself, the planner must meet requirements. This may mean reducing requirements or reallocating resources among competing claimants. In general, the process is reactive, responding to real-time crises associated with the current

fiscal year budget, or short-fused threats to near-term fiscal year budgets which are constantly being raised in the Defense bureaucracy or in the Congress.

- In the intermediate term, defined by the later years in the FYDP, the planner should adjust requirements statements to reflect the realities of the current budget cycle and changing conditions in the personnel inventory and the external environment. As it becomes clear that current trends in force levels, personnel retention, or general economic conditions differ from initial planning assumptions, adjustments to the outyears of the FYDP should be made.

- In the longer term, beyond the FYDP, the planner should be aware of the long term impact of his decisions. Personnel acquired today in response to changing requirements will be in the Navy well beyond the FYDP timeframe. The expected service life of an Aviation Officer is about 10 years, and significant numbers remain for 30 years.

The most severe personnel management problems involving Aviation Officers today are concerned with surpluses or shortages of personnel with between 12 and 16 years of service. The accessions that established these inventory year groups occurred between 1968 and 1972. Since that time, force level changes, added missions, and variations in Aviation Officer retention have combined to create severe mismatches in several subcommunities between LCDR/CDR requirements and the inventory of officers available to fill these requirements. While such mismatches could probably not be avoided altogether, there were alternative accession plans available in 1968-1972 that would have significantly reduced the magnitude of current problems. Unfortunately, the manpower planner has very little time to devote to analysis of the long term impact of his decision within the context of the PPBS. The analytic tools available do not permit any extended assessment of these impacts.

The planner must obviously meet immediate requirements. Therefore, the short term planning objectives dominate the planning process. Given a

6 .

mismatch between inventory and requirements, the manpower planner must incre-
ment or decrement accessions even if the mismatches occur in senior grades.
In effect, he seeks quantitative balance under the implicit assumption that
qualitative matches will be made through application of appropriate training
and/or personnel management policies. There are two major problems that can
arise under this approach:

- Resources required to implement future changes in training or personnel
  management policies are left undefined. There is no assurance that
  they will be provided.

- Personnel management policies affect retention. To the extent that
  they are perceived to be inimical to the individual's career objec-
  tives, retention can be expected to decline. Thus, the manpower
  planner can heavily influence one of the principal variables affecting
  the inventory projections used in the planning process. However, these
  effects are difficult to exploit in the planning process because they
  lie beyond the immediate planning horizon.

While the focus of manpower planners on immediate requirements is una-
voidable, it is reasonable to suggest that a significant consideration in
selecting among competing short term courses of action would be the assessment
of the long term impacts of those courses of action. Unfortunately, such
assessments are difficult with currently available planning tools. What is
needed is a simple planning model that does the following:

- Establishes the long term context of requirements determination as an
  inventory building process. The ultimate objective is to achieve the
  "proper" match of inventory with stated requirements.

- Accounts for personnel management policies that constrain the applica-
  tion of inventory to requirements; that is, the model must go beyond
  simple quantitive measures of inventory and address qualitative factors
  such as skill and experience levels.

- Incorporates a consistent set of the variables and parameters used to
  describe both requirements and inventory. While the user may be pri-
  marily concerned with a few variables in the set, he needs the
  assurance that manipulation of these variables occurs in a context
  which maintains consistency over the entire set.

- Permits rapid iteration to permit evaluation of alternative strategies
  and parametric analysis of the impact of key variables such as reten-
  tion.

7

- Provides outputs which identify requirements in terms of both skill and experience mix.

- Defines accession requirements to support the personnel inventory.

The Aviation Officer Requiremen Model, described in the following sections of this report, is a planning model intended for application in the determination of Aviation Officer requirements in the PPBS. It meets all of the above criteria.

III. MODEL DESCRIPTION

A. GENERAL DESCRIPTION

The Aviation Officer Requirements Model was described in a previous report[1]/ of this study. That description provided an exposition of the structure of the model, an analysis of model parameters, and a discussion of potential solution procedures. A computer program that implemented one solution procedure was also described.

The discussion which follows presents the model structure from a slightly different perspective in an effort to demonstrate how the criteria enumerated at the end of Section II are satisfied. In the interest of brevity, unnecessary repetition of material from the previous report is avoided. The reader who is interested in a detailed description of model parameters, their derivation, and the functional relationships among them should refer to that report.

In general, the Aviation Officer Requirements Model meets the effectiveness criteria proposed in Section I in three ways:

- Requirements Specification. Requirements are specified in a way that accounts for both the skill and experience level needed in billet incumbents.

- Inventory Specification. The inventory is defined in a way that is directly related to requirements. Accession levels and the inventory ageing process are specified.

- Personnel Management Policies. Personnel Management is the process by which inventory is matched to requirements. Policies imply rules for assigning officers. Rules imply constraints in the application of inventory to meet requirements. Thus an inventory which is numerically equal to requirements may not in fact meet requirements. The Aviation Officer Requirements model accounts for these constraints.

_____

1/F.E. O'Connor, Aviation Officer Requirements Study, ISI Report No. V-2693-01, (Information Spectrum, Inc., Arlington, VA, 22202, 31 May 1982).

9

The implementation of each of these three facets of the Aviation Officer requirements model is discussed in detail below.

B. REQUIREMENTS SPECIFICATION

The concept of manpower requirements implies number, skill, and experience; that is, the Navy needs a certain number of Aviation Officers who can operate particular kinds of weapon systems, and—given that the level of proficiency will vary—experience criteria are specified. Thus the Navy might specify that it needs 50 Naval Aviators who are fighter pilots with at least 15 years of experience in order to provide commanding officers for fighter squadrons. Alternatively, the experience specification might require that the 50 Naval Aviators have reached the grade of Commander.

Aviation Officer Requirements are implicitly partitioned in at least three dimensions:

- By General Specialty - Naval Aviators or Naval Flight Officers. Naval Aviators are trained to pilot aircraft and control essential aircraft systems. Naval Flight Officers are trained to operate sensor systems, manage tactical display and analysis systems, and navigate the aircraft.

- By Generic Weapon System Type. A number of platform or system characteristics operate to require significantly different skills of weapon system operators. Specific missions also differ in training or experience requirements. Major differences in skill requirements exist for:

  - Fixed Wing vs. Rotary Wing Aircraft
  - Ship Based vs. Shore Based Aircraft

  Similar differences exist with respect to primary aircraft mission. Thus aircraft with an Anti-Submarine Warfare (ASW) mission differ from aircraft with an Anti-Air Warfare (AAW) mission in the demands placed on the Naval Aviators and Naval Flight Officers that operate them.

- By Grade Level. Three distinct levels of experience can be identified as required of Aviation Officers in Units which are responsible for the operation of aircraft. These levels can be classified by grade level:

10

Lieutenant and Below - The Operating Level
Lieutenant Commander - The Department Head Level
Commander   - The Command Level

While this division is given in organizational administrative terms, the distinctions between the groups carry over to tactical supervision and training responsibilities.

The basic structure of the Aviation Officer Requirements model is established by partitioning the total Aviation Officer requirement along the lines outlined above. The resulting groupings are referred to as subcommunities. The current subcommunities residing within the Model are given in Table I.

TABLE I

AVIATION OFFICER SUBCOMMUNITIES

SUBCOMMUNITY (SYMBOL)	PRIMARY MISSION	CURRENT A/C TYPE	CURRENT SQUADRONS	INCLUDES	
				NA	NFO
Light Attack (VA)	AGW	A7/A18	24	X	-
Fighter (VF)	AAW	F4/F14/F18	24	X	X
Medium Attack (VAM)	AGW	A6	12	X	X
Air Early Warning (VAW)	AAW	E2C	12	X	X
Tactical Electronic Warfare (VAQ)	EW	EA6	9	X	X
Carrier Based (VS)	ASW	S3	11	X	X
Anti Sub Warfare Helicopter ASW (HS)	ASW	SH3/SH60	11	X	-
Light Airborne Multi-Purpose System (HSL)	ASW	SH2/SH6	14	X	-
Maritime Patrol (VP)	ASW	P3	24	X	X
Electronic Warforce (VQ)	EW	EA3, EP3	2	X	X
Force Support, Jet (VR, VC)	SUPPORT	C9, C2, A4	13	X	X
Force Support, Prop. (VQ)	SUPPORT	EC130	2	X	X
Force Support, Helo. (HC, HM)	SUPPORT	N47, N53	8	X	-

AGW - Air to Ground Warfare
AAW - Anti Air Warfare
EW - Electronic Warfare
ASW - Anti Submarine Warfare

X indicates NA/NFO's required in Subcommunity
- indicates NFO's not required in Subcommunity

11

Within each subcommunity, requirements are further partitioned by the grade level of the requirement. Four grade levels have been established:

- LT and Below
- LCDR
- CDR
- Senior Commander

The fourth category, Senior Commander, was established when it became apparent that significant numbers of billets require commanders who have had experience as commanding officers. The model identifies senior commanders in the inventory as commanders with more than three years in grade.

The division of Aviation Officer requirements into subcommunities based on weapon system characteristics has the important advantage of providing a direct connection between force levels and Aviation Officer requirements. Force level decisions during the planning process affecting the number of aircraft or the number of Aviation Squadrons can dramatically influence the number of Aviation Officers required. Recomputation of these manpower requirements in response to force level changes involves adjustments to both direct squadron requirements and certain indirect requirements, such as manpower required to train personnel to meet direct requirements. In the dynamics of the planning process, when potential force level changes are frequent, these computations are tedious and subject to error. Since force level changes are easily related to a subcommunity or group of subcommunities, it is possible to express subcommunity related manpower changes as a function of force level changes. In general manpower changes are given by:

(1) $\Delta MP = \Delta NS \times AC \times CF \times NC + AF \times IN$

Where

ΔMP = Change in Manpower Requirement
ΔNS = Change in Number of Subcommunity Squadrons
AC = Number of Aircraft per Squadron
CF = Crew Factor – Number of Crews Required per Assigned Aircraft
NC = Number of Naval Aviators or NFOs Required per Crew.
AF = Annual Training Flow required to Support ΔMP
IN = Number of Instructors Required to Produce the Required Annual flow.

The first term on the right relates to the direct squadron requirements, while the second refers to indirect requirements. These functional relationships are incorporated in the Aviation Officer Requirements Model. User specification of force level changes causes an automatic recomputation of manpower requirements for affected subcommunities. In addition, the user can alter any or all of the parameters specified on the right hand side of the equation so that analysis of their impact on manpower requirements at a given force level is also possible.

While establishing the force level dependence of Aviation Officer requirements is crucially important to the creation of a successful planning model, it should be pointed out that force level dependent manpower requirements represent only a fraction of the total requirement for Aviation Officers. In the previous report of this study[2] an analysis of the then current requirements was presented which attributes about 62 percent of total Aviation Officer requirements to operating squadrons and associated indirect support (principally training). The remaining 38 percent of requirements are associated with the operation of the shore establishment of the Navy or major

---

[2]/Ibid., p. 14.

13.

staffs ashore. Since these requirements are not directly related to force levels, they are included in the subcommunity-based requirements statement by means of an allocation process which is described below.

The principal problem in establishing an allocation procedure for requirements which are not specific to the defined subcommunities is the definition of a basis for allocation that will result in "fair sharing" of these requirements among subcommunities. Depending on the nature of the requirement, it may be preferable to allocate indirect requirements based on the ratio of direct subcommunity requirements to:

- Total Direct Naval Aviator Requirements
- Total Direct Naval Flight Officer Requirements
- Total Direct Aviation Officer Requirements

Additionally, for certain training requirements it is more appropriate to base allocation on annual graduate flows rather than on total requirements.

The Aviation Officer Requirements Model partitions the total requirement into Activities, which classify billet requirements in terms of the general purpose which the requirement is supporting. For activities where allocation is necessary, the appropriate allocation basis is established. Seven activities, described in Table II, are defined. The allocation method used with each activity is also identified in the Table.

It will be noted that the first four activities in Table II involve requirements for which frequent flights are required. The last three do not. This effectively segregates billets coded for Duty Involving Flying (DIF) within the requirements structure. This in turn makes it possible to examine

14

TABLE II

DEFINITION OF ACTIVITIES FOR
AVIATION OFFICER REQUIREMENTS MODEL

	ACTIVITY	DESCRIPTION	ALLOCATION METHOD
1.	Force and Force Support Squadrons	Naval Aviators or Naval Flight Officers are required for the operation and control of air weapon systems in tactical units.	Direct requirements.
2.	Fleet Readiness Squadrons	Naval Aviators or Naval Flight Officers are required to train others in the operation and control of air weapon systems within a subcommunity.	Based on annual flow of graduates within the sub-community. Force level driven.
3.	Training Command Squadrons	Naval Aviators or Naval Flight Officers are required to provide entry level training for student Naval Aviators and student Naval Flight Officers.	Based on annual flow of graduates to the subcommunity. Indirectly driven by force levels.
4.	RDT&E	Naval Aviators or Naval Flight Officers are required for experimental, developmental, or test and evaluation of air weapon systems.	Based on general Aviation Officer skills required (Helicopter Pilot, Navigator, etc.). Allocation only to Subcommunities possessing required skills.
5.	Afloat (ships company and afloat staffs	Naval Aviators or Naval Flight Officers are required to supply aviation experience in the operation of air-capable ships or as members of afloat staffs.	Based on total Aviation Officer, total Naval Aviator, or total Naval Flight Officer requirements in Force and Force Support Squadrons.
6.	Professional Development (PG School/War	Naval Aviators or Naval Flight Officers are required to receive advanced education as part of the large effort to enhance the technical competence and managerial skills of the officer corps.	Based on total subcommunity requirements.
7.	Other	Naval Aviators or Naval Flight Officers are required to provide aviation experience in the shore stations and on major staffs ashore.	Based on total Aviation Officer requirements.

15

the influence of planning decisions on the levels of operational flight experience in terms consistent with the requirements of the Aviation Career Incentive Pay Act.3/

In summary, the Aviation Officer Requirements Model specifies requirements by:

- Dividing the total Aviation Officer requirement into subcommunities based on specialty (Naval Aviator or Naval Flight Officer) and on Weapon System/Mission (Fighter, Helicopter ASW). The resulting set contains 14 Naval Aviator subcommunities and 9 Naval Flight Officer subcommunities.

- Dividing requirements within each subcommunity based on grade level and activity. Four grade levels and seven activities are defined.

The subcommunity design is mutually exclusive and exhaustive; that is, the sum of the requirements in the 23 subcommunities equals the total Aviation Officer requirement and each individual billet specification is represented in only one subcommunity. Given the design, the objective of the manpower planning process becomes the creation of a set subcommunity inventories that meet the requirement in detail.

C. INVENTORY SPECIFICATION

The essential elements required to describe the Aviation Officer Inventory are the specification of gains or losses and the mechanism used to describe the evolution of the inventory over time.

3/Ibid., pp. 6-8.

Gains to the Aviation Officer inventory come only by means of graduation from initial entry training and designation as either a Naval Aviator or Naval Flight Officer. Time of designation is the reference point for inventory ageing. Individuals in the inventory have a chronological age expressed in years of aviation service measured from designation. Annual cohorts are identified as Aviation Year Groups, consisting of all officers designated in a given fiscal year. Gains to inventory, or accessions, are the total number of fiscal year graduates from undergraduate flight training. The size of the first year cohort is taken as equal to accessions minus losses in the first year. The size of the cohort in the nth year of aviation service is the number of aviation officers remaining at year n-1 less losses in year N.

The Aviation Officer Requirements Model assumes that losses in a given year are uniformly distributed throughout the year. A further assumption is made that for substantial periods of time during the life of a given cohort year-to-year loss rates are constant. The effect of these assumptions is to permit representation of the inventory ageing process by means of a series of straight line segments as in Figure 1. The principal features of Figure 1 are described in detail in the previous report of this study.[4] The breakpoints in the figure are listed below:

- MSR (Minimum Service Requirement) - The length of the service obligation incurred by an Aviation Officer upon designation (currently five years).

- MSR+2 - The point at which officer retention is measured (currently seven years for Aviation Officers).

- Career Stable Point - The point at which an aviation year group stabilizes at relatively low mid-career loss rates.

4/Ibid., pp. 6-8.

- **18 Year Point** – The point at which losses begin to occur due to initial retirement eligibility and promotion to the grade of captain. (Captains are not counted in specifying either Aviation Officer requirements or inventory.)

- **20 Year Point** – The point at which early retirement and promotion losses are largely completed.

FIGURE 1
THE AVIATION OFFICER INVENTORY

The shape of Figure 1 can be completely specified by means of the continuation vector C_i where:

$$(2) \quad C_i = \frac{N_i}{N_{i-1}}$$

is the ratio of number of entries into the i^{th} year of aviation service to the number entering the $(i-1)$th year.

18

Then if the number of personnel entering year M is known the number in a later year n can be determined:

$$(3) \quad N_n = N_m \prod_{i=m}^{n} C_i$$

More specifically:

$$(4) \quad N_{MSR+2} = N_{MSR-1} \times \prod_{i=MSR-1}^{MSR} C_i$$

And:

$$(5) \quad \text{RETENTION} = \frac{N_{MSR+2}}{N_{MSR-1}} \quad \text{(BY DEFINITION)}$$

The importance of (4) is that the relationship between retention and overall inventory shape is established.

The Aviation Officer Requirements Model generates an inventory for each subcommunity in the form of Figure 1. Very briefly, it does this by estimating subcommunity accessions based on requirements and shaping the resulting steady state inventory.

In response to user specification of subcommunity retention, this inventory is then tested on an iterative basis (adjusting accessions as necessary) to establish a final requirements/inventory match to grade level detail.

In order to create an exact match between model inventory and requirements statements, it is necessary to specify some mechanism for converting years of aviation service to grade level. Requirements are specified by grade level. Thus, in assessing the ability to meet the requirement for Lieutenant Commanders, it is necessary to know what part of the inventory consists of Lieutenant Commanders. Fortunately, the correlation between grade level and years of Aviation service is good.

19

Aviation Year groups are composed of officers who are predominantly from two or three adjacent commissioned year groups.[5/] The Aviation Officer Requirements Model uses promotion flow points, adjusted to the years of Aviation Service scale,[6/] to partition the inventory by grade. The promotion flow point parameters are under user control.

The introduction of promotion flow points into the inventory specification process adds additional detail to the inventory description. The inventory becomes more than a set of one year cohorts of constantly decreasing size. Certain other characteristics of the cohorts are also important. These characteristics are acquired by individuals as a result of assignments to fill requirements. They become important as cohort characteristics when the experience they imply is either required or desired as a pre-requisite for future assignments. Experience requirements for squadron department heads and commanding officers are obvious examples. Most senior positions in the requirements structure have flight hour, educational, or specific mission area requirements.

An important objective of personnel management is to ensure that the inventory will contain the proper mix of skills and experience in the future. Because of this, the way in which inventory can be used to meet requirements is constrained in ways that should be accounted for in the planning process. The unique feature of the Aviation Officer Requirements Model is that it provides a mechanism for accomplishing this by accounting for those personnel management policies which govern the development of the Aviation Officer

---

[5/]Commissioned year groups consist of all officers who were commissioned in a given fiscal year.

[6/]The mean time of designation for Aviation Officers is at 1.5 years of commissioned service. Thus: YAS = YCS-1.5

inventory and constrain its application to requirements.

D. PERSONNEL MANAGEMENT POLICIES

The Aviation Officer Requirements Model accounts for personnel management
policy by forcing the inventory-requirements match to take place in the con-
text of a career path network. This network is simply a graph of tours
classified by activitiy and sequential position. A sequence of connected arcs
represents a potential career path through the network for an officer or group
of officers. Associated with each tour number-activity node in the network is
a tour length, input flow, and output flow. Arcs connecting the network nodes
represent permissible transitions within the network. The absence of an arc
connecting two sequential nodes means that the transition is barred, either
explicitly or implicitly by current personnel management policies.

Figure 2 is the network diagram employed in the Aviation Officer
Requirements Model. Network nodes are identified by a two-digit number. The
first digit identifies the activity in accordance with the entry numbers of
Table II. The second digit identifies the tour number. Some of the currently
permissible arc sequences are diagrammed in Figure 2. The portrayal is
complete through tour 2. However, in the interest of clarity only a represen-
tative sample of permissible sequences beyond tour 2 is portrayed. All net-
work flows originate at node 10 which represents the output of undergraduate
flight training.

Some specific examples are given below to illustrate how personnel manage-
ment policy is represented in the network of Figure 2:

- Training command output may only be assigned to fleet squadrons or to
  the training command (Plowback Instructors). The only permissible arcs
  from node 10 are (10-11) and (10-31).

21

YEARS OF AVIATION SERVICE

FIGURE 2

AVIATION OFFICER CAREER PATH NETWORK

- Plowback Instructors are guaranteed a subsequent fleet tour. The only permissible arc from node 31 is (31-12).

- Sequential sea duty tours are not permitted. The transition (11-52) is barred.

It should be apparent that any policy or procedure having to do with personnel assignment can be represented in the network diagram. Furthermore, since the basic variable represented is personnel flow and since a tour length is associated with each network node, the number of officers available at a

22

node to meet the specific requirements for the activity involved can be computed.[7]/ If the match of inventory to requirements is made within the constraints imposed by the network, the planner is assured that it is feasible to meet immediate requirements while developing a viable skill experience mix in the inventory.

The Aviation Officer Requirements Model imposes the network model described above on the inventory of Aviation Officers in each subcommunity. That is, inventory is assumed to flow only on permissible network arcs. Therefore, the number of officers at a given activity with a given number of years of aviation service is a function of the total flow to the appropriate network node. Network specification both in terms of permissible transitions and tour length at any node are under user control. Thus the user can test the impact of policy alternatives on requirements.

E. MODEL IMPLEMENTATION

The Aviation Officer Requirements Model has been implemented as a "user friendly," interactive computer program in a WANG 2200 VS computer. The model is "user friendly" in that no special competence in the operation of the computer is required of the user (although familiarity with the Aviation Officer requirements determation process is presumed). The user is cued by means of a series of CRT displays through the process of model setup, selection of run alternatives, and designation of outputs. The displays are completely self-explanatory menus. They allow the user to extensively alter model parameters and run modes. The model is reasonably fast, so that the user can make multiple runs in a single sitting. Provision is made for both the visual display of results and hard copy printouts.

7/Ibid., p. 23.

Appendix A to this report contains a user's manual that gives a detailed description of the Model's operation. Appendix B contains a program source listing for the model which is extensively documented internally. Appendix C contains the complete set of model default parameters.

The following discussion gives a general overview of model functioning and identifies the parameters which are under user control.

At the beginning of each model iteration, the user selects a subcommunity or subcommunities to be included in the run. Runs are made on a subcommunity basis. Upon subcommunity selection, a complete set of default values for the model parameters is loaded. The user is then led through a series of displays which show the default parameters and give the opportunity to make desired changes. Provision is made for bypassing displays as desired. The following model parameters are placed under user control in this process:

1. Requirements Parameters

    a. Force Level Parameters
       - Number of Squadrons in the Subcommunity
       - Number of Aircraft per Squadron
       - Crew Factor (Number of Crews/Assigned Aircraft)
       - Aviators or NFOs per Crew
       - Squadron Grade Structure

    b. Training Parameters
       - Undergraduate Training Pipeline Source
       - Undergraduate Instructor/Graduate Ratio
       - Training Squadron Grade Structure
       - Readiness Squadron Grade Structure

    c. Allocation Parameters
       - Subcommunity Fraction of All Naval Aviators or NFOs
       - Subcommunity Fraction of Strike Naval Aviators or NFOs
       - Subcommunity Fraction of Carrier-Based Subcommunities
       - Subcommunity Fraction of All Aviation Officers

2. Inventory Parameters

    a. Subcommunity Retention
    b. Minimum Service Requirement
    c. Career Stable Point

3. Personnel Management Policies

    a. For Each Node in the Career Path Network (49)
        - Permissible Precedent Nodes
        - Node Tour Length

    b. Promotion Flow Points to LCDR and CDR

    c. Plowback Instructor Fraction

    d. Professional Education
        - Postgraduate Education Fraction
        - War College Education Fraction

Execution of the model solution is straightforward. A trial inventory is generated that will just meet the subcommunity numerical requirement. The accessions implied by this inventory are then divided as specified by the plowback fraction, and flows to fleet squadrons and training command are calculated. The first tour length required to make fleet squadron flow meet fleet squadron requirements is calculated and recorded. Flows out of the first fleet squadron node and the training command node are then calculated in preparation for second tour processing.

For the second and subsequent tours, each source flow is checked against all destinations to identify permissible transitions. Where transitions are permitted, the requirement associated with the destination is examined. If the node requirement is greater than zero, source flow is assigned such that either the requirement is met or the source flow is exhausted. The source flow and destination node requirement are then appropriately decremented.

The above procedure is followed for all permissible source flow-destination node combinations within the tour. The scanning sequence is such that low activity number destination nodes (Fleet Tour = 1) are examined first. Thus, nodes involving operational flying assignments (Activities 1-4) tend to be favored.

When the node scan for a given tour is complete, there may still be some unused source flow, either because all destination node requirements have been met, or because source nodes with available flow have no permissible transitions to destination nodes with unfilled requirements. When this occurs, the remaining source flows are sent to an unconstrained destination labeled "Out-of-Aviation". Processing for this dummy node consists only of compution of the proper output flow (based on the tour length specified for "Other") and accounting for the resulting inventory at that destination.[8]

The node scanning procedure described above is repeated for successive tours through tour 7. Upon completion of tour 7, the degree of requirements fill is examined. If all requirements have been met, the computation is complete and a transfer is made to the model output routines. If all requirements have not been met, an inventory increment sufficient to cover unmet requirements is generated. The network flow computations are then repeated. Iterations continue until all requirements are met.

The model output routines consist of a series of computations and formatting routines that tabulate subcommunity results, develop some elementary derivative parameters, and print a summary output. An example of output format is included in Appendix A. The following outputs are currently provided in the subcommunity summary printout:

---

[8]/This process is analagous to that by which Aviation Officers are used to fill non-aviation billets (billets coded either 1000 (any line officer) or 1050 (any warfare specialty)). However, it should be stressed that the model flows Aviation Officers to the Out-Of-Aviation Activity ONLY when it cannot make an aviation assignment. In actual practice, a portion of 1000 and 1050 billets are routinely allocated to the aviation community as requirements. These additional requirements may at times enjoy a higher fill priority than aviation billets. The approach taken in the model treats Out-Of-Aviation as pure surplus. This was done in order to provide planners who use the model with an estimate of future Ability to fill non-aviation billet demand.

1. Community Description

    - Number of Squadrons
    - Aircraft per Squadron
    - Crew Factor
    - Naval Aviators (NFOs) per Crew
    - Subcommunity Retention
    - Plowback Fraction

2. Projected Subcommunity Population Characteristics

    - Grade Distribution
    - Command Opportunity (Squadron)
    - Department head Opportunity (Squadron)
    - Annual Accessions to Designator
    - Annual Accessions to Training
    - First Tour Length

3. Subcommunity Employment Projections

    - Distribution by Grade and Activity
    - Aviation Career Incentive Pay-Gate Achievement Projections
    - Fraction of Subcommunity Employed in Non-Aviation Assignments
    - Total Annual Permanent Change of Station Moves Attributable to the Subcommunity

The Aviation Officer Requirements Model is basically a simulation. For each subcommunity, a set of structured requirements is presented. An accession level is established and made to flow through the model under a specified set of personnel management policies. In essence, the model acts like an omniscient detailer, meeting all subcommunity requirements and never violating the policy constraints. The Aviation Officer manpower planner is assured that the solution presented is feasible in the sense that, under the initial conditions specified, the subcommunity inventory recommended can meet all requirements. By summing over all subcommunities, a statement of total Aviation Officer requirements is obtained.

F. ENHANCEMENTS TO THE BASIC MODEL

1. Introduction

During the current effort on the Aviation Officer Requirements Model, a

27

number of significant improvements has been made. In making changes, the basic format in which the user interacts with the model was preserved. The user who is familiar with the Version 5.0[9]/ model will find the current version almost identical when making single subcommunity runs. However, there are a number of additional features in the current version and changes to previous computation procedures with which the user should be familiar. They are discussed below.

2. Multiple Community Runs

The original version of the Aviation Officer Requirements Model made only single subcommunity runs. In order to obtain a complete solution for all Aviation Officers, it was necessary to set up and run all 23 subcommunities in sequence. Once all runs had been made, considerable additional manual calculation was required to obtain totals and averages. The current version of the model contains a Multiple Run Option which eliminates most of this post-processing calculation.

In developing the Multiple Run Option, the following three basic design objectives were established:

- Maximize Flexibility – Let the user decide which subcommunities are involved. Account for both subcommunities selected and those not selected within the program.

- Minimize Setup Time and Effort – Limit the number of key strokes needed to setup and run 23 subcommunities. Permit the user to bypass data entry options where possible.

- Minimize the Need for Post Processing Calculation – Perform Summary Calculations across subcommunities and prepare appropriate outputs within the program.

All of these objectives have been met.

9/O'Connor, Aviation Officer Requirements Study, Appendix B. (Version 5.0 is the model as previously described. The enhanced model is Version 7.0.)

The approach taken in establishing the Multiple Run Option was to allow the user to place subcommunities into groups of his choice; that is, the user is permitted to define any number of subcommunity groupings between 1 (all Aviation Officers in one group) and 23 (each subcommunity in a separate group). Within each group, certain model parameters are assumed to be constant (e.g., Policy Variables). Others are permitted to vary at user option (e.g., Career Path parameters). In any case, the user is afforded at least one opportunity to review default model parameters[10] for each group. He may change any or all of these values. In those cases where intra-group variation is permitted, he may change values for each subcommunity within the group or elect to bypass review of the remaining subcommunities, assigning a single change to all members of the group.

As with all other parameters in the Aviation Officer Requirements Model, the Multiple Run Option is preset to a default subcommunity grouping. This default grouping classifies the 23 subcommunities into 7 groups (3 for Naval Aviators, 4 for Naval Flight Officers). The default groups consist of subcommunities with the same undergraduate training pipeline source. Definitions of these groups follow:

a. Naval Aviators

- Strike Pipeline (Group A)
    - Light Attack (VA)
    - Fighter (VF)
    - Medium Attack (VAM)
    - Electronic Warfare (VAQ)
    - Carrier Base ASW (VS)
    - Force Support, Jet

---

[10]/The Aviation Officer Requirements Model contains a complete set of model parameters representing the approximate state of affairs in the Aviation Officer Community in FY 81. These values are the default values of model parameters.

- Maritime Patrol Pipeline (Group B)
  - Maritime Patrol (VP)
  - Early Warning (VAW)
  - Electronic Warefare (VQ)
  - Force Support - Prop

- Helicopter Pipeline (Group C)
  - Helicopter ASW (HS)
  - LAMPS MK I (HSL)
  - LAMPS MK III (HSL)
  - FORCE Support - Helo

b. Naval Flight Officers

- Radar Intercept Officer Pipeline (Group D)
  - Fighter

- Attack Navigation Pipeline (Group E)
  - Medium Attack (VAM)
  - Electronic Warfare (VAQ)
  - Carrier ASW (VS)
  - Force Support - Jet

- Airborne Tactical Data Systems Pipeline (Group F)
  - Early Warning (VAW)

- Navigator Pipeline (Group G)
  - Maritime Patrol (VP)
  - Electronic Warfare (VQ)
  - Force Support - Prop

Groups are identified by a single letter. The process of group formation consists of assigning a single letter to each subcommunity. Upon entering the Multiple Community Run option, the user is presented with a list of subcommunities and asked to make group assignments. At this time he can:

o Make no entry, in which case the default group assignment will be used;

o Enter a group assignment pattern of his own selection;

o Enter a zero for subcommunities to be excluded from the run.

Once group assignments have been made, the user is given the opportunity to make model parameter changes for each group in succession. At the conclusion of parameter adjustment for each group, a listing of group members is

presented for review. At this point, the option of resetting the group selection process is available.

After group selection and parameter adjustment, model solution proceeds on a subcommunity by subcommunity basis for each selected group. Summary sheets are prepared for each subcommunity processed. In addition, separate summary sheets are prepared for Naval Aviators and Naval Flight Officers. These latter sheets also contain a list of subcommunities excluded from the run by the user. A detailed presentation of the operation of the Multiple Community Run Option is given in Appendix A. Sample output summary sheets are also presented.

3. Optimization of Assignment Patterns

As originally designed, the Aviation Officer Requirements model made ource to destination flow assignments using the following procedure:

a. The highest numbered source node having positive source flow available was identified (Activity 7, Other, is the highest numbered; Activity 1 is the lowest).

b. The lowest numbered destination node having unmet requirements was identified.

c. If flow available from a. was less or equal than that needed to meet requirements b., the flow was assigned and the requirement decremented appropriately. Available flow was reduced to zero and processing continued at a.

d. If flow available from a. was greater than that needed to meet requirements, sufficient flow was assigned to meet the requirement. Source flow and requirement were decremented. Processing continued at b.

e. If destination node scanning reached Node 7 with flow still available, the remaining flow was assigned to Out-Of-Aviation. Processing continued at a.

f. Upon completion of source node scanning at Node 1, the tour number was incremented and the process repeated.

31

This procedure has the advantage of defining a feasible flow pattern which:

- Favors flow assignment to activities consisting of Operational Flying Billets (Activities 1-4); and

- Gives assignment priority to flows from activities consisting of non-operational flying billets (Activities 7 through 5).

Thus the procedure is similar to what could be expected to be the general philosophy governing the personnel assignment process; namely "fill cockpits first" and "get non-flying aviators back in the cockpit."

The above procedure has a flaw which can lead to an overstatement of requirements. Source flow assignments early in the scanning process may completely foreclose the assignment of flow from later nodes, thereby forcing flow to Out-Of-Aviation. An alternative assignment at the earlier node may well have permitted the assignment from the later node to an aviation assignment, thereby reducing the overall flow to Out-Of-Aviation. Since an obvious planning objective ought to be the minimization of the inventory specified to meet requirements, the procedure outlined above was modified to provide assurance that the flow pattern adopted at each tour was such as to maximize the fill of billets at aviation assignments. This was accomplished by adapting the problem of specifying the flow between nodes in a given tour so as to make it amenable to solution using the maximum flow algorithm of network theory.11/

Figure 3 is a network diagram illustrating the device used to formulate the tour source-destination flows as a maximum flow problem. The seven desti-nation nodes for Tour i are shown right-of-center in ascending order of acti-

---

11/See, for example, H.M. Wagner, Principles of Operations Research, 2nd ed. (Englewood Cliff, New Jersey: Prentice Hall, 1969), Appendix I.

vity number (i=1-7). On the left the source nodes representing flows out of tour j-1 are shown in a similar manner. Arcs connecting these two node sets represent the permissible transitions between tour j-1 and tour j. Finally, it is conceptually useful to envision all flows as originating at a single source and terminating at a single sink.

FIGURE 3

MAXIMUM FLOW PROBLEM FOR TOUR TRANSITIONS

Arc capacities in Figure 3 are set as follows:

   a. Source to Nodes (j-1): Arc capacity is equal to the availab..
   flow at the (j-1) Node. The total source flow is therefore equal to
   the total output flow from the previous tour.

   b. Nodes (j-1) to Nodes (j): Arc capacity is the lesser of:

   • Available source flow;

   • The flow which will just meet the remaining requirement at
     Node (i,j).[12] Subject to the constraint that barred tran-
     sitions have zero flow capacity.

   c. Nodes (j) to Sink: Arc capacity is the flow which will just m. t
   the remaining requirement at Node (i,j).

When arc capacities are specified in the manner outlined above, a.

resulting flows within the tour are guaranteed to be within source node fl..

constraints and less than or equal to the flow required to fill destinat...

node requirements.

The network of Figure 3 is solved using the maximum flow algorithm.[13]

This algorithm employs a systematic search of all possible paths through th

network to find one that will permit an increase in total network flow. Th

procedure terminates when no such path exists. In the present case, th

geometry of the network permits a simplified path scanning process which

---

[12]/The flow meeting the remaining requirement at Node (i,j) is given by

$$(6) \quad F_{i,j} = \frac{2 \times REQ_{i,j}}{2 \times TL - \sum_{k=1}^{TL} \left(\frac{1 - r_{i+k}}{r_i} \right) \times \prod_{l=1}^{k} R_{i+1}}$$

Where: F_{ij} = Arc capacity for Arcs terminating at Node (i,j)
         REQ_{ij} = Remaining Requirement at Node (i,j)
         TL = Tour Length Specified for Node (i,j)
         RT = Continuation rate for year t
Note: t and TL specified in years

[13]/F.B. Hiller and G.J. Lieberman, Introduction to Operations Research,
(San Francisco: Holden-Day, Inc., August 1967), pp. 214-218 for the specific
algorithm used.

greatly simplifies computer implementation of the algorithm.

Consider an initial trial solution for the network of Figure 3 which simply proceeds from source node arc to source node arc, allocating as much of the source flow as possible to available paths through the remainder of the network. At the conclusion of this step, one of the three conditions will hold:

a. The capacity specified for source flow arcs will be exhausted, indicating an optimum flow;

b. The capacity specified for sink flow arcs will be exhausted, indicating an optimum flow;

c. The capacity will remain on one or more source flow arcs AND on one or more sink flow arcs, indicating a potential for increased flow. In this case, iteration is required until either a. or b. above occurs.

Given the condition described in c. above, the objective of the algorithm becomes the elimination of positive flows on either side of the network. In the general case, the positive source capacities will not be connected to the positive sink capacities (since otherwise the capacities would have been eliminated during initial assignment of flows). Path analysis then consists of transferring existing flows to other feasible sources/destinations so as to create a positive flow capacity on some arc out of the source and a positive flow capacity on some arc into the destination. The proper adjustment can be found by defining a path between the two nodes consisting of forward arcs (j-1 to j) with positive remaining capacity and reverse arcs (j to j-1) currently having positive (forward) flow.

Having found such a path, the proper adjustment is given by the minimum of the available capacity on forward arcs or current flow on reverse arcs. The adjustment can be made by simply proceeding along the defined path, adding the flow on forward paths and subtracting it on reverse paths. When no such path

35

can be found, maximum possible flow has been attained. The dashed lines in Figure 3 represent one such path search for the case where positive source flow remains at node (5, j-1) and requirements remain at node (5,j).

When the procedure outlined above terminates, any remaining source flow is surplus to aviation requirements for the tour in question. This flow is then assigned to the Out-of-Aviation destination. For any given tour, this is the minimum flow that can be achieved, given the specification of tour transitions and destination tour lengths provided by the user.

The implementation of the maximum flow algorithm in the Aviation Officer Requirements Model will not be apparent to the user. Model operation is functionally similar and no additional inputs are required of the user. Provision is made for printing out interim network solutions when the in-process-monitor option is selected. The user familiar with the previous version of the model will also notice a significant reduction (about 10 percent) in both Out-Of-Aviation assignments and overall requirements.

4. Inclusion of Promotion Flow Points

The original version of the Aviation Officer Requirements Model converted inventory aviation year groups to an equivalent grade level for purposes of inventory/requirements comparisons. This was done by establishing grade level transitions at 8.5 years of aviation service (03 to 04) and 13.5 years of aviation service (04 to 05). A revision has now been incorporated to allow the user to specify promotion flow points in years of commissioned service.

The model processes user-specified promotion flow points by converting the input from years to months and subtracting 18 months to convert the entered value to months of aviation service. (The model makes all calculations in time increments of 1 month and expresses results in units of 1 year.)

Default values for the Promotion Flow Point Parameter are 10 years (03 to 04) and 15 years (04 to 05). These values correspond to the values used in the original version of the model.

5. Upward Detailing

Upward detailing refers to the process by which individuals at one grade level are used to fill requirements at the next higher grade level (e.g., the assignment of a Lieutenant to fill a Lieutenant Commander billet). A feature which allows the user to implement a simulation of this process has been incorporated in the model to allow planners to directly assess the effects of grade level mismatches between inventory and requirements. Inferences regarding such mismatches can be drawn from Out-Of-Aviation flows. However, if mismatches are severe, the model is likely to drive inventory up and first tour length down, thereby distorting indirect requirement flows. By allowing junior surpluses to meet senior requirements, this effect is avoided and the numbers so assigned become a direct indicator of grade imbalance. Furthermore, the planner gains insight into the long term personnel management problems likely to attend a given solution.

Implementation of upward detailing in the model is straightforward. The user specifies an upper limit on the fraction of senior billets in any activity which are permitted to be filled by flows from tours at a lower grade level (default value is set to 20 percent). The model, while processing flows, establishes maximum flow within each tour as described above. However,

37

if upward detailing is permitted, surplus flows from the tour assignment pro-
cess are first flowed against requirements at the next higher grade level
before being assigned to Out-of-Aviation. Feasible assignments are made.
Resulting flows are recorded in the current tour, while requirements are
decremented at the higher grade level. In the final result, the source grade
level will be shown in surplus for the activities involved, while the destina-
tion grade level will be shown in deficit. The model reports the aggregate
percentage of requirements met at each grade level by upward detailing.

In addition to the overall constraint described above, upward detailing is
constrained in the following ways:

- Upward detailing to command (Tour 6, Activities 1-3) is not allowed;

- Upward detailing to O4 billets in squadrons (Tours 4 and 5, Activities
  1-3) is constrained to preserve three LCDR billets for squadrons, with
  only Naval Aviators and four LCDR billets for squadrons with both
  Aviators and NFOs. (This preserves a minimum flow for department head
  level billets);

- Upward detailing to post command afloat billets (Tour 7, Activity 5) is
  not allowed;

- Upward detailing is not allowed prior to tour three for any activity.

The above restrictions were adopted as being reasonably representative of
current practice with respect to upward detailing. They are not variable at
user option, but they could easily be modified by means of minor program
changes within the model.

6. Automatic Allocation Parameter Scaling

The Aviation Officer Requirements Model uses a set of allocation factors
to determine the assignment of billets to a subcommunity in those cases where
the requirement cannot be directly or indirectly associated with the subcom-

munity mission. Activities 4 through 7 consist of allocated billets. The allocation base is the direct (Activity 1) requirement, with each subcommunity receiving a fraction of non-direct requirements equal to the ratio of subcommunity direct requirements to total Navy direct requirements. Three major allocation bases are employed--one for Naval Aviator billets, a second for Naval Flight Officer billets, and a third for billets designated for either Naval Aviators or Naval Flight Officers. A fourth allocation parameter is used only to allocate carrier air wing staff positions among carrier-based subcommunities. Thus there are four allocation parameters associated with each subcommunity.

The application of the allocation factors in subcommunity definition assumes that the subcommunities collectively cover all Aviation Officer requirements. The sum of the allocation factors of each type over all subcommunities equals one. These factors are presented to the user as model parameters under his control primarily so that they can be adjusted in response to force level changes.

The problem with allocation factor changes is that if one factor in a class is changed, the remaining factors over all subcommunities must also be adjusted to maintain a unity summation. In the original version of the model, the user had to make these adjustments manually for each subcommunity for which a run was desired. For complex force level changes, the process was tedious and subject to both computational and entry errors. The current version of the model corrects this deficiency.

The Aviation Officer Requirements Model now automatically rescales the allocation parameters. The user is assured a consistent set of allocation parameters over all subcommunities if he changes the number of squadrons in a

39

given subcommunity, or if he alters one of the allocation parameters for a subcommunity.

7. Total Permanent Change of Station (PCS) Moves

A great deal of attention is currently being directed to the cost of moving personnel from place to place within the Navy. Congressional interest in reducing these costs and a series of budget shortfalls in the Military Personnel Navy Appropriation account have caused repeated expressions of concern over the frequency of personnel moves. Explicit and implicit constraints in the PCS account are having a progressively greater impact on the overall process of personnel management.

While the issue of PCS moves is not directly related to the intended use of the Aviation Officer Requirements Model, the essential variables which drive such moves are included in the model formulation. Flows between states represent the bulk of such moves, and other moves--such as the move of accessions from home to duty and the move of losses from duty to home--are easily derived from the model parameters. Thus it is possible to attribute to each subcommunity an estimate of the annual number of PCS moves resulting from a given configuration of force level and policy parameters. Since this information is potentially useful to the planner, the necessary calculations were incorporated into the model and the results presented in the community summary outputs.

8. Model Speed of Execution

In the process of revising the Aviation Officer Requirements Model, the following changes have been made which decrease model solution time:

- The method used to make initial inventory estimates and inventory increment calculations has been refined. This has significantly reduced the number of iterations necessary.

40

- While the adoption of the within tour optimization procedure has increased computational time, the increase is more than offset by decreases in the overall number of iterations resulting from the higher level of assignments within aviation.

- Implementation of the Multiple Run Option forced revision of a large number of processing and storage routines. In the process of revision, these routines were made more efficient.

- The model has been moved from the WANG 2200 VS 80 computer to the WANG 2200 VS 90. The VS 90 is a faster computer. (Source codes and object codes remain compatible with the VS 80.)

As result of the above factors, execution time has improved by a factor of three. For example, the version 5.0 model required approximately 7.5 minutes to complete calculations on the Light Attack Subcommunity after model setup. The current version takes 2.5 minutes to complete the same task. A multiple subcommunity run over all subcommunities typically takes 25 minutes to complete.

IV. APPLICATION OF THE MODEL

A. GENERAL

The previous sections of this report have given the underlying rationale and a detailed description of the Aviation Officer Requirements Model. The principal features of the model bearing on its utility are:

- The large number of model parameters under user control;

- The user friendly environment created for the model which facilitates its employment;

- The speed of execution which facilitates comparison of alternative strategies.

Because of the broad range of parameters available to the user, the model is highly flexible. It can be used to analyze a broad range of manpower issues. The subsections which follow demonstrate a few such applications. Others will undoubtedly come to mind. The intent here is to introduce the potential user to the model. It should be emphasized that the examples are for illustrative purposes only. The numbers do not necessarily reflect the currently specified Navy Aviation Officer requirements, nor do some of the key parameters (such as retention levels) necessarily reflect current Navy experience.

B. FORCE LEVEL VARIATIONS

The principal force level issue impacting on Naval Aviation today is the impending increase from 12 to 15 Carrier Battle Groups. Among the manpower problems attending that increase will be meeting additional air crew requirements for a minimum of two more Carrier Air Wings. Model set up and post run

analysis of runs for a 12 Air Wing configuration and a 14 Wing configuration are given below:

1. Run Set Up

Two sets of two runs each were made in Multiple Community Run Mode:

- 12 Air Wing Runs
  - Carrier Based Subcommunities
  - Non-Carrier Based Subcommunities

- 14 Air Wing Runs
  - Carrier Based Subcommunities
  - Non-Carrier Based Subcommunities

The same information could have been obtained by making only two runs for all subcommunities. However, by splitting the runs as indicated, the user obtains the benefit of summary statistics which are focused on the indicated subgroups. This eliminates the necessity of gathering and summing data from individual subcommunity printouts.

Runs for both 12 and 14 carrier air wings were made at model default parameter values with the following exceptions:

- Retention
  - Fixed Wing Aviators   45%
  - Rotary Wing Aviators   50%
  - Naval Flight Officers   55%

- Tour Lengths
  - Fourth and Fifth Fleet Tours = 30 months (Default = 36 months)

These values were selected as being more representative of current experience than model default values.

2. Results

The overall results of the runs indicate an increase in Aviation Officers from 15,779 to 16,846--a total increase of 1,067. Of these, 614 are Naval Aviators and 443 are Naval Flight Officers. An analysis of these differences by activity for subcommunities which are carrier based and those which are not is presented in Table III.

TABLE III

ANALYSIS OF REQUIREMENTS CHANGE
(12 to 14 CARRIER AIR WINGS)

Model Run		Change Activities 1-3	Activities 4-7	Out-of- Aviation	Total
CV Subcommunities	NA	+584	+130	+112	+ 826
	NFO	+290	+ 61	+222	+ 573
	TOTAL	+874	+191	+334	+1399
Non-CV Subcomm.	NA	- 20	-126	- 56	- 202
	NFO	- 8	- 51	- 71	- 130
	TOTAL	- 28	-177	-127	- 332
Net All Subcomm.		+846	+ 14	+207	+1067

The changes in Activities 1-3 in Table III reflect changes in fleet manning and associated increments to training resources and the training and transient pipeline. For the CV Subcommunities, a total of 874 officers are required as a result of the addition of two Carrier Air Wings. In addition, because of the increase in relative size of the CV Subcommunities, allocation parameters are changed, resulting in an increase in requirements in Activities 4-7 of 191 officers. The increase in Out-Of-Aviation flow of 334 is caused by the large relative increase in junior officer requirements associated with the

44

new Air Wings. These officers become available for Out-Of-Aviation assignments at more senior grades because few senior aviation requirements are added. The relatively larger increase associated with Naval Flight Officers reflects the higher retention (55 percent) assumed for NFOs.

For the Non-Carrier Subcommunities, Activities 4-7 show a decrease in requirements as a result of change in reallocation parameters. As the relative size of the CV Subcommunities increases, the Non-CV Subcommunities are allocated less of the indirect requirements.14/

The Non-CV Subcommunities also experience reduced requirements in Activities 1-3 and in Out-Of-Aviation flow. The minor change (-28) in Activities 1-3 is due to changes in transient and pipeline requirements resulting from flow patterns which tend to favor operational flying billets at the higher force levels. The reduction in Out-Of-Aviation flow reflects an improved match between inventory and requirement grade levels in these subcommunities at the retention levels assumed.

Overall, the increase in force level by two Carrier Air Wings results in a net increase in direct requirements of 846, an increase in indirect requirements of 14, and an increase in Out-Of-Aviation flow of 207. Thus, approximately 20 percent of the increase is the result of an imbalance between junior requirements and senior requirements. The user could eliminate this surplus by relaxing the 20 percent constraint on upward detailing (the model default

_____

14/The net change in Activities 4-7 over all subcommunities would be zero except for the fact that the model generates professional development requirements that are proportional to the population. The net increase of 14 reflects an increase in postgraduate education and War College student requirements resulting from the larger overall size of the projected Aviation Officer inventory.

value). However, a word of caution is in order regarding the interpretation of Out-Of-Aviation flow.

The Navy currently has requirements for approximately 40,000 unrestricted line officers. This includes approximately 7,500 1000/1050 billets (Any URL Officer/Any Warfare Specialist) that are not directly associated with any unrestricted line community. The aviation "fair share" of these billets is approximately 2,800. These are NOT included in the requirements statement of the Aviation Officer Requirements Model. Instead, the model identifies resources which, because of career path or grade level constraints, will be surplus to direct aviation requirements and therefore are AVAILABLE to meet non-aviation requirements. The total Out-Of-Aviation flow supplied in the baseline case (12 Air Wings) of the above analysis is 1,894--about two-thirds of a "fair share". The increment added in the force level increase to 14 Carrier Air Wings in fact increases the disparity between available fill resources and the "fair share". The implication for the planner is that the 1100 officer community will have to assume responsibility for a proportionately larger share of the 1000/1050 billet requirements.

The Aviation Officer Requirements Model also provides projections of Aviation Officer accession requirements and undergraduate flight training requirements. For the present case, the results summarized for CV Subcommunities and Non-CV Subcommunities are shown in Table IV.

The increase in force level from 12 to 14 Carrier Air Wings increases annual undergraduate training output requirements by 63 Naval Aviators and 45 Naval Flight Officers. Annual accessions to support the higher training rates increase by 89 student Naval Aviators and 45 student Naval Flight Officers. The mix implied in the increase is more significant to the planner. More than

TABLE IV

ACCESSIONS AND UNDERGRADUATE TRAINING REQUIREMENTS
(12 VS. 14 CARRIER AIR WINGS)

Training Pipeline	CV Subcommunities		NON-CV Subcommunities		Totals	
	Accessions (12/14)	Training Rate (12/14)	Accessions 12/14	Training Rate 12/14	Accessions 12/14	Training Rate 12/14
Naval Aviator						
o Strike	458/554	326/395	124/114	8/81	528/668	414/476
(Difference)	(+96)	(+69)	(−10)	(−7)	(+86)	(+62)
o Maritime P/T	37/42	28/33	349/348	271/269	386/390	300/302
(Difference)	(+5)	(+4)	(−1)	(−2)	(+4)	(+2)
o Helicopter	74/85	55/63	340/328	252/243	414/413	307/306
(Difference)	(+11)	(+8)	(−12)	(−9)	(−1)	(−1)
Totals	569/681	410/491	813/790	611/593	1382/1471	1021/1084
	(+112)	(+81)	(−23)	(−18)	(+89)	(+63)
Naval Flight Officers						
o Radar Int. Off.	122/153	68/85	0/0	0/0	122/153	68/85
(Difference)	(+31)	(+17)	(0)	(0)	(+31)	(+17)
o Attack Nav.	224/281	126/158	15/15	8/9	238/296	134/167
(Difference)	(+57)	(+32)	(0)	(−1)	(+57)	(+33)
o ATDS Off.	61/72	40/48	0/0	0/0	61/72	40/48
(Difference)	(+11)	(+8)	(0)	(0)	(+11)	(+8)
o Navigator	0/0	0/0	270/251	189/176	270/251	189/176
(Difference)	(0)	(0)	(−19)	(−13)	(−19)	(−
Totals	407/506	234/291	285/266	197/185	692/772	431/4..
	(+99)	(+57)	(−19)	(−12)	(+80)	(+45)

half of the total increase in training rate is in the Strike (Jet) Training Pipeline. This is the most costly pipeline by far. The per capita cost of the increased undergraduate training will therefore be significantly higher than the current average cost per graduate.

As with any model, the results obtained above suggest other alternatives which should be examined. In an actual planning scenario, the user would undoubtedly want to examine the impact of variations in subcommunity retention on the outcome. Upward detailing constraints could also be tested. The planner can even examine the impact of varying squadron grade structure, aircraft per squadron, or seat factor in order to assess the impact of short term resource constraints on the long term Aviation Officer inventory.

A word of advice to the potential user is in order at this point. The Aviation Officer Requirements Model places a large number of parameters under user control. If the user changes many parameters in a single run, he may have difficulty interpreting the results. To avoid this, the following approach to model utilization is recommended, based on experience gained on more than a hundred model runs:

- Establish a baseline run for comparison purposes. The default parameter settings approximate FY 81 requirements.

- Change no more than a half dozen parameters from run to run.

- Have a plan of attack. Take a few minutes to outline a sequence of runs before going on the computer. This saves times and minimizes rerun requirements.

For user convenience, runs are marked with the date and time of completion in the upper right hand corner of each sheet. The frequent user eventually will find this feature useful in organizing the data. The four runs used in the discussion of the 12 to 14 Air Wing force level change produced 54 pages

48

of printout. The total time to complete the four runs was one hour and three minutes.

C. GRADE STRUCTURE ANALYSIS

Requirements are basically billet-by-billet statements of Navy needs. Inventory development is dominated by loss rates that are largely determined by factors exogenous to the Navy. Given those facts, it is not surprising that inventory and requirements seldom match exactly at the grade level of detail. Occasionally, after a period of extremely high or extremely low retention for example, it may be necessary to correct the imbalances by either adjusting requirements grade levels or modifying inventory grade distribution (by changing promotion flow points). The Aviation Officer Requirements Model can be used as an analytic tool in support of this process.

The model outputs which provide a measure of grade imbalance are the upward detailing fills and the Out-Of-Aviation flows. The model reports lower grade fills and the number of Out-Of-Aviation fills by grade level for each subcommunity. The model resorts to upward detailing only when it cannot employ source flow in the current tour at maximum flow.

Out-Of-Aviation flow is employed only when flow cannot be employed within aviation, either because requirements have been met or upward detailing limits have been achieved. In either case, the existence of such flows indicates a surplus of inventory over grade level requirements.

To illustrate this application, Table V reproduces output data for the Light Attack and Fighter Subcommunities from the runs produced in the preceding example.

49

TABLE V

UPWARD DETAIL AND OUT OF AVIATION FLOWS
(LIGHT ATTACK AND FIGHTER NAVAL AVIATORS)

Subcommunity	LT	Grade LCDR	CDR	SEN CDR	TOTAL
Light Attack					
Number Up Detailed to	-	52	0	0	
Out-Of-Aviation	41	20	0	13	74
Fighter					
Number Up Detailed to		5	0	0	
Out-Of-Aviation	0	0	0	11	11

Note: Base-Line Case (12 Air Wings)
Retention   = 45%

In the case of Light Attack, a total of 93 surplus Lieutenants occurred, of which 52 were upward detailed within the 20 percent constraint. The remaining 41 were flowed to Out-Of-Aviation. The indication here is that converting 52 billets at the LT Level to LCDR-CDR billets would provide a better grade match. Additionally, if CDR billet requirements could be reduced, the lower grade surpluses would also be reduced, thus decreasing Out-Of-Aviation flow. Alternatively, moving the promotion flow point to LCDR forward (earlier) would achieve the same effect.

In the case of the Fighter Subcommunity, a total of nine lower grade fills were used at the LCDR and CDR levels indicating a near perfect inventory-requirements match.

D. RETENTION ANALYSIS

The role of projected retention rates for Aviation Officers in determining inventory projections has already been discussed. Clearly, retention is a key model variable. Since retention is not under Navy control, the planner is

required to use estimates which are largely based on history but which hopefully take cognizance of the sociological and economic phenomena known to influence retention. Above all, the planner should recognize the sensitivity of model results to retention and perform the required sensitivity analysis. The following example illustrates this point.

The retention values used earlier in this section for the baseline case (B. Force Level Variations) were 45 percent for fixed wing aviators, 50 percent for rotary wing aviators, and 55 percent for Naval Flight Officers. These estimates assume that historical differences in retention between these Aviation Officer groups will persist, and that there will be a modest recovery in retention rates from the very low levels experienced in the late 1970s. In the 1984 Manpower Requirements Report submitted by the Office of the Secretary of Defense to the Congress in February 1983, Navy estimates of current retention are provided, and steady state retention goals for Aviation Officers are established at 55 percent for Naval Aviators and 60 percent for Naval Flight Officers.15/ Table VI compares the model output for the baseline case described previously and that obtained using the Manpower Requirement Report (MRR-84) steady state retention values.

Table VI shows that the model produces essentially the same inventory for both cases. However, the grade distribution is significantly different. The MRR-84 case contains 327 fewer Lieutenants, 148 more Lieutenant Commanders, and 183 more Commanders. Thus, compensation costs would be somewhat higher at the MRR-84 retention figures (About 4.5 m/year RMC in FY 83 dollars).

15/U.S. Department of Defense, Military Manpower Report to the Congress, February 1983, p. IV-13.

TABLE VI

BASELINE VS. MRR-84 RETENTION

CASE	CLASS	Grade Distribution				Training Rate	Out Of Aviation
		LT	LCDR	LDR	TOTAL		
BASELINE	NA	6728	1844	2325	10907	1020	1007
CASE	NFO	2920	885	1067	4872	432	887
	TOTAL	9648	2729	3392	15779	1452	1894
MRR-84	NA	6491	1973	2470	10934	960	1097
CASE	NFO	2830	904	1105	4839	414	879
	TOTAL	9321	2877	3575	15773	1374	1976
DIFFERENCE	NA	-237	+129	+145	+27	-60	+90
	NFO	- 90	+ 19	+ 38	-33	-18	- 8
	TOTAL	-327	+148	+183	- 6	-78	+98

However, this increase would be more than offset by the reduced accession training rates associates with the MRR-84 case. The higher retention results in a reduction of 60 in the Pilot Training Rate and 18 in the Naval Flight Officer Training Rate. The annual savings in military personnel costs associated with training at these lower levels total 6.3 M.

A review of other model parameters on a subcommunity-by-subcommunity basis reveals the following:

- First tour lengths increase due to the smaller entry cohort size. The change is about 3 months for Naval Aviators and 1 month for Naval Flight Officers.

- Command opportunity decreases slightly for Naval Aviators due to the larger number of Commanders. Naval Flight Officer command opportunity decreases much less because the retention differential between the two cases is smaller.

- ACIP Gate I projections generally increase by about 2 percent indicating more cockpit employment time across the board.

52

Overall, the conclusion is that increased retention would significantly lower costs, and in addition, provide a more manageable inventory of Aviation Officers.

E. A WORD OF CAUTION

The foregoing examples have been presented to illustrate, to potential users of the Aviation Officer Requirements Model, some ways in which the model can be useful as a planning tool. The model is admittedly complex. It must be if it is to reasonably represent the universe with which the planner must cope. Unfortunately, complexity, while conferring a degree of versatility, also demands a higher level of intellectual involvement on the part of the user. First of all, he must understand the reality that the model represents. He must then be prepared to expend considerable mental effort in interpreting model results in the context of that external reality. In a word, the planner must learn to use the tool. The foregoing examples were presented solely in the interest of facilitating that learning process. It would be a mistake to attach any great significance to the numerical results. The baseline case represents Aviation Officer requirements in 1981. A number of significant changes in force structure and support concepts have occurred since then which would alter the numerical results for the baseline case. Before attempting to employ the model in the planning process, the basic requirements arrays in the model should be respecified to reflect the current Aviation Officer billet structure, and the validity of certain force level parameters--most notably crew factors--should be confirmed.

V. APPLICATION OF THE MODELING TECHNIQUE
TO THE SURFACE WARFARE OFFICER COMMUNITY

A. INTRODUCTION

A natural extension of the current effort to develop and implement an analytical tool for determining Naval Aviation Officer requirements is the application of the basic modeling technique to other officer communities. A preliminary analysis of the Surface Warfare Officer Community was conducted to identify any significant changes to the basic model structure that would be required. These changes are discussed in this section in terms of their influence on the model requirements specification, inventory specification, and career path specification.

B. REQUIREMENTS SPECIFICATION

The basic force element for Surface Warfare Officers is the individual ship. In specifying direct force level requirements, ships may be grouped by class to identify units with similar officer manpower requirements. These groups are then analogous to the subcommunities established in the Aviation Officer Requirements Model. In addition, ship classes may be grouped into ship types (e.g., DD-TYPE/DD 963-CLASS). There is some utility inherent in accomodating both type and class in the requirements structure of a Surface Warfare Officer Model. For example, the user may desire to specify force level changes in terms of class (e.g., add 5 DD963s) or type (Add 5 DDs). In the latter case, model logic would make additions to the latest (highest numbered) class in the type group, while losses would be taken from the oldest class.

While the ship class in the case of Surface Warfare Officers is analogous to aircraft type in the Aviation Officer Requirements Model, there does not

appear to be any need to establish a subcommunity structure for the Surface Warfare Officer Model. Movement of Aviation Officers between subcommunities is infrequent--a fact which tends to focus manpower management on the weapon system type. On the other hand, Surface Warfare Officers move freely between classes and types so that, while class and type are important to requirements specification, there is no need for independent processing of subcommunities. Therefore, there would be no subdivisions of the Surface Warfare Officer community.

The Aviation Officer Requirements Model partitions requirements into four grade levels: LT, LCDR, CDR, SENIOR CDR). Two changes would be required in a Surface Warfare Officer Model.

- The grade of Captain (06) would be added. Aviation Officer requirements, by definition, include only Commanders and below. On the other hand, Surface Warfare Officer requirements include the grade of Captain. This grade would replace the artificially-created grade of Senior Commander.

- At the lower end of the grade scale, the LT and below category would be divided to separate Lieutenants from LTJG and below. Aviation Officers receive entry level training in a separate undergraduate training activity and become manpower resources upon designation at the completion of that training. Undergraduate training can thus be treated as a single network source for both inventory and requirements specification. Surface Warfare Officers proceed from initial training to a shipboard assignment. However, they are not designated Surface Warfare Officers until an initial qualification period aboard ship has been completed. This means that significant numbers of junior shipboard billets are filled by undesignated general line officers. Division of the lower grade requirement will provide a means of accounting for this phenomenon. The division is proposed at the LTJG rather than the Ensign level because a review of several ship manning documents revealed that there probably were not enough Ensign billets specified in requirements documents to permit accounting for all of the undesignated fills likely to occur at normal personnel flows. It is recognized that some allocation rule will have to be defined to segregate undesignated from designated Lieutenants Junior Grade.

A Surface Warfare Officer Model would specify requirements at five grade levels:

- Lt JG and Ensign
- Lieutenant
- Lieutenant Commander
- Commander
- Captain

C. INVENTORY SPECIFICATIONS

The fundamental shape of the officer inventory curve as a function of years of service will be the same for Surface Warfare Officers as for Aviation Officers. The shape will be specified by a continuation vector reflecting the year-to-year changes in Surface Warfare Officer inventory. This will also be linked to a retention specification. Differences in detail will be evident as follows:

- The time axis will specify years of commissioned service rather than years since designation.

- Captains will not leave the inventory. Therefore the sharp break evident at roughly the 20 year point will be reduced since it will reflect only early retirements

- Because of the inclusion of Captains in the inventory the model time frame will be extended to 30 years.

- Unrestricted Line Officer (11XX) continuation rates will have to be adjusted to reflect Surface Warfare (1110) continuation. Because of the nature of the accession process, decribed above, a Surface Warfare continuation vector may show continuation rates greater than unity in the early years of commissioned service.

D. CAREER PATH NETWORK

The major changes in the career path network for Surface Warfare Officers will be the extension in time covered to a nominal ten tours and the redefinition of activities represented. The increased number of tours results from the addition of Captains to the inventory at the senior end of the time scale and the addition of pre-designation commissioned time at the junior end. The definition of activities depends on analysis of Surface Warfare Officer career paths and the significance of career path considerations as constraints on the

56

manpower planner. The definitions suggested in this Section are highly ten-tative, being based for the most part on discussions with experienced Surface Warfare Officers. It may well be that detailed analysis of the Surface Warfare Officer Billet Structure and detailing patterns will suggest alter-native activity definitions. In view of the fact that the Surface Warfare designation is only a little more than ten years old, an analysis of this type is an obvious first step in the actual construction of a model.

The primary reason for including career path constraints in a requirements model is to ensure that plans based on that model account for the need to develop certain skills and experience levels in the inventory over time. The specification of a billet title and grade level generally implies the existence in the inventory of personnel with a fairly explicit set of skills gained in past assignments. Thus, personnel assignment has two objectives: the filling of immediate requirements and the development of the inventory so that future requirements can also be met. A useful planning tool must account for both of these objectives.

The Aviation Officer Requirements Model accounted for skill/experience requirements in two ways: First, set of general background requirements are defined by the seven activity definitions. Second, more explicit set of war-fare skills are implicit in the 23 defined subcommunities. For example, a body of expertise in Anti-Air Warfare is established in the definition of the VF (Fighter) and Early Warning (VAW) Subcommunities. Since subcommunities are not envisioned for a Surface Warfare Officer Model, it was necessary to accom-modate some specific skill/experience identifiers in the activity definitions of the career path network.

57

Surface ships in the Navy can be placed in one of three categories depending on their fundamental mission. These are:

- Fleet Combatants
- Amphibious Ships
- Fleet Auxiliaries

There are specialized skills associated with the operation and handling of ships in each of these categories. It is important that the Surface Warfare Officer inventory contain officers with experience in each of these mission areas. Therefore, they are specified as separate Surface Warfare Officer Activities governing both requirements partitioning and inventory distribution.

The three activities identified above correspond to the Fleet Squadron Activity of the Aviation Officer Requirements Model; that is, Aviation Officers are primarily needed to operate fleet aircraft and Surface Warfare Officers are primarily needed to operate fleet ships. Subdividing the activity in the case of Surface Warfare Officers makes the structure of the requirement visible, and in addition, provides the opportunity for a degree of user control. In specifying network arcs, the user can either permit or inhibit flow between these activities.

Arc capacity constraints can also be employed to limit flows between activities. In fact, the user will have available a range of options from completely free flow between activities to complete isolation of activities. The first extreme would represent the way the Surface Warfare Officer community is managed, while the second would approximate the subcommunity structure of the Aviation Officer Requirements Model.

In addition to ship's company assignments, Surface Warfare Officers are also required on afloat staffs. This Afloat Activity corresponds to the

Afloat Assignments Activity of the Aviation Officer Requirements Model.

The fifth activity identified for the Surface Warfare Officer Requirements Model is Professional Training. This is intended to make visible the significant training provided by Surface Warfare Officer schools at the department head and command level. It is envisioned that the model would implicitly specify flows to this activity as a function of flows to shipboard billets.

The remaining two activities proposed for the Surface Warfare Officer Requirements Model, Professional Education and Other, are identical to those defined for the Aviation Officer Requirements Model.

In summary, seven career activities are proposed for a Surface Warfare Officer Requirements Model:

- Fleet Combatants
- Amphibious Forces
- Fleet Auxiliaries
- Professional Training
- *Afloat Staffs*
- Professional Education
- Other

Figure 4 is an example of a Surface Warfare Officer career path network. The arcs selected show all source flow going to activities 1-3 for the first tour. These flows then divide between Professional Education and OTHER for a second tour which is assumed to be ashore. These in turn, divide for the third tour covering all possible destination activities. Beyond the third tour no attempt is made to portray all possible arcs, instead, typical flows to shipboard department head and command tours are depicted. It is important to note that the three year tour length depicted in the diagram is nominal. The model user would have the capability of specifying the actual tour length in months, for every model destination node.

The analysis of the Surface Warfare Officer community, while tentative with respect to some fairly important details, demonstrates the feasibility of implementing a Surface Warfare Officer Requirements Model that is functionally similar to the Aviation Officer Requirements Model. The major changes required are elimination of the subcommunity structure and redefinition of career activities. Other changes might be necessary after detailed analysis of the Surface Warfare Officer billet structure, but based on experience with the Aviation Officer Requirements Model, such changes should be minor in nature. Overall, the model would be somewhat less complicated than the Aviation Officer Model and require significantly shorter execution time on the computer.

YEARS OF COMMISSIONED SERVICE

FIGURE 4

SURFACE WARFARE OFFICER CAREER PATH NETWORK

60

VI. CONCLUSION

Previous sections of this report have attempted to achieve three main goals:

- Describe the process by which manpower requirements are determined in the context of the Planning, Programming, and Budgeting process by which personnel resources are obtained. The central theme of that discussion was the contrast between the potential long term consequences of manpower decisions and the relatively short planning horizon of the PPBS.

- Describe a planning tool, the Aviation Officer Requirements Model, which allows consideration of both the long and short term consequences of manpower decisions in the planning process.

- Demonstrate some ways in which the model can be applied as a planning tool. The model is necessarily complex. An understanding of Aviation Officer manpower requirements on the part of the user is presumed. However, no computer expertise is required. It is a menu driven, "user friendly" model.

In addition, the general applicability of the basic modeling technique to other officer communities has been demonstrated by developing the basic outline of a Surface Warfare Officer Requirements Model.

A final word of stress on a point repeatedly made in this report: the Aviation Officer Requirement Model is a tool. Hammers and saws do not build houses, carpenters do; computer programs do not make plans, planners do. Good planners, like good carpenters, are distinguished by the skill with which they use their tools.

BIBLIOGRAPHICAL REFERENCES

Hillier, F.B., and Lieberman, C.J. Introduction to Operations Research. San Francisco: Holden Day, Inc., August 1967.

O'Connor, F.E. Aviation Officer Requirements Study. ISI Report No. V-2693-01. Arlington, Virginia: Information Spectrum, Inc., 31 May 1982.

U.S. Department of Defense, OASD (MR&L). Manpower Requirements Report FY 1984. Washington, D.C.: February 1983.

Wagner, H.M. Principles of Operations Research. San Francisco: Holden-Day, Inc., August 1967.

APPENDIX A

AVIATION OFFICER REQUIREMENTS MODEL

USER'S GUIDE

The objective of this appendix is to provide non-ADP personnel with the information necessary to effectively use the Aviation Officers Requirements Model.

The Aviation Officers Requirements Model provides an automated capability to effectively deal with officer requirements determinations through interactive, user-friendly processing.

The user of the Aviation Officer Requirements Model must know how to initiate and stop computer processing as well as how to use the system to produce useful results. This appendix is presented in such a way as to walk the user through the system from start to finish and provide an example to every screen or option possible. Use of this appendix should make the Aviation Officer Requirements Model easy to operate for all personnel. While the model is designed for personnel with limited computer experience, it is assumed that users are familiar with the Aviation Officer Requirements Determination process.

On the next page of this appendix is a picture of the computer keyboard and a brief explanation of the user entry keys, which are used for the majority of the interactions in the Aviation Officer Requirements Model. An explanation of the cursor control keys and parameter definitions are also provided.

THE KEYBOARD

I. SPECIAL KEYS

1. ENTER key
    - The normal means of terminating user entry and requesting the program to process data. SHIFT does not affect the action of ENTER, and ENTER is not honored while the keyboard data entry keys are locked.

2. PF key
    (Program Function)
    - Most command options in response to screen menus are entered by use of the PF keys. The values of the 16 PF keys are affected by the SHIFT key. Thus there are 32 Program Functions keys. Next to the description of each option on the display is the number of one of the PF keys. Command options are entered by pressing the appropriate PF key.

A-2

All keys have the capability of being turned off or on. When the user is asked to make a PF or "ENTER" key selection, only those keys are turned on. If an off key is pressed, the workstation alarm will sound as a warning that an invalid key was pressed and another key selection should be made.

II. CURSOR CONTROL KEYS

1. TAB key

- Many screens present predefined fields in which entries can be made. By using the "TAB" key the cursor jumps only to those predefined fields freeing the user from having to count spaces.

2. ARROW keys

- There are four directions the user can move the cursor: up, down, right and left. These arrow keys position the cursor without regard for the presence of predefined fields. They can position the cursor at any location on the screen and provide automatic repeat for as long as the key is pressed. All keys also have a wraparound feature. For example, if the cursor is positioned in the top row, and the user presses the up arrow, the cursor moves to the bottom row in the same column.

III. PARAMETERS

1. Defined (on screen)

- Most parameters are set initially to default values (See default values) and the user can either change them to suit his purpose or continue using those values. To change a parameter value, position the cursor (cursor control keys) under the variable to be

changed, and then type over it. If the new variable is smaller than the previous variable, use the space bar to delete those extra characters.

2. Defined

    (off screen)

    - Some paramet r fields initially appear with blanks, and the the user can enter parameter values in these fields. To make entries, position the cursor (via TAB key) and type in the information. If left blank, the model automatically uses default values.

3. Entering

    - Once parameters are set, the user should press "ENTER" unless otherwise specified. The cursor position is unimportant with regard to "ENTER", but make sure all parameters are correct before entering.

```
***** ........ 1 ....... 2 ....... 3 ....... 4 ....... 5 ....... 6 ....... 7 ....... 8 *****
**** 12345678901234567890123456789012345678901234567890123456789012345678901234567890 ****
********************************************************************************
*  *                                                                        * *
* 1*                                                                        * 1*
* 2*    *****************************************************************    * 2*
* 3*    *                                                               *    * 3*
* 4*    *          AVIATION OFFICER REQUIREMENTS MODEL                  *    * 4*
* 5*    *                                                               *    * 5*
* 6*    *****************************************************************    * 6*
* 7*                                                                        * 7*
* 8*    THE AVIATION OFFICER REQUIREMENTS MODEL DETERMINES THE              * 8*
* 9*    NUMBER OF NAVAL AVIATORS OR NAVAL FLIGHT OFFICERS REQUIRED          * 9*
*10*    IN RESPONSE TO THE SPECIFICATION OF OFFICER RETENTION AND           *10*
* 1*    A NUMBER OF FORCE LEVEL AND CAREER PLANNING PARAMETERS              * 1*
* 2*                                                                        * 2*
* 3*    THE MODEL TREATS NAVAL AVIATORS AND NAVAL FLIGHT OFFICERS           * 3*
* 4*    SEPARATELY, AND BY COMMUNITY.  IT IS PRESENTLY SET TO WORK          * 4*
* 5*    ON NAVAL AVIATORS IN THE LIGHT ATTACK COMMUNITY                     * 5*
* 6*                                                                        * 6*
* 7*                                                                        * 7*
* 8*    TO CONTINUE WORKING IN THIS COMMUNITY PRESS       'ENTER'           * 8*
* 9*    TO BEGIN A NEW COMMUNITY OF AVIATORS   PRESS      PF 1              * 9*
*20*    TO BEGIN A NEW COMMUNITY OF NFOS       PRESS      PF 2              *20*
* 1*    TO MAKE MULTIPLE COMMUNITY RUNS        PRESS      PF 3              * 1*
* 2*    TO RESET MODEL TO DEFAULT VALUES       PRESS      PF 15             * 2*
* 3*                                                                        * 3*
* 4*    TO END PROCESSING                      PRESS      PF 16             * 4*
*  *                                                                        * *
********************************************************************************
**** ........ 1 ....... 2 ....... 3 ....... 4 ....... 5 ....... 6 ....... 7 ....... 8 ****
**** 12345678901234567890123456789012345678901234567890123456789012345678901234567890 ****
********************************************************************************
```

COMMUNITY SECTIONS MENU SCREEN

This screen acts as the Control Screen. It permits one to enter
and exit the program. On entry to the program, the above display
will be presented on the work station screen. Notice the words
NAVAL AVIATOR and LIGHT ATTACK; they have been underlined in the
above picture but will appear as flashing words on the display
screen. These words flash to indicate the current model status.
On entering the program, all variables are predefined to default
values (see Appendix C).

The user has one of five Run options to choose from:

1) Continue working in the Community which appears flashing
    on the screen (see A-10).
2) Begin working in a new Community of AVIATORS. (See A-8)
3) Begin working in a new Community of NAVAL FLIGHT OFFICERS
    (NFOs) (see A-9).
4) Make multiple Community runs (see A-19).
5) End processing (Note - on command of End processing,
    which causes exit from the program, printed output from
    the program run will begin).

A-5

SINGLE COMMUNITY RUN

The following pages A-7 to A-18 explain and describe the screens
in SINGLE COMMUNITY RUN processing. Figure A-1 of this section
is a basic flow diagram showing the logical sequence of screens
displayed in SINGLE COMMUNITY mode. The remainder of this sec-
tion is devoted to a detailed description of each screen shown
in the flow diagram.

AVIATIONAL OFFICER
REQUIREMENTS MODEL
SINGLE RUN MODE

VER.(7.1)

KEY

E:ENTER
PF:PROGRAM FUNCTION
():AUTOMATIC DECISION

FIGURE A-1

A-7

```
****************************************************************************
****         1         2         3         4         5         6         7         8   ****
**** 1234567890123456789012345678901234567890123456789012345678901234567890 ****
****************************************************************************
* *                                                                        * *
* 1*                                                                       * 1*
* 2*                                                                       * 2*
* 3*              NAVAL AVIATION COMMUNITY SELECTION                       * 3*
* 4*                                                                       * 4*
* 5*        YOU MAY SELECT FROM AMONG FOURTEEN COMMUNITIES IN WHICH        * 5*
* 6*        NAVAL AVIATORS ARE REQUIRED.  THEY ARE LISTED BELOW.  BY       * 6*
* 7*        PRESSING THE PF KEY CORRESPONDING TO THE ITEM NUMBER ON        * 7*
* 8*        THE LIST YOU WILL SELECT NAVAL AVIATORS IN THAT COMMUNITY      * 8*
* 9*        FOR ANALYSIS.                                                  * 9*
*10*                                                                       *10*
* 1*     PF KEY   COMMUNITY                    PF KEY    COMMUNITY         * 1*
* 2*                                                                       * 2*
* 3*        1     LIGHT ATTACK                   8      MARITIME PATROL    * 3*
* 4*        2     FIGHTER                        9      LAMPS MK I         * 4*
* 5*        3     MEDIUM ATTACK                 10      LAMPS MK III       * 5*
* 6*        4     EARLY WARNING    VAW          11      ELECTRONIC WARFARE   VXI  * 6*
* 7*        5     ELECTRONIC WARFARE  VAQ       12      FLEET AIR SUPPORT  FLT   * 7*
* 8*        6     CARRIER BASED ASW            13      FLEET SUPPORT       FSAW  * 8*
* 9*        7     HELICOPTER ASW               14      FORCE SUPPORT       HELO  * 9*
*20*                                                                       *20*
* 1*                                                                       * 1*
* 2*                                                                       * 2*
* 3*        TO RETURN TO BASIC MENU WITHOUT MAKING A SELECTION   PRESS ENTER  * 3*
* 4*                                                                       * 4*
* *                                                                        * *
****************************************************************************
****         1         2         3         4         5         6         7         8   ****
**** 1234567890123456789012345678901234567890123456789012345678901234567890 ****
****************************************************************************
```

NAVAL AVIATION COMMUNITY SELECTION MENU SCREEN

By pressing the PF-1 key when the Community Selection Screen
(S1) is displayed, the above screen (S2) will appear. This
screen allows the user to select one of 14 Subcommunities in
which NAVAL AVIATORS are required. By pressing one of the 14
PF-keys, the user will enter that corresponding Subcommunity for
analysis. By pressing the "Enter" key, the user will return to
the Community Selection Screen (S1) without altering the current
subcommunity selection.

```
**********************************************************************************
****    1      2      3      4      5      6      7      8   ****
****  12345678901234567890123456789012345678901234567890123456789012345678901234567890  ****
**********************************************************************************
*  *                                                                      *  *
* 1*                                                                      * 1*
* 2*                                                                      * 2*
* 3*            NAVAL FLIGHT OFFICER COMMUNITY SELECTION                  * 3*
* 4*                                                                      * 4*
* 5*     YOU MAY SELECT FROM AMONG NINE COMMUNITIES IN WHICH             * 5*
* 6*     NAVAL FLIGHT OFFICERS ARE REQUIRED.  THESE ARE LISTED          * 6*
* 7*     BELOW.  BY PRESSING THE PF KEY CORRESPONDING TO THE            * 7*
* 8*     ITEM NUMBER ON THE LIST YOU WILL SELECT NFO'S IN THAT          * 8*
* 9*     COMMUNITY FOR ANALYSIS.                                         * 9*
*10*                                                                      *10*
* 1*               PF KEY          COMMUNITY                              * 1*
* 2*                                                                      * 2*
* 3*                  1      FIGHTER                                      * 3*
* 4*                  2      MEDIUM ATTACK                                * 4*
* 5*                  3      EARLY WARNING    VAW                         * 5*
* 6*                  4      ELECTRONIC WARFARE    VAK                    * 6*
* 7*                  5      CARRIER BASED ASW                            * 7*
* 8*                  6      MARITIME PATROL                              * 8*
* 9*                  7      ELECTRONIC WARFARE    VQ                     * 9*
*20*                  8      FORCE SUPPORT    JET                         *20*
* 1*                  9      FORCE SUPPORT    PROP                        * 1*
* 2*                                                                      * 2*
* 3*     TO RETURN TO BASIC MENU WITHOUT MAKING A SELECTION   PRESS ENTER * 3*
* 4*                                                                      * 4*
*  *                                                                      *  *
**********************************************************************************
****    1      2      3      4      5      6      7      8   ****
****  12345678901234567890123456789012345678901234567890123456789012345678901234567890  ****
**********************************************************************************
```

NAVAL FLIGHT OFFICER (NFO) COMMUNITY SELECTION SCREEN

If the user selected the PF-2 key while the Community Selection
Screen (S1) appeared, the above screen will be displayed. This
screen allows the user to select one of the nine Subcommunities
in which NFOs are required.   By pressing one of the nine
PF-keys, the user will enter the corresponding Subcommunity for
analysis.   If the user wishes to return to the Community
Selection Screen (S1), press the "ENTER" key.

- NOTE -

When returning to the Community Selection Screen (S1), the Com-
munity and Subcommunity, which appear flashing, indicate the
current area for analysis.

A-9

```
•••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••
••••          1         2         3         4         5         6         7         8 ••••
••••  123456789012345678901234567890123456789012345678901234567890123456789012345678901  ••••
•••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••
•  •                                                                                • •
•  1•                                                                              • 1•
•  2•                                                                              • 2•
•  3•                                                                              • 3•
•  4•                                                                              • 4•
•  5•     ••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••         • 5•
•  6•     •                                                              •         • 6•
•  7•     •              WORKING IN NAVAL AVIATION                       •         • 7•
•  8•     •                                                              •         • 8•
•  9•     •                         IN                                   •         • 9•
•10•      •                                                              •         •10•
•  1•     •              LIGHT ATTACK COMMUNITY                          •         • 1•
•  2•     •                                                              •         • 2•
•  3•     ••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••         • 3•
•  4•                                                                              • 4•
•  5•                                                                              • 5•
•  6•     DO YOU DESIRE IN-PROCESS MONITORING?            YES     (YES/NO)          • 6•
•  7•                                                                              • 7•
•  8•     DO YOU DESIRE UPWARD DETAILING?                 YES     (YES/NO)          • 8•
•  9•                                                                              • 9•
•20•                                                                               •20•
•  1•                                                                              • 1•
•  2•                                                                              • 2•
•  3•                                                                              • 3•
•  4•     PRESS ENTER TO CONTINUE                                                  • 4•
•  •                                                                                • •
•••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••
••••          1         2         3         4         5         6         7         8 ••••
••••  123456789012345678901234567890123456789012345678901234567890123456789012345678901  ••••
•••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••••
```

COMMUNITY VERIFICATION AND RUN OPTIONS

Screen S4 (above) identifies the Subcommunity the model is
currently concerned with and allows the user to select run
options. IN-PROCESS MONITORING allows the user to see inter-
mediate results between iterations. The user may also run the
system with minimal interaction by typing "NO" in place of "YES"
for IN-PROCESS MONITORING.

UPWARD DETAILING allows the system to assign officers to require-
ments of the next higher grade when all requirements at the
current grade level have been met. If the user doesn't want
Upward Detailing, type "NO" in place of "YES".

-NOTE-

If the user initially entered "YES" for IN-PROCESS MONITORING,
he will later have the option to change this status after every
complete iteration.

```
********************************************************************
****        1        2        3        4        5        6        7        8  ****
****  1234567890123456789012345678901234567890123456789012345678901234567890  ****
********************************************************************
*  *                                                                      *  *
*  1*                                                                      *  1*
*  2*                                                                      *  2*
*  3*                                                                      *  3*
*  4*                                                                      *  4*
*  5*       THE AVIATION OFFICER REQUIREMENTS MODEL IS LOADED WITH         *  5*
*  6*       NOMINAL VALUES OF PARAMETERS REQUIRED TO DETERMINE THE         *  6*
*  7*       REQUIREMENT FOR NAVAL AVIATORS IN THE LIGHT ATTACK             *  7*
*  8*       COMMUNITY                                                      *  8*
*  9*                                                                      *  9*
*10*        YOU CAN REVIEW AND/OR ALTER THESE PARAMETERS BY PRESSING THE   *10*
*  1*        PF KEY CORRESPONDING TO THE ITEM NUMBERS IN THE LIST OF       *  1*
*  2*        PARAMETER CATEGORIES GIVEN BELOW.  THIS ACTION WILL CALL UP   *  2*
*  3*        A LIST OF THE INDICATED PARAMETERS WITH THEIR CURRENT VALUES  *  3*
*  4*                                                                      *  4*
*  5*                PF KEY      PARAMETER CATEGORY                        *  5*
*  6*                   1        BASIC COMMUNITY DATA                      *  6*
*  7*                   2        TRAINING REQUIREMENTS DATA                *  7*
*  8*                   3        POLICY VARIABLES                          *  8*
*  9*                   4        ALLOCATION PARAMETERS                     *  9*
*20*                   5        CAREER PATH NETWORK                        *20*
*  1*                                                                      *  1*
*  2*                                                                      *  2*
*  3*        TO RETURN TO COMMUNITY SELECTION MENU PRESS 'PF 16'           *  3*
*  4*        TO CONTINUE PROGRAM WITHOUT PARAMETER REVIEW PRESS 'ENTER'    *  4*
*  *                                                                      *  *
********************************************************************
****        1        2        3        4        5        6        7        8  ****
****  1234567890123456789012345678901234567890123456789012345678901234567890  ****
********************************************************************
```

PARAMETER CATEGORY MENU SCREEN

This screen appears after screen S5 and screens S8-S13. It
allows the user to enter each of the five parameter categories in
order to inspect and/or change existing parameters. To inspect
any parameter category, select the corresponding PF-key. The
user may also return to the Community Selection Menu Screen (S1)
by pressing the PF-16 key. If the user wishes to bypass the
parameter review he may do so by pressing the "ENTER" key.

```
BASIC COMMUNITY DATA
LIGHT ATTACK NAVAL AVIATORS


                    PARAMETER          CURRENT VALUE
        NUMBER OF SQUADRON               24
        AIRCRAFT PER SQUADRON            12
        CREW FACTOR                      1.42
        NAVAL AVIATORS PER CREW          1.00

        SQUADRON GRADE DISTRIBUTION
                COMMANDERS               2
                LT. COMMANDERS           4
                LIEUTENANTS              11

        UPWARD DETAIL PERCENTAGE         20
        COMMUNITY RETENTION              45 PER CENT
        NUMBER OF CARRIER AIR WINGS      12


        PRESS ENTER TO RECORD CHANGES AND CONTINUE
```

BASIC COMMUNITY DATA SCREEN (PARAMETER REVIEW)

This screen displays the current value of basic parameters for the subcommunity being processed. The user may change one, none, or all existing parameters. The user should be aware that changes to the parameters CREW FACTOR and NAVAL AVIATORS PER CREW, will affect only the number of Lieutenants per squadron. The Commander and Lieutenant Commander parameters will remain unchanged. If Commander/Lieutenant Commander parameters are changed the adjustment of Lieutenant parameters is automatic and squadron grade distribution will conform to user specification. In order to record any changes and continue with the program, press "Enter". Upon doing so, the program will return to Screen S5 (Parameter Category Menu) allowing the user to make further changes or bypass the parameter review.

```
TRAINING REQUIREMENTS DATA
LIGHT ATTACK NAVAL AVIATORS


FLEET READINESS SQUADRONS (AGGREGATE REQUIREMENTS)
        COMMANDERS               *8
        LT. COMMANDERS           20
        LIEUTENANTS              *85

UNDERGRADUATE TRAINING     STRIKE TRAINING PIPELINE
        COMMANDERS               22
        LT. COMMANDERS           44
        INSTRUCTOR PILOTS PER GRADUATE    *.1800
        INSTRUCTOR NFOS PER GRADUATE      0.000



PRESS ENTER TO RECORD CHANGES AND CONTINUE
```

TRAINING REQUIREMENTS DATA SCREEN (PARAMETER REVIEW)

This screen displays the current value of the parameters within TRAINING REQUIREMENTS DATA. The user may change one, none, or all existing parameters to meet the necessary requirements. The user should be aware that the number of Lieutenants for undergraduate training is determined by the Instructor Planning Factors (Instructor Pilots per Graduate, Instructor NFOs per Graduate). In order to record any changes and continue with the program, press "Enter". Upon doing so, the program will return to Screen S5 allowing the user to make further changes or bypass the parameter review.

```
************************************************************************
****      1       2       3       4       5       6       7       8 ****
**** 123456789012345678901234567890123456789012345678901234567890123456 ****
************************************************************************
*  *
* 1*
* 2*              PROMOTION FLOW POINTS AND POLICY VARIABLES          * 2*
* 3*                   LIGHT ATTACK NAVAL AVIATORS                    * 3*
* 4*     **********************************************************   * 4*
* 5*                                                                  * 5*
* 6*                      PROMOTION FLOW POINTS                       * 6*
* 7*                                                                  * 7*
* 8*  COMM                                                            * 8*
* 9*                                                                  * 9*
*10*    0*1*2*3*4*5*6*7*8*9*10*11*12*13*14*15*16*17*18*19*20*21*22*23* 34  *10*
* 1*          *********************************************          * 1*
* 2*  DESIG              4              5                             * 2*
* 3*          *********************************************          * 3*
* 4*                                                                  * 4*
* 5*                      POLICY VARIABLES                            * 5*
* 6*                                                                  * 6*
* 7*  PLOWBACK INSTRUCTORS (FRACTION OF GRADUATES)       *.05         * 7*
* 8*  POSTGRADUATE FLOW (FRACTION OF 12 YEAR COHORT)     *.30         * 8*
* 9*  WAR COLLEGE FLOW (FRACTION OF 18 YEAR COHORT)      *.50         * 9*
*20*                                                                  *20*
* 1*          *********************************************          * 1*
* 2*                                                                  * 2*
* 3*  PRESS PF 1 TO RECORD CHANGES AND REDISPLAY                      * 3*
* 4*  PRESS ENTER TO RECORD CHANGES AND CONTINUE                      * 4*
*  *
************************************************************************
****      1       2       3       4       5       6       7       8 ****
**** 123456789012345678901234567890123456789012345678901234567890123456 ****
************************************************************************
```

PROMOTION FLOW/POLICY VARIABLES SCREEN (PARAMETER REVIEW)

This screen allows the user to change both Promotion Flow Points and Policy Variables. The Promotion Flow Points section of this screen is a bargraph representing years of commissioned service. Up-arrows under the graph show the promotion flow points to the grades of Lieutenant Commander and Commander (4 for LCDR, 5 for CDR). To change promotion flow points, position the cursor under the desired number of years and enter the appropriate number (4 or 5). (Note that entries made with years consisting of two digits (i.e., 10), the number (4 or 5) may be placed under either digit.) Half year promotion flow points (i.e., 10.5 years) may be selected by positioning the entry under the asterisk between numbers. Also note that both entries (4 & 5) must be made if any change is made. If either entry is left out, the resulting promotion flow point parameters will be inaccurate.

The Policy Variables section of this screen allows the user to enter different policy alternatives. PLOWBACK INSTRUCTORS are the fraction of training command graduates assigned immediately as instructors in undergraduate training. POSTGRADUATE FLOW is the fraction of the 12 year cohorts with a graduate level education. WAR COLLEGE FLOW is the fraction of 18 year cohorts with a war college education To record changes and redisplay variables press PF-1. To record changes and continue press "ENTER".

A-14

```
****                1         2         3         4         5         6         7         8 ****
****  1234567890123456789012345678901234567890123456789012345678901234567890123456789012345 ****
*  *                                                                                       *  *
*  1*                                                                                      *  1*
*  2*                                                                                      *  2*
*  3*                                                                                      *  3*
*  4*                                                                                      *  4*
*  5*                          ALLOCATION PARAMETERS                                       *  5*
*  6*                        LIGHT ATTACK NAVAL AVIATION                                   *  6*
*  7*                                                                                      *  7*
*  8*                                                                                      *  8*
*  9*                                                                                      *  9*
* 10*                                                                                      * 10*
*  1*                                                                                      *  1*
*  2*         FRACTION OF ALL NAVAL AVIATORS                    *.1048                      *  2*
*  3*                                                                                      *  3*
*  4*         FRACTION OF STRIKE NAVAL AVIATORS                 *.2690                      *  4*
*  5*                                                                                      *  5*
*  6*         FRACTION OF CARRIER NAVAL AVIATORS                *.2000                      *  6*
*  7*                                                                                      *  7*
*  8*         FRACTION OF ALL AVIATION OFFICERS                 *.0729                      *  8*
*  9*                                                                                      *  9*
* 20*                                                                                      * 20*
*  1*         *******************************************************************          *  1*
*  2*                                                                                      *  2*
*  3*                                                                                      *  3*
*  4*         PRESS ENTER TO RECORD CHANGES AND CONTINUE                                   *  4*
*  *                                                                                       *  *
****                1         2         3         4         5         6         7         8 ****
****  1234567890123456789012345678901234567890123456789012345678901234567890123456789012345 ****
```

ALLOCATION PARAMETERS SCREEN (PARAMETER REVIEW)

This screen displays the ALLOCATION PARAMETERS which the model
will use in assigning fractions of general Aviation Officer
requirements to the Subcommunity under investigation. The user
should note that a change to any allocation fraction will cause
an automatic adjustment in fractions for all other Subcom-
munities. (Note that the sum of allocation fractions across all
affected subcommunities equals one.) The "ENTER" key causes
changes to be recorded and adjustments to be made. Control is
returned to screen S5.

A-15

```
****...........................................................................**...
*       1         2         3         4         5         6         7         8 ****
****  12345678901234567890123456789012345678901234567890123456789012345678901234 7890 ****
****...........................................................................**...
*  *                                                                            *  *
*  1*                                                                           *  1*
*  2*        YOU CAN INSPECT AND/OR MODIFY THE CAREER PATH NETWORK CHARACTERISTICS  * 2*
*  3*        ASSOCIATED WITH ANY NODE IN THE NETWORK.  TO SELECT A PARTICULAR NODE  * 3*
*  4*        REPLACE THE 'O' IN THE DIAGRAM BELOW WITH AN 'X'.  TO BYPASS A NODE    * 4*
*  5*        PRESS 'TAB'.                                                        *  5*
*  6*                                                                           *  6*
*  7*                                       TOUR NUMBER                         *  7*
*  8*                                                                           *  8*
*  9*               ACTIVITY            1   2   3   4   5   6   7               *  9*
* 10*                                                                          * 10*
*  1*           FLEET TOURS             o   o   o   X   o   o   o              *  1*
*  2*           FLEET READINESS SQUADRON  o  o   o   o   o   o   o             *  2*
*  3*           TRAINING COMMAND         o   o   o   o   o   o   o             *  3*
*  4*           R&D COMMUNITY            o   o   o   o   o   o   o             *  4*
*  5*           AFLOAT ASSIGNMENTS       o   o   o   o   o   o   o             *  5*
*  6*           PROFESSIONAL EDUCATION   o   o   o   o   o   o   o             *  6*
*  7*           OTHER                    o   o   o   o   o   o   o             *  7*
*  8*                                                                          *  8*
*  9*                                                                          *  9*
* 20*                                                                          * 20*
*  1*                                                                          *  1*
*  2*                                                                          *  2*
*  3*        TO BEGIN NODE INSPECTION/MODIFICATION PRESS         'ENTER'       *  3*
*  4*        TO RETURN TO CATEGORY MENU PRESS                    'PF-1'        *  4*
*  *                                                                            *  *
****...........................................................................**...
****                                                                          ****
****  12345678901234567890123456789012345678901234567890123456789012345678901234 7890 ****
****...........................................................................**...
*       1         2         3         4         5         6         7         8
```

CAREER PATH NETWORK SCREEN #1 (PARAMETER REVIEW)

This screen displays nodes for the Career Path Network. The user
can inspect and/or modify the characteristics associated with any
node. To inspect/modify a node, replace any "o" with an "x" in
the 'tour number' table and press "ENTER". Note that the user
may select as many nodes for inspection/modification as desired.
The TAB key will step the cursor from node to node in the
display. The control of the program continues with screen S11 if
a node/nodes are to be inspected/modified. Otherwise the control
returns to Screen S5.

A-16

```
                        1         2         3         4         5         6         7         8
       1234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890

  1                             NODE CHARACTERISTICS                                          1
  2                                                                                           2
  3        NODE CHARACTERISTICS ARE REFERRED TO THE OUTPUT END OF THE ARC                     3
  4        IN QUESTION.   THAT NODE IDENTIFIES THE ACTIVITY IN WHICH THE                      4
  5        OFFICER IS ENGAGED.   THE ACTIVITY AND TOUR NUMBER CURRENTLY                       5
  6        BEING EXAMINED IS:                                                                 6
  7                                                                                           7
  8            FLEET TOURS                     TOUR NUMBER  4                                  8
  9                                                                                           9
 10        FOR TOURS TERMINATING AT THAT NODE                                                10
  1        THE FOLLOWING VALUES APPLY:                                                        1
  2                                                                                           2
  3                             TOUR LENGTH      3X                                           3
  4                                                                                           4
  5            PRECEDENT NODE         STATE           PRECEDENT NODE          STATE           5
  6        FLEET TOURS                NNN         FLEET READINESS SQUADRON    XXX             6
  7        TRAINING COMMAND           XXX         R&D COMMUNITY               XXX             7
  8        AFLOAT ASSIGNMENTS         XXX         PROFESSIONAL EDUCATION      XXX             8
  9        OTHER                      XXX                                                     9
 20                                                                                          20
  1              NOTE - 'NNN' MEANS THAT THE PRECEDENT NODE IS BARRED                         1
  2                                                                                           2
  3                                                                                           3
  4        TO ENTER CHANGES PRESS                 'ENTER'                                     4

                        1         2         3         4         5         6         7         8
       1234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890
```

CAREER PATH NETWORK SCREEN #2 (PARAMETER REVIEW)

This screen reconfirms the activity and tour number that the user
has chosen to inspect/modify. At this point, the user may change
the value of the tour length for tours ending at that node. He
may also make available any of the seven pecedent nodes. Once
the user has made desired changes and is ready to record these
changes, he must depress "ENTER". This screen will appear for
each x that the user placed into the table on the previous screen
(S10). Once all x's have been inspected/modified, the program
will return the user to the Parameter Category Menu Screen (S5).

A-17

```
         1         2         3         4         5         6         7         8
  1234567890123456789012345678901234567890123456789012345678901234567890123456789




          YOU HAVE REQUESTED A CHANGE IN RETENTION FOR NAVAL AVIATORS
          IN THE LIGHT ATTACK COMMUNITY
          THIS WILL CAUSE A CHANGE IN THE CONTINUATION VECTOR.  THE FOUR
          PARAMETERS WHICH DEFINE THIS VECTOR ARE DISPLAYED BELOW FOR
          REVIEW AND/OR CHANGE


          RETENTION                        45 PER CENT

          MINIMUM SERVICE REQUIREMENT      *5 YEARS

          RETENTION POINT                  *7 YEARS

          CAREER STABLE POINT              11 YEARS


          ***************************************************************

          PRESS ENTER TO MAKE CONTINUATION VECTOR CHANGES
```

RETENTION SCREEN

If the user had previously requested a change in retention (S9),
the above screen will be displayed. A change in retention will
cause the Continuation Vector to change. This screen shows the
four parameters that determine the Continuation Vector and offers
the user the opportunity to change those parameters or continue
the process.

-NOTE-

This is the last screen before the program iterations start. To
follow execution and processing sequence turn to page A-33.

A-18

MULTIPLE COMMUNITY RUN

The following pages A-20 to A-32 explain and describe the screens in MULTIPLE COMMUNITY processing. Figure A-2 on the following page is a basic flow diagram showing the logical sequence of screens displayed in MULTIPLE RUN mode. The remainder of this section is devoted to a detailed description of each screen in the flow diagram.

AVIATIONAL OFFICER
REQUIREMENTS MODEL
MUITIPLE RUNS MODE

VER.(7.1)

FIGURE A-2

A-20

```
****************************************************************************
****      1         2         3         4         5         6         7         8  ****
**** 1234567890123456789012345678901234567890123456789012345678901234567890 ****
****************************************************************************
*  *                                                                        *  *
*  1*                                                                       *  1*
*  2*                 NAVAL AVIATION COMMUNITY SELECTION                    *  2*
*  3*                        (MULTIPLE RUNS)                                *  3*
*  4*                                                                       *  4*
*  5*      YOU MAY ARRANGE AVIATOR SUBCOMMUNITIES INTO GROUPS WITH          *  5*
*  6*      SIMILAR CHARACTERISTICS TO SIMPLIFY THE PROCESS OF DEFINING      *  6*
*  7*      PARAMETERS.  ASSIGN A SINGLE CHARACTER GROUP IDENTIFIER TO       *  7*
*  8*      EACH SUBCOMMUNITY BELOW.  ASSIGNMENT OF 'ZERO' OR 'SPACE'        *  8*
*  9*      WILL ELIMINATE THAT SUBCOMMUNITY FROM THE RUN                    *  9*
*10*                                                                        *10*
*  1*      COMMUNITY                GROUP      COMMUNITY            GROUP    *  1*
*  2*                                                                       *  2*
*  3*      LIGHT ATTACK               *        MARITIME PATROL       *      *  3*
*  4*      FIGHTER                    *        LAMPS M  I            *      *  4*
*  5*      MEDIUM ATTACK              *        LAMPS M  III          *      *  5*
*  6*      EARLY WARNING   VAW        *        ELECTRONIC WARFARE VW *      *  6*
*  7*      ELECTRONIC WARFARE  VAQ    *        FORCE SUPPORT   JET   *      *  7*
*  8*      CARRIER BASED ASW          *        FORCE SUPPORT   PROP  *      *  8*
*  9*      HELICOPTER ASW             *        FORCE SUPPORT   HELO  *      *  9*
*20*                                                                        *20*
*  1*      RUN DESCRIPTION:   ***********************************            *  1*
*  2*                                                                       *  2*
*  3*      TO RETURN TO BASIC MENU              PRESS    PF 10              *  3*
*  4*      TO CONTINUE WITH NFO SUBCOMMUNITIES  PRESS    'ENTER'           *  4*
*  *                                                                        *  *
****************************************************************************
****      1         2         3         4         5         6         7         8  ****
**** 1234567890123456789012345678901234567890123456789012345678901234567890 ****
****************************************************************************
```

NAVAL AVIATOR COMMUNITY SELECTION (MULTIPLE RUNS)

By pressing the PF-3 key while the Community Selection Screen
(S1) is displayed, the model adapts for multiple runs and shows
the above screen. This screen allows the user to group
Subcommunities with similar characteristics. This is done by
assigning the same alpha-character (group identifier) to all Sub-
communities that will be included in a given group. To eliminate
a Subcommunity from the run, put a "O" (ZERO) in the corresponding
group column. If Subcommunities are left blank (i.e., space),
the model will assign that Subcommunity by default values. To
continue with NFO SUBCOMMUNITIES, press "ENTER" (see next page).

A-21

```
********************************************************************************
****    1         2         3         4         5         6         7         8 ****
****  12345678901234567890123456789012345678901234567890123456789012345678901234567890 ****
********************************************************************************
*  *                                                                          *  *
*  1*                                                                         *  1*
*  2*              NAVAL FLIGHT OFFICER COMMUNITY SELECTIONS                  *  2*
*  3*                        (MULTIPLE RUNS)                                  *  3*
*  4*                                                                         *  4*
*  5*       NAVAL FLIGHT OFFICER SUBCOMMUNITIES MAY ALSO BE GROUPED           *  5*
*  6*       BY ASSIGNING GROUP IDENTIFIERS.  USE CAUTION IN ASSIGNING         *  6*
*  7*       GROUP IDENTIFIERS.  IF IDENTIFIER IS THE SAME AS ONE USED         *  7*
*  8*       FOR PILOTS THAT NFO SUBCOMMUNITY WILL BE INCLUDED WITH THE        *  8*
*  9*       PREVIOUSLY DEFINED PILOT GROUP                                    *  9*
* 10*                                                                         * 10*
*  1*                         COMMUNITY            GROUP                       *  1*
*  2*                                                                         *  2*
*  3*                    FIGHTER                      *                        *  3*
*  4*                    MEDIUM ATTACK                *                        *  4*
*  5*                    EARLY WARNING   VAW          *                        *  5*
*  6*                    ELECTRONIC WARFARE  VAQ      *                        *  6*
*  7*                    CARRIER BASED ASW            *                        *  7*
*  8*                    MARITIME PATROL              *                        *  8*
*  9*                    ELECTRONIC WARFARE   VQ      *                        *  9*
* 20*                    FORCE SUPPORT - JET          *                        * 20*
*  1*                    FORCE SUPPORT - PROP         *                        *  1*
*  2*                                                                         *  2*
*  3*        TO RETURN TO BASIC MENU             -  PRESS  PF 16               *  3*
*  4*        TO CONTINUE MULTIPLE COMMUNITY RUN     PRESS  ENTER              *  4*
*  *                                                                          *  *
********************************************************************************
****    1         2         3         4         5         6         7         8 ****
****  12345678901234567890123456789012345678901234567890123456789012345678901234567890 ****
********************************************************************************
```

NFO'S COMMUNITY SELECTIONS (MULTIPLE RUNS)

When "ENTER" is pressed while the NAVAL AVIATOR COMMUNITY
SELECTIONS (multiple runs) screen (S4) is displayed, the model
continues with NFOs Community Selections (multiple runs). This
allows the user to create Subcommunities as on the previous page
(A-21). If the user wishes to return to the Community Selection
Menu Screen (S1), press PF-16. Otherwise, press "ENTER" to con-
tinue.

(Note - if the user uses the same group identifier for both
PILOTS AND NFO's they will be assigned to the same group.)

```
**************************************************************************************
****        1       2       3       4       5       6       7       8  ****
****  123454 7B9012345 7B9012345 7P90123454 7B9012345 7B90123454 7B9012345 7B90123454 7B90  ****
**************************************************************************************
*  *                                                                            *  *
*  1*                                                                           *  1*
*  2*                                                                           *  2*
*  3*                                                                           *  3*
*  4*                                                      GROUP  A             *  4*
*  5*   **********************************************************              *  5*
*  6*   *                                                        *              *  6*
*  7*   *            WORKING ON NAVAL AVIATION                   *              *  7*
*  8*   *                                                        *              *  8*
*  9*   *                     IN                                 *              *  9*
*10*   *                                                        *              *10*
*  1*   *            LIGHT ATTACK COMMUNITY                      *              *  1*
*  2*   *                                                        *              *  2*
*  3*   **********************************************************              *  3*
*  4*                                                                           *  4*
*  5*                                                                           *  5*
*  6*   DO YOU DESIRE IN PROCESS MONITORING?        NO    (YES/NO)             *  6*
*  7*                                                                           *  7*
*  8*   DO YOU DESIRE UPWARD DETAILING?             YES   (YES/NO)             *  8*
*  9*                                                                           *  9*
*20*                                                                           *20*
*  1*                                                                           *  1*
*  2*                                                                           *  2*
*  3*                                                                           *  3*
*  4*   PRESS ENTER TO CONTINUE                                                *  4*
*  *                                                                            *  *
**************************************************************************************
****        1       2       3       4       5       6       7       8  ****
****  123454 7B9012345 7B9012345 7P90123454 7B9012345 7B90123454 7B9012345 7B90  ****
**************************************************************************************
```

COMMUNITY VERIFICATION AND RUN OPTIONS (MULTIPLE RUN)

This screen is functionally identical to screen S4 in single run
mode (see A-10).

NOTE

The following multiple run screens S4M-S12M are functionally
identical to screens S4-S12 in SINGLE RUN mode. In MULTIPLE RUN
mode, however, these screens will display a group identifier in
the top right corner. The group identifier indicates that the
model is in the MULTIPLE RUN mode and identifies the group
currently being processed.

```
         1         2         3         4         5         6         7         8
    1234567890123456789012345678901234567890123456789012345678901234567890123456789

  1
  2
  3
  4
  5       THE AVIATION OFFICER REQUIREMENTS MODEL IS LOADED WITH
  6       NOMINAL VALUES OF PARAMETERS REQUIRED TO DETERMINE THE
  7       REQUIREMENT FOR NAVAL AVIATORS IN THE LIGHT ATTACK
  8       COMMUNITY
  9
 10       YOU CAN REVIEW AND/OR ALTER THESE PARAMETERS BY PRESSING THE
  1       PF KEY CORRESPONDING TO THE ITEM NUMBERS IN THE LIST OF
  2       PARAMETER CATEGORIES GIVEN BELOW.  THIS ACTION WILL CALL UP
  3       A LIST OF THE INDICATED PARAMETERS WITH THEIR CURRENT VALUES
  4
  5            PF KEY     PARAMETER CATEGORY
  6              1        BASIC COMMUNITY DATA
  7              2        TRAINING REQUIREMENTS DATA
  8              3        POLICY VARIABLES
  9              4        ALLOCATION PARAMETERS
 20              5        CAREER PATH NETWORK
  1
  2
  3       TO RETURN TO COMMUNITY SELECTION MENU PRESS 'PF 10'
  4       TO CONTINUE PROGRAM WITHOUT PARAMETER REVIEW PRESS 'ENTER'
```

PARAMETER CATEGORY MENU SCREEN (MULTIPLE RUN)

This screen appears only if the user selected the PF-1 utility
when screen S10M was displayed. This screen permits the user to
reinspect a parameter category for the current group identifier.
Note that screens which have been bypassed can not be redisplayed.

```
*****************************************************************
****  12345678901234567890123456789012345678901234567890123456789 ****
*****************************************************************
* *                                                           * 1*
* 1*                                                          * 2*
* 2*                                                          * 3*
* 3*              BASIC COMMUNITY DATA            GROUP A     * 3*
* 4*           LIGHT ATTACK NAVAL AVIATION                    * 4*
* 5*                                                          * 5*
* 6*                                                          * 6*
* 7*               PARAMETER          CURRENT VALUE           * 7*
* 8*         NUMBER OF SQUADRONS           24                 * 8*
* 9*         AIRCRAFT PER SQUADRON         12                 * 9*
*10*         CREW FACTOR                   1.40               *10*
* 1*         NAVAL AVIATORS PER CREW       1.00               * 1*
* 2*   ********************************************           * 2*
* 3*         SQUADRON GRADE DISTRIBUTION                      * 3*
* 4*               COMMANDERS              *2                 * 4*
* 5*               LT. COMMANDERS          *4                 * 5*
* 6*               LIEUTENANTS             11                 * 6*
* 7*   ********************************************           * 7*
* 8*         UPWARD DETAIL PERCENTAGE      20                 * 8*
* 9*         COMMUNITY RETENTION           40 PER CENT        * 9*
*20*         NUMBER OF CARRIER AIR WINGS   12                 *20*
* 1*                                                          * 1*
* 2*   ********************************************           * 2*
* 3*   PRESS PF 10 IF YOU WANT TO BYPASS THIS SCREEN FOR THIS GROUP  * 3*
* 4*   PRESS ENTER TO RECORD CHANGES AND CONTINUE             * 4*
* *                                                           * *
*****************************************************************
****      1       2       3       4       5       6       7    8 ****
****  12345678901234567890123456789012345678901234567890123456789 ****
*****************************************************************
```

BASIC COMMUNITY DATA SCREEN (MULTIPLE RUN)

This screen is functionally identical to screen S6 in SINGLE RUN mode (see A-12).

NOTE

Screens S6M-S11M will appear automatically in the sequence shown. Some of the screens have a PF-10 utility which allows the user to bypass all subsequent screens in that parameter category for the entire group.   Screens without this utility will be bypassed automatically.   Screen S8M and S10M have a PF-1 utility which allows the redisplay of prior screens.

TRAINING REQUIREMENTS DATA SCREEN (MULTIPLE RUN)

This screen is functionally identical to screen S7 in SINGLE RUN
mode (See A-13).

```
************************************************************
****   1    2    3    4    5    6    7    8  ****
****  12 456 78 901234 56 78 901234 56 78 901234 56 78 901234 56 78 901234 56 78 901234 56 78 90  ****
************************************************************
*  *                                                      *  *
* 1*                                                      * 1*
* 2*        PROMOTION FLOW POINTS AND POLICY VARIABLES      GROUP A   * 2*
* 3*              LIGHT ATTACK NAVAL AVIATION               * 3*
* 4*        ************************************************* 4*
* 5*                                                      * 5*
* 6*                  PROMOTION FLOW POINTS                * 6*
* 7*                                                      * 7*
* 8*     COMM                                             * 8*
* 9*                                                      * 9*
*10*    0*1*2*3*4*5*6*7*8*9*10*11*12*13*14*15*16*17*18*19*20*21*22*23* 24  *10*
* 1*           *****************************************************  * 1*
* 2*    DESIG          4              5                   * 2*
* 3*        *************************************************** 3*
* 4*                                                      * 4*
* 5*                  POLICY VARIABLES                    * 5*
* 6*                                                      * 6*
* 7*    PLOWBACK INSTRUCTOR (FRACTION OF GRADUATED)      *.00   * 7*
* 8*    POSTGRADUATE FLOW (FRACTION OF 10 YEAR GROUP)    *.30   * 8*
* 9*    WAR COLLEGE FLOW (FRACTION OF 18 YEAR GROUP)     *.50   * 9*
*20*                                                      *20*
* 1*        *************************************************** 1*
* 2*                                                      * 2*
* 3*    PRESS PF 1 TO RECORD CHANGES AND REDISPLAY        * 3*
* 4*    PRESS ENTER TO RECORD CHANGES AND CONTINUE        * 4*
*  *                                                      *  *
************************************************************
****   1    2    3    4    5    6    7    8  ****
****  12 456 78 901234 56 78 901234 56 78 901234 56 78 901234 56 78 901234 56 78 901234 56 78 90  ****
************************************************************
```

PROMOTION FLOW POINTS AND POLICY VARIABLES SCREEN (MULTIPLE RUN)

This screen is functionally identical to screen S8 in SINGLE RUN
mode (See A-14).

A-27

MICROCOPY RESOLUTION TEST CHART

NATIONAL BUREAU OF STANDARDS-1963-A

```
**** ...................................................................................... ****
**** ...1...........2...........3...........4...........5...........6...........7...........8 ****
**** 12345678901234567890123456789012345678901234567890123456789012345678901234567890 ****
**** ...................................................................................... ****
*  *                                                                                    *  *
* 1*                                                                                    * 1*
* 2*                                                                                    * 2*
* 3*                                                                                    * 3*
* 4*                                                                                    * 4*
* 5*                   ALLOCATION PARAMETERS                        GROUP A             * 5*
* 6*                   LIGHT ATTACK NAVAL AVIATORS                                      * 6*
* 7*                                                                                    * 7*
* 8*                                                                                    * 8*
* 9*                                                                                    * 9*
*10*                                                                                    *10*
* 1*                                                                                    * 1*
* 2*         FRACTION OF ALL NAVAL AVIATORS                        *.1008              * 2*
* 3*                                                                                    * 3*
* 4*         FRACTION OF STRIKE NAVAL AVIATORS                     *.2090              * 4*
* 5*                                                                                    * 5*
* 6*         FRACTION OF CARRIER NAVAL AVIATORS                    *.2090              * 6*
* 7*                                                                                    * 7*
* 8*         FRACTION OF ALL AVIATION OFFICERS                     *.0729              * 8*
* 9*                                                                                    * 9*
*20*                                                                                    *20*
* 1*         ***************************************************************            * 1*
* 2*                                                                                    * 2*
* 3*         PRESS PF 10 IF YOU WANT TO BYPASS THIS SCREEN FOR THIS GROUP               * 3*
* 4*         PRESS ENTER TO RECORD CHANGES AND CONTINUE                                 * 4*
*  *                                                                                    *  *
**** ...................................................................................... ****
**** ...1...........2...........3...........4...........5...........6...........7...........8 ****
**** 12345678901234567890123456789012345678901234567890123456789012345678901234567890 ****
**** ...................................................................................... ****
```

ALLOCATION PARAMETERS SCREEN (MULTIPLE RUN)

This screen is functionally identical to screen S9 in SINGLE RUN
mode (See A-15).

A-28

```
****************************************************************************************
****        1         2         3         4         5         6         7        8 ****
****  1234567890123456789012345678901234567890123456789012345678901234567890123456 7890 ****
****************************************************************************************
* *                                                                           * *
* 1*                                                             GROUP A       * 1*
* 2*    YOU CAN INSPECT AND/OR MODIFY THE CAREER PATH NETWORK CHARACTERISTICS  * 2*
* 3*    ASSOCIATED WITH ANY NODE IN THE NETWORK.  TO SELECT A PARTICULAR NODE  * 3*
* 4*    REPLACE THE 'O' IN THE DIAGRAM BELOW WITH AN 'X'.  TO BYPASS A NODE     * 4*
* 5*    PRESS 'TAB'.                                                           * 5*
* 6*                                                                           * 6*
* 7*                                  TOUR NUMBER                              * 7*
* 8*                                                                           * 8*
* 9*            ACTIVITY              1   2   3   4   5   6   7                 * 9*
*10*                                                                           *10*
* 1*         FLEET TOURS             o   o   x   x   o   o   o                 * 1*
* 2*         FLEET READINESS SQUADRON o  o   o   o   o   o   o                 * 2*
* 3*         TRAINING COMMAND        o   o   o   o   o   o   o                 * 3*
* 4*         R&D COMMUNITY           o   o   o   o   o   o   o                 * 4*
* 5*         AFLOAT ASSIGNMENTS      o   o   o   o   o   o   o                 * 5*
* 6*         PROFESSIONAL EDUCATION  o   o   o   o   o   o   o                 * 6*
* 7*         OTHER                   o   o   o   o   o   o   o                 * 7*
* 8*                                                                           * 8*
* 9*                                                                           * 9*
*20*                                                                           *20*
* 1*                                                                           * 1*
* 2*                                                                           * 2*
* 3*    TO BEGIN NODE INSPECTION/MODIFICATION PRESS        'ENTER'             * 3*
* 4*    TO RETURN TO CATEGORY MENU PRESS                   'PF 1'              * 4*
* *                                                                           * *
****************************************************************************************
****        1         2         3         4         5         6         7        8 ****
****  1234567890123456789012345678901234567890123456789012345678901234567890123456 7890 ****
****************************************************************************************
```

CAREER PATH NETWORK SCREEN #1 (MULTIPLE RUN)

This screen is functionally identical to screen S10 in SINGLE RUN
mode (See A-16).

A-29

```
****  ************************************************************
****  1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 ****
****  ************************************************************
* 1*                        NODE CHARACTERISTICS                    GROUP A      * 1*
* 2*                                                                             * 2*
* 3*     NODE CHARACTERISTICS ARE REFERRED TO THE OUTPUT END OF THE ARC          * 3*
* 4*     IN QUESTION.   THAT NODE IDENTIFIES THE ACTIVITY IN WHICH THE           * 4*
* 5*     OFFICER IS ENGAGED.   THE ACTIVITY AND TOUR NUMBER CURRENTLY            * 5*
* 6*     BEING EXAMINED IS:                                                      * 6*
* 7*                                                                             * 7*
* 8*          FLEET TOURS                        TOUR NUMBER   3                  * 8*
* 9*                                                                             * 9*
*10*     FOR TOURS TERMINATING AT THAT NODE                                      *10*
* 1*     THE FOLLOWING VALUES APPLY:                                             * 1*
* 2*                                                                             * 2*
* 3*                           TOUR LENGTH     36                                * 3*
* 4*                                                                             * 4*
* 5*        PRECEDENT NODE        STATE           PRECEDENT NODE        STATE     * 5*
* 6*     FLEET TOURS              NNN      FLEET READINESS SQUADRON     OOO       * 6*
* 7*     TRAINING COMMAND         OOO      R&D COMMUNITY                OOO       * 7*
* 8*     AFLOAT ASSIGNMENTS       NNN      PROFESSIONAL EDUCATION       OOO       * 8*
* 9*     OTHER                    OOO                                            * 9*
*20*                                                                             *20*
* 1*              NOTE    'NNN' MEANS THAT THE PRECEDENT NODE IS BARRED          * 1*
* 2*                                                                             * 2*
* 3*                                                                             * 3*
* 4*     TO ENTER CHANGES PRESS                      'ENTER'                     * 4*
* *                                                                             * *
****  ************************************************************
****  1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 ****
****  ************************************************************
```

CAREER PATH NETWORK SCREEN #2 (MULTIPLE RUN)

This screen is functionally identical to screen S11 in SINGLE RUN
mode (See A-17).

A-30

```
****************************************************************************
          1       2       3       4       5       6       7       8  ****
**** 1234567890123456789012345678901234567890123456789012345678901234567890 ****
****************************************************************************
*  *                                                                    *  *
*  1*                                                                   *  1*
*  2*                                                                   *  2*
*  3*                                                                   *  3*
*  4*                                                      GROUP  A     *  4*
*  5*     YOU HAVE REQUESTED A CHANGE IN RETENTION FOR NAVAL AVIATORS   *  5*
*  6*     IN THE LIGHT ATTACK COMMUNITY                                 *  6*
*  7*     THIS WILL CAUSE A CHANGE IN THE CONTINUATION VECTOR.  THE FOUR*  7*
*  8*     PARAMETERS WHICH DEFINE THIS VECTOR ARE DISPLAYED BELOW FOR   *  8*
*  9*     REVIEW AND/OR CHANGE                                          *  9*
* 10*                                                                   * 10*
*  1*                                                                   *  1*
*  2*     RETENTION                     45 PER CENT                     *  2*
*  3*                                                                   *  3*
*  4*     MINIMUM SERVICE REQUIREMENT    5 YEARS                        *  4*
*  5*                                                                   *  5*
*  6*     RETENTION POINT                7 YEARS                        *  6*
*  7*                                                                   *  7*
*  8*     CAREER STABLE POINT           11 YEARS                        *  8*
*  9*                                                                   *  9*
* 20*                                                                   * 20*
*  1*     ***************************************************           *  1*
*  2*                                                                   *  2*
*  3*     PRESS ENTER TO MAKE CONTINUATION VECTOR CHANGES               *  3*
*  4*                                                                   *  4*
*  *                                                                    *  *
****************************************************************************
****          1       2       3       4       5       6       7       8  ****
**** 1234567890123456789012345678901234567890123456789012345678901234567890 ****
****************************************************************************
```

RETENTION SCREEN (MULTIPLE RUN)

This screen is functionally identical to screen S12 in SINGLE RUN
mode (See A-18).

EXECUTION AND PROCESSING SEQUENCE

The following pages A-34 to A-43 explain and describe the screens
during processing modes.   The figure A-3 on the following page,
is a basic flow diagram showing the logical sequence of screens
displayed during processing.   The remainder of this section is
devoted to a detailed description of each screen in the flow
diagram.

A-33

AVIATIONAL OFFICER
REQUIREMENTS MODEL
PROCESS MODES

VER.(7.1)

KEY

E ENTER
PF PROGRAM FUNCTION
() AUTOMATIC DECISION

FIGURE A-3

A-34

```
 ****************************************************************************
 ****    1      2      3      4      5      6      7      8 ****
 **** 12345678901234567890123456789012345678901234567890123456789012345678910 ****
 ****************************************************************************
 *  *                                                                    *  *
 *  1*                                                                   *  1*
 *  2*                                                                   *  2*
 *  3*                                                                   *  3*
 *  4*                                                                   *  4*
 *  5*                                                                   *  5*
 *  6*                                                                   *  6*
 *  7*                                                                   *  7*
 *  8*                                                                   *  8*
 *  9*                                                                   *  9*
 *10*                                                                    *10*
 *  1*                                                                   *  1*
 *  2*                                                                   *  2*
 *  3*                                                                   *  3*
 *  4*                EXECUTION CONTINUES                                *  4*
 *  5*                                                                   *  5*
 *  6*                  WORKING ON                                       *  6*
 *  7*                                                                   *  7*
 *  8*         NAVAL AVIATORS IN LIGHT ATTACK COMMUNITY                  *  8*
 *  9*                                                                   *  9*
 *20*                                                                    *20*
 *  1*                                                                   *  1*
 *  2*     13:07:41                           MAIN ITERATION    1        *  2*
 *  3*                                       'OTHER' ITERATION   0        *  3*
 *  4*                                                                   *  4*
 *  *                                                                    *  *
 ****************************************************************************
 ****    1      2      3      4      5      6      7      8 ****
 **** 12345678901234567890123456789012345678901234567890123456789012345678910 ****
 ****************************************************************************
```

EXECUTION SCREEN (NO IN-PROCESS MONITORING)

This is an advisory screen which appears during program execution
(without IN-PROCESS MONITORING) displaying the current Community,
Subcommunity, time, and current iteration information.

```
********************************************************************************
****       1         2         3         4         5         6         7        8 ****
**** 1234567890123456789012345678901234567890123456789012345678901234567890123456789O ****
********************************************************************************
* *                                                                          * *
* 1*                                                                        * 1*
* 2*                                                                        * 2*
* 3*                                                                        * 3*
* 4*                                                                        * 4*
* 5*                                                                        * 5*
* 6*                                                                        * 6*
* 7*                                                                        * 7*
* 8*                                                                        * 8*
* 9*                                                                        * 9*
*10*                                                                        *10*
* 1*                                                                        * 1*
* 2*                                                                        * 2*
* 3*                                                                        * 3*
* 4*                    EXECUTION CONTINUES                                 * 4*
* 5*                                                                        * 5*
* 6*                      WORKING ON                                        * 6*
* 7*                                                                        * 7*
* 8*          NAVAL AVIATORS IN LIGHT ATTACK COMMUNITY                      * 8*
* 9*                                                                        * 9*
*20*                                                                        *20*
* 1*                                                                        * 1*
* 2*        13:07:41                    MAIN ITERATION     1                * 2*
* 3* STOP END TOUR TWO - PF-14 FOR DATA  'OTHER' ITERATION   0              * 3*
* 4*                                                                        * 4*
* *                                                                          * *
********************************************************************************
****       1         2         3         4         5         6         7        8 ****
**** 1234567890123456789012345678901234567890123456789012345678901234567890123456789O ****
********************************************************************************
```

EXECUTION SCREEN (IN-PROCESS MONITORING)

This screen is an advisory screen which appears during program
execution. IN-PROCESS MONITORING mode allows the user to stop
and check the data at one or all stop-check points. To inspect
data at check points, press PF-14 (see next page).

```
                 1      2      3      4      5      6      7      8
     12345678901234567890123456789012345678901234567890123456789012345678901234567890

 1
 2
 3
 4
 5              WORKING ON NAVAL AVIATORS IN LIGHT ATTACK COMMUNITY
 6
 7     AT END TOUR TWO                ITERATION  1      04/08/83
 8                                                      13:08
 9
10                  FRACTION OF FILL
 1            SENIOR COMMANDERS      0.000
 2            COMMANDERS             0.000
 3            LT. COMMANDERS         0.000
 4            LT. AND BELOW           .895
 5            ==============================
 6
 7     ACCESSIONS                    103.45
 8     FIRST TOUR LENGTH              35.00
 9
20     OUTPUT OPTIONS. PRESS PF KEY:
 1            1. NODE FLOWS    2. INVENTORY          3. REQUIREMENTS
 2            4. EXCESS FLOW
 3     FOR SCREEN PRINTS PRESS PF 11
 4     PRESS ENTER TO CONTINUE PROGRAM

                 1      2      3      4      5      6      7      8
     12345678901234567890123456789012345678901234567890123456789012345678901234567890
```

OUTPUT MENUS SCREEN (IN-PROCESS MONITORING)

This screen is displayed at each stop-check point if the user
pressed PF-14 when screen S16 was displayed.   It is also
displayed when returning from an output option (screens S18-S22).
This screen shows the extent to which the requirements have been
filled thus far.   The user may chose to look at any of four out-
put options by pressing a PF-key.   The next five pages of this
appendix describe the output options.   To print this screen or
any of the IN-PROCESS MONITORING screens, press PF-11 while a
particular screen is displayed.

- NOTE -

The only time this screen appears automatically (without user
request) is at the end of each main iteration. The user would
either press the "ENTER" key to continue processing or select an
output option.

```
****************************************************************************
****         1         2         3         4         5         6         7         8 ****
**** 12345678901234567890123456789012345678901234567890123456789012345678901234567890 ****
****************************************************************************
*  *                                                                        *  *
*  1*                                                                       *  1*
*  2*                                                                       *  2*
*  3*                                                                       *  3*
*  4*                                                                       *  4*
*  5*                      NODE FLOW VALUES                                 *  5*
*  6*                                                                       *  6*
*  7*                      TOUR NUMBERS                                     *  7*
*  8*                                                                       *  8*
*  9*       ACTIVITY          ONE    TWO   THREE  FOUR   FIVE   SIX   SEVEN  *  9*
* 10*                                                                       * 10*
*  1* FLEET TOURS            93.55   3.90  0.00   0.00   0.00   0.00  0.00   *  1*
*  2* FLEET READINESS SQUADRON 0.00 17.73  0.00   0.00   0.00   0.00  0.00   *  2*
*  3* TRAINING COMMAND        5.02  10.43  0.00   0.00   0.00   0.00  0.00   *  3*
*  4* R&D COMMUNITY           0.00   4.21  0.00   0.00   0.00   0.00  0.00   *  4*
*  5* AFLOAT ASSIGNMENTS      0.00   0.00  0.00   0.00   0.00   0.00  0.00   *  5*
*  6* PROFESSIONAL EDUCATION  0.00   9.52  0.00   0.00   0.00   0.00  0.00   *  6*
*  7* OTHER                   0.00   5.15  0.00   0.00   0.00   0.00  0.00   *  7*
*  8*                                                                       *  8*
*  9*   ****************************************************************    *  9*
* 20*                                                                       * 20*
*  1*                                                                       *  1*
*  2*       PRESS ENTER TO RETURN TO OUTPUT MENU                            *  2*
*  3*                                                                       *  3*
*  4*                                                                       *  4*
*  *                                                                        *  *
****************************************************************************
****         1         2         3         4         5         6         7         8 ****
**** 12345678901234567890123456789012345678901234567890123456789012345678901234567890 ****
****************************************************************************
```

NODE FLOW OUTPUT SCREENS (IN-PROCESS MONITORING)

This screen appears when the PF-1 key is selected from the Output
Options screen S17. It displays the node flow values (which are
the annual flows of officers) out of various nodes of the career
path network. To print this screen, press PF-11. To return to
the Output Menu Screen (S17), press "ENTER".

A-38

```
        1          2          3          4          5          6          7          8
 1234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890

 1
 2
 3
 4
 5                              INVENTORY DISPLAY
 6
 7              SELECT FOUR YEARS FOR OUTPUT BETWEEN 1 AND 30
 8
 9
10                  FIRST YEAR       01
 1
 2                  SECOND YEAR      02
 3
 4                  THIRD YEAR       03
 5
 6                  FOURTH YEAR      04
 7
 8
 9
20
 1                  PRESS PF2 TO RETURN TO OUTPUT MENU
 2
 3                  PRESS PF1 TO CONTINUE
 4
```

INVENTORY DISPLAY OUTPUT SCREEN #1 (IN-PROCESS MONITORING)

This display appears when the PF-2 key is pressed when the Output Menu screen appears. Inventory consists of two screens. The first inventory screen allows the user to select up to 4 years for which he would like to see the inventory. This is done by typing in the years (between 1 and 30) for output. To see the requested years output, press PF-1. Press PF-2 to return to the Output Menu screen. Press PF-11 to print this screen.

```
****************************************************************************
****        1         2         3         4         5         6         7         8 ****
****  123456 78901234567890123456789012345678901234567890123456789012345678901234567890  ****
****************************************************************************
*  *                                                                                *  *
*  1*                                                                               *  1*
*  2*                                                                               *  2*
*  3*                        INVENTORY DISPLAY                                       *  3*
*  4*                                                                               *  4*
*  5*                                                                               *  5*
*  6*                                                                               *  6*
*  7*                                    YEARS                                      *  7*
*  8*              ACTIVITY             1        2        3        4                 *  8*
*  9*                                                                               *  9*
*10*     FLEET TOURS                   97.59    90.23    99.45    51.86            *10*
*  1*     FLEET READINESS SQUADRON      0.00     0.00     0.00    16.47            *  1*
*  2*     TRAINING COMMAND              5.13     5.00      .41    15.27            *  2*
*  3*     R&D COMMUNITY                 0.00     0.00     0.00     3.91            *  3*
*  4*     AFLOAT ASSIGNMENTS            0.00     0.00     0.00     0.00            *  4*
*  5*     PROFESSIONAL EDUCATION        0.00     0.00     0.00     4.76            *  5*
*  6*     OTHER                         0.00     0.00     0.00     6.19            *  6*
*  7*     UNASSIGNED                    0.00     0.00      .00      .02            *  7*
*  8*                                                                               *  8*
*  9*     **************************************************************            *  9*
*20*                                                                               *20*
*  1*     NON-AVIATION ASSIGNMENTS      0.00     0.00     0.00     0.00            *  1*
*  2*                                                                               *  2*
*  3*     **************************************************************            *  3*
*  4*        PRESS ENTER TO RETURN TO OUTPUT MENU                                   *  4*
*  *                                                                                *  *
****************************************************************************
****        1         2         3         4         5         6         7         8 ****
****  123456 78901234567890123456789012345678901234567890123456789012345678901234567890  ****
****************************************************************************
```

INVENTORY DISPLAY OUTPUT SCREEN #2 (IN-PROCESS MONITORING)

If the PF-1 key is pressed when screen S19 is displayed, the
second inventory output screen (above) will appear. This screen
displays the breakdown for each activity the years the user has
requested. To print this screen, press PF-11. In order to return
to the Output Menu screen (S17), press "ENTER".

```
****************************************************************************
****          1         2         3         4         5         6         7         8 ****
**** 1234567890123456789012345678901234567890123456789012345678901234567890 ****
****************************************************************************
*  *                                                                      *  *
* 1*                                                                      * 1*
* 2*                                                                      * 2*
* 3*                          REQUIREMENTS DISPLAY                        * 3*
* 4*                                                                      * 4*
* 5*                                                                      * 5*
* 6*                                                                      * 6*
* 7*                                   CATEGORY                           * 7*
* 8*              ACTIVITY            LT      LCDR     CDR     CDR+        * 8*
* 9*                                                                      * 9*
*10*       FLEET TOURS              0.00    117.68   48.00   3.22        *10*
* 1*       FLEET READINESS SQUADRON 0.00     23.00    0.00   2.00        * 1*
* 2*       TRAINING COMMAND         0.00     11.83    5.91   0.00        * 2*
* 3*       R&D COMMUNITY            0.00     12.81    2.93   2.54        * 3*
* 4*       AFLOAT ASSIGNMENTS      23.33     17.88   11.21   9.39        * 4*
* 5*       PROFESSIONAL EDUCATION    .00      4.68    4.68   4.68        * 5*
* 6*       OTHER                   38.00     75.82   33.64  28.08        * 6*
* 7*                                                                      * 7*
* 8*       ********************************************************       * 8*
* 9*                                                                      * 9*
*20*       LOWER GRADE FILLS                 0.00    0.00   0.00         *20*
* 1*                                                                      * 1*
* 2*       ********************************************************       * 2*
* 3*                                                                      * 3*
* 4*          PRESS ENTER TO RETURN TO OUTPUT MENU                       * 4*
*  *                                                                      *  *
****************************************************************************
****          1         2         3         4         5         6         7         8 ****
**** 1234567890123456789012345678901234567890123456789012345678901234567890 ****
****************************************************************************
```

REQUIREMENTS DISPLAY OUTPUT SCREEN (IN-PROCESS MONITORING)

This display appears when the PF-3 key is pressed while the
Output Menu screen appears. It shows the requirements remaining
to be filled for each grade in each activity at the current point
in processing. To print this screen, press PF-11. To get back to
the Output Menu screen press "ENTER".

```
********************************************************************
****          1       2       3       4       5       C       8 ****
**** 123456789012345678901234567890123456789012345678901234567890 ****
********************************************************************
*  *                                                              *  *
* 1*                                                              * 1*
* 2*                                                              * 2*
* 3*              ELAPSED TIME (07) DISPLAY                       * 3*
* 4*                                                              * 4*
* 5*                                                              * 5*
* 6*                                                              * 6*
* 7*                          TOUR                                * 7*
* 8*        ACTIVITY          1    2    3    4    5    6    7      * 8*
* 9*                                                              * 9*
*10*   FLEET TOURS            42   67   0    0    0    0    0      *10*
* 1*   FLEET READINESS SQUADRON  0 79   0    0    0    0    0      * 1*
* 2*   TRAINING COMMAND      25   79   0    0    0    0    0       * 2*
* 3*   RND COMMUNITY          0   79   0    0    0    0    0       * 3*
* 4*   AFLOAT ASSIGNMENTS     0   67   0    0    0    0    0       * 4*
* 5*   PROFESSIONAL EDUCATION 0   67   0    0    0    0    0       * 5*
* 6*   OTHER                  0   79   0    0    0    0    0       * 6*
* 7*                                                              * 7*
* 8*   **********************************************************  * 8*
* 9*                                                              * 9*
*20*   NON-AVIATION MAN YEARS  0.0  4.2  0.0  0.0  0.0  0.0  0.0   *20*
* 1*                                                              * 1*
* 2*   **********************************************************  * 2*
* 3*                                                              * 3*
* 4*      PRESS ENTER TO RETURN TO OUTPUT MENU                    * 4*
*  *                                                              *  *
********************************************************************
****          1       2       3       4       5       6       7       8 ****
**** 123456789012345678901234567890123456789012345678901234567890 ****
********************************************************************
```

EXCESS FLOW SCREEN (IN-PROCESS MONITORING)

If PF-4 was pressed when screen S17 was displayed, the above screen would appear. It shows the excess flows out of nodes that the model could not assign up to this point in processing. To print this screen, press PF-11. Press "ENTER" to return to the Output Menu screen S17.

A-42

```
**** 1        2        3        4        5        6        7        8 ****
**** 1234567890123456789012345678901234567890123456789012345678901234567890 ****
* *                                                                      * *
* 1*                                                                     * 1*
* 2*                                                                     * 2*
* 3*                                                                     * 3*
* 4*                                                                     * 4*
* 5*          NAVAL AVIATORS  IN LIGHT ATTACK COMMUNITY                  * 5*
* 6*                                                                     * 6*
* 7*      RESULTS AT END TOUR 7       ITERATION  1     06/08/83          * 7*
* 8*                                       13:11                         * 8*
* 9*          COMMUNITY POPULATION              FLEET OPPORTUNITY        * 9*
*10*     GRADE     NUMBER                                                *10*
* 1*    SENIOR CDR    679                                                * 1*
* 2*    JUNIOR CDR    178         COMMAND OPPORTUNITY    .84             * 2*
* 3*    LT. CDR       141         DEPT HEAD OPPORTUNITY  .78             * 3*
* 4*    LIEUTENANT    120                                                * 4*
* 5*                                                                     * 5*
* 6*    TOTAL        1118                                                * 6*
* 7*    *********************************************************        * 7*
* 8*                                        ACIP PROJECTION             * 8*
* 9*    ACCESSIONS         103              GATE 1    1.55              * 9*
*20*                                        GATE 2    1.27              *20*
* 1*    FIRST TOUR LENGTH   35               GATE 3    1.55              * 1*
* 2*                                                                     * 2*
* 3*    DO YOU WISH TO CONTINUE IN PROCESS MONITORING?   YES   (YES/NO)  * 3*
* 4*    PRESS ENTER TO CONTINUE       PRESS PF 1 TO SUPPRESS PRINT       * 4*
* *                                                                      * *
**** 1        2        3        4        5        6        7        8 ****
```

RESULTS/CONTINUE SCREEN

This screen is displayed automatically when the solution criteria
for the model is set. It displays the final results of model
processing. This screen also allows the user to discontinue the
IN-PROCESS MONITORING by typing "NO" over "YES" for IN-PROCESS
MONITORING. To suppress printing these results, press PF-1. To
continue processing and print these results, press "ENTER".

A-43

SAMPLE OUTPUTS

The following pages present a complete set of output print-outs
for a run made with all model parameters set to default values.

SUMMARY DATA

LIGHT ATTACK COMMUNITY
NAVAL AVIATORS

NUMBER OF SQUADRONS	24
AIRCRAFT PER SQUADRON	12
CREW FACTOR	1.42
NAVAL AVIATORS PER CREW	1.00

****

RETENTION	45 %
PLOWBACK FRACTION	5 %

****

COMMUNITY POPULATION

SENIOR COMMANDERS	110	COMMAND OPPORTUNITY	.73
COMMANDERS	149	DEPT HEAD OPPORTUNITY	.84
LT. COMMANDERS	201		
LIEUTENANTS	759		

TOTAL 1219

****

ACCESSIONS TO TRAINING (13YX)	163
ACCESSIONS TO 131X DESIGNATOR	116
FIRST TOUR LENGTH	31

DISTRIBUTION BY GRADE AND ACTIVITY

GRADE

ACTIVITY	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TOURS	387	105	45	25	560
FLEET READINESS SQUADRON	96	16	6	0	118
TRAINING COMMAND	103	12	6	0	121
R&D COMMUNITY	21	0	15	3	40
AFLOAT ASSIGNMENTS	22	6	19	19	60
PROFESSIONAL EDUCATION	22	3	6	8	39
OTHER	67	95	63	44	208
NON-AVIATION ASSIGNMENTS	41	20	0	13	74

LOWER GRADE FILLS		52	0		

ACIP PROJECTIONS

GATE 1	1.47
GATE 2	1.19
GATE 3	1.45

NON AVIATION 6 %

HI UP IN TAG (LCDR) 20%

****

TOTAL ANNUAL PCS MOVES THRU COMMUNITY 707

****

ALL REQUIREMENTS MET   DEFAULT RUN LET TOURS 4, 5, = 30 MOS.   ITERATIONS = 1/6

A-45

SUMMARY DATA

FIGHTER COMMUNITY
NAVAL AVIATORS

****

RETENTION	45 %		NUMBER OF SQUADRONS	24
PLOWBACK FRACTION	5 %		AIRCRAFT PER SQUADRON	12
			CREW FACTOR	1.17
			NAVAL AVIATORS PER CREW	1.00

****

COMMUNITY POPULATION

ACCESSIONS TO TRAINING (133X)	173	SENIOR COMMANDERS	87		COMMAND OPPORTUNITY	.39
		COMMANDERS	126		DEPT HEAD OPPORTUNITY	.85
ACCESSIONS TO 131X DESIGNATOR	92	LT. COMMANDERS	170			
FIRST TOUR LENGTH	37	LIEUTENANTS	605			
		TOTALS	988			

****

DISTRIBUTION BY GRADE AND ACTIVITY

			GRADE			
ACTIVITY	LT	LCDR	CDR	SEN CDR	TOTAL	ACIP PROJECTIONS
FLEET TOURS	327	73	7	26	432	
FLEET READINESS SQUADRON	147	3	22	2	174	GATE 1 1.58
TRAINING COMMAND	81	10	4	1	96	GATE 2 1.27
R&D COMMUNITY	4	21	5	1	31	GATE 3 1.55
AIRDAT ASSIGNMENTS	11	18	3	3	47	
PROFESSIONAL EDUCATION	11	8	4	4	28	
OTHER	24	39	74	28	165	
NON-AVIATION ASSIGNMENTS	0	0	0	18	18	NON AVIATION 7 %

===
| LOWER GRADE FILL | 6 | 3 | | | | 1ST UP DETAIL (LCDR)   47 |
===

****

TOTAL ANNUAL FCS HOURS THIS COMMUNITY   467

****

DEFAULT RUN FLT HOURS 4.5 - 10 MOS.   ITERATIONS = 1/1

ALL REQUIREMENTS MET

A-46

SUMMARY DATA

MEDIUM ATTACK COMMUNITY
NAVAL AVIATORS

GROUP A
05/40/83
15:01

****

RETENTION	45 %	NUMBER OF SQUADRONS	12	
		AIRCRAFT PER SQUADRON	14	
PLOWBACK FRACTION	5 %	CREW FACTOR	1.16	
		NAVAL AVIATORS PER CREW	1.00	

****

COMMUNITY POPULATION

ACCESSIONS TO TRAINING (1 PX)	65	SENIOR COMMANDERS	49
		COMMANDERS	66	COMMAND OPPORTUNITY	.38
ACCESSIONS TO 1 31X DESIGNATOR	44	LT. COMMANDERS	86	DEPT HEAD OPPORTUNITY	.85
FIRST TOUR LENGTH	43	LIEUTENANTS	403		
		TOTALS	504		

****

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	GRADE				
	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TOURS	180	36	5	19	240
FLEET READINESS SQUADRON	47	3	2	1	53
TRAINING COMMAND	41	5	2	1	49
R&D COMMUNITY	0	18	7	0	18
AFLOAT ASSIGNMENTS	5	8	7	7	27
PROFESSIONAL EDUCATION	5	5	45	15	15
OTHER	9	24	0	13	13
NON AVIATION ASSIGNMENTS	0	0		11	11

NON AVIATION   2 %

LOWER GRADE FILLS	5	0	DT OF DETAIL (LCDR) 6%

ACIP PRODUCTIONS

GATE 1	1.57
GATE 2	1.62
GATE 3	1.49

****

TOTAL ANNUAL PCS MOVES THIS COMMUNITY   216

DETAIL TERM FLEET TOURS 4, 6 - 30 MOS.   ITERATIONS = 1/0

****

ALL REQUIREMENTS MET

A-47

GRAPH 6
09/20/83
15:03

SUMMARY DATA

ELECTRONIC WARFARE COMMUNITY
NAVAL AVIATORS

****

		NUMBER OF SQUADRONS	9
RETENTION	45 %	AIRCRAFT PER SQUADRON	4
		CREW FACTOR	1.50
PLOWBACK FRACTION	5 %	NAVAL AVIATORS PER CREW	1.00

****

COMMUNITY POPULATION

ACCESSIONS TO TRAINING (131X)	32	SENIOR COMMANDERS	23
		COMMANDERS	32	COMMAND OPPORTUNITY	.83
ACCESSIONS TO 131X DESIGNATOR	23	LT. COMMANDERS	44	DEPT HEAD OPPORTUNITY	.80
FIRST TOUR LENGTH	27	LIEUTENANTS	152		
		TOTALS	251		

****

DISTRIBUTION BY GRADE AND ACTIVITY

	GRADE					
ACTIVITY	LT	LCDR	CDR	SEN CDR	TOTAL	
FLEET TOURS	69	22	17	1	105	ACIP PROJECTIONS
FLEET READINESS SQUADRON	41	1	0	0	42	
TRAINING COMMAND	20	3	1	0	24	GATE 1 1.01
R&D COMMUNITY	4	3	1	0	7	GATE 2 1.24
AFLOAT ASSIGNMENTS	4	1	4	0	9	GATE 3 1.51
PROFESSIONAL EDUCATION	4	3	1	0	8	
OTHER	10	13	11	1	39	
NON-AVIATION ASSIGNMENTS	0	0	2	13	16	NON AVIATION 6 %

===
| LOWER GRADE FILLS | 9 | | | 1 | | DT HD DETAIL (131X) 18% |
===

****

TOTAL ANNUAL PCS MOVES THIS COMMUNITY   103

****

ALL REQUIREMENTS MET   DEFAULT RUN (131X GRADES 4, 5 - 30 MOS.)   ITERATIONS 1/1

SUMMARY DATA

CARRIER BASED ASW COMMUNITY
NAVAL AVIATORS

		NUMBER OF SQUADRONS	50
		AIRCRAFT PER SQUADRON	72
		CREW FACTOR	93
		NAVAL AVIATORS PER CREW	329

COMMUNITY POPULATION

		SENIOR COMMANDERS	50		COMMAND OPPORTUNITY	.33
		COMMANDERS	72		DEPT HEAD OPPORTUNITY	.92
		LT. COMMANDERS	93			
		LIEUTENANTS	329			

TOTALS 544

DISTRIBUTION BY GRADE AND ACTIVITY

| ACTIVITY | GRADE | | | | | ACTP PROJECTIONS |
	LT	LCDR	CDR	SEN CDR	TOTAL	
FLEET TOURS	202	40	5	12	261	GATE 1 1.58
FLEET READINESS SQUADRON	51	4	2	1	58	GATE 2 1.23
TRAINING COMMAND	45	6	2	1	53	GATE 3 1.51
R&D COMMUNITY	10	4	4	6	19	
AFLOAT ASSIGNMENTS	6	7	8	6	28	
PROFESSIONAL EDUCATION	6	5	6	0	17	
OTHER	10	26	45	17	98	
NON AVIATION ASSIGNMENTS	0	0	0	12	12	

NON AVIATION		2 %

LOWER GRADE FILLS	7	0

DEPTH OF DETAIL (CODE)	72	

RETENTION 65 %

PLOWBACK FRACTION 5 %

ACCESSIONS TO TRAINING (1300X) 70

ACCESSIONS TO 131X DESIGNATOR 50
FIRST TOUR LENGTH 43

TOTAL ANNUAL PCS MOVES THRU COMMUNITY 636

DETACH & PERDIEM HOURS 6.5 = 80 MOS

ALL REQUIREMENTS MET

OPERATIONS = 1 / 0

SUMMARY DATA

FLEET SUPPORT PILOT COMMUNITY
NAVAL AVIATORS

NUMBER OF SQUADRONS   13
AIRCRAFT PER SQUADRON   0
CREW FACTOR   0.00
NAVAL AVIATORS PER CREW   0.00

COMMAND OPPORTUNITY   .36
DEPT HEAD OPPORTUNITY   .34

RETENTION   45 %

FLOWBACK FRACTION   5 %

ACCESSIONS TO TRAINING (TRNX)   1.54

ACCESSIONS TO 13XX DESIGNATOR   833
FIRST TOUR LENGTH   35

COMMUNITY POPULATION

	SENIOR COMMANDERS	COMMANDERS	LT. COMMANDERS	LT. & BELOW	TOTAL

| | | | | | | TOTALS | 324 |

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY		GRADE				
	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TOURS	317	83	23	14	437
FLEET READINESS SQUADRON	0	0	0	0	0
TRAINING COMMAND	78	10	5	0	93
R&D COMMUNITY	23	6	2	3	33
AFLOAT ASSIGNMENTS	14	4	17	8	46
PROFESSIONAL EDUCATION	17	4	4	4	30
OTHER	58	24	60	33	175
NON AVIATION ASSIGNMENTS	68	19	0	21	108

LOWER GRADE TOURS   39   1

ACUP PROJECTIONS

GATE 1   1.32
GATE 2   1.00
GATE 3   0.30

NON AVIATION   1.2 %

HT UP DETAIL (CODE)   702

TOTAL ANNUAL PCS INPUT, FLEET COMMUNITY   437

FLEET SUPPORT PILOT COMMUNITY

ALL REQUIREMENTS MET

ITERATIONS = 30

SUMMARY DATA

EARLY WARNING COMMUNITY
NAVAL AVIATORS

****

RETENTION   45 %

PLOWBACK FRACTION   5 %

NUMBER OF SQUADRONS   12
AIRCRAFT PER SQUADRON   3
CREW FACTOR   1.06
NAVAL AVIATORS PER CREW   2.00

****

ACCESSIONS TO TRAINING (13X)   37

ACCESSIONS TO 13XX DESIGNATOR   23
FIRST TOUR LENGTH   33

COMMUNITY POPULATION

SENIOR COMMANDERS   27
COMMANDERS   42
LT. COMMANDERS   51
LIEUTENANTS   189

TOTALS   309

COMMAND OPPORTUNITY   .73
DEPT HEAD OPPORTUNITY   .84

****

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	GRADE				
	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TOURS	110	27	15	3	155
FLEET READINESS SQUADRON	37	4	1	0	42
TRAINING COMMAND	13	1	1	0	16
R&D COMMUNITY	6	3	5	1	12
AFLOAT ASSIGNMENTS	6	1	5	5	17
PROFESSIONAL EDUCATION	6	2	4	5	10
OTHER	12	13	17	13	55
NON AVIATION ASSIGNMENTS	0	0	0	2	3

AVG PROJECTIONS
GATE 1   1.56
GATE 2   1.22
GATE 3   0.83

NON AVIATION   1 %

DET OF DETAIL (LCDR) 12%
================================

LOWER GRADE FULL   13   0

TOTAL ANNUAL PCS MOVES INTO COMMUNITY   124

DEFAULT BUN PCS MOVES 4, 9 → 10 MOS.

****

ALL REQUIREMENTS MET

ITERATIONS = 1 / 0

SUMMARY DATA

MASTER PLAN PROFILE   COMMUNITY
NAVAL AVIATORS

GROUP D
01/??/??

RETENTION   45 %

PLOWBACK FRACTION   5 %

NUMBER OF SQUADRONS   24
AIRCRAFT PER SQUADRON   ?
CREW FACTOR   1.33
NAVAL AVIATORS PER CREW   3.00

ACCESSIONS TO TRAINING (133X)   230

ACCESSIONS TO 131X DESIGNATOR   274
FIRST TOUR LENGTH   43

COMMAND OPPORTUNITY   .21
DEPT HEAD OPPORTUNITY   .42

COMMUNITY POPULATION

SENIOR COMMANDERS	?
COMMANDERS	?
LT. COMMANDERS	331
LIEUTENANTS	1469
TOTALS	2313

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	GRADE				
	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TOURS	?	?	0	?	1083
FLEET READINESS SQUADRON	85	?	1	?	96
TRAINING COMMAND	103	10	3	4	119
R&D COMMUNITY	43	?	3	?	82
AFLOAT ASSIGNMENTS	20	43	13	43	134
PROFESSIONAL EDUCATION	43	13	14	45	76
OTHER	140	17	109	67	439
NON-AVIATION ASSIGNMENTS	105	85	94	43	793

LOWER GRADE FILLS   75 %   ?8 %

ACIP PROJECTIONS
GATE 1   1.35
GATE 2   1.02
GATE 3   1.?5

NON AVIATION   13 %

DEPTH OF DETAIL (CCR?)   70%

TOTAL ANNUAL PER ANNUM FILLS COMMUNITY   95.7

DEFAULT ENTITLEMENT FIGURES 4.5 - 30 MOS

ALL REQUIREMENTS MET   TERMINATIONS 24/0

A-52

SUMMARY DATA

ELECTRONIC WARFARE (24) COMMUNITY
NAVAL AVIATION

****

		NUMBER OF SQUADRONS	4
		AIRCRAFT PER SQUADRON	0
		CREW FACTOR	0.00
		NAVAL AVIATORS PER CREW	0.00

RETENTION   45 %

FEEDBACK FRACTION   5 %

****

COMMUNITY POPULATION

| | | | COMMAND OPPORTUNITY | .15 |
| | | | DEPT HEAD OPPORTUNITY | .50 |

ACCESSIONS TO TRAINING (132X)   45

		SENIOR COMMANDERS	71
		COMMANDERS	44
		LT. COMMANDERS	60
		LIEUTENANTS	217

ACCESSIONS TO 132X DESIGNATOR   45
FIRST TOUR LENGTH   42

| | TOTALS | 362 |

****

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	GRADE				
	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TOURS	140	21	2	2	165
FLEET READINESS SQUADRON	0	0	0	0	0
TRAINING COMMAND	10	5	1	0	18
R&D COMMUNITY	3	7	3	0	13
AFLOAT ASSIGNMENTS	7	7	4	0	18
PROFESSIONAL EDUCATION	7	3	2	0	12
OTHER	24	10	27	3	67
NON AVIATION ASSIGNMENTS	31	18	6	13	68

| LOWER GRADE TOURS | 13 | | 6 | | |

****

	ACIP PROJECTIONS	
GATE 1	1	1.74
GATE 2	2	.94
GATE 3	3	1.15

| NON AVIATION | 12 % |
| 1ST UP PH TGT (LCDR) | 20% |

TOTAL ANNUAL PCS MOVES, THIS COMMUNITY   362

****

****

ALL REQUIREMENTS MET   DETACH 1 DRAFT 1 TOURS A/C = 10 HRS.   OPERATIONS

A-53

SUMMARY DATA

FORCE SUPPORT PIPE COMMUNITY
NAVAL AVIATORS

GROUP 13
OF/A/AZZ3
15/03

RETENTION   45 %

FLOWBACK FRACTION   5 %

NUMBER OF SQUADRONS   13
AIRCRAFT PER SQUADRON   15
CREW FACTOR   0.00
NAVAL AVIATORS PER CREW   0.00

COMMUNITY POPULATION

SENIOR COMMANDERS   13
LT. COMMANDERS   15
LIEUTENANTS   74

COMMAND OPPORTUNITY   .74
DEPT HEAD OPPORTUNITY   .70

TOTALS   121

ACCESSIONS TO TRAINING (TPX)   15

ACCESSIONS TO 11?X DESIGNATOR   11
FIRST TOUR LENGTH   4.3

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	GRADE					
	LT	LCDR	CDR	SEN CDR	TOTAL	
	40	10	3		53	
FLEET TOURS						
FLEET READINESS SQUADRON	5	3	0	0	6	
TRAINING COMMAND	5	1	1	0	7	
R&D COMMUNITY	3	1	0	0	4	
AFLOAT ASSIGNMENTS	2	3	2	0	7	
PROFESSIONAL EDUCATION	2	3	0	0	4	
OTHER	13	3	3	0	74	
NON-AVIATION ASSIGNMENTS	2	3	3	0	17	

ACTP PROJECTIONS

GATE 1   1.31
GATE 2   1.61
GATE 3   1.74

NON AVIATION   14 %

LOWER GRADE FILLS   6   0   DEPT HEAD BILLS FILLED   20%

TOTAL ANNUAL PIPE BOARD TO PIPE COMMUNITY   73

ALL REQUIREMENTS MET   BILLET DEBITED PIPE GATES TO MET   TERMINATE   172

COMMAND DATA

HELICOPTER ASW COMMUNITY
NAVAL AVIATION

NUMBER OF SQUADRONS
AIRCRAFT PER SQUADRON
CREW FACTOR   1.04
NAVAL AVIATORS PER CREW   2.00

RETENTION   45 %

PLOWBACK FRACTION   5 %

COMMUNITY POPULATION

SENIOR COMMANDERS	53	
COMMANDERS	72	COMMAND OPPORTUNITY	.76
LT. COMMANDERS	104	DEPT HEAD OPPORTUNITY	.79
LIEUTENANTS	825		

TOTALS   627

ACCESSIONS TO TRAINING (13X)   79

ACCESSIONS TO 13X DESIGNATOR   52
FIRST TOUR LENGTH   34

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY

	GRADE				
	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TOURS	202	53	25	17	297
FLEET READINESS SQUADRON	63	11	0	0	78
TRAINING COMMAND	33	3	1	0	77
R&D COMMAND	11	4	5	1	21
AFLOAT ASSIGNMENTS	11	3	0	3	32
PROFESSIONAL EDUCATION	11	2	2	3	20
OTHER	34	17	33	24	108
NON AVIATION ASSIGNMENTS	13	10	1	3	13

LOWER GRADE FILLS   27   0   LT OF DETAIL (LCDR)   20%

ACIP PROJECTIONS

GATE 1   1.49
GATE 2   1.20
GATE 3   1.46

NON AVIATION   5 %

TOTAL ANNUAL PCS MOVES THIS COMMUNITY   25%

DEFAULT PROFILE (LINES 4, 5, 6, 10 HRS).

ALL REQUIREMENTS MET   ITERATIONS = 1/1

A-55

SUMMARY DATA

LAMPS MK I COMMUNITY
NAVAL AVIATORS

		NUMBER OF SQUADRONS	C
		AIRCRAFT PER SQUADRON	6
RETENTION	45 %	CREW FACTOR	2.00
PLOWBACK FRACTION	5 %	NAVAL AVIATORS PER CREW	2.00

COMMUNITY POPULATION

		SENIOR COMMANDERS	66	COMMAND OPPORTUNITY	.30
ACCESSIONS TO TRAINING (1YSX)	72	COMMANDERS	82	DEPT HEAD OPPORTUNITY	.65
ACCESSIONS TO 131X DESIGNATOR	53	LT. COMMANDERS	112		
FIRST TOUR LENGTH	45	LIEUTENANTS	325		
		TOTALS	645		

DISTRIBUTION BY GRADE AND ACTIVITY

			GRADE				
ACTIVITY		LT	LCDR	CDR	SEN CDR	TOTAL	
FLEET TOURS							
FLEET READINESS SQUADRON	84	30	6	13	3	317	
TRAINING COMMAND	35	4	15	3	1	75	AGGR PRODUCTIONS
R&D COMMUNITY	31	7	5	5		33	GATE 1 1.53
AFLOAT ASSIGNMENTS	62	33	7	10		73	GATE 2 1.12
PROFESSIONAL EDUCATION	13	10	4	5		30	GATE 3 1.46
OTHER	33	47	62	3	10	145	
NON AVIATION ASSIGNMENTS	0			1		16	NON AVIATION .2 %
LOWER GRADE TOUR		7	3				HT HEAD IN TOUR (LCDR) .64

TOTAL ANNUAL PRODUCTIONS THIS COMMUNITY   262

DEPARTMENT HEAD TOURS THIS COMMUNITY 45   10 HRS   UTILIZATION .7 %

ALL REQUIREMENT MET

GROUP C
05/06/07
TYPE

A-56

COMMUNITY DATA

LAMPS MK III COMMUNITY
NAVAL AVIATORS

NUMBER OF SQUADRONS	
AIRCRAFT PER SQUADRON	2.00
CREW FACTOR	2.00
NAVAL AVIATORS PER CREW	

RETENTION   45 %

PLOWBACK FRACTION   5 %

COMMUNITY POPULATION

SENIOR COMMANDERS	501
COMMANDERS	158
LT. COMMANDERS	595
LIEUTENANTS	737
TOTAL	6756

		COMMAND OPPORTUNITY	.70
		DEPT HEAD OPPORTUNITY	1.00

ACCESSIONS TO TRAINING (1TPX)   162

ACCESSIONS TO 131X DESIGNATOR   120
FIRST TOUR LENGTH   34

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TOURS	470	110			580
FLEET READINESS SQUADRON	48		0		54
TRAINING COMMAND	67		3	0	76
R&D COMMUNITY	22	15	4	2	42
AFLOAT ASSIGNMENTS	20	7	13	15	57
PROFESSIONAL EDUCATION	23	6	12	0	41
OTHER	75	33	86	35	226
NON AVIATION ASSIGNMENTS	106	27	0	48	181

ACIP PROJECTIONS		
GATE 1	1.31
GATE 2	1.04
GATE 3	1.02

NON AVIATION   14 %

LOWER GRADE FILLS   54 ...

TOTAL ANNUAL PCS MOVES THRU COMMUNITY   543

ALL REQUIREMENTS MET

SUMMARY DATA

FORCE SUPPORT INTER-COMMUNITY
NAVAL AVIATORS

RETENTION	45 %	NUMBER OF COMMANDERS	81	COMMAND OPPORTUNITY	.30
PLOWBACK FRACTION	5 %	AIRCRAFT PER SQUADRON	11.2	DEPT HEAD OPPORTUNITY	.63
		CREW PER TUBE	1.9		
		NAVAL AVIATORS PER CREW	.924		

ACCESSIONS TO TRAINING (13XX)   120

ACCESSIONS TO 131X DESIGNATOR   88
FIRST TOUR LENGTH   39

COMMUNITY POPULATION

SENIOR COMMANDERS	81
COMMANDERS	112
LT. COMMANDERS	122
LIEUTENANTS	924
TOTALS	335

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	GRADE				
	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TUBES	341	67	8	11	478
FLEET READINESS SQUADRON	0	0	0	0	0
TRAINING COMMAND	50	3	1	0	55
R&D COMMUNITY	18	2	6	1	26
AFLOAT ASSIGNMENTS	9	15	8	8	40
PROFESSIONAL EDUCATION	17	7	4	2	30
OTHER	47	28	51	15	140
NON-AVIATION ASSIGNMENTS	102	75	34	44	216

ACTP PRODUCTIONS

GATE 1	1.22
GATE 2	.95
GATE 3	1.16

NON-AVIATION   .77 %

| LOWER GRADE FILLS | 28 | 11 | DEPT HEAD TOUR (LCDR) | .20% |

TOTAL ANNUAL PCS MOVES FULL COMMUNITY   435%

ALL REQUIREMENTS MET   DEFAULT RUN LIFE SUBGROUPS = 30 MONTHS   DEGRADATIONS = .77 %

A-58

SUMMARY DATA

FIGHTER COMMUNITY
NAVAL FLIGHT OFFICERS

NUMBER OF SQUADRONS
AIRCRAFT PER SQUADRON
CREW FACTOR   1.17
NAVAL FLIGHT OFFICERS PER CREW   1.00

RETENTION   45 %

PLOWBACK FRACTION   5 %

COMMAND OPPORTUNITY
DEPT HEAD OPPORTUNITY

COMMUNITY POPULATION

	SENIOR COMMANDERS	SEN CDR	TOTAL
SENIOR COMMANDERS			
COMMANDERS			
LT. COMMANDERS			
LIEUTENANTS			
TOTALS			748

ACCESSIONS TO TRAINING (1172X)

ACCESSIONS TO 1132X DESIGNATOR   70
FIRST TOUR LENGTH   43

ACFP PROJECTIONS
GATE 1
GATE 2
GATE 3

NON AVIATION

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	GRADE				
	LT	LCDR	CDR	SEN CDR	
FLEET TOURS					
FLEET READINESS SQUADRON					
TRAINING COMMAND					
RAD COMMUNITY					
AFLOAT ASSIGNMENTS					
PROFESSIONAL EDUCATION					
OTHER					
NON AVIATION ASSIGNMENTS					
LOWER GRADE FILLS					

TOTAL ANNUAL PCS MOVES THIS COMMUNITY   373

ALL REQUIREMENTS MET

A-59

SUMMARY DATA

MEDIUM ATTACK COMMUNITY
NAVAL FLIGHT OFFICERS

NUMBER OF SQUADRONS: 12
AIRCRAFT PER SQUADRON: 14
CREW FACTOR 1.14
NAVAL FLIGHT OFFICERS PER CREW 1.00

RETENTION   45 %

FLOWBACK FRACTION   5 %

COMMUNITY POPULATION

		COMMAND OPPORTUNITY	.54
ACCESSIONS TO TRAINING (197X)	77	SENIOR COMMANDERS	42	DEPT HEAD OPPORTUNITY	.53
		COMMANDERS	54		
ACCESSIONS TO 192X DESIGNATOR	43	LT. COMMANDERS	74		
FIRST TOUR LENGTH	45	LIEUTENANTS	283		
		TOTALS	453		

DISTRIBUTION BY GRADE AND ACTIVITY

| ACTIVITY | GRADE | | | | ACIP PROJECTIONS |
	LT	LCDR	CDR	SEN CDR	TOTAL	
FLEET TOURS	183	77	3	17	280	
FLEET READINESS SQUADRON	34	4	2	1	40	GATE 1 1.33
TRAINING COMMAND	7	1	0	0	8	GATE 2 1.08
R&D COMMUNITY	8	1	1	2	12	GATE 3 1.33
AFLOAT ASSIGNMENTS	3	10	3	2	17	
PROFESSIONAL EDUCATION	8	2	4	0	15	
OTHER	30	3	28	8	77	
NON-AVIATION ASSIGNMENTS	8	20	13	13	53	NON AVIATION 13 %

| LOWER GRADE TOURS | 14 | 5 | | | | IN IN DETAIL (LCDR)   20% |

TOTAL ANNUAL PCS MOVES THIS COMMUNITY   ???

DEFAULT POINT TIMES, A, B, ... RE MODE.

ALL REQUIREMENTS MET

SUMMARY DATA

ELECTRONIC WARFARE COMMUNITY
NAVAL FLIGHT OFFICERS

NUMBER OF SQUADRONS		2
AIRCRAFT PER SQUADRON		4
CREW FACTOR		1.50
NAVAL FLIGHT OFFICERS PER CREW		3.00

RETENTION	45 %
PLOWBACK FRACTION	5 %

COMMAND OPPORTUNITY	.53
DEPT HEAD OPPORTUNITY	1.00

COMMUNITY POPULATION

		SEN CDR	TOTAL
SENIOR COMMANDERS		11	231
COMMANDERS		1	83
LT. COMMANDERS		0	6
LIEUTENANTS		2	12
		0	17
		7	14
		18	69
TOTALS			24
			456

ACCESSIONS TO TRAINING (137%)	74
ACCESSIONS TO 132X DESIGNATOR	42
FIRST TOUR LENGTH	47

ACIP PROJECTIONS

GATE 1	1.58
GATE 2	1.05
GATE 3	1.52

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TOURS	181	31	8	11	231
FLEET READINESS SQUADRON	72	0	3	1	83
TRAINING COMMAND	5	1	0	0	6
R&D COMMUNITY	1	10	1	0	12
AFLOAT ASSIGNMENTS	1	12	2	2	17
PROFESSIONAL EDUCATION	5	7	2	0	14
OTHER	5	23	33	7	69
NON-AVIATION ASSIGNMENTS	0	0	6	18	24

NON AVIATION 5 %

LOWER GRADE FILLS	0
DEPT HEAD DETAIL (CONG)	4
DEPT HEAD DETAIL (CONG) 20%	

TOTAL ANNUAL POSS MANMTS THIS COMMUNITY 227

DETAIL DURING FLT TOURS 4, 5 - 30 MOS.

ITERATIONS = 127

ALL REQUIREMENTS MET

A-61

SUMMARY DATA

CARRIER BASED ASW COMMUNITY
NAVAL FLIGHT OFFICERS

NUMBER OF SQUADRONS	44
AIRCRAFT PER SQUADRON	63
CREW FACTOR	1.44
NAVAL FLIGHT OFFICERS PER CREW	1.00

RETENTION	45 %
PLOWBACK FRACTION	5 %

COMMUNITY POPULATION

SENIOR COMMANDERS		8
COMMANDERS		63
LT. COMMANDERS		86
LIEUTENANCE		317
TOTALS		**510**

COMMAND OPPORTUNITY	.51
DEPT HEAD OPPORTUNITY	.66

ACCESSIONS TO TRAINING (1370)	80
ACCESSIONS TO 137X DESIGNATOR	48
FIRST TOUR LENGTH	44

ACIP PROJECTIONS

GATE 1	1.33
GATE 2	3.03
GATE 3	1.26

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TOURS	202	35	6	8	251
FLEET READINESS SQUADRON	27	3	1	0	31
TRAINING COMMAND	8	3	0	0	3
R&D COMMUNITY	2	4	1	0	13
AFLOAT ASSIGNMENTS	3	10	3	2	19
PROFESSIONAL EDUCATION	2	3	4	0	16
OTHER	35	17	28	8	83
NON-AVIATION ASSIGNMENTS	24	18	20	25	88

NON AVIATION 17 %

LOWER GRADE FILLS	15
DEPT HEAD DETAIL (LCDR)	20%

TOTAL ANNUAL REQUIREMENTS THIS COMMUNITY 251

DEPARTMENT HEAD TOURS 4.5 - 10 MOS.

ALL REQUIREMENTS MET

SUMMARY DATA

FIRST CAPTAIN ... OFF COMMUNITY
NAVAL FLIGHT OFFICERS

		NUMBER OF COMMANDING	13
		AIRCRAFT TYPE COMMANDED	0
		CREW FACTOR	0.00
		NAVAL FLIGHT OFF (OFF) PER CREW	0.00

RETENTION   45 %

PLOWBACK FRACTION   5 %

****

COMMUNITY POPULATION

| | | | | COMMAND OPPORTUNITY | 0.00 |
| | | | | DEPT HEAD OPPORTUNITY | .?? |

ACCESSIONS TO TRAINING (132X)   16

	SENIOR COMMANDERS	8
	COMMANDERS	11
	LT. COMMANDERS	16
	LIEUTENANTS	60

ACCESSIONS TO 132X DESIGNATOR   3

FIRST TOUR LENGTH   (?)

TOTALS   95

****

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	GRADE					
	LT	LCDR	CDR	SEN CDR	TOTAL	
FLEET TOURS	56	10	4	3	70	
FLEET READINESS SQUADRON	0	0	0	0	0	
TRAINING COMMAND	1	0	0	0	2	
R&D COMMUNITY	0	0	0	0	2	
AFLOAT ASSIGNMENTS	1	1	1	0	3	
PROFESSIONAL EDUCATION	3	2	3	2	10	
OTHER	2	6	4	2	9	
NON AVIATION ASSIGNMENTS						

****

TOTAL ANNUAL PCS MOVES THIS COMMUNITY   50

ACIP PROJECTIONS

GATE 1	1.59
GATE 2	1.??
GATE 3	1.??

NON AVIATION   ? %

DEFAULT RUN FIT TOURS   DEFAULT RUN FIT TOURS 4,5 = 30 MOS

****

ALL REQUIREMENTS MET   ITERATIONS   1/1

SUMMARY DATA

EARLY WARNING COMMUNITY
NAVAL FLIGHT OFFICERS

NUMBER OF SQUADRONS
AIRCRAFT PER SQUADRON
CREW FACTOR   1.66
NAVAL FLIGHT OFFICERS PER CREW   1.00

RETENTION   45 %

FLOWBACK FRACTION   5 %

COMMUNITY POPULATION

	SENIOR COMMANDERS	39
ACCESSIONS TO TRAINING (132X)	COMMANDERS	52
ACCESSIONS TO 132X DESIGNATOR 41	LT. COMMANDERS	71
FIRST TOUR LENGTH 45	LIEUTENANTS	266

TOTALS   428

COMMAND OPPORTUNITY
DEPT HEAD OPPORTUNITY

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	GRADE				
	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TOURS	172	27	5	11	215
FLEET READINESS SQUADRON	30	2	1	1	42
TRAINING COMMAND	4	3	1	0	7
R&D COMMUNITY	7	3	3	0	11
AFLOAT ASSIGNMENTS	3	2	4	2	16
PROFESSIONAL EDUCATION	8	10	25	7	14
OTHER	22	15	13	18	71
NON-AVIATION ASSIGNMENTS	7				53

LOWER GRADE FILLS   13   5

TOTAL ANNUAL PCS MOVES THRU COMMUNITY   189

ALL REQUIREMENTS MET   DEPART FROM T TARGET BY ... TO 100%

NON AVIATION   19 %

DEPT HEAD OPPORTUNITY

ACTP PROJECTIONS

GATE 1   1.41
GATE 2   1.11
GATE 3   1.35

A-64

SUMMARY DATA

MARITIME PATROL COMMUNITY
NAVAL FLIGHT OFFICERS

GROUP G
01/AVN3
1990

NUMBER OF SQUADRONS: 24
AIRCRAFT PER SQUADRON
CREW FACTOR   1.23
NAVAL FLIGHT OFFICERS PER CREW   3.00

RETENTION	45 %		
PLOWBACK FRACTION	5 %		

COMMAND OPPORTUNITY   .46
DEPT HEAD OPPORTUNITY   .55

COMMUNITY POPULATION

			SEN CDR	CDR	TOTAL
SENIOR COMMANDERS					727
COMMANDERS					66
LT COMMANDERS					17
LIEUTENANTS					77

TOTALS   1487

ACCESSIONS TO TRAINING (132X)   208
ACCESSIONS TO 132X DESIGNATOR   144
FIRST TOUR LENGTH   44

AVP PROJECTIONS

GATE 1   1.77
GATE 2   .22
GATE 3   1.00

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TOURS	601	94	5		
FLEET READINESS SQUADRON	40	4	1	2	
TRAINING COMMAND	15	1	1	0	
R&D COMMUNITY	24	3	3	1	
AFLOAT ASSIGNMENTS	2	2	8	6	
PROFESSIONAL EDUCATION	28	7	10	4	
OTHER	33	28	81	25	
NON AVIATION ASSIGNMENTS	110	70	60	66	307

TOTAL			
LOWER GRADE FILLS	42	13	

NON AVIATION   21 %

OUT OF INVENTORY (LCDR)   20%

TOTAL ANNUAL REQ. MARITIME PATROL COMMUNITY   654

DEFAULT RUN FLT HOURS A/C = 30 HRS   UTILIZATION = 127.3

ALL REQUIREMENTS MET

SUMMARY DATA

ELECTRONIC WARFARE   VAQ COMMUNITY
NAVAL FLIGHT OFFICERS

NUMBER OF SQUADRONS   4
AIRCRAFT PER SQUADRON   0
CREW FACTOR   0.00
NAVAL FLIGHT OFFICERS PER CREW 0.00

RETENTION   45 %
PI DMBACK FRACTION   ?

COMMUNITY POPULATION

SENIOR COMMANDERS	32		
COMMANDERS	41		
LT. COMMANDERS	63		
LIEUTENANTS	246		

COMMAND OPPORTUNITY   .21
DEPT HEAD OPPORTUNITY .26

ACCESSIONS TO TRAINING (117%)   54
ACCESSIONS TO 1 BYR DESIGNATOR   38
FIRST TOUR LENGTH   47

TOTALS   382

ACIP PROJECTIONS

GATE 1   1.12
GATE 2   .8?
GATE 3   1.09

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	GRADE				
	LT	LCDR	CDR	SEN CDR	TOTAL
	10%	15	7	3	180
FLEET READINESS SQUADRON	4	0	0	0	0
TRAINING COMMAND	8	2	1	0	5
RND COMMUNITY	7	15	6	2	11
AFLOAT ASSIGNMENTS	7	7	3	1	15
PROFESSIONAL EDUCATION	23	7	23	3	17
OTHER	23	30	17	17	67
NON AVIATION ASSIGNMENTS					90

NON AVIATION   24 %

LOWER GRADE FILLS   3   3   HT OF IN GRD (LCDR)   20%

TOTAL ANNUAL PCS WITHIN THIS COMMUNITY   26?

ALL REQUIREMENTS MET   DETACHT TURN OUT TOURS ...   NO IMP...   ITERATION   1 - 2

SUMMARY DATA

FORCE SUPPORT - PILOT COMMUNITY
NAVAL FLIGHT OFFICERS

RETENTION   45 %

PLAYBACK FRACTION   5 %

NUMBER OF SQUADRONS   ?
AIRCRAFT PER SQUADRON   0.00
CREW FACTOR   0.00
NAVAL FLIGHT OFFICERS PER CREW   0.00   .94

***

ACCESSIONS TO TRAINING (132X)   7

ACCESSIONS TO 132X DESIGNATOR   5
FIRST TOUR LENGTH   64

COMMUNITY POPULATION

SENIOR COMMANDERS   0
COMMANDERS   0
LT. COMMANDERS   ?
LIEUTENANTS   31

TOTALS   52

COMMAND OPPORTUNITY   0.00
DEPT HEAD OPPORTUNITY   .94

***

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY	GRADE				
	LT	LCDR	CDR	SEN CDR	TOTAL
FLEET TOURS	20	0	0	0	??
FLEET READINESS SQUADRON	0	0	0	0	0
TRAINING COMMAND	1	1	0	0	?
R&D COMMAND	0	0	0	0	?
AFLOAT ASSIGNMENTS	1	1	0	0	?
PROFESSIONAL EDUCATION	0	0	0	0	?
OTHER	3	3	4	0	10
NON AVIATION ASSIGNMENTS	0	0	0	0	3

NON AVIATION   0 %

ACFT PROJECTIONS

GATE 1   1.??
GATE 2   1.??
GATE 3   1.4?

***

TOTAL ANNUAL PCS MONTHS 132X COMMUNITY   ?4

DETAILED RESULTS USING GATES 4,5,6 = 30 MOS.

ALL REQUIREMENTS MET

ITERATIONS = 1/0

MILITARY PERSONNEL SUMMARY

01/10/83

NAVAL AVIATORS

DISTRIBUTION BY GRADE AND ACTIVITY

ACTIVITY		GRADE		
	LT	LCDR	CDR	TOTAL
FLEET TOURS	3345	705	861	4915
FLEET READINESS SQUADRON	673	79	79	721
TRAINING COMMAND	682	73	33	801
R&D COMMUNITY	195	109	69	373
AFLOAT ASSIGNMENTS	137	147	259	543
PROFESSIONAL EDUCATION	182	63	102	347
OTHER	530	376	1075	1981
NON AVIATION ASSIGNMENTS	475	235	343	1005
TOTALS	6826	1833	2338	11002

TOTAL ANNUAL PCS MOVES   4830

ACCESSION REQUIREMENTS BY TRAINING PIPELINE

	TO TRAINING	TO DESIGNATOR (DTR)
STRIKE	967	414
MARITIME PATROL	38	292
HELICOPTER	440	307
TOTALS	1408	1040

DEFAULT RUN DTR TIMES 6.5 - 30 MOS.

APPENDIX B

PROGRAM LISTING

This appendix provides the program and subroutine listing. After each listing is the basic cross-reference for variables, arrays, and labels.

```
10 **********************************************************************
20 *                                                                  *
30 *               AVIATION OFFICER REQUIREMENTS MODEL                 *
40 *                         VERSION 7.1                               *
50 *                                                                  *
60 *                                                                  *
70 * MULTIPLE RUNS                       (OKIE15 LINKED TO OKIE11)*
80 **********************************************************************
90 /*
100
110                      MODEL DESCRIPTION
120
130        THE AVIATION OFFICER REQUIREMENTS MODEL IS A STEADY STATE,
140 DETERMINISTIC, SIMULATION OF THE OFFICER CAREER PATH FLOWS FOR
150 THE AVIATION OFFICER COMMUNITY OF THE NAVY.  THE SET OF ALL
160 AVIATION OFFICER BILLETS (131X/132X) IS PARTITIONED INTO TWENTY
170 THREE SUBCOMMUNITIES (E.G. FIGHTER AVIATOR, MARITIME PATROL NFO).
180 A CAREER PATH NETWORK IS SPECIFIED FOR EACH SUBCOMMUNITY WHICH
190 CLASSIFIES SUBCOMMUNITY REQUIREMENTS IN TERMS OF TOUR NUMBER AND
200 ACTIVITY.  ACTIVITIES ARE DESCRIPTIVE CATEGORIES WHICH BROADLY
210 CHARACTERIZE THE DUTIES TO WHICH AVIATION OFFICERS ARE ASSIGNED.
220 THUS A SET OF 49 ACTIVITY/TOUR NUMBER STATES ARE CREATED FOR EACH
230 SUBCOMMUNITY.  IN ADDITION, THE MODEL SPECIFIES TRANSITION RULES
240 BY WHICH THE MOVEMENT OF OFFICERS BETWEEN STATES ARE GOVERNED.
250
260        THE MODEL IS WRITTEN IN WANG VS BASIC FOR THE WANG 2200VS
270 COMPUTER.  HOWEVER, THE MODEL IS 'USER FRIENDLY' IN THAT, HAVING
280 LOGGED ON AT A TERMINAL AND CALLED THE PROGRAM LISTED BELOW, THE
290 REMAINDER OF THE SESSION IS INTERACTIVELY CUED TO LEAD THE USER
300 THROUGH SELECTION OF RUN ALTERNATIVES, SETTING OF MODEL PARAMETERS
310 AND SELECTION OF OUTPUTS.  THE USER CAN ALTER ANY (OR ALL) OF 29
320 MODEL PARAMETERS FOR A GIVEN SUBCOMMUNITY RUN.  THE MODEL IS PRE-
330 LOADED WITH DEFAULT VALUES FOR ALL PARAMETERS.  THESE REPRESENT
340 CURRENT NAVY PRACTICE.  IF THE USER DOES NOT CHANGE A PARAMETER
350 DURING SET UP, THE DEFAULT VALUE IS USED.  THE USER ALSO HAS THE
360 OPTION OF MAKING SINGLE SUBCOMMUNITY RUNS OR MULTIPLE RUNS COVER-
370 ING ANY NUMBER OF SUBCOMMUNITIES IN A SINGLE SET UP.
380
390        THE PROGRAM LISTING HAS BEEN BROKEN DOWN INTO SEGMENTS WHICH
400 PRESENT THE MAJOR FUNCTIONS PERFORMED IN LOGICAL SEQUENCE.
410
420        SECTION                   CONTENTS
430
440        I          DEFAULT DATA AND PROGRAM INITIALIZATION
450       II          INTERACTIVE ENTRY/REENTRY ROUTINES
460      III          MULTIPLE RUN SET UP ROUTINES
470       IV          REQUIREMENTS COMPUTATION
480        V          NETWORK SOLUTION ROUTINES
490       VI          ITERATION CHECK ROUTINES
500      VII          SUBROUTINES
510
520 NOTE: OUTPUT LISTINGS ARE GENERATED IN AN EXTERNAL SUBROUTINE
530       CALLED 'OFFPRIN' WHICH IS NOT PART OF THIS LISTING.      */
```

```
550 COM DO(7,4),INVT(9,31),A$22,P5,P6,LABEL$(9)25,TYPE$(14)30,Q11,T$5
560 COM D$8,DB(8),S1(15,5),PO(10),RO2,D3(4),I4(7,7),T5(20),T8(20),T11
570 COM P1$(9)130,X4$130,X5$130,B$70,C$70,T15(20),Q7(7,7),TCO(7,5),D9
580 COM A1(15,9),E$130,T9$(7,7)26,Z1$3,Z4$3,Q37(8,4),OUTA(8),RO(30)
590 COM X$70,PRO4,PRO5,ACC1,MGROUP$30,TOT(8,3),TOTA(8,3),TOTN(8,3)
600 COM PTR(14),TRA$(7)25,Q76,Q85(5),Q89(5),Q75(5),Q73(5),Q74
610 DIM NO(7),T7(20),GO(15,13),OTH(3,2),INVTO(31),TC(20),I41(7,7)
620 DIM AUX(15,6),Q4(7,4),Q38(7),POSIT$(5)4,T10$(7,7)20,T22(50)
630 DIM T17(20),T18(50),A50(7),T11$(15)20,Z24$3,Z34$3,T13(7),T21(7)
640 DIM N9$(7,7)1,Q4$7,ROUTE$7,Q5$1,P2$(10)30,I40(7,7),PRO2$(0)5,FA1(5)
650 DIM GROUP$30,TGROUP$30,BGROUP$30,COM$CO,R2(7,7)
660 DIM I42(7,7),M$2,I$2,E$440,COM1$30
670 ***********************************************************
680 *                                                         *
690 *        THIS FIRST SECTION OF THE PROGRAM DEFINES         *
700 *        AND LOADS THE BASIC MATRICES RO, GO, S1, A1       *
710 *        TCO AND T9$                                       *
720 *                                                         *
730 ***********************************************************
740 REM CONTINUATION MATRIX
750 JMP106:DATA 5,2,4,8,1,6,4                             /*STRUCTURE*/
760 DATA .986,.676,.924,.980,.222,.652,0                  /*VALUES*/
770 REM GRADE MATRIX GO
780 REM SQ PILOT/NFO;FRS PILOT/NFO O5,O4,O3--
790 DATA 2,4,11,0,0,0,8,23,85,0,0,0,24                    /*VAL */
800 DATA 1,2,11,1,2,11,8,23,137,4,15,77,24                /*VF  */
810 DATA 1,2,13,1,2,13,2,5,44,2,6,31,12                   /*VAM */
820 DATA 1,2,7,1,2,12,2,6,34,2,5,33,12                    /*VAW */
830 DATA 1,2,3,1,3,14,1,3,38,1,3,76,9                     /*VAQ */
840 DATA 1,3,16,1,3,15,1,8,47,1,5,24,11                   /*VS  */
850 DATA 2,4,14,0,0,0,4,17,57,0,0,0,11                    /*HS*/
860 DATA 1,3,34,1,3,19,2,15,70,2,9,53,24                  /*VP*/
870 DATA 2,4,14,0,0,0,4,17,51,0,0,0,6                     /*HSL1*/
880 DATA 2,17,41,0,0,0,2,13,32,0,0,0,8                    /*HSL2*/
890 DATA 0,0,0,0,0,0,0,0,0,0,0,0,4                        /*VQ  */
900 DATA 0,0,0,0,0,0,0,0,0,0,0,0,13                       /*FSU */
910 DATA 0,0,0,0,0,0,0,0,0,0,0,0,2                        /*FSP */
920 DATA 0,0,0,0,0,0,0,0,0,0,0,0,8                        /*FSU */
930 DATA 1,3,1,0,0,0,0,0,0,0,0,0,12                       /*WING*/
940 REM SQUADRON MATRIX S1
950 REM NO SQ, A/C /SQ, CREW FACT,PILOT/CREW, NFO/CREW
960 DATA 24,12,1.42,1,0                                   /*VAL */
970 DATA 24,12,1.17,1,1                                   /*VF  */
980 DATA 12,14,1.14,1,1                                   /*VAM */
990 DATA 12,3,1.66,2,3                                    /*VAW */
1000 DATA 9,4,1.5,1,3                                     /*VAQ */
1010 DATA 11,9,1.44,1.5,1.5                               /*VS  */
1020 DATA 11,6,1.66,2,0                                   /*HS */
1030 DATA 24,9,1.33,3,2                                   /*VP */
```

SECTION I: DEFAULT DATA AND INITIALIZATION

```
1040 DATA 6,11,2,2,0                                /*HSL1*/
1050 DATA 8,15,2,2,0                                /*HSL2*/
1060 DATA 4,0,0,0,0                                 /*VQ  */
1070 DATA 13,0,0,0,0                                /*FSJ */
1080 DATA 2,0,0,0,0                                 /*FSP */
1090 DATA 8,0,0,0,0                                 /*FSH */
1100 DATA 12,0,0,0,0                                /*WING*/
1110 REM ALLOCATION MATRIX A1
1120 REM PILOT PIPE,NFO PIPE, PILOTS-ALL,COMMUNITY,CV;NFO - ALL,      ''
1130 COMMUNITY,CV, ALL.
1140 DATA 1,0,.1068,.2690,.2690,0,0,0,.0729          /*VAL*/
1150 DATA 1,4,.0838,.2110,.2110,.1797,1.0,.3101,.1142   /*VF */
1160 DATA 1,5,.0475,.1195,.1195,.1011,.3103,.1744,.0045   /*VAM*/
1170 DATA 2,6,.0311,.1045,.0783,.0929,1,.1604,.0507      /*VAW*/
1180 DATA 1,5,.0197,.0496,.0496,.0965,.3013,.1665,.0441  /*VAQ*/
1190 DATA 1,5,.0508,.1279,.1279,.1092,.3419,.1825,.0034  /*VQ */
1200 DATA 3,0,.0575,.1883,.1447,0,0,0,.0392             /*HS */
1210 DATA 2,7,.2210,.7424,0,.3047,.7472,0,.2478         /*VP */
1220 DATA 3,0,.0628,.2058,0,0,0,0,.0429                 /*HSL1*/
1230 DATA 3,0,.1141,.3739,0,0,0,0,.0778                 /*HSL2*/
1240 DATA 2,7,.0337,.1132,0,.0883,.2165,0,.0510         /*VQ */
1250 DATA 1,5,.0886,.2230,0,.0128,.0399,0,.0085         /*FSJ*/
1260 DATA 2,7,.0119,.0399,0,.0148,.0363,0,.0128         /*FSP*/
1270 DATA 3,0,.0708,.2319,0,0,0,0,.0483                 /*FSH*/
1280 DATA 1,1,.3972,0,1.0,.5794,0,1.0,.4550             /*WING*/
1290 REM AUXILLIARY MATRIX AUX
1300 REM PILOT/NFO TOTALS - 05,04,03
1310 DATA 0,12,18,0,0,0                                 /*AUX VA*/
1320 DATA 0,6,6,0,4,8                                   /*AUX VF*/
1330 DATA 0,4,0,0,2,0                                   /*AUX VAM*/
1340 DATA 0,2,2,0,2,0                                   /*AUX VAW*/
1350 DATA 2,4,21,1,5,29                                 /*AUX VAQ*/
1360 DATA 0,0,0,0,0,0                                   /*AUX VQ*/
1370 DATA 2,10,4,0,0,0                                  /*AUX HS*/
1380 DATA 0,56,6,0,17,27                                /*AUX VP*/
1390 DATA 0,6,0,0,0,0                                   /*AUX HSL1*/
1400 DATA 0,0,0,0,0,0                                   /*AUX HSL2*/
1410 DATA 4,20,117,3,12,140                             /*AUX VQ */
1420 DATA 25,96,247,6,10,47                             /*AUX FSJ*/
1430 DATA 2,10,38,2,4,23                                /*AUX FSP*/
1440 DATA 16,65,270,0,0,0                               /*AUX FSH*/
1450 DATA 0,0,0,0,0,0                                   /*AUX WING*/
1460 REM TRAINING COMMAND MATRIX TCO
1470 REM J,P,H,RIO,TN,ATDS,NAV.
1480 REM I/O RATIO, 05, 04, IP, INFO
1490 DATA 1.405,22,44,.800,0                            /*JET*/
1500 DATA 1.281,7,14,.443,0                             /*PROP*/
1510 DATA 1.347,7,14,.542,0                             /*HELO*/
1520 DATA 1.791,1,2,.180,.255                           /*RIO */
1530 DATA 1.771,1,2,.118,.150                           /*TN  */
```

SECTION I: DEFAULT DATA AND INITIALIZATION

```
1540 DATA 1.523,1,2,.070,.073                              /*ATDS*/
1550 DATA 1.426,1,2,.030,.083                              /*NAV */
1560 REM POLICY VECTOR
1570 REM PLOWBACK,PC,WARCOLLEGE,D4,D4+,D5,D6,DDP4,DDP5,DDP6
1580 DATA .05,.30,.50,.85,.20,.70,.60,1,1,1
1590 REM R&D, AFLOAT, OTHER (OTH MATRIX)
1600 REM D5+,D5,D4,D3-
1610 DATA 24,28,120,189,5,6,31,75                          /*R&D*/
1620 DATA 88,105,130,219,14,9,60,82                        /*AFLOAT*/
1630 DATA 263,315,710,634,91,91,243,312                    /*OTHER*/
1640 DATA"FLEET TOURS"
1650 DATA"FLEET READINESS SQUADRON"
1660 DATA"TRAINING COMMAND"
1670 DATA"R&D COMMUNITY"
1680 DATA"AFLOAT ASSIGNMENTS"
1690 DATA"PROFESSIONAL EDUCATION"
1700 DATA"OTHER"
1710 DATA"UNASSIGNED"
1720 DATA"NON-AVIATION ASSIGNMENTS"
1730 DATA"LIGHT ATTACK"
1740 DATA"FIGHTER"
1750 DATA"MEDIUM ATTACK"
1760 DATA"EARLY WARNING"
1770 DATA"ELECTRONIC WARFARE"
1780 DATA"CARRIER BASED ASW"
1790 DATA"HELICOPTER ASW"
1800 DATA"MARITIME PATROL"
1810 DATA"LAMPS MK I"
1820 DATA"LAMPS MK III"
1830 DATA"ELECTRONIC WARFARE - VQ"
1840 DATA"FORCE SUPPORT - JET"
1850 DATA"FORCE SUPPORT - PROP"
1860 DATA"FORCE SUPPORT - HELO"
1870 DATA"STRIKE"
1880 DATA"MARITIME PATROL"
1890 DATA"HELICOPTER"
1900 DATA"RADAR INTERCEPT OFFICER"
1910 DATA"TACTICAL NAVIGATOR"
1920 DATA"ATDS"
1930 DATA"NAVIGATOR"
1940 DATA"FIRST FLEET ITERATION COMPLETE"
1950 DATA"FIRST TOUR FILL-UP COMPLETE"
1960 DATA"CATEGORY SEARCH COMPLETE"
1970 DATA"NFEA'S CREATED"
1980 DATA"FIRST TOUR LENGTH ADJUSTED"
1990 REM LOAD T9$ WITH TOUR LENGTH AND BARRED TOURS
2000 DATA"36000NNNNNNNNNNNNNNNNN000"                       /*FLEET 1*/
2010 DATA"36NNNNNNN000NNNNNNNNNNN000"                      /*FLEET 2*/
2020 DATA"36NNN0000000000NNN0000000"                       /*FLEET 3*/
2030 DATA"36NNN00000000000000000000"                       /*FLEET 4*/
```

SECTION I: DEFAULT DATA AND INITIALIZATION

```
2040 DATA"36NNNO0000000000000000000000000"        /*FLEET 5*/
2050 DATA"240000000000000000000000000000"         /*FLEET 6*/
2060 DATA"120000000000000000000000000000"         /*FLEET 7*/
2070 DATA"36NNNNNNNNNNNNNNNNNNNNNNNNNO00"          /*FRS 1  */
2080 DATA"36000NNNNNNNNNNNNNNNNNNNNNNO00"          /*FRS 2  */
2090 DATA"36000NNNNNNNNNNNNNNNNNNNNNNO00"          /*FRS 3  */
2100 DATA"36000NNNNNNNNNNNNNNNNNNNNNNO00"          /*FRS 4  */
2110 DATA"36000NNNNNNNNNNNNNNNNNNNNNNO00"          /*FRS 5  */
2120 DATA"24000NNNNNN000000000000000000"          /*FRS 6  */
2130 DATA"24000NNNNNNNNNNNNNNNNNNNNO00"           /*FRS 7  */
2140 DATA"24000NNNNNNNNNNNNNNNNNNNNO00"           /*TRAC 1 */
2150 DATA"36000NNNNNNNNNNNNNNNNNNNNNO00"          /*TRAC 2 */
2160 DATA"36NNNNNNNNNNNNNNNN0000000000"           /*TRAC 3 */
2170 DATA"36000NNNNNNNNNNN0000000000000"          /*TRAC 4 */
2180 DATA"36000NNNNNNNNNN00000000000000"          /*TRAC 5 */
2190 DATA"240000000000000000000000000000"         /*TRAC 6 */
2200 DATA"36NNNNNNN000000000000000000000"         /*TRAC 7 */
2210 DATA"36NNNNNNNNNNNNNNNNNNNNNNNO00"           /*RD 1   */
2220 DATA"36000NNNNNNNNNNNNNNNNNNNNNO00"          /*RD 2   */
2230 DATA"36000000000000NNNNNN000NNNO00"          /*RD 3   */
2240 DATA"36000000NNNNNN0000000000000000"         /*RD 4   */
2250 DATA"3600000000000NNNN00000000000000"        /*RD 5   */
2260 DATA"36000000000NNNN000000000000000"         /*RD 6   */
2270 DATA"36000000000000NN000000000000000"        /*RD 7   */
2280 DATA"24NNNNNNNNNNNNNNNNNNNNNNNO00"           /*AFLT 1 */
2290 DATA"24NNNNNNNNNNNNNNNNNNNNNNNO00"           /*AFLT 2 */
2300 DATA"24NNNO000000000NNN000000000000"         /*AFLT 3 */
2310 DATA"24NNNO0000000000NNN000000000000"        /*AFLT 4 */
2320 DATA"24NNNO0000000000NNN000000000000"        /*AFLT 5 */
2330 DATA"24NNNO0000000000NNN000000000000"        /*AFLT 6 */
2340 DATA"24000000000000000NNN000000000000"       /*AFLT 7 */
2350 DATA"24NNNNNNNNNNNNNNNNNNNNNNNO00"           /*PROF 1 */
2360 DATA"24000NNNNNNNNNNNNNNNNNNNNNO00"          /*PROF 2 */
2370 DATA"24000000000000000NNNNNN000000"          /*PROF 3 */
2380 DATA"24000000NNN000000NNN000000"            /*PROF 4 */
2390 DATA"1200000000000000000NNN000000"          /*PROF 5 */
2400 DATA"12000000000000000000NNN000000"         /*PROF 6 */
2410 DATA"12000000000000000000NNN000000"         /*PROF 7 */
2420 DATA"36NNNNNNNNNNNNNNNNNNNNNNNNNO00"         /*OTH 1  */
2430 DATA"36000NNNNNNNNNNNNNNNNNNNNNO00"          /*OTH 2  */
2440 DATA"36000000000000000NNNNNNNNNNO00"         /*OTH 3  */
2450 DATA"36000000000000000NNNNNNNNNNO00"         /*OTH 4  */
2460 DATA"36000000000000000000000000000000"       /*OTH 5  */
2470 DATA"3600000000000000000000000000000"        /*OTH 6  */
2480 DATA"3600000000000000000000000000000"        /*OTH 7  */
2490 DATA .2,.1,.5,.1,.1
2500 SELECT #1,"TEMPO1",INDEXED,RECSIZE=158,KEYPOS=1,KEYLEN=2
2510 FILEFORM:FMT POS(1),CH(2),POS(3),PIC(##),POS(5),PIC(##),POS(7),
2520 PIC(##),POS(9),CH(3),POS(12),CH(3),POS(15),CH(3),POS(18),CH(22),
2530 POS(40),CH(30),POS(70),PIC(##),POS(72),PIC(##),POS(74),PIC(#.##),
```

B-5

SECTION I: DEFAULT DATA AND INITIALIZATION

```
2540 POS(78),PIC(#.#),POS(81),PIC(##),POS(83),PIC(##),POS(85),PIC(##), !
2550 POS(87),PIC(##),POS(89),PIC(##),POS(91),PIC(##),POS(93),PIC(##), !
2560 POS(95),PIC(###),POS(98),PIC(##),POS(100),PIC(##),POS(102), !
2570 PIC(#.###),POS(107),PIC(#.###),POS(112),PIC(#.##),POS(116), !
2580 PIC(#.##),POS(120),PIC(#.##),POS(124),PIC(#.####),POS(130), !
2590 PIC(#.####),POS(136),PIC(#.####),POS(142),PIC(#.####),POS(148), !
2600 PIC(#),POS(149),PIC(#.##),POS(153),PIC(##),POS(155),PIC(##), !
2610 POS(157),PIC(##)
2620 SELECT #2,"TEMPD2",VAR,INDEXED,RECSIZE=400,KEYPOS=1,KEYLEN=2
2630 FILECAR:FMT POS(1),CH(2),POS(3),PIC(##),POS(5),15*CH(26), !
2640      POS(395),PIC(###),POS(398),PIC(###)
2650 OPEN NODISPLAY #1,OUTPUT,SPACE=30,FILE="SOURCE",LIBRARY="DFFREQ", !
2660 VOLUME="VOL555"
2670 CLOSE #1
2680 OPEN NODISPLAY #2,OUTPUT,SPACE=30,FILE="CARRER",LIBRARY="DFFREQ", !
2690 VOLUME="VOL555"
2700 CLOSE #2
2710 JMP105:RESTORE LINE = JMP100
2720 REM LOAD CONTINUATION VECTOR
2730 FOR I = 1 TO 7
2740 READ NO(I)
2750 NEXT I
2760 FOR I = 1 TO 7
2770 READ A50(I)
2780 NEXT I
2790 B32 = 1
2800 FOR I = 1 TO 7
2810 FOR J = B32 TO B32 + NO(I) - 1
2820 RO(J) = A50(I)
2830 NEXT J
2840 B32 = B32 + NO(I)
2850 NEXT I
2860 RO1 = 1
2870 RO2 = .45
2880 RO3 = 5
2890 RO4 = 7
2900 RO5 = 11
2910 INIT(HEX(20))STR(PROD2$,12,53)
2920 PRO4=102:PRO5=102:PRO3=23:PROC=38
2930 STR(PROD2$,23,1)=HEX(5E):STR(PROD2$,38,1)=HEX(5E)
2940 STR(PROD2$,5,1)=HEX(5E)
2950 REM LOAD GRADE MATRIX GO
2960 FOR I = 1 TO 15
2970 FOR J = 1 TO 13
2980 READ GO(I,J)
2990 NEXT J
3000 NEXT I
3010 REM LOAD SQUADRON MATRIX S1
3020 FOR I = 1 TO 15
3030 FOR J = 1 TO 5
```

SECTION I: DEFAULT DATA AND INITIALIZATION

```
3040 READ S1(I,J)
3050 NEXT J
3060 NEXT I
3070 REM LOAD ALLOCATION MATRIX A1
3080 FOR I = 1 TO 15
3090 FOR J = 1 TO 9
3100 READ A1(I,J)
3110 NEXT J
3120 NEXT I
3130 REM LOAD AUX MATRIX
3140 FOR I = 1 TO 15
3150 FOR J = 1 TO 6
3160 READ AUX(I,J)
3170 NEXT J
3180 NEXT I
3190 REM LOAD TRACOM MATRIX
3200 FOR I = 1 TO 7
3210 FOR J = 1 TO 5
3220 READ TCO(I,J)
3230 NEXT J
3240 NEXT I
3250 REM LOAD POLICY VECTOR PO
3260 FOR I = 1 TO 10
3270 READ PO(I)
3280 NEXT I
3290 REM LOAD OTH
3300 FOR I = 1 TO 3
3310 FOR J = 1 TO 8
3320 READ OTH (I,J)
3330 NEXT J
3340 NEXT I
3350 FOR I = 1 TO 9
3360 READ LABEL$(I)
3370 NEXT I
3380 FOR K = 1 TO 14
3390 READ TYPE$(K)
3400 NEXT K
3410 FOR K = 1 TO 7
3420 READ TRA$(K)
3430 NEXT K
3440 FOR K = 1 TO 5
3450 READ POSIT$(K)
3460 NEXT K
3470 M = 1:Q11 = 1
3480 A$ = "NAVAL AVIATORS"
3490 Z1$ = "YES":Z3$ = "YES":Z4$ = "NO"
3500 REM LOAD T9$
3510 FOR I = 1 TO 7
3520 FOR J = 1 TO 7
3530 READ T9$(I,J)
```

SECTION I: DEFAULT DATA AND INITIALIZATION

```
3540 T10$(I,J) = T9$(I,J)
3550 N9$(I,J) = HEX(GF)
3560 NEXT J
3570 NEXT I
3580 FOR I = 1 TO 5
3590 READ FA1(I)
3600 NEXT I
```

```
3620 ****************************************************************
3630 *                                                              *
3640 *          AT THIS POINT ALL STANDARD DATA IS LOADED. AN       *
3650 *          INTERACTIVE ROUTINE TO ENTER CHANGES FOLLOWS.       *
3660 *                                                              *
3670 *                                                              *
3680 ****************************************************************
3690 JMP100:T50 = 1:T51 = 0:D2 = ROUND(RO2*100,0):DAT=20
3700 MAT Q85=ZER:MAT Q88=ZER:MAT Q75=ZER:MAT Q78=ZER:MAT PTR=ZER:Q74=0
3710 JMP110: ACCEPT AT(2,10), "***********************************!
3720 *****************" ,                                           !
3730           AT(3,10),"*",AT(3,70),"*",                          !
3740           AT(4,10),"*",AT(4,22),"AVIATION OFFICER REQUIREMENTS MODEL!
3750 ",AT(4,70),"*",                                               !
3760           AT(5,10),"*",AT(5,70),"*",                          !
3770           AT(6,10), "*********************************************!
3780 ****************" ,                                           !
3790             AT(8,10),"THE AVIATION OFFICER REQUIREMENTS MODEL DETERMI!
3800 NES THE",                                                     !
3810             AT(9,10),"NUMBER OF NAVAL AVIATORS OR NAVAL FLIGHT OFFICER!
3820 S REQUIRED",                                                  !
3830             AT(10,10),"IN RESPONSE TO THE SPECIFICATION OF OFFICER RET!
3840 ENTION AND",                                                  !
3850             AT(11,10),"A NUMBER OF FORCE LEVEL AND CAREER PLANNING PAR!
3860 AMETERS",                                                     !
3870             AT(13,10),"THE MODEL TREATS NAVAL AVIATORS AND NAVAL FLIGH!
3880 T OFFICERS",                                                  !
3890             AT(14,10),"SEPARATELY, AND BY COMMUNITY.  IT IS PRESENTLY  !
3900 SET TO WORK",                                                 !
3910             AT(15,10),"ON",AT(15,13),FAC(HEX(94)),A$,AT(15,14+LEN(A$))!
3920 ,"IN THE",AT(15,21+LEN(A$)),FAC(HEX(94)),TYPE$(Q11),          !
3930             AT(15,22+LEN(A$)+LEN(TYPE$(Q11))),"COMMUNITY",     !
3940             AT(18,10),"TO CONTINUE WORKING IN THIS COMMUNITY PRESS  !
3950    'ENTER'",                                                  !
3960             AT(19,10),"TO BEGIN A NEW COMMUNITY OF AVIATORS  PRESS   !
3970    PF-1",                                                     !
3980             AT(20,10),"TO BEGIN A NEW COMMUNITY OF NFO'S       PRESS  !
3990    PF-2",                                                     !
4000             AT(21,10),"TO MAKE MULTIPLE COMMUNITY RUNS         PRESS  !
4010    PF-3",                                                     !
4020             AT(22,10),"TO RESET MODEL TO DEFAULT VALUES        PRESS  !
4030    PF-15",                                                    !
4040             AT(24,10),"TO END PROCESSING                       PRESS  !
4050    PF-16",                                                    !
4060 KEYS(BIN(0)&BIN(1)&BIN(2)&BIN(3)&BIN(15)&BIN(16)),KEY(KY)
4070 IF KY = 16 THEN END
4080 IF KY = 15 THEN JMP105
4090 IF KY = 3 THEN JMP300
4100 IF KY = 2 THEN JMP140
```

```
4110 IF KY = 0 THEN JMP180
4120 /*NAVAL AVIATOR DISPLAY*/
4130 ACCEPT AT(3,22),"NAVAL AVIATOR COMMUNITY SELECTIONS",
4140        AT(5,10),"YOU MAY SELECT FROM AMONG FOURTEEN COMMUNITIES I
4150 N WHICH",
4160        AT(6,10),"NAVAL AVIATORS ARE REQUIRED.   THESE ARE LISTED B
4170 ELOW.  BY",
4180        AT(7,10),"PRESSING THE PF KEY CORRESPONDING TO THE ITEM NU
4190 MBER ON",
4200        AT(8,10),"THE LIST YOU WILL SELECT NAVAL AVIATORS IN THAT
4210 COMMUNITY",
4220        AT(9,10),"FOR ANALYSIS.",
4230        AT(11,5),"PF KEY",AT(11,14),"COMMUNITY",AT(11,45),"PF KEY"
4240 ,AT(11,54),"COMMUNITY",
4250        AT(13,8),"1",AT(13,12),"LIGHT ATTACK",AT(13,48),"8",AT(13,
4260 52),"MARITIME PATROL",
4270        AT(14,8),"2",AT(14,12),"FIGHTER",AT(14,48),"9",AT(14,52),"
4280 LAMPS MK I",
4290        AT(15,8),"3",AT(15,12),"MEDIUM ATTACK",AT(15,47),"10",
4300 AT(15,52),"LAMPS MK III",
4310        AT(16,8),"4",AT(16,12),"EARLY WARNING - VAW",AT(16,47),"11
4320 ",AT(16,52),"ELECTRONIC WARFARE - VQ",
4330        AT(17,8),"5",AT(17,12),"ELECTRONIC WARFARE - VAQ",AT(17,47
4340 ),"12",AT(17,52),"FORCE SUPPORT - JET",
4350        AT(18,8),"6",AT(18,12),"CARRIER BASED ASW",AT(18,47),"13",
4360 AT(18,52),"FORCE SUPPORT - PROP",
4370        AT(19,8),"7",AT(19,12),"HELICOPTER ASW",AT(19,47),"14",AT(
4380 19,52),"FORCE SUPPORT - HELO",
4390        AT(23,10),"TO RETURN TO BASIC MENU WITHOUT MAKING A SELECT
4400 ION  -  PRESS 'ENTER'",
4410 KEYS(BIN(0)&BIN(1)&BIN(2)&BIN(3)&BIN(4)&BIN(5)&BIN(6)&BIN(7)&BIN(
4420 8)&BIN(9)&BIN(10)&BIN(11)&BIN(12)&BIN(13)&BIN(14)),KEY(M5),
4430 ON BIN(0) GOTO JMP110
4440 IF M5 = 0 THEN JMP110
4450 M = M5
4460 Q11 = M
4470 GOTO JMP180
4480 JMP140:/*NFO COMMUNITY DISPLAY*/
4490 ACCEPT AT(3,20),"NAVAL FLIGHT OFFICER COMMUNITY SELECTIONS",
4500        AT(5,10),"YOU MAY SELECT FROM AMONG NINE COMMUNITIES IN WH
4510 ICH",
4520        AT(6,10),"NAVAL FLIGHT OFFICERS ARE REQUIRED.   THESE ARE L
4530 ISTED",
4540        AT(7,10),"BELOW.  BY PRESSING THE PF KEY CORRESPONDING TO
4550 THE",
4560        AT(8,10),"ITEM NUMBER ON THE LIST YOU WILL SELECT NFO'S IN
4570  THAT",
4580        AT(9,10),"COMMUNITY FOR ANALYSIS",
4590        AT(11,22),"PF KEY",AT(11,30),"COMMUNITY",
4600        AT(13,25),"1",AT(13,28),"FIGHTER",
```

```
4610          AT(14,25),"2",AT(14,29),"MEDIUM ATTACK",
4620          AT(15,25),"3",AT(15,29),"EARLY WARNING - VAW",
4630          AT(16,25),"4",AT(16,29),"ELECTRONIC WARFARE - VAQ",
4640          AT(17,25),"5",AT(17,29),"CARRIER BASED ASW",
4650          AT(18,25),"6",AT(18,29),"MARITIME PATROL",
4660          AT(19,25),"7",AT(19,29),"ELECTRONIC WARFARE - VQ",
4670          AT(20,25),"8",AT(20,29),"FORCE SUPPORT - JET",
4680          AT(21,25),"9",AT(21,29),"FORCE SUPPORT - PROP",
4690          AT(23,10),"TO RETURN TO BASIC MENU WITHOUT MAKING A SELECT
4700 ION  -   PRESS 'ENTER'",
4710 KEYS(BIN(0)&BIN(1)&BIN(2)&BIN(3)&BIN(4)&BIN(5)&BIN(6)&BIN(7)&BIN(
4720 8)&BIN(9)),KEY(M5),ON BIN(0) GOTO JMP110
4730 IF M5 = 0 THEN JMP110
4740 ON M5 GOTO ,,,,,JMP150,JMP160,JMP160,JMP160
4750 M = M5 + 16
4760 GOTO JMP170
4770 JMP150:M = M5 + 17
4780 GOTO JMP170
4790 JMP160:M = M5 + 18
4800 JMP170:Q11 = M - 15
4810 JMP180:IF M > 15 THEN A$ = "NAVAL FLIGHT OFFICERS"
4820 IF M < 16 THEN A$ = "NAVAL AVIATORS"
4830 IF M > 15 THEN S = 5 ELSE S = 4
4840 IF M > 15 THEN S1 = 4 ELSE S1 = 1
4850 P5 = LEN(A$)
4860 P6 = LEN(TYPE$(Q11))
4870 P7 = INT((59 - (11+P5))/2)
4880 P8 = INT((59 - (10+P6))/2)
4890 P9 = INT((79-P5-P6-25)/2)
4900 INIT(HEX(20))P1$(1)
4910 STR(P1$(1),1,10) = "WORKING ON"
4920 STR(P1$(1),12,LEN(A$)) = A$
4930 INIT(HEX(20))P1$(2)
4940 STR(P1$(2),1,LEN(TYPE$(Q11))) = TYPE$(Q11)
4950 STR(P1$(2),LEN(TYPE$(Q11))+2,9) = "COMMUNITY"
4960 IF Z4$ = "YES" AND STR(ROUTE$,1,1) <> HEX(20) THEN GOTO JMP220
4970 ACCEPT AT (4,70),FAC(HEX(94)),C4$,
4980          AT(5,10),"**********************************************
4990 ************",AT(6,10),"*",AT(6,70),"*",
5000 AT(7,10),"*",AT(7,10+P7),FAC(HEX(8C)),P1$(1),CH(33),
5010 AT(7,70),"*",AT(8,10),"*",AT(8,70),"*",AT(9,10),
5020 "*",AT(9,39),"IN",AT(9,70),"*",AT(10,10),"*",AT(10,70),"*",
5030 AT(11,10),"*",AT(11,10+P8),FAC(HEX(8C)),P1$(2),CH(33),
5040 AT(11,70),"*",AT(12,10),"*
5050                          *",AT(13,10),"***********************
5060 *********************************",AT(16,10),
5070 "DO YOU DESIRE IN-PROCESS MONITORING?",AT(16,55),FAC(HEX(81)),
5080 Z1$,CH(3),AT(16,61)," (YES/NO)",AT(18,10),"DO YOU DESIRE UPWARD DE
5090 TAILING?",AT(18,55),FAC(HEX(81)),Z3$,CH(3),AT(18,61)," (YES/NO)",
5100 AT(24,10),"PRESS ENTER TO CONTINUE"
```

```
5110 IF Z4$ = "YES" THEN STR(ROUTE$,1,1) = "A"
5120 IF Z4$ = "YES" THEN GOTO JMP220
5130 JMP190:ACCEPT AT(5,10),"THE AVIATION OFFICER REQUIREMENTS MODEL I'
5140 S LOADED WITH", AT(6,10),"NOMINAL VALUES OF PARAMETERS REQUIRED T'
5150 O DETERMINE THE", AT(7,10),"REQUIREMENT FOR",AT(7,26),FAC(HEX(94)'
5160 ),A$,CH(21),AT(7,27+P5),"IN THE",AT(7,34+P5),FAC(HEX(94)),
5170 TYPE$(Q11),CH(23),AT(8,10),"COMMUNITY",
5180 AT(10,10),"YOU CAN REVIEW AND/OR ALTER THESE PARAMETERS BY PRESSI'
5190 NG THE",AT(11,10),   "PF KEY CORRESPONDING TO THE ITEM NUMBERS IN'
5200  THE LIST OF",AT(12,10),"PARAMETER CATEGORIES GIVEN BELOW.   THIS '
5210 ACTION WILL CALL UP",AT(13,10),  "A LIST OF THE INDICATED PARAMET'
5220 ERS WITH THEIR CURRENT VALUES",
5230         AT(15,20),"PF KEY",AT(15,30),"PARAMETER CATEGORY",
5240         AT(16,23),"1",AT(16,28),"BASIC COMMUNITY DATA",
5250         AT(17,23),"2",AT(17,28),"TRAINING REQUIREMENTS DATA",
5260         AT(18,23),"3",AT(18,28),"POLICY VARIABLES",
5270         AT(19,23),"4",AT(19,28),"ALLOCATION PARAMETERS",
5280         AT(20,23),"5",AT(20,28),"CAREER PATH NETWORK",
5290         AT(23,10),"TO RETURN TO COMMUNITY SELECTION MENU PRESS 'PF'
5300 -16'",
5310         AT(24,10),"TO CONTINUE PROGRAM WITHOUT PARAMETER REVIEW PR'
5320 ESS 'ENTER'",
5330 KEYS(BIN(0)&BIN(1)&BIN(2)&BIN(3)&BIN(4)&BIN(5)&BIN(16)),
5340 ON (BIN(0)&BIN(1)&BIN(2)&BIN(3)&BIN(4)&BIN(5)&BIN(16)) GOTO
5350 JMP280,JMP220,JMP230,JMP240,JMP250,JMP260,JMP210
5360 JMP210:GOTO JMP110
5370 JMP220:/*BASIC DATA DISPLAY*/
5380 IF Z4$ = "YES" AND STR(ROUTE$,2,1) <> HEX(20) THEN GOTO JMP230
5390 A3$=HEX(8C):INIT(HEX(20))COM1$
5400 IF A1(Q11,5)>0 THEN A2$=HEX(8C) ELSE A2$=HEX(9C)
5410 IF A1(Q11,5)>0 THEN COM1$ = "NUMBER OF CARRIER AIR WINGS "
5420 A=D2
5430 ACCEPT AT(3,30),"BASIC COMMUNITY DATA",AT(3,70),FAC(HEX(94)),C4$,'
5440         AT(4,INT((79-(P5+P6+1))/2)),FAC(HEX(94)),TYPE$(Q11),CH(23)'
5450         ,AT(4,P6+1+INT((79-(P5+P6+1))/2)),FAC(HEX(94)),A$,CH(21),  '
5460         AT(7,28),"PARAMETER",AT(7,45),"CURRENT VALUE",
5470         AT(8,15),"NUMBER OF SQUADRONS",AT(8,50),S1(Q11,1),
5480                 PIC(##),
5490         AT(9,15),"AIRCRAFT PER SQUADRON",AT(9,50),S1(Q11,2),
5500                 PIC(##),
5510         AT(10,15),"CREW FACTOR",AT(10,51),S1(Q11,3),PIC(#.##),
5520         AT(11,15),FAC(HEX(8C)),A$,CH(21),AT(11,16+P5),"PER CREW",
5530         AT(11,51),S1(Q11,5),PIC(#.##),
5540         AT(12,10),"*******************************************
5550 ************",
5560         AT(13,15),"SQUADRON GRADE DISTRIBUTION",
5570         AT(14,20),"COMMANDERS",AT(14,50),G0(Q11,S1),PIC(##),
5580         AT(15,20),"LT. COMMANDERS",AT(15,50),G0(Q11,S1+1),PIC(##),'
5590         AT(16,20),"LIEUTENANTS",AT(16,50),G0(Q11,S1+2),PIC(##),
5600         AT(17,10),"*******************************************
```

```
5610  **********************,
5620        AT(18,15),"UPWARD DETAIL PERCENTAGE",AT(18,50),D4T,PIC(##)
5630       ,AT(19,15),"COMMUNITY RETENTION",AT(19,50),D2,PIC(##),
5640        AT(19,53),"PER CENT",
5650        AT(20,15),FAC(A3$),COM1$,AT(20,50),FAC(A2$),S1(15,1),
5660        PIC(##),
5670        AT(22,10),"**********************************************
5680  **********************,
5690        AT(23,10),FAC(HEX(8C)),COM4,
5700        AT(24,10),"PRESS ENTER TO RECORD CHANGES AND CONTINUE",
5710  KEYS(BIN(O)&BIN(10)),KEY(ND)
5720  IF Z4$ = "YES" AND ND = 10 THEN STR(ROUTE$,2,1) = "A"
5730  IF S1(15,1)<>GO(15,13) THEN GOSUB' 51(1)
5740  IF A1(Q11,5)>0 AND S1(15,1)=GO(15,13) AND S1(Q11,1)<>GO(Q11,13)
5750    THEN GOSUB' 51(Q11+1)
5760  IF A1(Q11,5)=0 AND S1(Q11,1)<>GO(Q11,13) THEN GOSUB' 51(Q11+1)
5770  GO(15,13)=S1(15,1)
5780  IF Z4$ <> "YES" THEN JMP130
5790  ND = 0
5800  JMP230:/*TRAINING REQUIREMENTS DISPLAY*/
5810  IF Z4$ = "YES" AND STR(ROUTE$,3,1) <> HEX(20) THEN GOTO JMP240
5820  ACCEPT AT(5,27),"TRAINING REQUIREMENTS DATA",AT(5,70),FAC(HEX(34)
5830  ),G4$,CH(7),
5840        AT(6,INT((79-(P5+P6+1))/2)),FAC(HEX(34)),TYPE$(Q11),CH(23)
5850       ,AT(6,P6+1+INT((79-(P5+P6+1))/2)),FAC(HEX(34)),A4,CH(21),
5860        AT(9,10),"**********************************************
5870  **********************,
5880        AT(10,10),"FLEET READINESS SQUADRONS (AGGREGATE REQUIREMEN
5890  TS)",
5900        AT(11,20),"COMMANDERS",AT(11,53),GO(Q11,S1+6),PIC(##),
5910        AT(12,20),"LT. COMMANDERS",AT(12,53),GO(Q11,S1+7),PIC(##),
5920        AT(13,20),"LIEUTENANTS",AT(13,52),GO(Q11,S1+8),PIC(###),
5930        AT(14,10),"**********************************************
5940  **********************,
5950        AT(15,10),"UNDERGRADUATE TRAINING  -",AT(15,37),
5960                  FAC(HEX(8C)),TRA$(A1(Q11,S-3)),CH(23),
5970                  AT(15,38+LEN(TRA$(A1(Q11,S-3)))),
5980                  "TRAINING PIPELINE",
5990        AT(16,20),"COMMANDERS",AT(16,53),TCO(A1(Q11,S-3),2),PIC(##)
6000 ,AT(17,20),"LT. COMMANDERS",AT(17,53),TCO(A1(Q11,S-3),3),PIC(##),
6010        AT(18,20),"INSTRUCTOR PILOTS PER GRADUATE",AT(18,54),
6020                  TCO(A1(Q11,S-3),4),PIC(#.###),
6030        AT(19,20),"INSTRUCTOR NFOS PER GRADUATE",AT(19,54),
6040                  TCO(A1(Q11,S-3),5),PIC(#.###),
6050        AT(20,10),"**********************************************
6060  **********************,
6070        AT(23,10),FAC(HEX(8C)),COM4,
6080        AT(24,10),"PRESS ENTER TO RECORD CHANGES AND CONTINUE",
6090  KEYS(BIN(O)&BIN(10)),KEY(ND)
6100  IF Z4$ = "YES" AND ND = 10 THEN STR(ROUTE$,3,1) = "A"
```

```
6.110 IF Z4$ <> "YES" THEN GOTO JMP190
6.120 ND = 0
6.130 JMP240:/*POLICY VARIABLES*/
6.140 IF Z4$ = "YES" AND STR(ROUTE$,4,1) <> HEX(20) THEN GOTO JMP250
6.150 ACCEPT AT(2,19),"PROMOTION FLOW POINTS AND POLICY VARIABLES",      '
6.160        AT(2,70),FAC(HEX(94)),G4$,CH(7),                            '
6.170        AT(3,INT((79-(P5+P6+1))/2)),FAC(HEX(94)),TYPE$(Q11),CH(23)  '
6.180       ,AT(3,P6+1+INT((79-(P5+P6+1))/2)),FAC(HEX(94)),A$,CH(21),    '
6.190        AT(4,10),"*********************************************     '
6.200 ************",                                                     '
6.210        AT(6,29),"PROMOTION FLOW POINTS",                           '
6.220        AT(8,7),"COMM",                                             '
6.230        AT(9,9),HEX(06),                                           '
6.240        AT(10,8)," 0*1*2*3*4*5*6*7*8*9*10*11*12*13*14*15*16*17*18*  '
6.250 19*20*21*22*23*24",                                               '
6.260        AT(11,8),FAC(HEX(8C)),STR(PRO2$,1,12),CH(12),              '
6.270        AT(11,20),FAC(HEX(88)),STR(PRO2$,13,53),CH(53),            '
6.280        AT(12,9),"DESIG",AT(12,PRO3+7),"4",AT(12,PRO6+7),"5",      '
6.290        AT(13,10),"****************************************        '
6.300 ************",                                                    '
6.310        AT(15,32),"POLICY VARIABLES",                              '
6.320        AT(17,10),"PLOWBACK INSTRUCTORS (FRACTION OF GRADUATES)",  '
6.330        AT(17,60),PO(1),PIC(#.##),                                 '
6.340        AT(18,10),"POSTGRADUATE FLOW (FRACTION OF 12 YEAR COHORT)" '
6.350 ,AT(18,60),PO(2),PIC(#.##),                                      '
6.360        AT(19,10),"WAR COLLEGE FLOW (FRACTION OF 18 YEAR COHORT)", '
6.370                AT(19,60),PO(3),PIC(#.##),                         '
6.380        AT(21,10),"*****************************************       '
6.390 ************",                                                   '
6.400        AT(23,10),"PRESS PF-1 TO RECORD CHANGES AND REDISPLAY",   '
6.410        AT(24,10),"PRESS ENTER TO RECORD CHANGES AND CONTINUE",   '
6.420 KEYS(BIN(0)&BIN(1)),KEY(PR),NOALT GOTO JMP245
6.430 PRO3 = POS(PRO2$="4")
6.440 PRO6 = POS(PRO2$="5")
6.450 INIT(HEX(20))STR(PRO2$,13,53)
6.460 STR(PRO2$,PRO3,1) = HEX(5E)
6.470 STR(PRO2$,PRO6,1) = HEX(5E)
6.480 IF PRO3 > 21 AND INT((PRO3-21)/3)=(PRO3-21)/3 THEN PRO4 = 9.5 +   '
6.490 INT((PRO3-21)/3)
6.500 IF PRO3 > 21 AND INT((PRO3-21)/3)<>(PRO3-21)/3 THEN PRO4 = 9.5 +  '
6.510 INT((PRO3-21)/3) + .5
6.520 IF PRO3 < 22 THEN PRO4 = PRO3/2 - 1
6.530 IF PRO6 > 21 AND INT((PRO6-21)/3)=(PRO6-21)/3 THEN PRO5 = 9.5 +   '
6.540 INT((PRO6-21)/3)
6.550 IF PRO6 > 21 AND INT((PRO6-21)/3)<>(PRO6-21)/3 THEN PRO5 = 9.5 +  '
6.560 INT((PRO6-21)/3) + .5
6.570 IF PRO6 < 22 THEN PRO5 = PRO6/2 - 1
6.580 PRO4 = 12*PRO4 - 18:PRO5 = 12*PRO5 - 18
6.590 IF PR = 1 THEN JMP240
6.600 JMP245:IF Z4$ = "YES" THEN STR(ROUTE$,4,1) = "A"
```

SECTION II: INTERACTIVE ENTRY/REENTRY ROUTINES

```
6610 IF Z4$ = "YES" THEN GOTO JMP250 ELSE GOTO JMP190
6620 JMP250:/*ALLOCATION PARAMETERS)*/
6630 IF Z4$ = "YES" AND STR(ROUTE$,5,1) <> HEX(20) THEN GOTO JMP260
6640 ACCEPT AT(5,30),"ALLOCATION PARAMETERS",AT(5,70),FAC(HEX(94)),G4$
6650          ,AT(6,INT((79-(P5+P6+1))/2)),FAC(HEX(94)),TYPE$(Q11),CH(23)
6660          ,AT(6,P6+1+INT((79-(P5+P6+1))/2)),FAC(HEX(94)),A$,CH(21),
6670          AT(12,10),"FRACTION OF ALL ",AT(12,26),FAC(HEX(8C)),A$,
6680                  CH(23),AT(12,65),A1(Q11,S1+2),PIC(#.####),
6690          AT(14,10),"FRACTION OF",AT(14,22),FAC(HEX(8C)),
6700          TRA$(A1(Q11,S-3)),CH(23),AT(14,23)+LEN(TRA$(A1(Q11,S-3))),
6710            FAC(HEX(8C)),A$,CH(21),AT(14,65),A1(Q11,S1+3),
6720                  PIC(#.####),
6730          AT(16,10),"FRACTION OF CARRIER",AT(16,30),FAC(HEX(8C)),
6740                  A$,CH(21),AT(16,65),A1(Q11,S1+4),PIC(#.####),
6750          AT(18,10),"FRACTION OF ALL AVIATION OFFICERS",AT(18,65),
6760                  A1(Q11,9),PIC(#.####),
6770          AT(21,10), "*********************************************
6780 ***********",
6790          AT(23,10),FAC(HEX(8C)),COM$,
6800          AT(24,10),"PRESS ENTER TO RECORD CHANGES AND CONTINUE",
6810 KEYS(BIN(0)&BIN(10)),KEY(ND)
6820 IF Z4$ = "YES" AND ND = 10 THEN STR(ROUTE$,5,1) = "A"
6830 IF Z4$ <> "YES" THEN JMP190
6840 ND = 0
6850 JMP260:/* NETWORK NODE DISPLAY */
6860 IF Z4$ = "YES" AND STR(ROUTE$,6,1) <> HEX(20) THEN GOTO JMP280
6870 ACCEPT AT(1,70),FAC(HEX(94)),G4$,
6880          AT(2,10),"YOU CAN INSPECT AND/OR MODIFY THE CAREER PATH NE
6890 TWORK CHARACTERISTICS",
6900          AT(3,10),"ASSOCIATED WITH ANY NODE IN THE NETWORK.   TO SEL
6910 ECT A PARTICULAR NODE",
6920          AT(4,10),"REPLACE THE 'O' IN THE DIAGRAM BELOW WITH AN 'X'
6930 .   TO BYPASS A NODE",
6940          AT(5,10),"PRESS 'TAB'.",
6950          AT(7,42),"TOUR NUMBER",
6960          AT(9,23),"ACTIVITY",AT(9,42),"1    2    3    4    5    6    7",
6970          AT(11,15),FAC(HEX(8C)),LABEL$(1),AT(11,42),FAC(HEX(88)),
6980                  N9$(1,1),AT(11,46),FAC(HEX(88)),N9$(1,2),AT(11,50),
6990                  FAC(HEX(88)),N9$(1,3),AT(11,54),FAC(HEX(88)),
7000                  N9$(1,4),AT(11,58),FAC(HEX(88)),N9$(1,5),AT(11,62),
7010                  FAC(HEX(88)),N9$(1,6),AT(11,66),FAC(HEX(88)),
7020                  N9$(1,7),
7030          AT(12,15),FAC(HEX(8C)),LABEL$(2),AT(12,42),FAC(HEX(88)),
7040                  N9$(2,1),AT(12,46),FAC(HEX(88)),N9$(2,2),
7050                  AT(12,50),FAC(HEX(88)),N9$(2,3),AT(12,54),
7060                  FAC(HEX(88)),N9$(2,4),AT(12,58),FAC(HEX(88)),
7070                  N9$(2,5),AT(12,62),FAC(HEX(88)),N9$(2,6),
7080                  AT(12,66),FAC(HEX(88)),N9$(1,7),
7090          AT(13,15),FAC(HEX(8C)),LABEL$(3),AT(13,42),FAC(HEX(88)),
7100                  N9$(3,1),AT(13,46),FAC(HEX(88)),N9$(3,2),
```

```
7110                    AT(13,50),FAC(HEX(88)),N9$(3,3),AT(13,54),
7120                    FAC(HEX(88)),N9$(3,4),AT(13,58),FAC(HEX(88)),
7130                    N9$(3,5),AT(13,62),FAC(HEX(88)),N9$(3,6),
7140                    AT(13,66),FAC(HEX(88)),N9$(3,7),
7150           AT(14,15),FAC(HEX(8C)),LABEL$(4),AT(14,42),FAC(HEX(88)),
7160                    N9$(4,1),AT(14,46),FAC(HEX(88)),N9$(4,2),
7170                    AT(14,50),FAC(HEX(88)),N9$(4,3),AT(14,54),
7180                    FAC(HEX(88)),N9$(4,4),AT(14,58),FAC(HEX(88)),
7190                    N9$(4,5),AT(14,62),FAC(HEX(88)),N9$(4,6),
7200                    AT(14,66),FAC(HEX(88)),N9$(4,7),
7210           AT(15,15),FAC(HEX(8C)),LABEL$(5),AT(15,42),FAC(HEX(88)),
7220                    N9$(5,1),AT(15,46),FAC(HEX(88)),N9$(5,2),
7230                    AT(15,50),FAC(HEX(88)),N9$(5,3),AT(15,54),
7240                    FAC(HEX(88)),N9$(5,4),AT(15,58),FAC(HEX(88)),
7250                    N9$(5,5),AT(15,62),FAC(HEX(88)),N9$(5,6),
7260                    AT(15,66),FAC(HEX(88)),N9$(5,7),
7270           AT(16,15),FAC(HEX(8C)),LABEL$(6),AT(16,42),FAC(HEX(88)),
7280                    N9$(6,1),AT(16,46),FAC(HEX(88)),N9$(6,2),
7290                    AT(16,50),FAC(HEX(88)),N9$(6,3),AT(16,54),
7300                    FAC(HEX(88)),N9$(6,4),AT(16,58),FAC(HEX(88)),
7310                    N9$(6,5),AT(16,62),FAC(HEX(88)),N9$(6,6),
7320                    AT(16,66),FAC(HEX(88)),N9$(6,7),
7330           AT(17,15),FAC(HEX(8C)),LABEL$(7),AT(17,42),FAC(HEX(88)),
7340                    N9$(7,1),AT(17,46),FAC(HEX(88)),N9$(7,2),
7350                    AT(17,50),FAC(HEX(88)),N9$(7,3),AT(17,54),
7360                    FAC(HEX(88)),N9$(7,4),AT(17,58),FAC(HEX(88)),
7370                    N9$(7,5),AT(17,62),FAC(HEX(88)),N9$(7,6),
7380                    AT(17,66),FAC(HEX(88)),N9$(7,7),
7390                    AT(23,10),"TO BEGIN NODE INSPECTION/MODIFICATION
7400 PRESS          'ENTER'",
7410                    AT(24,10),"TO RETURN TO CATEGORY MENU PRESS
7420               'PF-1'",
7430 KEYS(HEX(0001)),ON(BIN(1)) GOTO JMP190
7440 FOR I = 1 TO 7
7450 FOR J = 1 TO 7
7460 IF N9$(I,J) = HEX(6F) THEN JMP270
7470 ACCEPT AT(1,30),"NODE CHARACTERISTICS",AT(1,70),FAC(HEX(84)),G4$,
7480         AT(3,10),"NODE CHARACTERISTICS ARE REFERRED TO THE OUTPUT
7490 END OF THE ARC",
7500         AT(4,10),"IN QUESTION.   THAT NODE IDENTIFIES THE ACTIVITY
7510 IN WHICH THE",
7520         AT(5,10),"OFFICER IS ENGAGED.   THE ACTIVITY AND TOUR NUMBE
7530 R CURRENTLY",
7540         AT(6,10),"BEING EXAMINED IS:",
7550         AT(8,15),FAC(HEX(8C)),LABEL$(I),AT(8,42),"TOUR NUMBER",
7560         AT(8,55),FAC(HEX(8C)),J,PIC(#),
7570         AT(10,10),"FOR TOURS TERMINATING AT THAT NODE",
7580         AT(11,10),"THE FOLLOWING VALUES APPLY:",
7590         AT(13,34),"TOUR LENGTH",AT(13,50),FAC(HEX(88)),STR(T9$(I,J
7600 ),1,2),
```

```
7610          AT(15,10),"PRECEDENT NODE          STATE",AT(15,50),"PRECEDE
7620 NT NODE          STATE",
7630          AT(16,5),FAC(HEX(8C)),LABEL$(1),AT(16,33),FAC(HEX(89)),
7640                  STR(T9$(I,J),3,3),AT(16,45),FAC(HEX(8C)),LABEL$(2
7650 ),AT(16,73),FAC(HEX(89)),STR(T9$(I,J),6,3),
7660          AT(17,5),FAC(HEX(8C)),LABEL$(3),AT(17,33),FAC(HEX(89)),
7670                  STR(T9$(I,J),9,3),AT(17,45),FAC(HEX(8C)),LABEL$(4
7680 ),AT(17,73),FAC(HEX(89)),STR(T9$(I,J),12,3),
7690          AT(18,5),FAC(HEX(8C)),LABEL$(5),AT(18,33),FAC(HEX(89)),
7700                  STR(T9$(I,J),15,3),AT(18,45),FAC(HEX(8C)),LABEL$(
7710 6),AT(18,73),FAC(HEX(89)),STR(T9$(I,J),18,3),
7720          AT(19,5),FAC(HEX(8C)),LABEL$(7),AT(19,33),FAC(HEX(89)),
7730                  STR(T9$(I,J),21,3),
7740          AT(21,20),"NOTE - 'NNN' MEANS THAT THE PRECEDENT NODE IS D
7750 ARRED",
7760          AT(24,5),"TO ENTER CHANGES PRESS          'ENTER'",
7770 KEYS(BIN(0))
7780 IF Z4$ = "YES" THEN Q12 = Q12 + 1 ELSE JMP270
7790 CONVERT I TO STR(T11$(Q12),24,1),PIC(#)
7800 CONVERT J TO STR(T11$(Q12),25,1),PIC(#)
7810 STR(T11$(Q12),1,23) = STR(T9$(I,J),1,23)
7820 JMP270:NEXT J
7830 NEXT I
7840 IF Z4$ = "YES" THEN STR(ROUTE$,6,1) = "A"
7850 IF Z4$ = "YES" THEN GOTO JMP280 ELSE GOTO JMP190
7860 JMP280:IF A = D2 THEN JMP290
7870 IF Z4$="YES" AND STR(ROUTE$,7,1)<>HEX(20) THEN JMP290
7880 B = RO3:C = RO4:D = RO5
7890 ACCEPT AT(4,70),FAC(HEX(94)),G4$,
7900          AT(5,10),"YOU HAVE REQUESTED A CHANGE IN RETENTION FOR",
7910          AT(5,55),FAC(HEX(8C)),A$,CH(21),
7920          AT(6,10),"IN THE",AT(6,17),FAC(HEX(8C)),TYPE$(Q11),CH(23),
7930          AT(6,18+LEN(TYPE$(Q11))),"COMMUNITY",
7940          AT(7,10),"THIS WILL CAUSE A CHANGE IN THE CONTINUATION VEC
7950 TOR.   THE FOUR",
7960          AT(8,10),"PARAMETERS WHICH DEFINE THIS VECTOR ARE DISPLAYE
7970 D BELOW FOR",
7980          AT(9,10),"REVIEW AND/OR CHANGE",
7990          AT(12,10),"RETENTION",AT(12,45),D2,PIC(##),AT(12,48),
8000                  "PER CENT",
8010          AT(14,10),"MINIMUM SERVICE REQUIREMENT",AT(14,45),RO3,
8020                  PIC(##),AT(14,48),"YEARS",
8030          AT(16,10),"RETENTION POINT",AT(16,45),RO4,PIC(##),
8040          AT(16,48),"YEARS",
8050          AT(18,10),"CAREER STABLE POINT",AT(18,45),RO5,PIC(##),
8060          AT(18,48),"YEARS",
8070          AT(21,10),"*********************************************
8080 ***********",
8090          AT(23,10),"PRESS ENTER TO MAKE CONTINUATION VECTOR CHANGES
8100 ",
```

SECTION II: INTERACTIVE ENTRY/REENTRY ROUTINES

```
8110 KEYS(BIN(0))
8120 JMP280:R03 = B:R04 = C:R05 = D:R02=D2/100
8130 IF Z4$ = "YES" THEN STR(ROUTE$,7,1) = "A" ELSE GOTO JMP410
8140 GOTO JMP380
```

```
8160 **************************************************************
8170 *          MULTIPLE RUN SET UP ROUTINES PERMIT SELECTING     *
8180 *     GROUPS OF SUBCOMMUNITIES WHICH HAVE SIMILAR CHARACT-    *
8190 *     ERISTICS FOR SEQUENTIAL SOLUTION WITHOUT USER INTER-    *
8200 *     VENTION.  ANY NUMBER OF GROUPS MAY BE SPECIFIED.  THE   *
8210 *     DEFAULT GROUPING CORRESPONDS TO THE PRESENT UNDER-      *
8220 *     GRADUATE TRAINING PIPELINES.                            *
8230 **************************************************************
8240 JMP300:/*MULTIPLE RUN SETUP ROUTINE*/
8250 IF L6=16 THEN GOSUB' 85
8260 L6=0
8270 INIT(HEX(20))GROUP$,TGROUP$,ROUTE$,EM$
8280 Z4$ = "YES"
8290 BGROUP$ = "AAABAACBCCBADCOODENEOGOOGESOO"
8300 ACCEPT AT(2,22),"NAVAL AVIATOR COMMUNITY SELECTIONS",
8310         AT(2,70),FAC(HEX(94)),G4$,
8320         AT(3,32),"(MULTIPLE RUNS)",
8330         AT(5,10),"YOU MAY ARRANGE AVIATOR SUBCOMMUNITIES INTO GROU
8340 PS WITH",
8350         AT(6,10),"SIMILAR CHARACTERISTICS TO SIMPLIFY THE PROCESS
8360 OF DEFINING",
8370         AT(7,10),"PARAMETERS.  ASSIGN A SINGLE CHARACTER GROUP IDE
8380 NTIFIER TO",
8390         AT(8,10),"EACH SUBCOMMUNITY BELOW.  ASSIGNMENT OF 'ZERO' O
8400 R 'SPACE'",
8410         AT(9,10),"WILL ELIMINATE THAT SUBCOMMUNITY FROM THE RUN",
8420         AT(11,10),"COMMUNITY",AT(11,33),"GROUP",AT(11,50),"COMMUNI
8430 TY",AT(11,73),"GROUP",
8440         AT(13,8),"LIGHT ATTACK",AT(13,35),STR(GROUP$,1,1),AT(13,48
8450 ),"MARITIME PATROL",AT(13,75),STR(GROUP$,8,1),
8460         AT(14,8),"FIGHTER",AT(14,35),STR(GROUP$,2,1),AT(14,48),"LA
8470 MPS MK I",AT(14,75),STR(GROUP$,9,1),
8480         AT(15,8),"MEDIUM ATTACK",AT(15,35),STR(GROUP$,3,1),
8490 AT(15,48),"LAMPS MK III",AT(15,75),STR(GROUP$,10,1),
8500         AT(16,8),"EARLY WARNING - VAW",AT(16,35),STR(GROUP$,4,1),
8510 AT(16,48),"ELECTRONIC WARFARE - VQ",AT(16,75),STR(GROUP$,11,1),
8520     AT(17,8),"ELECTRONIC WARFARE - VAQ",AT(17,35),STR(GROUP$,5,1),
8530     AT(17,48),"FORCE SUPPORT - JET",AT(17,75),STR(GROUP$,12,1),
8540         AT(18,8),"CARRIER BASED ASW",AT(18,35),STR(GROUP$,6,1),
8550 AT(18,48),"FORCE SUPPORT - PROP",AT(18,75),STR(GROUP$,13,1),
8560         AT(19,8),"HELICOPTER ASW",AT(19,35),STR(GROUP$,7,1),
8570 AT(19,48),"FORCE SUPPORT - HELO",AT(19,75),STR(GROUP$,14,1),
8580         AT(21,10),"RUN DESCRIPTION: ",AT(21,30),EM$,
8590         AT(23,10),"TO RETURN TO BASIC MENU           - PRESS",
8600 AT(23,60),"PF 16",
8610         AT(24,10),"TO CONTINUE WITH NEO SUBCOMMUNITIES  - PRESS",
8620 AT(24,60),"'ENTER'",
8630 KEYS(BIN(0)&BIN(16)),KEY(M5),NOALT GOTO JMP310
8640 IF M5 = 16 THEN Z4$ = "NO" ELSE GOTO JMP320
```

SECTION III: MULTIPLE RUN SET UP ROUTINES

```
8650 INIT(HEX(20))G4$
8660 GOTO JMP110
8670 JMP310: IF M5 = 16 THEN Z4$ = "NO"
8680 IF M5 = 16 THEN JMP110
8690 STR(GROUP$,1,15) = STR(BGROUP$,1,15):Q=1
8700 JMP320:/*NFO GROUP SELECTIONS/
8710 ACCEPT AT(2,20),"NAVAL FLIGHT OFFICER COMMUNITY SELECTIONS",
8720       AT(2,70),FAC(HEX(94)),G4$,
8730       AT(3,33),"(MULTIPLE RUNS)",
8740       AT(5,10),"NAVAL FLIGHT OFFICER SUBCOMMUNITIES MAY ALSO BE
8750 GROUPED",
8760       AT(6,10),"BY ASSIGNING GROUP IDENTIFIERS.  USE CAUTION IN
8770 ASSIGNING",
8780       AT(7,10),"GROUP IDENTIFIERS.  IF IDENTIFIER IS THE SAME AS
8790  ONE USED",
8800       AT(8,10),"FOR PILOTS THAT NFO SUBCOMMUNITY WILL BE INCLUDE
8810 D WITH THE",
8820       AT(9,10),"PREVIOUSLY DEFINED PILOT GROUP",
8830       AT(11,32),"COMMUNITY",AT(11,53),"GROUP",
8840       AT(13,25),"FIGHTER",AT(13,55),STR(GROUP$,17,1),
8850       AT(14,25),"MEDIUM ATTACK",AT(14,55),STR(GROUP$,18,1),
8860       AT(15,25),"EARLY WARNING - VAW",AT(15,55),STR(GROUP$,19,1)
8870 ,      AT(16,25),"ELECTRONIC WARFARE - VAQ",AT(16,55),
8880        STR(GROUP$,20,1),
8890       AT(17,25),"CARRIER BASED ASW",AT(17,55),STR(GROUP$,21,1),
8900       AT(18,25),"MARITIME PATROL",AT(18,55),STR(GROUP$,22,1),
8910       AT(19,25),"ELECTRONIC WARFARE - VQ",AT(19,55),
8920              STR(GROUP$,26,1),
8930       AT(20,25),"FORCE SUPPORT - JET",AT(20,55),STR(GROUP$,27,1)
8940 ,
8950       AT(21,25),"FORCE SUPPORT - PROP",AT(21,55),
8960        STR(GROUP$,28,1),
8970       AT(23,10),"TO RETURN TO BASIC MENU              - PRESS"
8980 ,AT(23,58),"PF-16",
8990       AT(24,10),"TO CONTINUE MULTIPLE COMMUNITY RUN    - PRESS"
9000 ,AT(24,58),"ENTER",
9010 KEYS(BIN(0)&BIN(16)),KEY(M5),NOALT GOTO JMP330
9020 IF M5 = 16 THEN Z4$ = "NO" ELSE GOTO JMP340
9030 INIT(HEX(20))G4$
9040 GOTO JMP110
9050 JMP330: IF M5 = 16 THEN Z4$ = "NO"
9060 IF M5 = 16 THEN JMP110
9070 STR(GROUP$,16,15) = STR(BGROUP$,16,15)
9080 IF Q = 1 THEN JMP370
9090 JMP340:/*ELIMINATE BLANKS#/
9100 L1 = 1
9110 IF STR(GROUP$,1,1)="0" AND POS(STR(GROUP$,2,14)<>" ")=0 THEN
9120      INIT("0")STR(GROUP$,1,15)
9130 IF STR(GROUP$,17,1)="0" AND POS(STR(GROUP$,18,13)<>" ")=0 THEN
9140      INIT("0")STR(GROUP$,16,15)
```

SECTION III: MULTIPLE RUN SET UP ROUTINES

```
9150 IF POS(GROUP$<>"O")=0 THEN JMP300
9160 FOR Q = 1 TO 30
9170 IF STR(BGROUP$,Q,1) = "O" THEN STR(GROUP$,Q,1) = "O"
9180 IF STR(GROUP$,Q,1)<>" " THEN JMP360
9190 FOR K = 1 TO 30
9200 IF STR(GROUP$,K,1) <> STR(BGROUP$,Q,1) THEN JMP350
9210 STR(GROUP$,Q,1) = STR(BGROUP$,Q,1)
9220 GOTO JMP360
9230 JMP350:NEXT K
9240 CONVERT L1 TO STR(GROUP$,Q,1),PIC(#)
9250 FOR K = Q+1 TO 30
9260 IF (STR(BGROUP$,K,1)=STR(BGROUP$,Q,1)) AND (STR(GROUP$,K,1)=" ")
9270 THEN STR(GROUP$,K,1) = STR(GROUP$,Q,1)
9280 NEXT K
9290 L1 = L1 + 1
9300 JMP360:NEXT Q
9310 JMP370:COM$ = "PRESS PF-10 IF YOU WANT TO BYPASS THIS SCREEN FOR
9320 THIS GROUP"
9330 STR(G4$,1,6) = "GROUP "
9340 TGROUP$ = GROUP$
9350 Q12 = 0: INIT(HEX(20))T11$()
9360 FOR P = 1 TO 30
9370 IF STR(TGROUP$,P,1) = " " OR STR(TGROUP$,P,1) = "O" THEN JMP400
9380 G5$ = STR(TGROUP$,P,1)
9390 STR(G4$,7,1) = G5$
9400 INIT(HEX(20))ROUTE$
9410 INIT(HEX(20))P2$()
9420 L4 = 1
9430 FOR Q = 1 TO 30
9440 IF STR(GROUP$,Q,1) <> G5$ THEN GOTO JMP380
9450 M = Q
9460 IF M > 15 THEN Q11 = M - 15 ELSE Q11 = M
9470 GOTO JMP180
9480 JMP380:CONVERT M TO M$,PIC(##)
9490 OPEN NODISPLAY #1,IO,FILE="SOURCE",LIBRARY="OFFREQ",
9500 VOLUME="VOL555"
9510 OPEN NODISPLAY #2,IO,FILE="CAREER",LIBRARY="OFFREQ",
9520 VOLUME="VOL555"
9530 WRITE #1,USING FILEFORM,M$,Q11,S,S1,Z1$,ZP$,Z3$,A$,TYPE$(Q11),
9540 S1(Q11,1),S1(Q11,2),S1(Q11,3),S1(Q11,5),GO(Q11,S1),GO(Q11,S)+1),
9550 GO(Q11,S1+2),DAT,D2,GO(Q11,S1+6),GO(Q11,S1+7),GO(Q11,S1+2),
9560 TCO(A1(Q11,S-3),2),TCO(A1(Q11,S-3),3),TCO(A1(Q11,S-3),4),
9570 TCO(A1(Q11,S-3),5),PO(1),PO(2),PO(3),A1(Q11,S1+2),A1(Q11,S1+3),
9580 A1(Q11,S1+4),A1(Q11,9),RO1,RO2,RO3,RO4,RO5
9590 WRITE #2 USING FILECAR,M$,Q12,T11$(),PRD4,PRD5
9600 STR(TGROUP$,Q,1) = " "
9610 STR(P2$(L4),1,22) = TYPE$(Q11)
9620 IF M>15 THEN STR(P2$(L4),25,5)="(NEO)" ELSE STR(P2$(L4),25,4)=
9630 "(NA)"
9640 L4 = L4+1
```

SECTION III: MULTIPLE RUN SET UP ROUTINES

```
9650 CLOSE #1
9660 CLOSE #2
9670 JMP390:NEXT Q
9680 ACCEPT AT(5,32),FAC(HEX(8C)),G4$,AT(5,40),"COMPLETED",
9690        AT(7,28),"SUBCOMMUNITIES INCLUDED",
9700        AT(10,25),FAC(HEX(8C)),P2$(1),
9710        AT(11,25),FAC(HEX(8C)),P2$(2),
9720     AT(12,25),FAC(HEX(8C)),P2$(3),AT(13,25),FAC(HEX(8C)),P2$(4),
9730     AT(14,25),FAC(HEX(8C)),P2$(5),AT(15,25),FAC(HEX(8C)),P2$(6),
9740     AT(16,25),FAC(HEX(8C)),P2$(7),AT(17,25),FAC(HEX(8C)),P2$(8),
9750     AT(18,25),FAC(HEX(8C)),P2$(9),AT(19,25),FAC(HEX(8C)),P2$(10),
9760        AT(23,10),"TO CONTINUE WITH NEXT GROUP PRESS",AT(23,60),
9770        "PRESS 'ENTER'",
9780        AT(24,10),"TO REINITIATE THE GROUP SELECTION PROCESS PRESS
9790 ",AT(24,60),"'PF-16'",
9800 KEYS (BIN(0)&BIN(16)),KEY(L6)
9810 IF L6 = 16 THEN JMP300
9820 JMP400:NEXT P
9830 MAT TOT = ZER:MAT TOTA = ZER:MAT TOTN = ZER
9840 INIT(HEX(20))MGROUP$
9850 TGROUP$ = GROUP$
9860 FOR I4 = 1 TO 30
9870 IF STR(BGROUP$,I4,1)="0" THEN JMP1640
9880 IF STR(TGROUP$,I4,1)="0" THEN STR(MGROUP$,I4,1)="X"
9890 IF STR(TGROUP$,I4,1)="0" OR STR(TGROUP$,I4,1)="#" THEN JMP1640
9900 G5$ = STR(TGROUP$,I4,1)
9910 FOR I5 = 1 TO 30
9920 CONVERT I5 TO I$,PIC(##)
9930 IF STR(GROUP$,I5,1) <> G5$ THEN JMP1630
9940 OPEN NODISPLAY #1,I0,FILE="SOURCE",LIBRARY="OFFREG",VOLUME="VOL55
9950 5"
9960 OPEN NODISPLAY #2,I0,FILE="CAREER",LIBRARY="OFFREG",VOLUME="VOL55
9970 5"
9980 READ #1,KEY=I$,USING FILEFORM,M$,Q11,S,S1,Z1$,Z2$,Z3$,
9990 A$,TYPE$(Q11),S1(Q11,1),S1(Q11,2),S1(Q11,3),S1(Q11,5),
10000 GO(Q11,S1),GO(Q11,S1+1),GO(Q11,S1+2),DAT,D2,GO(Q11,S1+6),
10010 GO(Q11,S1+7),GO(Q11,S1+8),TCO(A1(Q11,S-3),2),TCO(A1(Q11,S-3),3),
10020 TCO(A1(Q11,S-3),4),TCO(A1(Q11,S-3),5),PO(1),PO(2),PO(3),
10030 A1(Q11,S1+2),A1(Q11,S1+3),A1(Q11,S1+4),A1(Q11,3),
10040 RO1,RO2,RO3,RO4,RO5
10050 CLOSE #1
10060 READ #2,KEY=I$,USING FILECAR,M$,Q12,T11$(),PRO4,PRO5
10070 CLOSE #2
10080 CONVERT M$ TO M
10090 IF Q12 = 0 THEN JMP410
10100 FOR K = 1 TO Q12
10110 CONVERT STR(T11$(K),24,1) TO I
10120 CONVERT STR(T11$(K),25,1) TO J
10130 STR(T3$(I,J),1,23) = STR(T11$(K),1,23)
10140 NEXT K
```

SECTION III: MULTIPLE RUN SET UP ROUTINES

```
10150 JMP 410:
10160 B32 = 1
10170 FOR I = 1 TO 7
10180 FOR J = B32 TO B32 + NO(I) - 1
10190 RO(J) = A50(I)
10200 NEXT J
10210 B32 = B32 + NO(I)
10220 NEXT I
10230 E = SQR(RO2/RO(1))
10240 FOR I = RO3 + 1 TO RO4
10250 RO(I) = E
10260 NEXT I
10270 E = .924*(((.45 + RO2)/(2*RO2))**.12)
10280 FOR I = RO4 + 1 TO RO5
10290 RO(I) = E
10300 NEXT I
10310 GOSUB' 63
```

SECTION IV: REQUIREMENTS COMPUTATION

```
10330 ***********************************************************
10340 *                                                         *
10350 *         MODIFICATION OF DATA COMPLETE, BEGIN REQUIREMENTS *
10360 *         COMPUTATION>                                     *
10370 *                                                         *
10380 ***********************************************************
10390 MAT DO = ZER:DAT=DAT/100
10400 IF M > 15 THEN P=4 ELSE P=1
10410 IF M>15 THEN B=5 ELSE B=4
10420 /*FLEET TOURS*/
10430 DO(1,1) = S1(Q11,1)*S1(Q11,2)*S1(Q11,3)*S1(Q11,B)*(GO(Q11,P)+
10440    GO(Q11,P+1))*S1(Q11,1)+AUX(Q11,P+2)+A1(Q11,P+4)*S1(15,1)*
10450    GO(15,P+2)
10460 DO(1,2) = GO(Q11,P+1)*S1(Q11,1)+AUX(Q11,P+1)+A1(Q11,P+4)*S1(15,1)
10470    *GO(15,P+1)
10480 DO(1,3) = GO(Q11,P)*S1(Q11,1)+AUX(Q11,P)
10490 DO(1,4) = A1(Q11,P+4)*S1(15,1)*GO(15,P)
10500 /* FRS TOURS */
10510 DO(2,1) = GO(Q11,P+8)
10520 DO(2,2) = GO(Q11,P+7)
10530 A=2
10540 IF GO(Q11,10)>0 THEN A=1
10550 IF GO(Q11,7)=0 THEN A=0
10560 IF M>15 AND GO(Q11,10)=0 THEN A=0
10570 DO(2,3) = GO(Q11,P+6)-A
10580 DO(2,4) = A
10590 /* TRAINING COMMAND TOURS (LESS FIRST TOUR) */
10600 IF M>15 THEN A=2 ELSE A=1
10610 DO(3,2) = A1(Q11,P+3)*TCO(A1(Q11,A),3)
10620 DO(3,3) = A1(Q11,P+3)*TCO(A1(Q11,A),2)
10630 /* OTHER REQUIREMENTS */
10640 IF M>15 THEN B=9 ELSE B=5
10650 FOR I = 1 TO 3
10660 IF I=3 THEN N=I+4 ELSE N=I+3
10670 FOR J = 1 TO 4
10680 DO(N,J) = A1(Q11,P+2)*OTH(I,B-J)
10690 NEXT J
10700 NEXT I
```

```
10720 ****************************************************************
10730 *                                                              *
10740 *          BASIC REQUIREMENTS COMPUTATION COMPLETE.            *
10750 *      BEGIN NETWORK SOLUTION PROCEDURE.   THE MATRIX          *
10760 *      DO( ) IS NOW LOADED WITH ALL VALUES EXCEPT TRACOM       *
10770 *      FIRST TOUR AND PROFESSIONAL EDUCATION.   BEGIN          *
10780 *      CALCULATION OF ENTRIES TO INVT MATRIX.  INVTO IS        *
10790 *      WORKING FILE.                                           *
10800 *                INVT(8,-) = TOTAL LINE                        *
10810 *                INVT(9,-) = CUMULATIVE INVENTORY LINE         *
10820 *                                                              *
10830 ****************************************************************
10840 D2 = 0
10850 IF M < 15 THEN L = 1 ELSE L = 2
10860 FOR I = 1 TO 7
10870 Q38(I) = 0
10880 FOR J = 1 TO 4
10890 Q4(I,J) = DO(I,J)
10900 NEXT J
10910 NEXT I
10920 FOR J = 1 TO 4
10930 FOR I = 1 TO 7
10940 D2 = D2 + DO(I,J)
10950 NEXT I
10960 NEXT J
10970 C5 = 1:RO8 = 0
10980 FOR J = 1 TO 30
10990 RO8 = RO8 + C5*(1+RO(J))
11000 C5 = C5*RO(J)
11010 NEXT J
11020 P2 = 1
11030 FOR J = 1 TO 18
11040 P2 = P2*RO(J)
11050 IF J = 12 THEN P1 = P2
11060 NEXT J
11070 DLT = TCO(A1(Q11,L),31) + 2*PO(2)*P1 + PO(3)*P2 + 1/6
11080 IO = D2/((RO8/(2*(1+1/30)))-DLT)
11090 GOSUB' 53(IO)
11100 GOSUB' 67
11110 JMP 1120.REM COMPUTE TRACOM FIRST TOUR NUMBERS.
11120 IF M<15 THEN L=1 ELSE L=2
11130 DO(3,1)=DO(3,1)+TCO(A1(Q11,L),31)*INVTO(31)
11140 /*COMPUTE PROFESSIONAL EDUCATION NUMBERS*/
11150 DO(6,1) = DO(6,1) + PO(2)*INVTO(12)*2
11160 DO(6,2) = DO(6,2) + PO(3)*INVTO(18)*1/3
11170 DO(6,3) = DO(6,3) + PO(3)*INVTO(18)*1/3
11180 DO(6,4) = DO(6,4) + PO(3)*INVTO(18)*1/3
11190 D80=0
11200 FOR J = 1 TO 4
```

```
11210 DR(J) = 0
11220 FOR I = 1 TO 7
11230 DR(J) = DR(J) + DO(I,J)
11240 NEXT I
11250 DRO = DRO + DR(J)
11260 NEXT J
11270 /* COMPUTE FRONT END NUMBERS */
11280 CONVERT STR(T9$(3,1),1,2)TO T12
11290 GOSUB' 55(0,T12,INVTO(31)+PO(1),3,1)
11300 DO(3,1)=ROUND((DO(3,1)-C),4)
11310 I4(3,1)=ROUND(T2,4)
11320 Q7(3,1)=T12+1
11330 T12=T12+1
11340 CONVERT INT(C2+.5) TO STR(T9$(3,1),3,3),PIC(###)
11350 FOR I=1 TO T8(1)
11360 INVT(3,I)=INVT(3,I)+T8(I+1)
11370 INVT(8,I)=INVT(8,I)-T8(I+1)
11380 NEXT I
11390 /* COMPUTE FLEET FIRST TOUR LENGTH */
11400 CONVERT STR(T9$(1,1),1,2) TO T11
11410 GOSUB' 55(T12,T11,T2,1,2)
11420 D3=C
11430 GOSUB' 55(0,T11,INVTO(31)*(1-PO(1)),1,1)
11440 IF (D3+C)<DO(1,1) THEN JMP1142                /*INCREASE T11*/
11450 IF (D3+C)=DO(1,1) THEN JMP1143
11460 JMP1141 : T11=T11-1                           /*DECREASE T11*/
11470 GOSUB' 55(T12,T11,I4(3,1),1,2)
11480 D3=C
11490 GOSUB' 55(0,T11,INVTO(31)*(1-PO(1)),1,1)
11500 IF (D3+C)<DO(1,1) THEN T11=T11+1 ELSE JMP1141
11510 GOTO JMP1143
11520 JMP1142 : T11=T11+1
11530 GOSUB' 55(T12,T11,I4(3,1),1,2)
11540 D3=C
11550 GOSUB' 55(0,T11,INVTO(31)*(1-PO(1)),1,1)
11560 IF (D3+C)>DO(1,1) THEN JMP1143 ELSE JMP1142
11570 JMP1143: GOSUB' 55(0,T11,INVTO(31)*(1-PO(1)),1,1)
11580 GOSUB' 61(0,INVTO(31)*(1-PO(1)),1,1,1)
11590 DO(1,1)=ROUND((DO(1,1)-C),4)
11600 I4(1,1)=ROUND(T2,4)
11610 Q7(1,1)=T11+7
11620 CONVERT INT(C2+.5) TO STR(T9$(1,1),3,3),PIC(###)
11630 CONVERT T11 TO STR(T9$(1,1),1,2),PIC(##)
11640 CONVERT T11 TO STR(T9$(1,2),1,2),PIC(##)
11650 GOSUB' 55(T12,T11,I4(3,1),1,2)
11660 FOR I=1 TO T8(I)
11670 INVT(1,INT(T12/12+I))=INVT(1,INT(T12/12+I))+T8(I+1)
11680 INVT(8,INT(T12/12+I))=INVT(8,INT(T12/12+I))-T8(I+1)
11690 IF INVT(8,INT(T12/12+I))<0 THEN INVT(8,INT(T12/12+I))=0
11700 NEXT I
```

SECTION V: NETWORK SOLUTION ROUTINES

```
11710 DO(1,1)=DO(1,1)-C
11720 IF DO(1,1)<0 THEN DO(1,1)=0
11730 DO(1,1)=ROUND(DO(1,1),5)
11740 I4(1,2)=ROUND(T2,4)
11750 Q7(1,2)=T12+T11+7
11760 CONVERT INT(C2+.5) TO STR(T9$(1,2),6,3),PIC(###)
11770 T13=T11+7
11780 /* DISTRIBUTE FIRST TOUR OUTPUT */
11790 S10=1
11800 MAT T6 = ZER
11810 T6(2) = I4(1,1)
11820 FOR I = 2 TO 7
11830 CONVERT STR(T9$(I,2),1,2) TO T2
11840 IF DO(I,1) <= 0 THEN JMP1200
11850 IF STR(T9$(I,2),3,3) = "NNN" THEN JMP1200
11860 IF T6(I) <= 0 THEN JMP1200
11870 /* COMPUTE FLOWS */
11880 IF I=6 THEN JMP1210
11890 GOSUB' 55(T13,T2,T6(I),I,2)
11900 GOSUB' 61(T13,T6(I),I,2,1)
11910 GOTO JMP1220
11920 JMP1210 : /*PROFESSIONAL DEVELOPMENT*/
11930 GOSUB' 60(T13,T2,T6(I),2,1)
11940 JMP1220 : /*COLLECT RESULTS*/
11950 DO(I,1)=ROUND((DO(I,1)-C),5)
11960 I4(I,2)=I4(I,2)+ROUND(T2,4)
11970 Q7(I,2)=T11+T2+8
11980 CONVERT STR(T9$(I,2),3,3) TO D2
11990 CONVERT (D2+INT(C2+.5)) TO STR(T9$(I,2),3,3),PIC(###)
12000 T6(I+1)=T6(I+1)+DLT
12010 GOTO JMP1230
12020 JMP1200:C = 0:C2 = 0:T2 = 0
12030 T6(I+1) = T6(I+1) + T6(I)
12040 Q7(I,2)=T11+T2+8
12050 JMP1230:NEXT I
12060 /*COMPUTE OUT OF AVIATION*/
12070 IF T6(8)<=0 THEN JMP1250
12080 CONVERT STR(T9$(7,2),1,2) TO T2
12090 GOSUB' 55(T13,T2,T6(8),9,2)
12100 GOSUB' 61(T13,T6(8),9,2,1)
12110 OUTA(2)=OUTA(2)+C2
12120 I4(7,2)=I4(7,2)+ROUND(T2,4)
12130 JMP1250 : /*END SECOND TOUR COMPUTATIONS*/
12140 IF Z1$<>"YES" THEN JMP1350
12150 C$="AT END TOUR TWO"
12160 STOP "END TOUR TWO - PF 14 FOR DATA"
12170 JMP1350 : /*BEGIN ITERATION ON J*/
12180 /* MAXIMAL FLOW ALGORITHM */
12190 FOR J = 3 TO 7                          /* TOUR NUMBER */
12200 MAT T6 = ZER:MAT T7 = ZER:MAT I40 = ZER
```

SECTION V: NETWORK SOLUTION ROUTINES

```
12210 MAT I41 = ZER:MAT R2 = ZER
12220 FOR N = 1 TO 7                                    /* SOURCE NODE */
12230 T13 = Q7(N,J-1)                                   /* START TIME */
12240 IF T13<PRO4 THEN S10 = 1
12250 IF T13>=PRO4 AND T13<PRO5 THEN S10 = 2
12260 IF T13>=PRO5 AND T13<=PRO5+48 THEN S10 = 3
12270 IF T13>PRO5+48 THEN S10 = 4
12280 FOR I = 1 TO 7                                    /*DEST. NODE */
12290 IF I4(N,J-1)=0 THEN JMP1300
12300 IF STR(T9$(I,J),3*N,3)="NNN" THEN JMP1360
12310 CONVERT STR(T9$(I,J),1,2) TO T2
12320 IF J=7 THEN T2 = 311-Q7(N,J-1)
12330 GOSUB' 55(T13,T2,I4(N,J-1),I,J)
12340 T7(I)=(C2/C)*DO(I,S10)
12350 I40(N,I) = C2                                     /* INTERIOR NETWORK FLOW */
12360 R2(N,I) = I4(N,J-1)/C2
12370 JMP1360:IF STR(T9$(I,J),3*N,3) = "NNN" THEN I40(N,I) = 0
12380 IF I40(N,I)>TG(N) THEN TG(N) = I40(N,I)
12390 NEXT I
12400 NEXT N
12410 IF Z1$<>"YES" THEN JMP3007
12420 C$="TOUR    - NETWORK SETUP COMPLETE"
12430 CONVERT J TO STR(C$,6,1),PIC(#)
12440 GOSUB' 16
12450 JMP3007:
12460 /* LOCAL NETWORK SET-UP  -- ASSIGN FLOWS */
12470 FOR N = 7 TO 1 STEP -1
12480 FOR I = 1 TO 7
12490 IF TG(N) = 0 THEN JMP1371
12500 IF T7(I) = 0 THEN JMP1372
12510 IF I40(N,I) = 0 THEN JMP1372
12520 IF TG(N) < I40(N,I) THEN Q5 = TG(N) ELSE Q5 = I40(N,I)
12530 IF Q5>T7(I) THEN Q5=T7(I)
12540 TG(N)=TG(N)-Q5
12550 T7(I)=T7(I)-Q5
12560 I40(N,I)=I40(N,I)-Q5
12570 I41(N,I)=I41(N,I)+Q5
12580 IF I40(N,I)=0 THEN TG(N) = 0
12590 JMP1372:NEXT I
12600 JMP1371:NEXT N
12610 /* PRELIMINARY ASSIGNMENT COMPLETE */
12620 /* CHECK TG/T7 FOR NULL */
12630 JMP1303:K1,K2=0
12640 FOR N = 1 TO 7
12650 IF TG(N)>0 THEN K1=N
12660 IF T7(N)>0 THEN K2=N
12670 NEXT N
12680 IF K1=0 OR K2=0 THEN JMP1301                      /* MAX FLOW - OUT */
12690 /* FLOW NOT MAX - DEVELOP ALTERNATE PATHS */
12700 /* SET COUNTERS */
```

SECTION V: NETWORK SOLUTION ROUTINES

```
12710 MAT T19=ZER:MAT T21=ZER:MAT T18=ZER:MAT T22=ZER:MAT T17=ZER
12720 T19(K1) = 1:L5 = 1
12730 IF T6(K1)>T7(K2) THEN Q5 = T7(K2) ELSE Q5 = T6(K1)
12740 N1 = K1:I3=1
12750 T17(K1)=1
12760 JMP1362:IF I40(N1,K2)<=0 THEN JMP1367
12770 IF I40(N1,K1)<Q5 THEN Q5 = I40(N1,K2)
12780 T18(L5)=K2:T22(L5)=Q5
12790 GOTO JMP1365
12800 JMP1367:IF I3>=8 THEN JMP1354
12810 FOR I = I3 TO 7
12820 IF T21(I) = 1 THEN JMP1364                        /* NEXT I */
12830 IF I40(N1,I)<=0 THEN JMP1364
12840 IF Q5>I40(N1,I) THEN Q5 = I40(N1,I)
12850 T21(I) = 1
12860 T18(L5) = I:T22(L5) = Q5:I1=I:N2=1
12870 IF L5<49 THEN JMP1359
12880 JMP1358:CALL "OFFPRIN" ("ARC COUNTER EXCEEDED",1)
12890 GOTO JMP100
12900 JMP1359:L5=L5+1
12910 GOTO JMP1366                                      /*GO TO N SCAN*/
12920 JMP1364:NEXT I
12930 /* NO SATISFACTORY PATH FROM N1 */
12940 JMP1354:IF L5 = 1 THEN JMP1351
12950 L5 = L5-1
12960 N2 = T18(L5)+1
12970 I1 = T18(L5-1)
12980 Q5 = T22(L5-1)
12990 JMP1366:/* MOVE TO FORWARD N SCAN */
13000 IF N2>=8 THEN JMP1353
13010 FOR N = N2 TO 7
13020 IF T19(N) = 1 THEN JMP1368
13030 IF I41(N,I1)<=0 THEN JMP1368
13040 IF Q5>I41(N,I1) THEN Q5 = I41(N,I1)
13050 T19(N) = 1
13060 T18(L5)=N:T22(L5)=Q5:N1=N:I3=1
13070 IF L5>=49 THEN JMP1358
13080 L5=L5+1
13090 GOTO JMP1362
13100 JMP1368:NEXT N
13110 /* NO SATISFACTORY PATH FROM I1 */
13120 JMP1353:L5=L5-1
13130 IF L5 = 1 THEN JMP1351
13140 I3 = T18(L5)+1
13150 N1 = T18(L5-1)
13160 Q5=T22(L5-1)
13170 GOTO JMP1362
13180 JMP1351:FOR N = 1 TO 7
13190 IF T6(N)<=0 THEN JMP1352
13200 IF T17(N)>0 THEN JMP1352
```

SECTION V: NETWORK SOLUTION ROUTINES

```
13210 K1 = N
13220 T17(N)=1
13230 MAT T18=ZER:MAT T19=ZER:MAT T21=ZER:MAT T22=ZER
13240 T19(K1)=1:N1=K1:I3=1
13250 GOTO JMP1362
13260 JMP1352:NEXT N
13270 GOTO JMP1361
13280 JMP1365:/* CONNECTED PATH IN T18 */
13290 /* Q5 IS MAX AVAILABLE CAPACITY */
13300 T6(K1) = T6(K1)-Q5
13310 T7(K2) = T7(K2)-Q5
13320 N1 = K1:L6=1
13330 JMP1379:I40(N1,T18(L6))=I40(N1,T18(L6))-Q5
13340 I41(N1,T18(L6))=I41(N1,T18(L6))+Q5
13350 IF L6=L5 THEN JMP1363
13360 L6=L6+1
13370 I41(T18(L6-1),T18(L6))=I41(T18(L6-1),T18(L6))-Q5
13380 I40(T18(L6-1),T18(L6))=I40(T18(L6-1),T18(L6))+Q5
13390 N1 = T18(L6)
13400 L6=L6+1
13410 GOTO JMP1379
13420 JMP1363:/* DISTRIBUTE FLOWS */
13430 MAT T7 = ZER:MAT I42 = ZER
13440 Q45,Q46=0
13450 FOR N = 1 TO 7
13460 FOR I = 1 TO 7
13470 I41(N,I)=I41(N,I)*R2(N,I)
13480 NEXT I
13490 T6(N) = I4(N,J-1)
13500 Q45 = Q45 + Q7(N,J-1)*T4(N,J-1)
13510 Q46 = Q46 + I4(N,J-1)
13520 NEXT N
13530 Q71 = Q45/Q46
13540 IF Z1$<>"YES" THEN JMP9068
13550 INIT(HEX(20))C$
13560 C$ = "TOUR    MAXIMAL FLOW SOLUTION REACHED"
13570 CONVERT J TO STR(C$,6,1),PIC(#)
13580 GOSUB' 16
13590 JMP9068:
13600 /* T6 CONTAINS ACTUAL FLOWS */
13610 /* COMPUTE FLOWS */
13620 MAT I40 = ZER
13630 MAT T7 = ZER:MAT T8 = ZER
13640 FOR N = 1 TO 7
13650 T13 = Q7(N,J-1)
13660 FOR I = 7 TO 1 STEP -1
13670 IF STR(T9$(I,J),3*N,3)="NNN" THEN JMP1370
13680 IF DO(I,S10)<=0 THEN JMP1370
13690 IF I41(N,I)<=0 THEN JMP1370
13700 CONVERT STR(T9$(I,J),1,2) TO T2
```

SECTION V: NETWORK SOLUTION ROUTINES

```
13710 IF J = 7 THEN T2 = 311-Q7(N,J-1)
13720 DLT=0
13730 FOR K = 1 TO 5
13740 T14 = T13-9+3*K
13750 IIN = I41(N,I)*FA1(K)+DLT
13760 GOSUB' 55(T14,T2,IIN,I,J)
13770 GOSUB' 61(T14,IIN,I,J,S10)
13780 DO(I,S10)=ROUND((DO(I,S10)-C),4)
13790 I4(I,J)=I4(I,J)+ROUND(I2,4)
13800 I40(N,I)=I40(N,I)+Q8*T14
13810 I42(N,I) = I42(N,I) + Q8
13820 CONVERT STR(T9#(I,J),3*N,3) TO D2
13830 CONVERT (D2+INT(C2+.5)) TO STR(T9#(I,J),3*N,3),PIC(###)
13840 T6(N)=T6(N)-Q8
13850 NEXT K
13860 JMP1370:NEXT I
13870 /* CHECK UPWARD DETAILING */
13880 IF Z3$ <> "YES" THEN JMP1400
13890 IF DAT = 0 THEN JMP1400
13900 IF T6(N)<=0 THEN JMP1400
13910 T6(8) = T6(N):T6(N)=0
13920 GOSUB' 60(T13,N,J,S10)
13930 T6(N) = T6(8)
13940 JMP1400:NEXT N
13950 FOR I = 1 TO 7
13960 IF I = 1 THEN TD = 5 ELSE TD = 1
13970 L5 = 0:Q5 = 0:Q3 = 0
13980 FOR N = 1 TO 7
13990 IF I40(N,I) <= 0 THEN JMP140)
14000 Q5=Q5+I40(N,I)
14010 Q3=Q3+I42(N,I)
14020 JMP140):NEXT N
14030 CONVERT STR(T9#(I,J),1,2) TO T2
14040 IF Q3=0 THEN JMP1395
14050 Q7(I,J) = Q5/Q3 + T2 + TD
14060 Q7(I,J) = ROUND(Q7(I,J),0)
14070 GOTO JMP1396
14080 JMP1395:Q7(I,J) = Q71+T2+TD
14090 Q7(I,J) = ROUND(Q7(I,J),0)
14100 JMP1396:NEXT I
14110 /*COMPUTE OUT OF AVIATION*/
14120 FOR N = 1 TO 7
14130 IF T6(N)<=0 THEN JMP1415
14140 T13 = Q7(N,J-1)
14150 CONVERT STR(T9#(7,J),1,2) TO T2
14160 IF J=7 THEN T2=311-Q7(N,J-1)
14170 GOSUB' 55(T13,T2,T6(N),9,J)
14180 GOSUB' 61(T13,T6(N),9,J,S10)
14190 OUTA(J)=OUTA(J)+C2
14200 I4(7,J)=I4(7,J) + ROUND(I2,4)
```

SECTION V: NETWORK SOLUTION ROUTINES

```
14210 JMP1415:NEXT N
14220 IF Z1$<>"YES" THEN JMP1410
14230 INIT(HEX(20))C$
14240 C$ = "RESULTS AT END TOUR"
14250 CONVERT J TO STR(C$,21,1),PIC(#)
14260 GOSUB' 14(C$)
14270 JMP1416:
14280 NEXT J
```

SECTION VI: ITERATION CHECK ROUTINES

```
14300 **********************************************************************
14310 *                                                                    *
14320 *         ITERATION COMPLETE.   COMPUTE REMAINING REQUIREMENT         *
14330 *         AND DEVELOP INCREMENTAL ACCESSION REQUIREMENT.              *
14340 *         THIS IS IMPLEMENTED AS A TWO STAGE PROCESS.   ALL           *
14350 *         ACTIVITIES EXCEPT "OTHER" ARE TESTED FOR COMPLETION         *
14360 *         IN THE FIRST STAGE.  WHEN THESE REQUIREMENTS ARE            *
14370 *         MET AN OUTPUT DISPLAY IS GENERATED AND THE PROGRAM          *
14380 *         CAN THEN PROCEED TO COMPLETE THE "OTHER" REQUIREMENT        *
14390 *                                                                    *
14400 **********************************************************************
14410 D2 = 0:S2 = 0:T1 = 12
14420 FOR J = 1 TO 4
14430 FOR I = 1 TO 6
14440 IF DO(I,J) <= 0 THEN JMP1460
14450 D2 = D2 + DO(I,J)
14460 JMP1460:NEXT I
14470 NEXT J
14480 IO = D2/(R08/(2*(1+1/36)) - 1/6)
14490 D25=IO
14500 IF IO < 1 THEN JMP1480
14510 IO = IO + INVTO(3)
14520 T50 = T50 + 1
14530 IF Z1$ <> "YES" THEN JMP1470
14540 INIT(HEX(20))C$
14550 C$ = "END ITERATION      ,        NEW ACCESSIONS"
14560 CONVERT T50 TO STR(C$,15,2),PIC(##)
14570 CONVERT ROUND(D25,1) TO STR(C$,32,5),PIC(###.#)
14580 CALL "OFFPRIN" (C$,1)
14590 JMP1470: GOSUB' 53(IO)
14600 GOSUB' 63
14610 GOSUB' 67
14620 GOTO JMP1120
14630 **********************************************************************
14640 *                                                                    *
14650 *         FIRST STAGE REQUIREMENTS TESTING COMPLETE.   BEGIN         *
14660 *         TESTING OF "OTHER" REQUIREMENTS.                            *
14670 *                                                                    *
14680 **********************************************************************
14690 JMP1480 : IF Z1$<>"YES" THEN JMP1485
14700 INIT(HEX(20))C$
14710 STR(C$,1,37)="ITERATION      ,       ACCESSIONS ADDED"
14720 CONVERT(T50+T51) TO STR(C$,13,2),PIC(##)
14730 CONVERT ROUND(D25,1) TO STR(C$,16,5),PIC(###.#)
14740 INIT(HEX(20))C$
14750 STR(C$,1,22) = "AT END OF    ITERATION"
14760 CONVERT(T50+T51) TO STR(C$,11,2),PIC(##)
14770 STOP C$
14780 JMP1485: IF T51 > 0 OR Z4$ = "YES" THEN JMP1480
```

B-33

SECTION VI: ITERATION CHECK ROUTINES

```
14790 E$ = "ALL REQUIREMENTS EXCEPT 'OTHER' COMPLETELY FILLED"
14800 STR(E$,65,13)  = "ITERATIONS = "
14810 CONVERT T50 TO STR(E$,78,2),PIC(##)
14820 CALL "OFFPRIN" (E$,8)
14830 JMP1490:S2 = 0:T1 = 12
14840 FOR J = 1 TO 4
14850 D2 = D2 + DO(7,J)
14860 NEXT J
14870 IO=D2/(RO8/(2*(1+1/30))-1/6)
14880 D25=IO
14890 IF IO<1 AND IO<.01*D80 THEN JMP1600
14900 IO = 10 + INVTO(31)
14910 IF Z1$ <> "YES" THEN JMP1500
14920 INIT(HEX(20))C$
14930 STR(C$,1,35) = "OTHER REQUIREMENTS REMAINING =    "
14940 CONVERT ROUND(D2,1) TO STR(C$,32,5),PIC(###.#)
14950 CALL "OFFPRIN" (C$,1)
14960 CALL "OFFPRIN" (C$,8)
14970 JMP1500: GOSUB' 53(IO)
14980 T51 = T51 + 1
14990 GOSUB' 63
15000 GOSUB' 67
15010 GOTO JMP1120
15020 ********************************************************************
15030 *                                                                  *
15040 *       REQUIREMENTS DETERMINATION IS COMPLETE.  DISPLAY           *
15050 *       OUTPUTS AND SELECT PRINT OPTION.  AFTER PRINT MODE         *
15060 *       RESETS IN PREPARATION FOR A NEW RUN.                       *
15070 *                                                                  *
15080 ********************************************************************
15090 JMP1600: INIT(HEX(20))E$
15100 E$ = "ALL REQUIREMENTS MET"
15110 STR(E$,105,13) = "ITERATIONS = "
15120 CONVERT T50 TO STR(E$,118,2),PIC(##)
15130 STR(E$,120,1) = "/"
15140 CONVERT T51 TO STR(E$,121,2),PIC(##)
15150 STR(E$,130,1)=STR(TGROUP$,15,1)
15160 IF Z4$="YES" THEN STR(E$,48,40) = EM$
15170 CALL "OFFPRIN" (E$,8)
15180 IF M>15 THEN JMP1610
15190 PTR(A1(M,1)) = PTR(A1(M,1)) + INVT(8,31)
15200 PTR(A1(M,1)+7) = PTR(A1(M,1)+7) + ACC1
15210 GOTO JMP1611
15220 JMP1610:PTR(A1(M-15,2)) = PTR(A1(M-15,2)) + INVT(8,31)
15230 PTR(A1(M-15,2)+7) = PTR(A1(M-15,2)+7) + ACC1
15240 JMP1611:IF M>15 THEN MAT TOT = TOTN ELSE MAT TOT = TOTA
15250 FOR I = 1 TO 9
15260 IF I = 8 THEN JMP1603
15270 IF I<8 THEN K = I ELSE K=8
15280 FOR J = 1 TO ROUND(PRO4/12-1,0)
```

SECTION VI: ITERATION CHECK ROUTINES

```
15290 TOT(K,1) = TOT(K,1) + INVT(I,J)
15300 NEXT J
15310 FOR J = ROUND(PRO4/12,0) TO ROUND(PRO5/12-1,0)
15320 TOT(K,2) = TOT(K,2) + INVT(I,J)
15330 NEXT J
15340 FOR J = ROUND(PRO5/12,0) TO 30
15350 TOT(K,3) = TOT(K,3)+INVT(I,J)
15360 NEXT J
15370 JMP1603:NEXT I
15380 IF M>15 THEN MAT TOTN=TOT ELSE MAT TOTA = TOT
15390 MAT DO = ZER
15400 MAT Q4 = ZER
15410 MAT INVTO = ZER
15420 MAT INVT = ZER
15430 MAT Q37 = ZER
15440 MAT OUTA = ZER
15450 MAT I4 = ZER
15460 MAT Q7 = ZER
15470 FOR J = 1 TO 7
15480 FOR I = 1 TO 7
15490 T9$(I,J) = T10$(I,J)
15500 NEXT I
15510 NEXT J
15520 FOR I = 1 TO 20
15530 T5(I),T6(I),T7(I),TR(I),T15(I),T17(I),T18(I)=0
15540 NEXT I
15550 STR(T9$(1,1),1,2) = "30"
15560 STR(T9$(1,2),1,2) = "30"
15570 T50=1:T51=0:R01=0
15580 IF Z4$<>"YES" THEN JMP1650
15590 STR(TGROUP$,I5,1) = "#"
15600 JMP1630:NEXT I5
15610 JMP1640:NEXT I4
15620 CALL "OFFPRIN" (FM$,9)
15630 SELECT CRT
15640 GOSUB' 85
15650 JMP1650:GOTO JMP100
```

```
15670 ****************************************************************
15680 *                                                              *
15690 *                        SUBROUTINES                           *
15700 *                                                              *
15710 ****************************************************************
15720 ****************************************************************
15730 *                                                              *
15740 *      #14 - THIS SUBROUTINE PROVIDES ACCESS TO THE            *
15750 *            IN-PROCESS MONITOR DISPLAYS IN RESPONSE           *
15760 *            TO TEMPORARILY INSERTED) STOPS.                   *
15770 *                                                              *
15780 ****************************************************************
15790 DEFFN' 14(C$)
15800 INIT(HEX(20))X$
15810 STR(X$,1,25) = STR(C$,1,25)
15820 STR(X$,28,9) = "ITERATION"
15830 CONVERT T50 TO STR(X$,38,2),PIC(##)
15840 CALL "OFFPRIN" (X$,1)
15850 RETURN
```

```
15870 ***************************************************************
15880 *                                                            *
15890 *      #16 - THIS SUBROUTINE PROVIDES PRINTS OF THE SOURCE,   *
15900 *            INTER-TOUR, AND SINK FLOWS SET UP FOR THE        *
15910 *            MAXIMAL FLOW ALGORITHM.   NEEDS T6,I40,I41,T7.   *
15920 *                                                            *
15930 ***************************************************************
15940 DEFFN' 16
15950 SELECT PRINTER
15960 PRINT PAGE
15970 PRINT SKIP(5);TAB(40);C$
15980 PRINT SKIP(5);TAB(11);"SOURCE";TAB(50);"FORWARD FLOWS";TAB(90);
15990 PRINT "SINK"
16000 PRINT TAB(50);"REVERSE FLOWS";SKIP(2)
16010 FOR P = 1 TO 7
16020 PRINT TAB(8);
16030 PRINT USING PRTCAR15,T6(P);
16040 PRINT TAB(20);
16050 FOR Q = 1 TO 7
16060 PRINT USING PRTCAR15,I40(P,Q);
16070 NEXT Q
16080 PRINT TAB(90);
16090 PRINT USING PRTCAR15,T7(P)
16100 PRINT TAB(20);
16110 FOR Q = 1 TO 7
16120 PRINT USING PRTCAR15,I41(P,Q);
16130 NEXT Q
16140 PRINT SKIP(2)
16150 PRTCAR15:FMT XX(3),PIC(###.#),XX(7)
16160 NEXT P
16170 SELECT CRT
16180 RETURN
```

```
16200 ***********************************************************************
16210 *                                                                    *
16220 *      #51 - THIS SUBROUTINE RESETS GO,S1 AND A1 IN RESPONSE          *
16230 *            TO FORCE LEVEL CHANGES.  Y=1 CHANGES A COMPLETE          *
16240 *            CARRIER AIR WING.  Y>1 CHANGES SUBCOMMUNITY              *
16250 *            Y-1.                                                     *
16260 *                                                                    *
16270 ***********************************************************************
16280 DEFFN' 51(Y)
16290 MAT T5 = ZER
16300 IF Y>1 THEN JMP5150
16310 A = S1(15,1)/GO(15,13)
16320 FOR P1 = 1 TO 14
16330 IF A1(P1,5)=0 THEN JMP5192
16340 FOR Q1 = 3 TO 12 STEP 3
16350 GO(P1,Q1) = ROUND(GO(P1,Q1)*A,0)
16360 NEXT Q1
16370 S1(P1,1)=ROUND(S1(P1,1)*A,0)
16380 GO(P1,13)=S1(P1,1)
16390 T5(1) = T5(1) + A1(P1,3)
16400 T5(2) = T5(2) + A1(P1,6)
16410 T5(A1(P1,1)+2) = T5(A1(P1,1)+2) + A1(P1,4)
16420 IF A1(P1,2)>0 THEN T5(A1(P1,2)+2) = T5(A1(P1,2)+2) + A1(P1,7)
16430 JMP5192:NEXT P1
16440 FOR Q1 = 1 TO 9
16450 T5(Q1) = 1+(A-1)*T5(Q1)
16460 NEXT Q1
16470 FOR P1 = 1 TO 14
16480 IF A1(P1,5)>0 THEN JMP5193
16490 A1(P1,3) = ROUND(A1(P1,3)/T5(1),4)
16500 A1(P1,6) = ROUND(A1(P1,6)/T5(2),4)
16510 A1(P1,4) = ROUND(A1(P1,4)/T5(A1(P1,1)+2),4)
16520 IF A1(P1,2)>0 THEN A1(P1,7) = ROUND(A1(P1,7)/T5(A1(P1,2)+2),4)
16530 GOTO JMP5194
16540 JMP5193:A1(P1,3) = ROUND(A*A1(P1,3)/T5(1),4)
16550 A1(P1,6) = ROUND(A*A1(P1,6)/T5(2),4)
16560 A1(P1,4) = ROUND(A*A1(P1,4)/T5(A1(P1,1)+2),4)
16570 IF A1(P1,2)>0 THEN A1(P1,7) = ROUND(A*A1(P1,7)/T5(A1(P1,2)+2),4)
16580 JMP5194:NEXT P1
16590 RETURN
16600 JMP5150:A=S1(Y-1,1)/GO(Y-1,13)
16610 FOR Q1 = 3 TO 12 STEP 3
16620 GO(Y-1,Q1) = ROUND(GO(Y-1,Q1)*A,0)
16630 NEXT Q1
16640 FOR P1 = 1 TO 14
16650 IF P1=Y-1 THEN JMP5151
16660 A1(P1,3) = ROUND(A1(P1,3)/(1+(A-1)*A1(Y-1,3)),4)
16670 A1(P1,6) = ROUND(A1(P1,6)/(1+(A-1)*A1(Y-1,6)),4)
16680 IF A1(P1,1)<>A1(Y-1,1) THEN JMP5163
```

SECTION VII: SUBROUTINES

```
16690 A1(P1,4) = ROUND(A1(P1,4)/(1+(A-1)*A1(Y-1,4)),4)
16700 JMP5161:IF A1(P1,2)<>A1(Y-1,2) THEN JMP5162
16710 A1(P1,7) = ROUND(A1(P1,7)/(1+(A-1)*A1(Y-1,7)),4)
16720 JMP5162:IF A1(Y-1,5)=0 THEN JMP5163
16730 A1(P1,5) = ROUND(A1(P1,5)/(1+(A-1)*A1(Y-1,5)),4)
16740 A1(P1,8) = ROUND(A1(P1,8)/(1+(A-1)*A1(Y-1,8)),4)
16750 JMP5163:GOTO JMP5152
16760 JMP5151:FOR Q1 = 3 TO 8
16770 A1(P1,Q1) = ROUND(A1(P1,Q1)*A/(1+(A-1)*A1(P1,Q1)),4)
16780 NEXT Q1
16790 JMP5152:NEXT P1
16800 RETURN
```

```
16820 *************************************************************
16830 *                                                           *
16840 *        #53 - THIS SUBROUTINE COMPUTES THE ENTRIES FOR     *
16850 *              LOS CELLS IN INVTO RESULTING FROM IO         *
16860 *              ACCESSIONS                                   *
16870 *              NOTE: RO(T3) IS THE RATIO OF THE NUMBER      *
16880 *                    AT THE END OF YEAR T3 TO THAT AT THE   *
16890 *                    END OF YEAR T3-1.  RO(1)=YR1/ACC.  THE *
16900 *                    INVENTORY IN YEAR T3 IS THE AREA UNDER *
16910 *                    THE DISTRIBUTION CURVE IN THE YEAR T3. *
16920 *                                                           *
16930 *************************************************************
16940 DEFFN' 53(IO)
16950 H = IO
16960 FOR P = 1 TO 30
16970 INVTO(P) = H*(1+RO(P))/2
16980 H = H*RO(P)
16990 NEXT P
17000 INVTO(31) = IO
17010 MAT INVT = ZER:Q76 = 0
17020 FOR P = 1 TO 31
17030 INVT(8,P) = INVTO(P)
17040 NEXT P
17050 FOR P = 2 TO 30
17060 Q76 = Q76 + INVT(8,P-1) - INVT(8,P)
17070 NEXT P
17080 RETURN
```

```
17100 ******************************************************************
17110 *                                                              *
17120 *       #55 - THIS SUBROUTINE ACCEPTS START TIME (T1),         *
17130 *             TOUR LENGTH (T2), START FLOW (IO),               *
17140 *             DESTINATION ACTIVITY (A), AND TOUR NUMBER        *
17150 *             (B).  IT PRODUCES THE VALUE OF THE               *
17160 *             DESTINATION REQUIREMENT MET (C) AND OF THE       *
17170 *             DESTINATION REQUIREMENT INCREMENT + TRANSIENT    *
17180 *             REQUIREMENTS (C2).  THE DISTRIBUTION OF C2 BY    *
17190 *             YEAR IS GIVEN IN T8( ).                          *
17200 *                                                              *
17210 ******************************************************************
17220 DEFFN' 55(T1,T2,IO,A,B)
17230 C,C2,I2 = 0
17240 IF IO = 0 THEN RETURN
17250 MAT T8 = ZER
17260 L = 1
17270 T1 = ROUND(T1,0):T2 = ROUND(T2,0)
17280 T10 = T1/12 : T3 = INT(T10+1)
17290 /* COMPUTE TRANSIENT TIME */
17300 T4 = 1
17310 IF A = 1 AND B < 3 THEN T4 = 7
17320 IF A = 1 AND B > 2 THEN T4 = 5
17330 /* COMPUTE C2 */
17340 T20 = (T2+T4)/12
17350 K1 = (T3-T10) * (1-RO(T3))
17360 H = IO * (1-K1)
17370 T8(L+1) = ((IO+H)/2) * (T3-T10)
17380 C2 = C2+T8(L+1)
17390 T20 = T20-(T3-T10)
17400 IF T20 <= 0 THEN JMP23                     /* SHORT FIRST ENTRY */
17410 JMP21 : L = L+1 : T3 = T3+1
17420 IF T20 <= 1 THEN JMP22                     /* GO TO LAST ENTRY */
17430 T8(L+1) = H * (1+RO(T3))/2
17440 H = H * RO(T3)
17450 C2 = C2 + T8(L+1)
17460 T20 = T20-1
17470 GO TO JMP21
17480 JMP22 : K1 = T20 * (1-RO(T3))              /* CREATE LAST ENTRY */
17490 T8(L+1) = H * ((2-K1)/2) * T20
17500 C2 = C2 + T8(L+1)
17510 T8(1) = L
17520 I2 = H * (1-K1)
17530 GO TO JMP24
17540 JMP23 : T20 = T20 - (T3-T10)               /* SHORT FIRST ENTRY */
17550 K1 = K1 * (1-T20)/(T3-T10)
17560 T8(L+1) = T8(L+1) - ((H*(2-K1)/(2*(1-K1)))*((T3-T10)-T20))
17570 C2 = T8(L+1)
17580 I2 = H/(1-K1)
```

SECTION VII: SUBROUTINES

```
17590 JMP24 : /* COMPUTE C */
17600 T3 = INT(T10+1)
17610 IF T4/12 > (T3-T10) THEN JMP25
17620 K1 = (T4/12) * (1-RO(T3))
17630 C = (IO * (2-K1)/2) * (T4/12)
17640 GO TO JMP26
17650 JMP25 : C = T8(2)
17660 K1 = (T3-T10) * (1-RO(T3))
17670 H = IO * (1-K1)
17680 T4 = (T4/12) -(T3-T10)
17690 T3 = T3+1
17700 K1 = T4 * (1-RO(T3))
17710 C = C+(H*(2-K1)/2) * T4
17720 JMP26 :   C = C2 -C
17730 RETURN
```

```
17750 *************************************************************
17760 *                                                           *
17770 *       #60 - THIS SUBROUTINE CALCULATES THE CORRECT FLOW   *
17780 *             TO PROFESSIONAL EDUCATION (ACTIVITY 6).       *
17790 *             NEEDS START TIME (T1), TOUR LENGTH (T2),      *
17800 *             INPUT FLOW (P1), TOUR NUMBER (J) AND SOURCE   *
17810 *             ACTIVITY (N). OUTPUTS ARE IDENTICAL TO        *
17820 *             SUBROUTINE #55/#61.                           *
17830 *                                                           *
17840 *************************************************************
17850 DEFFN' 60(T1,T2,P1,J,N)
17860 C,C2,I2 = 0
17870 IF P1 = 0 THEN RETURN
17880 IF DO(6,S10) <= 0 THEN DLT = P1 ELSE JMP704
17890 GOTO JMP713
17900 JMP704:GOSUB' 55(T1,T2,P1,6,J)
17910 GOSUB' 61(T1,P1,6,J,S10)
17920 /* C,C2,I2,Q8,T8() SCALED:L,DLT AVAILABLE*/
17930 IF Q8 = 0 THEN DLT = P1 ELSE JMP711
17940 GOTO JMP713
17950 JMP711:T3 = T1/12:T20 = (T2+1)/12:L1 = 1
17960 MAT T17 = T8
17970 MAT T8 = ZER
17980 IF T20 < 1 THEN JMP700
17990 T8(1) = (INT(T3+1)-T3)*12
18000 T20 = T20 - (INT(T3+1)-T3)
18010 JMP705:L1 = L1 + 1
18020 IF T20 < 1 THEN JMP700
18030 T8(L1) = 12
18040 T20 = T20 - 1
18050 GOTO JMP705
18060 JMP700:T8(L1) = T20*12
18070 FOR R = 1 TO L
18080 T17(R) = T17(R) - T8(R)
18090 INVT(6,INT(T3+R)) = INVT(6,INT(T3+R)) + T8(R)
18100 INVT(8,INT(T3+R)) = INVT(8,INT(T3+R)) - T8(R)
18110 T8(R) = T17(R)
18120 NEXT R
18130 K4 = C:K5 = C2
18140 C2 = I2*(T2+1)/12:C = I2*T2/12
18150 K4 = K4 - C:K5 = K5 - C2
18160 IF K4<=0 THEN DLT=P1 ELSE JMP710
18170 GOTO JMP713
18180 JMP710:Q6 = 0:Q8 = 0
18190 IF DO(2,S10)+DO(3,S10) <= 0 THEN JMP707
18200 IF (DO(2,S10)<=0 OR STR(T9$(2,J),3*N,3)="NNN") THEN JMP708
18210 Q6 = 1/6
18220 IF DO(2,S10)<K4*Q6 THEN Q6 = (DO(2,S10)/(K4*Q6))*Q6
18230 FOR R = 1 TO L
```

```
18240 INVT(2,INT(T3+R)) = INVT(2,INT(T3+R)) + T17(R)*Q6
18250 T8(R) = T8(R)-T17(R)*Q6
18260 NEXT R
18270 CONVERT STR(T9$(2,J),3*N,3) TO D2
18280 D2 = D2 + K5*Q6
18290 CONVERT INT(D2+.5) TO STR(T9$(2,J),3*N,3),PIC(###)
18300 DO(2,S10) = DO(2,S10) - K4*Q6
18310 JMP708:
18320 IF (DO(3,S10) <= 0 OR STR(T9$(3,J),3*N,3) = "NNN") THEN JMP707
18330 Q8 = 1/2 - Q6
18340 IF DO(3,S10) < K4*Q8 THEN Q8 = (DO(3,S10)/(K4*Q8))*Q8
18350 FOR R = 1 TO L
18360 INVT(3,INT(T3+R)) = INVT(3,INT(T3+R)) + T17(R)*Q8
18370 T8(R) = T8(R)-T17(R)*Q6
18380 NEXT R
18390 CONVERT STR(T9$(3,J),3*N,3) TO D2
18400 D2 = D2 + K5*Q8
18410 CONVERT INT(D2+.5) TO STR(T9$(3,J),3*N,3),PIC(###)
18420 DO(3,S10) = DO(3,S10) - K4*Q8
18430 JMP707:K3 = K4 - K4*(Q6+Q8)
18440 Q6 = 1 - Q6 - Q8
18450 IF (DO(7,S10)<=0 OR STR(T9$(7,J),3*N,3)="NNN") THEN JMP709
18460 IF DO(7,S10)<(K4*Q6) THEN Q6 = (DO(7,S10)/(K4*Q6))*Q6
18470 FOR R = 1 TO L
18480 INVT(7,INT(T3+R)) = INVT(7,INT(T3+R)) + T17(R)*Q6
18490 T8(R) = T8(R)-T17(R)*Q6
18500 INVT(8,INT(T3+R)) = INVT(8,INT(T3+R)) - T17(R)+T8(R)
18510 NEXT R
18520 CONVERT STR(T9$(7,J),3*N,3) TO D2
18530 D2 = D2 + K5*Q6
18540 CONVERT INT(D2+.5) TO STR(T9$(7,J),3*N,3),PIC(###)
18550 DO(7,S10) = DO(7,S10) - K4*Q6
18560 K3 = K4 - K4*Q6 - K3
18570 JMP709:OUTA(J) = OUTA(J) + K3*(K5/K4)
18580 FOR R = 1 TO L
18590 IF INVT(8,INT(T3+R))<0 THEN JMP6010
18600 IF INVT(8,INT(T3+R))<T8(R) THEN OUTA(J) = OUTA(J)-(T8(R)-
18610    INVT(8,INT(T3+R)))
18620 IF INVT(8,INT(T3+R))<T8(R) THEN T8(R) = INVT(8,INT(T3+R))
18630 INVT(8,INT(T3+R))=ROUND(INVT(8,INT(T3+R))-T8(R),0)
18640 INVT(9,INT(T3+R))=ROUND(INVT(9,INT(T3+R))+T8(R),0)
18650 GOTO JMP6011
18660 JMP6010:INVT(8,INT(T3+R))=0
18670 OUTA(J) = OUTA(J) - T8(R)
18680 JMP6011:NEXT R
18690 OUTA(J) = ROUND(OUTA(J),4)
18700 RETURN
18710 JMP713:C = 0:I2 = 0:C2 = 0
18720 RETURN
```

SECTION VII: SUBROUTINES

```
18740 ***************************************************************
18750 *                                                             *
18760 *      #61 - THIS SUBROUTINE CHECKS INPUT AGAINST             *
18770 *            REQUIREMENTS DO( ) AND INVENTORY INVT( ),        *
18780 *            AND ADJUSTS TO STAY WITHIN LIMITS.  NEEDS        *
18790 *            START TIME (T1), INPUT(IO), DESTINATION          *
18800 *            (I), DESTINATION TOUR NUMBER (J) AND             *
18810 *            REQUIREMENTS COLUMN INDEX (S100). T8( ), C,C2     *
18820 *            AND I2 ARE FROM SUBROUTINE #55.                  *
18830 *                                                             *
18840 ***************************************************************
18850 DEFFN' 61(T1,IO,I,J,S100)
18860 IF IO = 0 THEN RETURN
18870 L = T8(1)
18880 Q6 = 1
18890 Q8 = IO
18900 FOR R = 1 TO L
18910 T8(R) = T8(R+1)
18920 NEXT R
18930 T8(L+1) = 0
18940 IF I = 9 THEN JMP755
18950 IF J<3 AND I = 6 THEN C5 = I2*(T2/12) ELSE C5 = C
18960 IF C5 <= DO(I,S100) THEN JMP755
18970 Q6 = DO(I,S100)/C5
18980 FOR R = 1 TO L
18990 T8(R) = Q6*T8(R)
19000 NEXT R
19010 C = C*Q6
19020 C2 = C2*Q6
19030 I2 = I2*Q6
19040 Q8 = Q8*Q6
19050 I6 = IO*Q6
19060 JMP755: Q6 = 1:Q45 = 0:Q46 = 0:MAT T22 = ZER
19070 IF J<3 AND I=6 THEN JMP760
19080 FOR R = 1 TO L
19090 IF T8(R) = 0 THEN JMP753
19100 IF T8(R) <= INT(INVT(8,INT(T1/12)+R)+1) THEN JMP753
19110 FOR P = 1 TO L
19120 IF INVT(8,INT(T1/12)+P)<0 THEN INVT(8,INT(T1/12)+P)=0
19130 Q45 = Q45 + INVT(8,INT(T1/12)+P)
19140 Q46 = Q46 + T8(P)
19150 IF INVT(8,INT(T1/12)+P)>=T8(P) THEN JMP761
19160 T22(P) = T8(P) - INVT(8,INT(T1/12)+P)
19170 INVT(I,INT(T1/12)+P)=INVT(I,INT(T1/12)+P)+INVT(8,INT(T1/12)+P)
19180 INVT(8,INT(T1/12)+P) = 0
19190 GOTO JMP762
19200 JMP761: INVT(I,INT(T1/12)+P)=INVT(I,INT(T1/12)+P)+T8(P)
19210 INVT(8,INT(T1/12)+P)=INVT(8,INT(T1/12)+P)-T8(P)
19220 JMP762: IF INVT(8,INT(T1/12)+P)<0 THEN INVT(8,INT(T1/12)+P)=0
```

```
19230 NEXT P
19240 FOR P = 1 TO L
19250 IF T22(P)<=0 THEN JMP763
19260 FOR Q = 1 TO L
19270 IF INVT(8,INT(T1/12)+Q)<=0 THEN JMP764
19280 IF T22(P)<=INVT(8,INT(T1/12)+Q) THEN JMP765
19290 INVT(I,INT(T1/12)+Q)=INVT(I,INT(T1/12)+Q)+INVT(8,INT(T1/12)+Q)
19300 T22(P)=T22(P) - INVT(8,INT(T1/12)+Q)
19310 INVT(8,INT(T1/12)+Q)=0
19320 GOTO JMP764
19330 JMP765: INVT(I,INT(T1/12)+Q)=INVT(I,INT(T1/12)+Q)+T22(P)
19340 INVT(8,INT(T1/12)+Q)=INVT(8,INT(T1/12)+Q)-T22(P)
19350 T22(P)=0
19360 GOTO JMP763
19370 JMP764: NEXT Q
19380 JMP763: NEXT P
19390 IF Q45<Q46 THEN Q6=Q45/Q46
19400 GOTO JMP766
19410 JMP753: NEXT R
19420 FOR P = 1 TO L
19430 INVT(I,INT(T1/12)+P)=INVT(I,INT(T1/12)+P)+T8(P)
19440 INVT(8,INT(T1/12)+P)=INVT(8,INT(T1/12)+P)-T8(P)
19450 NEXT P
19460 JMP766: C = ROUND(C*Q6,4)
19470 C2 = ROUND(C2*Q6,4)
19480 I2 = ROUND(I2*Q6,4)
19490 Q8 = ROUND(Q8*Q6,4)
19500 DLT =ROUND(IO-Q8,4)
19510 I6 = IO*Q6
19520 FOR P = 1 TO L
19530 INVT(I,INT(T1/12)+P)=ROUND(INVT(I,INT(T1/12)+P),4)
19540 INVT(8,INT(T1/12)+P)=ROUND(INVT(8,INT(T1/12)+P),4)
19550 IF INVT(8,INT(T1/12)+P)<0 THEN INVT(8,INT(T1/12)+P)=0
19560 NEXT P
19570 IF I>2 THEN JMP6120
19580 IF I=1 AND N<>2 THEN JMP6120
19590 Q74 = Q74+I6
19600 JMP6120:RETURN
```

```
19620 ***************************************************************
19630 *                                                             *
19640 *      #63 - THIS SUBROUTINE IS USED TO CLEAR THE SCREEN       *
19650 *            AND RESET FOR PERIODS WHEN THE PROGRAM IS         *
19660 *            RUNNING.                                          *
19670 *                                                             *
19680 ***************************************************************
19690 DEFFN' 63
19700 INIT(HEX(20))P1$(1)
19710 P5 = LEN(A$):P6 = LEN(TYPE$(Q1,1))
19720 STR(TO$,1,2) = STR(TIME,1,2)
19730 STR(TO$,3,1) = ":"
19740 STR(TO$,4,2) = STR(TIME,3,2)
19750 STR(TO$,6,1) = ":"
19760 STR(TO$,7,2) = STR(TIME,5,2)
19770 INIT(HEX(20))B$
19780 STR(P1$(1),1,P5) = A$
19790 STR(P1$(1),P5+2,2) = "IN"
19800 STR(P1$(1),P5+5,P6) = TYPE$(Q1,1)
19810 STR(P1$(1),P5+P6+6,9) = "COMMUNITY"
19820 DISPLAY AT(10,30),"EXECUTION CONTINUES",
19830         AT(12,35),"WORKING ON",
19840         AT(14,20),P1$(1),CH(60),
19850         AT(21,50),"MAIN ITERATION",AT(21,69),T50,PIC(##),
19860         AT(22,10),TO$,CH(3),
19870         AT(22,50),"'OTHER' ITERATION",AT(22,69),T51,PIC(##)
19880 RETURN
```

```
19900 ********************************************************************
19910 *                                                                  *
19920 *        #66 - THIS SUBROUTINE IMPLEMENTS UPWARD DETAILING         *
19930 *               WHEN LOWER GRADE REQUIREMENTS ARE ALL MET.         *
19940 *               REQUIRES TOUR START TIME (T1), SOURCE NODE         *
19950 *               (N), TOUR NUMBER (J) AND CURRENT REQUIREMENT       *
19960 *               INDEX (S11), SOURCE FLOW IS IN T6(8).   FLOWS      *
19970 *               ARE PLACED IN CURRENT TOUR. REQUIREMENTS ARE       *
19980 *               REDUCED IN NEXT HIGHER REQUIREMENT.   C, C2        *
19990 *               AND I2 ARE HANDLED INTERNALLY.   T6(8) IS          *
20000 *               RESET EQUAL TO DLT ON EXIT.   Q37( ) CONTAINS      *
20010 *               NUMBER (C2) DETAILED UPWARD.                       *
20020 *                                                                  *
20030 ********************************************************************
20040 DEFFN' 66(T1,N,J,S11)
20050 IF S11<4 THEN S12=S11+1 ELSE S12=3
20060 MAT T5 = ZER
20070 T5(1) = T6(8)
20080 IF Q37(8,S12)>=DAT*D8(S12) THEN RETURN
20090 C3 = DAT*D8(S12)-Q37(8,S12)
20100 IF S11=1 AND J<3 THEN RETURN
20110 IF S11=2 AND J<5 THEN RETURN
20120 Q3=0
20130 FOR R1=1 TO 7
20140 IF C3<=0 THEN JMP30C4
20150 TD = 1
20160 IF R1 = 1 AND J < 3 THEN TD = 7
20170 IF R1 = 1 AND J > 2 THEN TD = 5
20180 CONVERT STR(T94(R1,J),1,2) TO T2
20190 IF J=7 THEN T2=R11-Q7(N,J-1)
20200 IF T5(R1) <= 0.0 THEN JMP30C4
20210 IF D0(R1,S12) <= 0 THEN JMP30C4
20220 IF S1(Q11,1)=0 THEN JMP30C3
20230 Q3 = 3
20240 IF A1(Q11,2)>0 THEN Q3 = 2
20250 IF S12=2 AND R1=1 AND D0(1,S12)/S1(Q11,1)<Q3 THEN JMP30C4
20260 JMP30C3:
20270 IF STR(T94(R1,J),3*N,3)="NNN" THEN JMP30C4   /*BARRED TRANSITION*/
20280 IF S11=2 AND R1<4 THEN JMP30C4 /*NO UPWARD DETAILING TO COMMAND*/
20290 IF R1=6 AND S11=1 THEN JMP30C4   /*NO PG TO WAR COLLEGE DETAILING*/
20300 IF S11 = 3 AND (R1=2 OR R1=5) THEN JMP30C4 /*SGD COMMAND DETAILED*/
20310 IF S11=4 AND R1=1 THEN JMP30C4      /*SR CDR FRS AND AFLOAT*/
20320 JMP30C3:GOSUB' 55(T1,T2,T5(R1),R1,J)
20330 IF C<=C3 THEN JMP66O2
20340 IF S11>2 THEN JMP66O2
20350 Q6=C3/C
20360 T5(R1+1) = T5(R1+1) + (1-Q6)*T5(R1)
20370 T5(R1) = Q6*T5(R1)
20380 GOTO JMP66O3
```

SECTION VII: SUBROUTINES

```
20390 JMP6602:GOSUB' 61(T1,T5(R1),R1,J,S12)
20400 DO(R1,S12)=ROUND((DO(R1,S12)-C),4)
20410 C3 = C3 - C
20420 I4(R1,J) = I4(R1,J) + ROUND(I2,4)
20430 I40(N,R1) = I40(N,R1) + Q8*T1
20440 I42(N,R1)= I42(N,R1) + Q8
20450 IF S11 > 2 THEN JMP6601
20460 Q37(R1,S12)=Q37(R1,S12)+C:Q37(8,S12)=Q37(8,S12)+C
20470 CONVERT STR(T94(R1,J),24,3) TO D2
20480 CONVERT (D2+INT(C2+.5))TO STR(T94(R1,J),24,3),PIC(###)
20490 JMP6601:T5(R1+1)=T5(R1+1)+DLT
20500 GOTO JMP3065
20510 JMP3064:T5(R1+1)=T5(R1+1)+T5(R1)
20520 JMP3065:NEXT R1
20530 T6(8)=T5(8)
20540 RETURN
```

```
20560 ***************************************************************
20570 *                                                            *
20580 *      #67 - THIS SUBROUTINE RESETS ALL VARIABLES AND        *
20590 *             VARIABLE ARRAYS IN PREPARATION FOR A NEW       *
20600 *             ITERATION.                                     *
20610 *                                                            *
20620 ***************************************************************
20630 DEFFN' 67
20640 MAT D8 = ZER
20650 FOR P = 1 TO 7
20660 FOR Q = 1 TO 4
20670 D0(P,Q) = Q4(P,Q)
20680 NEXT Q
20690 NEXT P
20700 MAT Q37 = ZER
20710 FOR P = 1 TO 8
20720 OUTA(P) = 0
20730 NEXT P
20740 FOR Q = 1 TO 7
20750 FOR P = 1 TO 7
20760 I4(P,Q) = 0
20770 Q7(P,Q) = 0
20780 I40(P,Q) = 0
20790 FOR K = 1 TO 7
20800 IF STR(T9$(P,Q),3*K,3) = "NNN" THEN JMP899
20810 STR(T9$(P,Q),3*K,3) = "000"
20820 JMP899:NEXT K
20830 STR(T9$(P,Q),24,3) = "000"
20840 NEXT P
20850 NEXT Q
20860 Q74 = 0
20870 FOR P = 1 TO 20
20880 T5(P),T6(P),T7(P),T8(P),T15(P),T17(P),T18(P) = 0
20890 NEXT P
20900 RETURN
```

```
20920 RETURN
20930 ****************************************************************
20940 *                                                             *
20950 *        #85 - THIS SUBROUTINE IS USED TO DELETE THE          *
20960 *               WORKING FILES 'CAREER' AND 'SOURCE' TO        *
20970 *               RESET THE MODEL FOR GROUP SPECIFICATION       *
20980 *               WHEN USER SO REQUESTS.                        *
20990 *                                                             *
21000 ****************************************************************
21010 DEFFN' 85
21020 OPEN NODISPLAY #1,IO,FILE = "SOURCE",LIBRARY = "OFFREQ",   '
21030 VOLUME = "VOL555"
21040 OPEN NODISPLAY #2,IO,FILE = "CAREER",LIBRARY = "OFFREQ",   '
21050 VOLUME = "VOL555"
21060 FOR K = 1 TO 30
21070 READ #1,HOLD,EOD GOTO JMP8501
21080 DELETE #1
21090 JMP8501:READ #2,HOLD,EOD GOTO JMP8502
21100 DELETE #2
21110 NEXT K
21120 JMP8502:CLOSE #1
21130 CLOSE #2
21140 RETURN
```

Basic Cross Reference

Float Variable (Static)	A	5420	7840	10780	10840	10560	10540	10760	10580	10600	10600	10640	10710	10740	10760	10450
		16540	16540	16640	16660	16600	16640	16640	16640	16640	16620	16720	16720	16770	16730	17310
		17330														
String Variable (Common)	A$(8)	550	7480	7310	7310	7380	4540	4550	4850	4550	4550	5450	6380
		6440	6670	6710	6760	6630	6630	17710	17710	12780
Float Array (Common)	A1(15,12)															
	580	9100	5400	5400	5410	5760	5710	5760	5970	5910	6070	6070	6680	6780	6700	6710
	6740	6740	8440	3540	3540	9440	9570	9570	9410	9410	10040	10080	10080	10010	10070	10070
	10080	10080	10080	10440	10460	10810	10810	10870	11140	11140	15180	15180	15180	15280
	15430	15230	15240	15280	15780	15400	15410	15410	16420	16430	16430	16490	16500
	16440	16570	16600	16700	16580	16530	16520	16520	16550	16560	16540	16540	16640
	16700	16780	16710	16710	16730	16780	16740	16740	16770	16770	20760
String Variable (Static)	A2$,10	5400	5400													
String Variable (Static)	A3$,10	5390	5640													
Float Array (Static)	A50(7)	630	2770	7820	10190											
Float Variable (Common)	ACC1	530	15200	15280												
Float Array (Static)	AUX(15,6)	620	3100	10440	10410	10460	10480									
Float Variable (Static)	B	7880	8120	10410	10410	10410	10480	10480	10480							
String Variable (Static)	D$,70	570	19770													
Float Variable (Static)	B3$	2790	2810	2810	2840	2840	10190	10180	10210							
String Variable (Static)	BGROUP$,70	650	8280	8080	9070	9170	8780	8780	8780							
Float Variable (Static)	C	7880	8540	11700	11470	11440	11680	11640	11440	11540	11540	11600	11730
	17230	17030	17710	17710	17710	17690	17690	17880	18180	18160	18710	18840
	19440	20180	20680	20460	20460	20460									
String Variable (Common)	C$,70	570	14940	14940	14740	14740	14240	14440	14440	14940	14840
	14700	14710	14720	14730	14760	14820	14770	14740	14720	14770	15210

Basic Cross Reference

Float Variable
(Static)
C2
11340 11640 11760 11790 11790 ... ... 14590 12170 16760 16780 17630
17880 17680 17670 17780 ... ... 17680 18210

Float Variable
(Static)
C3
20090 20140 20730 20740 20740 20410

Float Variable
(Static)
C5
10370 10990 11000 11000 18940 18940 18320

String Variable
(Static)
CDM$ (4)
650 5690 6070 6790 3270

String Variable
(Static)
CDM1$ 30
660 5390 5410

Float Variable
(Common)
D
7B90 81970

String Variable
(Common)
D$ B
540

Float Array
(Common)
DO(7,4)
550
11130 10390 10470 10470 10490 10570 10570 10770 10580 10610 10630 10830 10740
11170 11150 11160 11160 11170 11170 11180 11190 11200 11300 11400 11400 11200
11590 11710 13710 11720 11730 11730 11840 11730 11950 11950 16240 17580 17730
16450 16840 17930 17930 18140 18220 18220 18220 18400 18400 18720 20780 18450
18450 18460 18550 18540 18940 20980 20980

Float Variable
(Static)
D2
36330 56490 56470 7890 78130 81770 9750 10880 10770 10780 10830
14410 14450 14450 14480 14870 14870 14870 14260
18520 18580 18540 20470 20580

Float Variable
(Static)
D$5
14490 14570 14890

Float Array
(Static)
D3
11420 11640 11640 11560 11540 11540

Float Array
(Common)
DB(8)
560 11010 11230 11740 11790 11790

Float Array
(Static)
DK()
11130 11740 11950 14880

Float Array
(Common)
D3(4)
440

Float Variable
(Static)
DLT
11070 11090 11990 11920 11920 13980 17100 18910

Float Variable
(Static)
l
10790 10790 10790 10970

Basic Cross Reference

Name / Type												

String Variable C$ 170
(Common)   780

String Variable FM$ 40
(Static)   600

Float Array   FA1(5)
(Static)   640

Label   FILECHR
                 2030

Label   FILEFORM
                 2510

Float Array   GO(15,17)
(Static)   610

String Variable G4$ 7
(Static)   640

String Variable G5$ 1
(Static)   640

String Variable GROUP$ 30
(Static)   650

Float Variable   H
(Static)   16950

Float Variable   I
(Static)

String Variable I$ 5
(Static)

B-54

33

END
DATE
FILMED

11-83

DTIC

MICROCOPY RESOLUTION TEST CHART

NATIONAL BUREAU OF STANDARDS-1963-A

Basic Cross-Reference

Float Variable
(Static)   I0

Float Variable
(Static)   I1

Float Variable
(Static)   I2

Float Variable
(Static)   I3

Float Variable
(Static)   I4

Float Array
(Common)   I4(7,7)

Float Array
(Static)   I40(7,7)

Float Array
(Static)   I41(7,7)

Float Array
(Static)   I42(7,7)

Float Variable
(Static)   I5

Float Variable
(Static)   I6

Float Variable
(Static)   IIN

Float Array
(Common)   INVT(3,31)

Float Array
(Static)   INVTO(31)

Float Variable
(Static)   J

B-55

Basic Cross-Reference

Label

Label

Label

Label

Label

Label

Label

Label

Label

Label

Label

Label

Label

Label

Label

Basic Cross Reference

Label   JMP1742
     13180   13200   13800

Label   JMP1743
     13000   13120

Label   JMP1744
     12800   12840

Label   JMP1748
     12880   13070

Label   JMP1759
     12870   12880

Label   JMP1760
     12530   12300   12370

Label   JMP1761
     12680   13570   13420

Label   JMP1762
     12760   13090   13170   13290

Label   JMP1763
     12630   12930

Label   JMP1764
     12820   12830   12920

Label   JMP1765
     12760   13280

Label   JMP1766
     12910   06920

Label   JMP1767
     12760   12820

Label   JMP1768
     06900   13010   13100

Label   JMP1770
     13570   13080   06920   13300

Label   JMP1771
     12420   12900

Label   JMP1772
     12500   12910   12520

Label   JMP1773
     12930   13410

Label   JMP1774

Basic Cross-Reference

14040 14080

Label   JMP13% 14070 141(X)

Label   JMP140 4100 4480

Label   JMP1400 18830 13830 13800 13840
        13930

Label   JMP1401 13990 14020

Label   JMP1415 14130 14210

Label   JMP1416 14520 14270

Label   JMP1450 14440 14460

Label   JMP1470 16530 16590

Label   JMP1480 14500 14630

Label   JMP14B5 14690 14780

Label   JMP1490 14780 14830

Label   JMP150 4740 4770

Label   JMP1500 14910 14970

Label   JMP160 4740 4740 4740 4790

Label   JMP1600 14830 15030

Label   JMP1603 15290 15370

Label   JMP1610 15380 15430

Label   JMP1611 15210 15240

B-58

Basic Cross-Reference

Label   JMP10(30) 15600
         9930

Label   JMP1640   9880   15610
         9870

Label   JMP1650   15600
         15500

Label   JMP170   4760   4780   4800
         4760

Label   JMP180   4110   4470   4810   9470
         4110

Label   JMP190   5780   6110   6610   6830   7430   7850
         5130

Label   JMP21   17470
         17410

Label   JMP210   5360
         5350

Label   JMP22   17480
         17420

Label   JMP220   5120   5350   5370
         4960

Label   JMP23   17540
         17400

Label   JMP230   5380   5800
         5350

Label   JMP24   17580
         17530

Label   JMP240   5810   6130   6590
         5350

Label   JMP245   6600
         6420

Label   JMP25   17650
         17610

Label   JMP250   6160   6610   6670
         5350

Label   JMP26   17700
         17640

Basic Cross Reference

Label   JMP2360
         5350   (3C39)   (385O)

Label   JMP2270
         7460   77RO   7870

Label   JMP2280
         5350   6980   7RSO   78CO

Label   JMP2290
         7860   7870   RSSO

Label   JMP2300
         4090   8240   9150   9810

Label   JMP2303
         20220   20270

Label   JMP2304
         20140   20200   20210   20270   20300

Label   JMP2305,
         20500   20540

Label   JMP2310
         8630   R670

Label   JMP2320
         R460   R700

Label   JMP2330
         9010   9060

Label   JMP2340
         8206   8306

Label   JMP2350
         9000   9256

Label   JMP2360
         8010   8220   9200

Label   JMP2370
         9080   9110

Label   JMP2380
         B140   24880

Label   JMP2400
         9440   9270

Label   JMP2400
         9280   9270

Label   JMP2410

	B130	0000	10150
Label	JMP5150 16300	16600	
Label	JMP5151 16650	16760	
Label	JMP5152 16750	16790	
Label	JMP5161 16580	16700	
Label	JMP5162 16700	16720	
Label	JMP5163 16720	16750	
Label	JMP5192 16330	16430	
Label	JMP5193 16480	16540	
Label	JMP5194 16530	16580	
Label	JMP6010 18590	18660	
Label	JMP6011 18650	18680	
Label	JMP6180 19570	19580	19640
Label	JMP6601 20450	20490	
Label	JMP6602 20330 20340	20380	
Label	JMP6603 20330	20380	
Label	JMP7704 17880	17900	
Label	JMP7705 18010	18050	
Label	JMP7706 17980	18020	18080

Basic Cross Reference

Label

JMP707
1B190   1B190   1B470

Label

JMP708
1B200   1B310

Label

JMP709
1B450   1B570

Label

JMP710
1B160   1B180

Label

JMP711
17930   17950

Label

JMP713
17890   17940   1B170   1B710

Label

JMP753
18090   19100   19410

Label

JMP755
18940   18960   19060

Label

JMP761
19150   19200

Label

JMP762
19190   19220

Label

JMP763
05260   19350   19610

Label

JMP764
19270   19330   19370

Label

JMP765
19280   19330

Label

JMP766
19070   19400   19460

Label

JMP8501
21070   21090

Label

JMP8502
21090   21120

Label

JMP8509
20800   20820

Label

JMP9007
1,410   1,650

Basic Cross-Reference

Label															
JMP?XXB	13540														
Float Variable (Static) K	7380	7390	9460	10110	3470	3430	3440	3450	3460	9380	3180	3200	9250	3260	9270
	9380	10100	10110	10120	10180	20040	20080	13740	13750	13770	13840	15270	15280	15280	15280
	15350	15350	20730	20800	20810	20820	21110								
Float Variable (Static) K1	12630	12650	12680	12720	12770	12780	12740	12770	12740	12780	13210	13240	13780	13240	13300
	17640	17680	17680	17520	17560	17540	17560	17580	17620	17630	17630		17710		
Float Variable (Static) K2	12630	12660	12680	12730	12760	12770	12780	13310							
Float Variable (Static) K3	18430	18560	18560	18160	18220	18300	18340	18430	18440	18460					
Float Variable (Static) K4	18130	18150	18150	18220	18300	18340	18340	18430	18460	18560					
	18560	18570													
Float Variable (Static) K5	18130	18150	18150	18280	18400	18530	18570								
Float Variable (Static) KY	4060	4070	4080	4090	4100	4110									
Float Variable (Static) L	10850	10850	11070	11120	11120	11120	11170	17740	17370	17380	17410	17410	17450	17480	
	17500	17510	17740	17570	18070	18230	18350	18470	18580	18370	18900	13080	13110		
	13240	13260	13560												
Float Variable (Static) L1	9100	9240													
Float Variable (Static) L4	9420	9610													
Float Variable (Static) L5	12720	12780	12780	12830											
	13070	13080	13080												
Float Variable (Static) L6	8250	8240													
	13380	13380													
String Array (Common) LADII$(?)	550	7340													
	7720														
Float Variable (Static) M	3470	4460													

Basic Cross Reference

Type	Name											
String Variable (Static)	MM.C 660	9480	9530	9590	9980	10080						9090
Float Variable (Static)	MF, 4420 9000	4440	4450	4720	4730	4740	4750	4770	4790	8040	8070	9010	9070	9090
String Variable (Common)	MRRDLF\$ 590	9840	9880									
Float Variable (Static)	N 10660 12380 17580 13060 13510 13900 14180 20430	10660 12400 12800 13100 13640 17910 14210 20430	10680 12470 12840 13130 13670 17850 18700 20440	12700 12490 12580 13300 13670 17830 18700	12740 13640 12870 13510 13740 17940 18270	12780 13670 12870 13710 13740 17920 18270	12760 13670 12660 17860 13760 13730	12750 13670 12660 13000 13740 14830 13730	12730 13870 12670 13460 13800 14000 18410	12760 13670 13010 13670 13800 14010 18470	12760 13740 13070 13470 13810 14070 18520	12760 13740 13070 13470 13810 16780 18540	12770 13740 13040 13630 13830 16140 70440	12370 13740 13040 13430 13830 16140 70040	12570 13740 13040 13430 13830 16140 70130	12380 13570 13060 13600 13840 16170 70770
Float Array (Static)	NO(7) 610	9740	9810	9340	9840	10210	10180					
Float Variable (Static)	N1 12740	12700	12770	12770	12830	13440	13000	13060	13740	13760	13740	13340	13840
Float Variable (Static)	N2 12860	12960	13000	13010								
String Array (Static)	N\$(7,7) 640 7100 7230 7370	9550 7100 7240 7370	9580 7110 7250 7380	9580 7120 7260 7460	9580 7130 7280	9380 7140 7280	9380 7160 7300	7030 7160 7300	7030 7160 7310	7040 7170 7310	7070 7190 7320	7070 7180 7340	7070 7160 7340	7070 7200 7340	7080 7230 7340
Float Variable (Static)	ND 5710	5720	5720	6090	6100	6120	6310	6360	6540			
Float Variable (Static)	OAT 3690	9620	9550	10000	10330	10380	20080	20080				
Float Array (Static)	OTH(3,8) 610	3320	10080									
Float Array (Common)	OUTA(8) 590	12110	12110	14120	14120	15440	18570	18570	16670	18600	18600	18620	18630	18690	20720
Float Variable (Static)	P 9360 10480 16710 16430 16740 16700	9370 10480 16180 16430 16740 16780	9370 10480 16760 16470 16730 16710	9380 10480 16760 16480 16740 16710	9380 10480 16170 16480 16740 16700	9370 10610 16170 16430 16730 16700	9370 10670 16370 16480 16730 16700	9780 10910 16400 16630 16730 16700	10440 10650 16400 16630 16740 16730	10460 16470 16410 16630 16740 16700	10460 16410 16410 16630 16740 16700	10460 16410 16410 16530 16740 16700	10460 16410 16410 16540 16640 16700	10460 16410 16410 16540 16640 16700	10470 16100 16740 16740 16740 16900

Float Array (Common)	P0(10)													
Float Variable (Static)	P1													
String Array (Common)	P1$(9)													
Float Variable (Static)	P2													
String Array (Static)	P2$(10)													
Float Variable (Common)	P5													
Float Variable (Common)	P6													
Float Variable (Static)	P7													
Float Variable (Static)	P8													
Float Variable (Common)	P9													
String Array (Static)	POSIT$													
Float Variable (Static)	PR													
String Variable (Static)	PRD$													
Float Variable (Static)	PRD													
Float Variable (Common)	PRD4													

B-65

Basic Cross Reference

Float Variable (Common)	PROS
Float Variable (Static)	PROC
Label	PRICCARIG
Float Array (Common)	PTR(14)
Float Variable (Static)	Q
Float Variable (Common)	Q11
Float Variable (Static)	Q1
Float Variable (Static)	Q3
Float Array (Common)	Q37(8,4)
Float Array (Static)	Q38(7)
Float Array (Static)	Q4(7,4)
Float Variable (Static)	Q4
Float Variable (S)	Q4
Float Variable (Static)	Q
Float Variable	Q

Basic Cross-Reference

Label		Addresses
(Static)	1B1R0 1B46C0 1B8X60	1BC210 18R440 1BR480 ...
Float Array (Common)	Q7(7,7) 570 140R80	11R80 141C0 ...
Float Variable (Static)	Q71 135C0	140R0
Float Variable (Common)	Q74 600	37R0 19R580
Float Array (Common)	Q75(5) 600	37R0
Float Variable (Common)	Q76 600	17010 170C0
Float Array (Common)	Q79(5) 600	37R0
Float Variable (Static)	Q8 13B00 19040	17R110 19040
Float Array (Common)	Q85(5) 600	37R0
Float Array (Common)	Q89(5) 600	37R0
Float Variable (Static)	R 1B070 1B240 1B4R0 1B6C0 1B9R0	1B0R0 1B250 1B4R0 1B6C0 1B9R0 ...
Float Array (Common)	R0(30) 580 170C0	25R0 170R0
Float Variable (Common)	R01 2B00	25R0 100R0
Float Variable (Static)	R02 560	25R0 30R0 81R0
Float Variable (Static)	R03 2980	78R0 80R0 81R0
Float Variable (Static)	R04 2B00	7B80 80R0 81R0

B-67

Float Variable (Static)	R05	2300	7380	8050	8170	9340	10040	10280					
Float Variable (Static)	ROR	10970	10990	10990	11080	14480	14870						
Float Variable (Static)	R1	20130 20360 20470	20160 20360 20480	20170 20370 20430	20180 20370 20430	20200 20370 20410	20210 20380 20510	20230 20400 20520	20250 20400 20510	20270 20400 20510	20280 20420	20300 20430	20310 20440	20320 20440
Float Array (Static)	R2(7,7)	650	12210	12360	12360	13470							
String Variable (Static)	RDJTE$ 7	640 9400	4960	5110	5380	5810	7720	8140	6600	8320		7840	8170 8770
Float Variable (Static)	S	4830 9570	4830 9980	5530 9930	5960 10010	5970 10010	6020 10000	6030 10000	6040	6700	9530	9540	9560 9560
Float Variable (Static)	S1	4840 9550	4840 9550	5570 9570	5530 9570	5580 9980	5800 9980	5810 10000	6630 10000	6710 10010	6740 10010	9530 10010	9540 10030 9550
Float Array (Common)	S1(15,5)	560 9990 16370	3040 9990 16380	5470 9930 16600	5430 9930 20220	5510 10430 20520	5530 10430	5730 10430	5740 10440	5740 10440	5770 10460	9540 10480	9540 10370
Float Variable (Static)	S10	11790 18200	12240 18220	12250 18220	12260 18300	12270 18300	12340 18320	13430 18340	17740 18420	17780 18420	17820 18450	14180 18460	17810 18520 18130
Float Variable (Static)	S100	18850	18960	18970										
Float Variable (Static)	S11	20040	20040	20050	20100	20110	20280	20300	20310	20240	20450			
Float Variable (Static)	S12	20050	20050	20050	20080	20080	20080	20210	20340	20350	20460	20460	20460	20460
Float Variable (Static)	S2	14410	14830											
String Variable (Common)	T$ 5	550												
String Variable (Static)	T04.1C	13720	13730	13740	13740	13760	13800							
Float Variable	T1													

Basic Cross-Reference

Name	Type										
T10	Float Variable (Static)										
T10$(7,7)	String Array (Static)										
T11	Float Variable (Common)										
T11$(15)	String Array (Static)										
T12	Float Variable (Static)										
T13	Float Variable (Static)										
T14	Float Variable (Static)										
T15(20)	Float Array (Common)										
T17(20)	Float Array (Static)										
T1B(50)	Float Array (Static)										
T19(7)	Float Array (Static)										
T2	Float Variable (Static)										
T20	Float Variable (Static)										
T21(7)	Float Array (Static)										
T22(50)	Float Array (Static)										

Basic Cross Reference

Float Variable (Static)	T3
Float Variable (Static)	T4
Float Array (Common)	T5(20)
Float Variable (Static)	T50
Float Variable (Static)	T51
Float Array (Static)	T6(20)
Float Array (Static)	T7(20)
Float Array (Common)	T8(20)
String Array (Common)	T9$(7,7)
Float Array (Common)	TC0(7,5)
Float Variable (Static)	TD
String Variable (Static)	TGRUP$
Float Array (Common)	TL0(5,7)

The numeric data table is too degraded to read reliably.

Type	Name																	
Float Array (Common)	TOTA(8,3) 590	9830	15240	15380														
Float Array (Common)	TOTN(8,) 590	9830	15240	15360														
String Array (Common)	TRA$(7) 25 600	3420	5960	6700	6700													
String Array (Common)	TYPE$(14) 30 550	7790	3720	3730	4340	4840	4940	5170	7440	6170	6650	7420	7970	9530			
	9610	9930	13710	13800														
String Variable (Common)	X$ 70 590	15800	15810	15820	15830													
String Variable (Common)	X4$ 130 570			15340														
String Variable (Common)	X5$ 130 570																	
Float Variable (Static)	Y 16300 16300	16400	16420	16450	16500	16520	16540	16560	16570	16600	16680	16700	16710	16720	16730	16740	
String Variable (Common)	Z1$ 3 580	3490	5080	9500	9880	12410	12540	14220	14530	14030	14310						
String Variable (Static)	Z2$ 3 630	9530	9380														
String Variable (Static)	Z3$ 3 630	3490	5490	9530	9980	13880											
String Variable (Common)	Z4$ 3 580	3490	4940	5110	5720	5780	5810	6100	6110	6140	6630	6630					
	6830	6860	7780	7840	7860	8130	8470	8640	8670	9020	9040	14780	15080	15380			

B-71

```
10 SUB "OFFPRIN" (Y$,Y1)
20 ***********************************************************
30 *                                                         *
40 *      OFFPRIN - THIS EXTERNAL SUBROUTINE CONTAINS THE    *
50 *               SUMMARY CALCULATION AND PRINT ROUTINES    *
60 *               FOR THE OFFICER REQUIREMENTS MODEL.       *
70 *                                                         *
80 *                          (FILE OKIE11 LINKED TO OKIE12)*
90 ***********************************************************
100 COM DO(7,4),INVT(9,31),A$22,P5,P6,LABEL$(9)25,TYPE$(14)30,Q11,T$5
110 COM D$8,D8(8),S1(15,5),PO(10),RO2,D9(4),I4(7,7),T5(20),TP(20),T11
120 COM P1$(9)130,X4$130,X5$130,B$70,C$70,T1$(20),Q7(7,7),TC0(7,5),P9
130 COM A1(15,9),E$130,T9$(7,7)20,Z1$3,Z4$3,Q37(8,4),OUTA(8),R0(30)
140 COM X$70,PRO4,PRO5,ACC1,MGROUP$30,TOT(8,3),TOTA(8,3),TOTN(8,3)
150 COM PTR(14),TRA$(7)25,Q76,Q85(5),Q89(5),Q75(5),Q73(5),Q74
160 DIM DES$30,TDES$30,Y$130,Q9(7,7),F$70,T6(20),T7(20)
170 DIM Q77(5)
180 SELECT PRINTER
190 STR(D$,1,2) = STR(DATE,3,2)
200 STR(D$,3,1) = "/"
210 STR(D$,4,2) = STR(DATE,5,2)
220 STR(D$,6,1) = "/"
230 STR(D$,7,2) = STR(DATE,1,2)
240 STR(T$,1,2) = STR(TIME,1,2)
250 STR(T$,3,1) = ":"
260 STR(T$,4,2) = STR(TIME,3,2)
270 INIT(HEX(20))X4$                    /*    (#)    */
280 INIT(HEX(2A))X5$
290 INIT(HEX(20))B$
300 IF Y1 = 8 THEN JMP1407
310 IF Y1 = 9 THEN JMP1409
320 FOR Q = 1 TO 4
330 D9(Q) = 0
340 FOR P = 1 TO 7
350 D9(Q) = D9(Q) + DO(P,Q)
360 NEXT P
370 D9(Q) = (D8(Q) - D9(Q))/D8(Q)
380 NEXT Q
390 JMP501: INIT(HEX(20))P1$(1)
400 STR(P1$(1),1,10) = "WORKING ON"
410 STR(P1$(1),12,P5) = A$
420 STR(P1$(1),13+P5,2) = "IN"
430 STR(P1$(1),16+P5,P6) = TYPE$(Q11)
440 STR(P1$(1),17+P5+P6,9) = "COMMUNITY"
450 ACCEPT AT(5,P9),FAC(HEX(8C)),P1$(1),
460            AT(7,10),FAC(HEX(8C)),STR(Y$,1,40),AT(7,54),
470                 FAC(HEX(8C)),D$,AT(8,54),FAC(HEX(8C)),T$,
480            AT(10,20),"FRACTION OF FILL",
490            AT(11,15),"SENIOR COMMANDERS",AT(11,35),
500                 FAC(HEX(8C)),D9(4),PIC(##.###),
510            AT(12,15),"COMMANDERS",AT(12,35),FAC(HEX(8C)),
520                 D9(3),PIC(##.###),
530            AT(13,15),"LT. COMMANDERS",AT(13,35),FAC(HEX(8C)),
```

```
540                          D9(2),PIC(##.###),
550             AT(14,15),"LT. AND BELOW",AT(14,35),FAC(HEX(8C)),
560                          D9(1),PIC(##.###),
570             AT(15,15),"===========================",
580             AT(17,10),"ACCESSIONS",AT(17,39),FAC(HEX(8C)),
590                          INVT(R,31),PIC(###.##),
600             AT(18,10),"FIRST TOUR LENGTH",AT(18,39),
610             FAC(HEX(8C)),T11,PIC(###.##),
620             AT(20,10),"OUTPUT OPTIONS, PRESS PF KEY:",
630             AT(21,15),"1. NODE FLOWS",AT(21,32),"2. INVENTORY",
640                          AT(21,54),"3. REQUIREMENTS",
650             AT(22,15),"4. EXCESS FLOW",
660             AT(23,10),"FOR SCREEN PRINTS PRESS PF-11",
670             AT(24,10),"PRESS ENTER TO CONTINUE PROGRAM",
680 KEYS(BIN(0)&BIN(1)&BIN(2)&BIN(3)&BIN(4)&BIN(11)&BIN(12)),KEY(MG)
690 IF MG = 0 THEN END
700 ON MG GOTO JMP402,JMP403,JMP404,JMP405,,,,,,JMP5101,JMP5100
710 GOTO JMP501
720 JMP5101:GOSUB' 41(Y$)
730 GOTO JMP501
740 JMP5100:GOSUB' 47(Y$)
750 GOTO JMP501
760 JMP402:/*OUTPUT MATRIX I4*/
770 FOR P = 1 TO 7
780 INIT(HEX(20))P1$(P)
790 FOR R = 1 TO 7
800 CONVERT I4(P,R) TO STR(P1$(P),7*R-6,6),PIC(###.##)
810 NEXT R
820 NEXT P
830 ACCEPT AT(5,32),"NODE FLOW VALUES",
840          AT(7,34),"TOUR NUMBERS",
850          AT(9,8),"ACTIVITY",
860          AT(9,29),"ONE", AT(9,36),"TWO",AT(9,42),"THREE",
870          AT(9,49),"FOUR",AT(9,56),"FIVE",AT(9,64),"SIX",
880          AT(9,70),"SEVEN",
890          AT(11,2),FAC(HEX(8C)),LABEL$(1),AT(11,27),FAC(HEX(8C)),
900                  P1$(1),CH(49),
910          AT(12,2),FAC(HEX(8C)),LABEL$(2),AT(12,27),FAC(HEX(8C)),
920                  P1$(2),CH(49),
930          AT(13,2),FAC(HEX(8C)),LABEL$(3),AT(13,27),FAC(HEX(8C)),
940                  P1$(3),CH(49),
950          AT(14,2),FAC(HEX(8C)),LABEL$(4),AT(14,27),FAC(HEX(8C)),
960                  P1$(4),CH(49),
970          AT(15,2),FAC(HEX(8C)),LABEL$(5),AT(15,27),FAC(HEX(8C)),
980                  P1$(5),CH(49),
990          AT(16,2),FAC(HEX(8C)),LABEL$(6),AT(16,27),FAC(HEX(8C)),
1000                  P1$(6),CH(49),
1010         AT(17,2),FAC(HEX(8C)),LABEL$(7),AT(17,27),FAC(HEX(8C)),
1020                  P1$(7),CH(49),
1030         AT(19,5),"*****************************************
1040 ********************",
1050         AT(22,10),"PRESS ENTER TO RETURN TO OUTPUT MENU",
1060                  KEYS(BIN(0)&BIN(11)),ON (BIN(0)&BIN(11)) GOTO
```

```
1070                         JMP501,JMP5102
1080 JMP5102:GOSUB' 42(Y$)
1090 GOTO JMP501
1100 JMP403:/*OUTPUT SELECTED INVENTORY ENTRIES*/
1110 ACCEPT AT(5,32),"INVENTORY DISPLAY",                                    :
1120         AT(7,10),"SELECT FOUR YEARS FOR OUTPUT BETWEEN 1 AND 30",       :
1130         AT(10,15),"FIRST YEAR",AT(10,30),T15(1),                        :
1140                 PIC(##),                                                :
1150         AT(12,15),"SECOND YEAR",AT(12,30),T15(2),                       :
1160                 PIC(##),                                                :
1170         AT(14,15),"THIRD YEAR",AT(14,30),T15(3),                        :
1180                 PIC(##),                                                :
1190         AT(16,15),"FOURTH YEAR",AT(16,30),T15(4),                       :
1200                 PIC(##),                                                :
1210         AT(21,10),"PRESS PF2 TO RETURN TO OUTPUT MENU",                 :
1220         AT(23,10),"PRESS PF1 TO CONTINUE",                             :
1230 KEYS(BIN(0)&BIN(1)&BIN(2)&BIN(11)),ON(BIN(1)&BIN(2)&BIN(11)) GOTO      :
1240 JMP502,JMP501,JMP5103
1250 GOTO JMP502
1260 JMP5103:GOSUB' 43(Y$)
1270 GOTO JMP501
1280 JMP502:/*CREATE AND DISPLAY INVT SELECTION*/
1290 FOR P = 1 TO 9
1300 INIT(HEX(20))P1$(P)
1310 STR(P1$(P),1,24) = LABEL$(P)
1320 FOR R = 1 TO 4
1330 CONVERT INVT(P,T15(R)) TO STR(P1$(P),18+9*R,6),PIC(###.##)
1340 NEXT R
1350 NEXT P
1360 ACCEPT AT(3,32),"INVENTORY DISPLAY",                                    :
1370         AT(7,38),"YEARS",                                              :
1380         AT(8,16),"ACTIVITY",AT(8,38),FAC(HEX(8C)),T15(1),PIC(##),       :
1390         AT(8,47),FAC(HEX(8C)),T15(2),PIC(##),AT(8,56),FAC(HEX(8C)),     :
1400             ,T15(3),PIC(###),AT(8,65),FAC(HEX(8C)),T15(4),PIC(##),      :
1410         AT(10,8),FAC(HEX(8C)),P1$(1),                                   :
1420         AT(11,8),FAC(HEX(8C)),P1$(2),                                   :
1430         AT(12,8),FAC(HEX(8C)),P1$(3),                                   :
1440         AT(13,8),FAC(HEX(8C)),P1$(4),                                   :
1450         AT(14,8),FAC(HEX(8C)),P1$(5),                                   :
1460         AT(15,8),FAC(HEX(8C)),P1$(6),                                   :
1470         AT(16,8),FAC(HEX(8C)),P1$(7),                                   :
1480         AT(17,8),FAC(HEX(8C)),P1$(8),                                   :
1490         AT(19,5),"****************************************************  :
1500 ************************",                                             :
1510         AT(21,8),FAC(HEX(8C)),P1$(9),                                   :
1520         AT(23,5),"*****************************************************  :
1530 ***********************",                                              :
1540         AT(24,10),"PRESS ENTER TO RETURN TO OUTPUT MENU",               :
1550 KEYS(BIN(0)&BIN(11)),ON (BIN(0)&BIN(11)) GOTO JMP501,JMP5104
1560 JMP5104:GOSUB' 44(Y$)
1570 GOTO JMP501
1580 JMP404:/*DISPLAY REQUIREMENTS MATRIX*/
1590 FOR P = 1 TO 7
```

```
1600 INIT(HEX(20))P1$(P)
1610 STR(P1$(P),1,24) = LABEL$(P)
1620 FOR R = 1 TO 4
1630 CONVERT DO(P,R) TO STR(P1$(P),18+9*R,7),PIC(####.##)
1640 NEXT R
1650 NEXT P
1660 INIT(HEX(20))P1$(8)
1670 STR(P1$(8),1,24) = "LOWER GRADE FILLS"
1680 FOR R = 1 TO 3
1690 CONVERT Q37(8,R) TO STR(P1$(8),27+9*R,7),PIC(####.##)
1700 NEXT R
1710 ACCEPT AT(3,31),"REQUIREMENTS DISPLAY",
1720           AT(7,36),"CATEGORY",
1730           AT(8,16),"ACTIVITY",AT(8,37),"LT",AT(8,46),"LCDR",
1740           AT(8,55),"CDR",AT(8,64),"CDR+",
1750           AT(10,8),FAC(HEX(8C)),P1$(1),
1760           AT(11,8),FAC(HEX(8C)),P1$(2),
1770           AT(12,8),FAC(HEX(8C)),P1$(3),
1780           AT(13,8),FAC(HEX(8C)),P1$(4),
1790           AT(14,8),FAC(HEX(8C)),P1$(5),
1800           AT(15,8),FAC(HEX(8C)),P1$(6),
1810           AT(16,8),FAC(HEX(8C)),P1$(7),
1820           AT(18,5),"**********************************************
1830 *********************",
1840           AT(20,8),FAC(HEX(8C)),P1$(8),
1850           AT(22,5),"**********************************************
1860 *********************",
1870           AT(24,10),"PRESS ENTER TO RETURN TO OUTPUT MENU",
1880 KEYS(BIN(0)&BIN(11)), ON (BIN(0)&BIN(11)) GOTO JMP501,JMP5105
1890 JMP5105:GOSUB' 45(Y$)
1900 GOTO JMP501
1910 JMP405:/*DISPLAY ELAPSED TIME (Q7) */
1920 FOR P = 1 TO 8
1930 INIT(HEX(20))P1$(P)
1940 STR(P1$(P),1,24) = LABEL$(P)
1950 FOR R = 1 TO 7
1960 CONVERT ROUND(Q7(P,R),0) TO STR(P1$(P),21+6*R,5),PIC(###)
1970 NEXT R
1980 NEXT P
1990 STR(P1$(8),1,24) = "NON-AVIATION MAN-YEARS"
2000 FOR R = 1 TO 7
2010 CONVERT ROUND(OUTA(R),1) TO STR(P1$(8),21+6*R,5),PIC(###.#)
2020 NEXT R
2030 ACCEPT AT(3,28),"ELAPSED TIME (Q7) DISPLAY",
2040           AT(7,38),"TOUR",
2050           AT(8,16),"ACTIVITY",AT(8,37),"1",AT(8,43),"2",AT(8,49),
2060           "3",AT(8,55),"4",AT(8,61),"5",AT(8,67),"6",AT(8,73),"7",
2070           AT(10,8),FAC(HEX(8C)),P1$(1),
2080           AT(11,8),FAC(HEX(8C)),P1$(2),
2090           AT(12,8),FAC(HEX(8C)),P1$(3),
2100           AT(13,8),FAC(HEX(8C)),P1$(4),
2110           AT(14,8),FAC(HEX(8C)),P1$(5),
2120           AT(15,8),FAC(HEX(8C)),P1$(6),
```

```
2130        AT(16,8),FAC(HEX(8C)),P1$(7),
2140        AT(18,5),"**************************************************
2150 *********************",
2160        AT(20,8),FAC(HEX(8C)),P1$(8),
2170        AT(22,5),"**************************************************
2180 *********************",
2190        AT(24,10),"PRESS ENTER TO RETURN TO OUTPUT MENU",
2200 KEYS(BIN(0)&BIN(11)),ON (BIN(0)&BIN(11)) GOTO JMP50),JMP5100
2210 JMP5100:GOSUB' 46(Y$)
2220 GOTO JMP501
2230 RETURN
2240 /*                                    OPTION 8 */
2250 JMP1407:D3 = 0
2260 MAT T5 = ZER:MAT T8 = ZER
2270 FOR Q = 1 TO ROUND(PRO4/12-1,0)
2280 FOR P = 1 TO 7
2290 T8(1) = T8(1) + INVT(P,Q)
2300 NEXT P
2310 T8(1) = T8(1) + INVT(9,Q)
2320 NEXT Q
2330 FOR Q = ROUND(PRO4/12,0) TO ROUND(PRO5/12-1,0)
2340 FOR P = 1 TO 7
2350 T8(2) = T8(2) + INVT(P,Q)
2360 NEXT P
2370 T8(2) = T8(2) + INVT(9,Q)
2380 NEXT Q
2390 FOR Q = ROUND(PRO5/12,0) TO ROUND(PRO5/12+3,0)
2400 FOR P = 1 TO 7
2410 T8(3) = T8(3) + INVT(P,Q)
2420 NEXT P
2430 T8(3) = T8(3) + INVT(9,Q)
2440 NEXT Q
2450 FOR Q = ROUND(PRO5/12+4,0) TO 30
2460 FOR P = 1 TO 7
2470 T8(4) = T8(4) + INVT(P,Q)
2480 NEXT P
2490 T8(4) = T8(4) + INVT(9,Q)
2500 NEXT Q
2510 FOR Q = 1 TO 11
2520 FOR P = 1 TO 4
2530 T5(1) = T5(1) + INVT(P,Q)
2540 NEXT P
2550 FOR P = 5 TO 7
2560 T5(2) = T5(2) + INVT(P,Q)
2570 NEXT P
2580 T5(2) = T5(2) + INVT(9,Q)
2590 NEXT Q
2600 T8(5) = (11*T5(1))/(6*(T5(1)+T5(2)))
2610 FOR Q = 12 TO 18
2620 FOR P = 1 TO 4
2630 T5(1) = T5(1) + INVT(P,Q)
2640 NEXT P
2650 FOR P = 5 TO 7
```

```
2660 T5(2) = T5(2) + INVT(P,Q)
2670 NEXT P
2680 T5(2)=T5(2)+INVT(9,Q)
2690 NEXT Q
2700 T8(6) = (18*T5(1))/(11*(T5(1)+T5(2)))
2710 T8(7) = (18*T5(1))/(9*(T5(1)+T5(2)))
2720 GOSUB' R1(4)
2730 T8(8) = D3
2740 GOSUB' R1(5)
2750 T8(8) = T8(8) + D3
2760 GOSUB' R1(6)
2770 T8(9) = D3
2780 FOR P = 1 TO 4
2790 T8(P) = ROUND(TR(P),0)
2800 NEXT P
2810 FOR P = 5 TO 9
2820 T8(P) = ROUND(T8(P),2)
2830 NEXT P
2840 X45 = ROUND(INVT(8,31),0):X46 = ROUND(T11,0)
2850 IF Z4$ = "YES" THEN JMP 1412
2860 SELECT CRT
2870 D3 = T8(1)+T8(2)+T8(3)+T8(4)
2880 INIT(HEX(20))P1$(1)
2890 STR(P1$(1),1+P3,P5) = A$
2900 STR(P1$(1),3+P5+P3,2) = "IN"
2910 STR(P1$(1),6+P5+P3,P6) = TYPE$(Q1)
2920 STR(P1$(1),7+P5+P6+P3,9) = "COMMUNITY"
2930 ACCEPT AT(5,1),FAC(HEX(8C)),P1$(1),
2940             AT(7,10),FAC(HEX(8C)),STR(X$,1,40),AT(7,54),
2950                     FAC(HEX(8C)),D$,AT(8,54),FAC(HEX(8C)),T4,
2960         AT(9,10),"COMMUNITY POPULATION",AT(9,45),"FLEET OPPORTUNIT
2970 Y",
2980         AT(10,7),"GRADE",AT(10,16),"NUMBER",
2990         AT(11,5),"SENIOR CDR",AT(11,18),FAC(HEX(8C)),T8(1),
3000 PIC(####),
3010         AT(12,5),"JUNIOR CDR",AT(12,18),FAC(HEX(8C)),T8(2),
3020 PIC(####),AT(12,40),"COMMAND OPPORTUNITY",AT(12,62),FAC(HEX(8C)),
3030 T8(9),PIC(#.##),
3040         AT(13,5),"LT. CDR",AT(13,18),FAC(HEX(8C)),T8(3),PIC(####),
3050 AT(13,40),"DEPT HEAD OPPORTUNITY",AT(13,62),FAC(HEX(8C)),T8(8),
3060 PIC(#.##),
3070     AT(14,5),"LIEUTENANT",AT(14,18),FAC(HEX(8C)),T8(4),PIC(####),
3080         AT(16,5),"TOTAL",AT(16,18),FAC(HEX(8C)),D3,PIC(####),
3090         AT(17,5),"*****************************************
3100 *********************",
3110         AT(18,50),"ACIP PROJECTION",
3120         AT(19,5),"ACCESSIONS        ",AT(19,23),FAC(HEX(8C)),
3130         X45,PIC(####),AT(19,50),"GATE 1",AT(19,60),
3140         FAC(HEX(8C)),T8(5),PIC(#.##),
3150         AT(20,50),"GATE 2",AT(20,60),FAC(HEX(8C)),T8(6),PIC(#.##),
3160         AT(21,5),"FIRST TOUR LENGTH",AT(21,25),FAC(HEX(8C)),
3170         X46,PIC(##),AT(21,50),"GATE 3",AT(21,60),
3180          FAC(HEX(8C)),T8(7),PIC(#.##),
```

```
3190          AT(23,5),"DO YOU WISH TO CONTINUE IN PROCESS MONITORING?",
3200 AT(23,55),FAC(HEX(81)),Z1$,CH(3),AT(23,61)," (YES/NO)",
3210          AT(24,5),"PRESS ENTER TO CONTINUE",AT(24,35),"PRESS PF-1 T
3220 O SUPPRESS PRINT",KEYS(BIN(0)&BIN(1)),KEY(PR)
3230 JMP1412:IF PR=1 THEN END
3240 MAT Q9=ZER
3250 MAT T5=ZER
3260 FOR P = 1 TO 7
3270 FOR Q = 1 TO ROUND(PRO4/12-1,0)
3280 Q9(P,1) = Q9(P,1) + INVT(P,Q)
3290 Q9(P,5) = Q9(P,5) + INVT(P,Q)
3300 NEXT Q
3310 FOR Q = ROUND(PRO4/12,0) TO ROUND(PRO5/12-1,0)
3320 Q9(P,2) = Q9(P,2) + INVT(P,Q)
3330 Q9(P,5) = Q9(P,5) + INVT(P,Q)
3340 NEXT Q
3350 FOR Q = ROUND(PRO5/12,0) TO ROUND(PRO5/12+3,0)
3360 Q9(P,3) = Q9(P,3) + INVT(P,Q)
3370 Q9(P,5) = Q9(P,5) + INVT(P,Q)
3380 NEXT Q
3390 FOR Q = ROUND(PRO5/12+4,0) TO 30
3400 Q9(P,4) = Q9(P,4) + INVT(P,Q)
3410 Q9(P,5) = Q9(P,5) + INVT(P,Q)
3420 NEXT Q
3430 NEXT P
3440 FOR P = 1 TO 7
3450 FOR Q = 1 TO 7
3460 Q9(P,Q) = ROUND(Q9(P,Q),0)
3470 NEXT Q
3480 NEXT P
3490 FOR Q = 1 TO ROUND(PRO4/12-1,0)
3500 T5(1) = T5(1) + INVT(9,Q)
3510 T5(5) = T5(5) + INVT(9,Q)
3520 NEXT Q
3530 FOR Q = ROUND(PRO4/12,0) TO ROUND(PRO5/12-1,0)
3540 T5(2) = T5(2) + INVT(9,Q)
3550 T5(5) = T5(5) + INVT(9,Q)
3560 NEXT Q
3570 FOR Q = ROUND(PRO5/12,0) TO ROUND(PRO5/12+3,0)
3580 T5(3) = T5(3) + INVT(9,Q)
3590 T5(5) = T5(5) + INVT(9,Q)
3600 NEXT Q
3610 FOR Q = ROUND(PRO5/12+4,0) TO 30
3620 T5(4) = T5(4) + INVT(9,Q)
3630 T5(5) = T5(5) + INVT(9,Q)
3640 NEXT Q
3650 FOR P = 1 TO 5
3660 T5(P) = ROUND(T5(P),0)
3670 NEXT P
3680 D3 = T8(1) + T8(2) + T8(3) + T8(4)
3690 Q = LEN(TYPE$(Q11)):R = INT((25-Q)/2)
3700 STR(B$,R,Q) = TYPE$(Q11)
3710 STR(B$,R+Q+2,9) = "COMMUNITY"
```

```
3720 SELECT PRINTER
3730 PRINT PAGE
3740 PRINT SKIP(4)
3750 PRINT TAB(53),"SUMMARY DATA"
3760 PRINT SKIP(1),TAB(48),B1;
3770 IF Z4$="YES" THEN PRINT TAB(120),"GROUP ";STR(Y$,130,1)
3780 IF A$ = "NAVAL AVIATORS" THEN PRINT TAB(58),A$,TAB(120),D$ ELSE
3790   PRINT TAB(55),A$,TAB(120),D$
3800 PRINT TAB(120),T$
3810 PRINT SKIP(1),X5$
3820 PRINT SKIP(1)
3830 IF S1(Q11,1)>0 THEN JMP1420
3840 PRINT USING SHP20,"RETENTION",ROUND(RO2*100,0),"%","NO"
3850 PRINT USING SHP30,"COMMUNITY"
3860 PRINT USING SHP31,"PLOWBACK FRACTION",PO(1)*100,"%","PLANNING"
3870 PRINT USING SHP51,"FACTORS. "
3880 GOTO JMP1421
3890 JMP1420:PRINT USING SHP20,"RETENTION",ROUND(RO2*100,0),"%",
3900 "NUMBER OF SQUADRONS",S1(Q11,1)
3910 SHP20:FMT COL(10),CH(20),COL(32),PIC(##),COL(35),CH(1),COL(75),
3920 CH(25),COL(105),PIC(##)
3930 PRINT USING SHP30,"AIRCRAFT PER SQUADRON",S1(Q11,2)
3940 SHP30:FMT COL(74),CH(25),COL(105),PIC(##)
3950 PRINT USING SHP31,"PLOWBACK FRACTION",PO(1)*100,"%","CREW FACTOR"
3960 ,S1(Q11,3)
3970 SHP31:FMT COL(10),CH(20),COL(32),PIC(##),COL(35),CH(1),COL(74),
3980 CH(25),COL(100),PIC(#.##)
3990 INIT(HEX(20))F$
4000 STR(F$,1,LEN(A$)) = A$
4010 STR(F$,2+LEN(A$),8) = "PER CREW"
4020 IF A$ = "NAVAL AVIATORS" THEN S = 4 ELSE S = 5
4030 PRINT USING SHP51,F$,S1(Q11,S)
4040 SHP51:FMT COL(74),CH(30),COL(100),PIC(#.##)
4050 JMP1421:PRINT SKIP(1),X5$
4060 PRINT SKIP(2),TAB(57),"COMMUNITY POPULATION"
4070 PRINT SKIP(1)
4080 IF A$ = "NAVAL AVIATORS" THEN
4090         TDES$ = "ACCESSIONS TO TRAINING (132X)" ELSE
4100         TDES$ = "ACCESSIONS TO TRAINING (137X)"
4110 IF A$ = "NAVAL AVIATORS" THEN
4120         DES$ = "ACCESSIONS TO 131X DESIGNATOR" ELSE
4130         DES$ = "ACCESSIONS TO 132X DESIGNATOR"
4140 IF A$ = "NAVAL AVIATORS" THEN J1 = 1 ELSE J1 = 2
4150 ACC1 = (INVT(8,31))*TCO(A1(Q11,J1),1)
4160 PRINT USING SHP33,TDES$,ROUND(ACC1,0),"SENIOR COMMANDERS",T8(4)
4170 SHP33:FMT COL(10),CH(30),COL(42),PIC(####),COL(55),CH(18),COL(75)
4180 ,PIC(####)
4190 PRINT USING SHP34,"COMMANDERS",T8(3),"COMMAND OPPORTUNITY",T8(3)
4200 SHP34:FMT COL(55),CH(18),COL(75),PIC(####),COL(90),CH(23),COL(115
4210 ),PIC(#.##)
4220 PRINT USING SHP35,DES$,ROUND(INVT(8,31),0),"LT. COMMANDERS",T8(2)
4230 ,"DEPT HEAD OPPORTUNITY",T8(2)
4240 SHP35:FMT COL(10),CH(30),COL(42),PIC(####),COL(55),CH(18),COL(75)
```

```
4250 ,PIC(####),COL(90),CH(23),COL(115),PIC(#.##)
4260 PRINT USING SHP33,"FIRST TOUR LENGTH",X40,"LIEUTENANTS",T8(1)
4270 PRINT SKIP(1)
4280 PRINT USING SHP34,"        TOTALS",D3
4290 D3 = ROUND((T5(5)/D3)*100,0)
4300 PRINT SKIP(1),X5$
4310 PRINT SKIP(2),TAB(29),"DISTRIBUTION BY GRADE AND ACTIVITY"
4320 PRINT SKIP(1),TAB(21),"ACTIVITY                            GRADE"
4330 PRINT TAB(45),"LT      LCDR     CDR    SEN CDR   TOTAL
4340   ACIP PROJECTIONS"
4350 INIT(HEX(20))P1$()
4360 FOR P = 1 TO 7
4370 STR(P1$(P),14,25)=LABEL$(P)
4380 FOR Q = 1 TO 5
4390 CONVERT Q9(P,Q) TO STR(P1$(P),31+8*Q,8),PIC(########)
4400 NEXT Q
4410 NEXT P
4420 STR(P1$(8),14,25)=LABEL$(9)
4430 FOR Q = 1 TO 5
4440 CONVERT T5(Q) TO STR(P1$(8),31+8*Q,8),PIC(########)
4450 NEXT Q
4460 FOR P = 2 TO 4
4470 STR(P1$(P),94,4) = "GATE"
4480 CONVERT P-1 TO STR(P1$(P),100,1),PIC(#)
4490 CONVERT T8(P+3) TO STR(P1$(P),100,4),PIC(#.##)
4500 NEXT P
4510 STR(P1$(8),80,25) = "NON-AVIATION          %"
4520 CONVERT D3 TO STR(P1$(8),107,2),PIC(##)
4530 FOR P = 1 TO 8
4540 PRINT P1$(P)
4550 NEXT P
4560 IF A$ = "NAVAL AVIATORS" THEN MAT Q77 = Q85 ELSE MAT Q77 = Q22
4570 STR(P1$(9),14,25) = "LOWER GRADE FILLS"
4580 FOR P = 2 TO 3
4590 CONVERT ROUND(Q37(8,P),0) TO STR(P1$(9),31+8*P,8),PIC(########)
4600 Q77(P) = Q77(P)+ROUND(Q37(8,P),0)
4610 NEXT P
4620 T5(20) = ROUND(Q37(8,2)+Q37(8,3)+Q37(8,4),0)
4630 Q78 = 0
4640 IF Q37(8,2)/D8(2)>Q37(8,3)/D8(3) THEN Q78 = Q37(8,2)/D8(2) ELSE
4650     Q78 = Q37(8,3)/D8(3)
4660 IF Q78<Q37(8,4)/D8(4) THEN Q78 = Q37(8,4)/D8(4)
4670 IF ROUND(Q78,2) = 0 THEN JMP1400
4680 PRINT SKIP(1),TAB(14),STR(X4$,1,97)
4690 FOR P = 2 TO 4
4700 IF ROUND(Q78,2)=ROUND(Q37(8,P)/D8(P),2) THEN JMP1400
4710 NEXT P
4720 JMP1400:STR(P1$(9),80,25) = "HI UP DETAIL          %"
4730 IF P = 2 THEN GRA$ = "(LCDR)"
4740 IF P = 3 THEN GRA$ = "(CDR)"
4750 IF P = 4 THEN GRA$ = "(SR CDR)"
4760 STR(P1$(9),99,8) = STR(GRA$,1,8)
4770 CONVERT ROUND(Q78,2)*100 TO STR(P1$(9),108,2),PIC(##)
```

```
4780 PRINT P1$(9)
4790 IF A$="NAVAL AVIATORS" THEN MAT Q85 = Q77 ELSE MAT Q83 = Q77
4800 PRINT TAB(14),STR(X4$,1,97)
4810 JMP1408:FOR P = 1 TO 7
4820 FOR Q = 1 TO 7
4830 T5(17) = T5(17) + I4(P,Q)
4840 NEXT Q
4850 NEXT P
4860 T5(17) = T5(17)-Q74
4870 T5(15) = ACC1
4880 T5(16) = ACC1 - INVT(R,31)
4890 T5(18) = Q76
4900 IF A$ = "NAVAL FLIGHT OFFICERS" THEN JMP1410
4910 FOR P = 1 TO 4
4920 T5(14+P) = ROUND(T5(14+P),0)
4930 Q75(P) = Q75(P) + T5(14+P)
4940 Q75(5) = Q75(5) + T5(14+P)
4950 NEXT P
4960 GOTO JMP1411
4970 JMP1410:FOR P = 1 TO 4
4980 T5(14+P) = ROUND(T5(14+P),0)
4990 Q79(P) = Q79(P) + T5(14+P)
5000 Q79(5) = Q79(5) + T5(14+P)
5010 NEXT P
5020 JMP1411:INIT(HEX(20))P1$(1)
5030 STR(P1$(1),30,38) = "TOTAL ANNUAL PCS MOVES THIS COMMUNITY "
5040 CONVERT (T5(15)+T5(16)+T5(17)+T5(18)) TO STR(P1$(1),74,5),
5050   PIC(#####)
5060 PRINT SKIP(1),X5$
5070 PRINT SKIP(1),P1$(1)
5080 PRINT SKIP(1),X5$
5090 PRINT SKIP(1),TAB(1),STR(Y$,1,123)
5100 SELECT CRT
5110 END
5120 JMP1409:GOSUB' 58
5130 PRINT PAGE
5140 SELECT CRT
5150 END
5160 ************************************************************
5170 *                                                          *
5180 *       #81 - THIS SUBROUTINE COMPUTES FLEET ASSIGNMENT    *
5190 *             OPPORTUNITY GIVEN THE TOUR NUMBER J.  THE     *
5200 *             RESULT IS RETURNED TO OUTPUT PRINT ROUTINE    *
5210 *                                                          *
5220 ************************************************************
5230 DEFFN' 81(J)
5240 D3=0:MAT T6 = ZER:MAT T7 = ZER
5250 FOR N = 1 TO 7
5260 IF STR(T9$(1,J),3*N,3) = "NNN" THEN JMP8102
5270 CONVERT STR(T9$(1,J),3*N,3) TO T6(N)
5280 FOR I = 1 TO 7
5290 IF STR(T9$(I,J),3*N,3) = "NNN" THEN JMP8101
5300 CONVERT STR(T9$(I,J),3*N,3) TO T7(20)
```

```
5310 T7(N) = T7(N) + T7(20)
5320 JMP8101:NEXT I
5330 JMP8102:NEXT N
5340 FOR N = 1 TO 7
5350 IF T7(N) <= 0 THEN JMP8103
5360 T1 = Q7(N,J-1)
5370 T6(N) = (T6(N)/T7(N))*T4(N,J-1)
5380 T7(20) = INVT(8,31)
5390 FOR P = 1 TO INT((T1/12)+1)
5400 T7(20) = T7(20)*R0(P)
5410 NEXT P
5420 D3 = D3 + T6(N)/T7(20)
5430 JMP8103:NEXT N
5440 RETURN
```

```
5450 *****************************************************************
5460 *                                                              *
5470 *      #58 - THIS SUBROUTINE PRODUCES A SUMMARY PRINT          *
5480 *            FOR MULTIPLE COMMUNITY RUNS WHICH GIVES           *
5490 *            ACTIVITY/GRADE DISTRIBUTIONS AND AN               *
5500 *            ACCESSION SUMMARY.                                *
5510 *                                                              *
5520 *****************************************************************
5530 DEFFN' 58
5540 MAT T6 = ZER:MAT T7 = ZER
5550 FOR P = 1 TO 8
5560 FOR Q = 1 TO 3
5570 TOTA(P,Q) = ROUND(TOTA(P,Q),0)
5580 TOTN(P,Q) = ROUND(TOTN(P,Q),0)
5590 T7(P) = T7(P) + TOTA(P,Q)
5600 T7(P+8) = T7(P+8) + TOTN(P,Q)
5610 NEXT Q
5620 NEXT P
5630 FOR Q = 1 TO 3
5640 FOR P = 1 TO 8
5650 T6(Q) = T6(Q) + TOTA(P,Q)
5660 T6(Q+3) = T6(Q+3) + TOTN(P,Q)
5670 NEXT P
5680 NEXT Q
5690 FOR P = 1 TO 3
5700 PTR(P) = ROUND(PTR(P),0)
5710 PTR(P+7) = ROUND(PTR(P+7),0)
5720 T6(7) = T6(7) + PTR(P)
5730 T6(8) = T6(8) + PTR(P+7)
5740 NEXT P
5750 FOR P = 4 TO 7
5760 PTR(P) = ROUND(PTR(P),0)
5770 PTR(P+7) = ROUND(PTR(P+7),0)
5780 T6(9) = T6(9) + PTR(P)
5790 T6(10) = T6(10) + PTR(P+7)
5800 NEXT P
5810 SELECT PRINTER
5820 PRINT PAGE
5830 PRINT SKIP(4)
5840 PRINT TAB(55),"MULTIPLE RUN SUMMARY";
5850 PRINT TAB(100),D$
5860 PRINT TAB(100),T$
5870 A$ = "NAVAL AVIATORS":MAT TOT = TOTA:K1,K2 = 0:MAT Q77 = Q75
5880 FOR P = 1 TO 15
5890 IF STR(MGROUP$,P,1)<>"X" AND STR(BGROUP$,P,1)<>"0" THEN JMP5920
5900 NEXT P
5910 A$ = "NAVAL FLIGHT OFFICERS":MAT TOT=TOTN:K1=8:K2=3:MAT Q77 = Q72
5920 JMP5801:PRINT SKIP(1),TAB(58),A$
5930 PRINT SKIP(1),X5$
5940 PRINT SKIP(1),TAB(48),"DISTRIBUTION BY GRADE AND ACTIVITY"
5950 PRINT SKIP(1),TAB(38),"ACTIVITY                          GRADE"
5960 PRINT TAB(61),"LT    LCDR    CDR    TOTAL"
```

B-83

```
5970 FOR P = 1 TO 7
5980 PRINT USING SHP5801,LABEL$(P);
5990 FOR Q = 1 TO 3
6000 PRINT USING SHP5802,TOT(P,Q);
6010 NEXT Q
6020 PRINT USING SHP5803,T7(P+K1)
6030 NEXT P
6040 PRINT USING SHP5801,LABEL$(8);
6050 FOR Q = 1 TO 3
6060 PRINT USING SHP5802,TOT(8,Q);
6070 NEXT Q
6080 PRINT USING SHP5803,T7(8+K1);
6090 PRINT SKIP(0),TAB(58),"_____      _____    _____    _____"
6100 PRINT SKIP(1)
6110 PRINT TAB(30),"TOTALS";
6120 T7(17)=0
6130 FOR Q = 1 TO 3
6140 T7(17) = T7(17) + T6(Q+K2)
6150 PRINT USING SHP5802,T6(Q+K2);
6160 NEXT Q
6170 PRINT USING SHP5803,T7(17)
6180 PRINT SKIP(1),X5$
6190 PRINT SKIP(1),TAB(30),"TOTAL ANNUAL PCS MOVES ";
6200 PRINT USING SHP5803,Q77(5)
6210 PRINT SKIP(1),X5$
6220 PRINT SKIP(1)
6230 PRINT TAB(45),"ACCESSION REQUIREMENTS BY TRAINING PIPELINE"
6240 PRINT SKIP(2),TAB(63),"TO TRAINING      TO DESIGNATOR";
6250 IF A$ = "NAVAL AVIATORS" THEN PRINT " (PTR)" ELSE PRINT " (NFOTS)"
6260 IF A$ = "NAVAL AVIATORS" THEN L=0 ELSE L=3
6270 FOR P = 1 TO 3
6280 PRINT USING SHP5801,TRA$(P+L);
6290 PRINT USING SHP5804,PTR(P+L+7);
6300 PRINT USING SHP5805,PTR(P+L);
6310 IF P<3 THEN PRINT
6320 NEXT P
6330 IF L > 0 THEN PRINT ELSE JMP5800
6340 PRINT USING SHP5801,TRA$(7);
6350 PRINT USING SHP5804,PTR(14);
6360 PRINT USING SHP5805,PTR(7);
6370 T6(7) = T6(9):T6(8)=T6(10)
6380 JMP5800:PRINT SKIP(0),TAB(66),"_____",TAB(85),"_____"
6390 PRINT SKIP(1),TAB(30),"TOTALS";
6400 PRINT USING SHP5804,T6(8);
6410 PRINT USING SHP5805,T6(7)
6420 PRINT SKIP(1),X5$
6430 IF L = 3 THEN L = 15
6440 K = 0
6450 FOR P = 1 TO 14
6460 IF STR(MGROUP$,P+L,1)<>"X" AND STR(BGROUP$,P+L,1)<>"0" THEN
6470          JMP5808
6480 IF K>0 THEN JMP5808
6490 K=1
```

B-84

```
6500 PRINT SKIP(1),TAB(20),"NOTE- THE FOLLOWING SUBCOMMUNITIES ARE NOT"
6510 PRINT TAB(26),"INCLUDED IN THE RESULTS PRESENTED ABOVE:"
6520 PRINT SKIP(1)
6530 JMP5803:PRINT TAB(30),TYPE$(P)
6540 JMP5808:NEXT P
6550 IF K=0 THEN JMP5811
6560 PRINT SKIP(1),X5$
6570 JMP5811:PRINT TAB(70),Y$:IF L>0 THEN RETURN
6580 FOR P = 16 TO 30
6590 IF STR(MGROUP$,P,1)<>"X" AND STR(BGROUP$,P,1)<>"0" THEN JMP5810
6600 NEXT P
6610 RETURN
6620 JMP5810:A$="NAVAL FLIGHT OFFICERS":MAT TOT=TOTN:K1=8:K2=3
6630 MAT Q77 = Q79
6640 PRINT PAGE
6650 PRINT SKIP(4)
6660 PRINT TAB(55),"MULTIPLE RUN SUMMARY (CONT.)"
6670 GOTO JMP5801
6680 SHP5801:FMT COL(30),CH(25)
6690 SHP5802:FMT COL(55),PIC(#########)
6700 SHP5803:FMT COL(80),PIC(#########)
6710 SHP5804:FMT COL(63),PIC(#########)
6720 SHP5805:FMT COL(82),PIC(#########)
```

```
6740 ****************************************************************
6750 *                                                            *
6760 *       #41 - THIS SUBROUTINE CREATES A PRINT OF THE         *
6770 *             SUMMARY SCREEN FOR THE CURRENT RUN/ITERATION.  *
6780 *                                                            *
6790 ****************************************************************
6800 DEFFN' 41(Y$)
6810 SELECT PRINTER
6820 N$ = HEX(FF)
6830 D10=ROUND(INVT(R,31),2)
6840 P9 = INT((79-P5-P6-25)/2)
6850 PRINT PAGE
6860 PRINT X5$
6870 PRINT SKIP(4),COL(21+P9),P1$(1)
6880 PRINT USING SHP10,Y$,D$
6890 SHP10:FMT COL(30),CH(40),COL(80),CH(8)
6900 PRINT COL(80),T$
6910 PRINT SKIP(1),COL(41),"FRACTION OF FILL"
6920 PRINT USING SHP1,"SENIOR COMMANDERS",D9(4)
6930 PRINT USING SHP1,"COMMANDERS",D9(3)
6940 PRINT USING SHP1,"LT. COMMANDERS",D9(2)
6950 PRINT USING SHP1,"LT. AND BELOW",D9(1)
6960 SHP1:FMT COL(30),CH(19),COL(56),PIC(##.###)
6970 PRINT COL(30),"=========================="
6980 PRINT SKIP(1)
6990 PRINT USING SHP2,"ACCESSIONS",D10
7000 PRINT USING SHP2,"FIRST TOUR LENGTH",T1
7010 SHP2:FMT COL(31),CH(18),COL(60),PIC(###.##)
7020 PRINT SKIP(2),X5$
7030 SELECT CRT
7040 N$ = N$ XOR HEX(FF)
7050 RETURN
```

'OFFPRIN' SUBROUTINES

```
7070 ***********************************************************
7080 *                                                        *
7090 *      #42 - THIS SUBROUTINE PRODUCES A PRINT OF THE      *
7100 *             OUTPUT FLOW MATRIX I4 IN RESPONSE TO THE    *
7110 *             SPECIFICATION OF THE USER.                  *
7120 *                                                        *
7130 ***********************************************************
7140 DEFFN' 42(Y$)
7150 SELECT PRINTER
7160 IF N$ = HEX(00) THEN JMP5050
7170 PRINT PAGE
7180 PRINT X5$
7190 JMP5050:N$ = N$ XOR HEX(FF)
7200 FOR P =1 TO 7
7210 INIT(HEX(20))P1$(P)
7220 FOR R = 1 TO 7
7230 CONVERT I4(P,R) TO STR(P1$(P),7*R-6,6),PIC(###.##)
7240 NEXT R
7250 NEXT P
7260 PRINT SKIP(4),TAB(53),"NODE FLOW VALUES"
7270 PRINT SKIP(1),TAB(55),"TOUR NUMBERS"
7280 PRINT SKIP(1)
7290 PRINT USING SHP9, "ACTIVITY","ONE","TWO","THREE","FOUR","FIVE", !
7300 "SIX","SEVEN"
7310 SHP9:FMT COL(29),CH(8),COL(50),CH(3),COL(57),CH(3),COL(63),CH(5), !
7320 COL(70),CH(4),COL(77),CH(4),COL(85),CH(3),COL(91),CH(5)
7330 PRINT SKIP(1)
7340 SHP3:FMT COL(23),CH(24),COL(48),CH(49)
7350 FOR P=1 TO 7
7360 PRINT USING SHP3, LABEL$(P),P1$(P)
7370 NEXT P
7380 PRINT SKIP(1),TAB(20), "************************************* !
7390 *****************"
7400 PRINT SKIP(2),X5$
7410 SELECT CRT
7420 INIT(HEX(20))B$
7430 IF Y2 = 1 THEN SELECT PRINTER ELSE RETURN
7440 STR(B$,1,LEN(TYPE$(Q11))) = TYPE$(Q11)
7450 STR(B$,LEN(TYPE$(Q11))+2,9) = "COMMUNITY"
7460 IF N$ = HEX(00) THEN JMP5057
7470 PRINT PAGE
7480 PRINT X5$
7490 JMP5057:N$ = N$ XOR HEX(FF)
7500 PRINT SKIP(2),TAB(54),B$
7510 PRINT SKIP(1),TAB(58),"INVENTORY DISPLAY"
7520 PRINT SKIP(1),TAB(54),"YEARS OF AVIATION SERVICE"
7530 PRINT SKIP(1),TAB(10),"ACTIVITY",TAB(32),"1    2    3    4    5  !
7540   6    7    8    9   10   11   12   13   14   15   16   17   18  !
7550  19   20"
```

'OFFPRIN' SUBROUTINES

```
7560 PRINT SKIP(1),TAB(1),X4$
7570 FOR P = 1 TO 8
7580 PRINT USING FLOW10,LABEL$(P);
7590 FOR Q = 1 TO 19
7600 PRINT USING FLOW20, ROUND(INVT(P,Q),0);
7610 NEXT Q
7620 PRINT USING FLOW20, ROUND(INVT(P,20),0)
7630 NEXT P
7640 FLOW10:FMT COL(2),CH(25),XX(2)
7650 FLOW20:FMT COL(28),PIC(###.#)
7660 PRINT SKIP(1),TAB(1),X4$
7670 PRINT USING FLOW1,LABEL$(9);
7680 FLOW1:FMT COL(2),CH(25),XX(2)
7690 FLOW2:FMT COL(28),PIC(#####)
7700 FOR Q = 1 TO 19
7710 PRINT USING FLOW2, ROUND(INVT(9,Q),0);
7720 NEXT Q
7730 PRINT USING FLOW2,ROUND(INVT(9,20),0)
7740 PRINT TAB(1),X4$
7750 PRINT SKIP(2),X5$
7760 SELECT CRT
7770 RETURN
```

'DEFPRIN' SUBROUTINES

```
7790 ***********************************************************************
7800 *                                                                     *
7810 *         #43 - THIS SUBROUTINE PRINTS A COPY OF THE SELECTED        *
7820 *               INVENTORY ENTRIES FROM THE DISPLAY SECTION.          *
7830 *                                                                     *
7840 ***********************************************************************
7850 DEFFN' 43(Y9)
7860 SELECT PRINTER
7870 IF N$ = HEX(00) THEN JMP5051
7880 PRINT PAGE
7890 PRINT X5$
7900 JMP5051:N$ = N$ XOR HEX(FF)
7910 PRINT SKIP(4),COL(53),"INVENTORY DISPLAY"
7920 PRINT SKIP(1),COL(31),"SELECT FOUR YEARS FOR OUTPUT BETWEEN 1 AND
7930   30"
7940 PRINT SKIP(2)
7950 PRINT USING SHP4,"FIRST YEAR",T15(1)
7960 SHP4:FMT COL(30),CH(14),COL(51),PIC(##)
7970 PRINT SKIP(1)
7980 PRINT USING SHP4,"SECOND YEAR",T15(2)
7990 PRINT SKIP(1)
8000 PRINT USING SHP4,"THIRD YEAR",T15(3)
8010 PRINT SKIP(1)
8020 PRINT USING SHP4,"FOURTH YEAR",T15(4)
8030 PRINT SKIP(2),X5$
8040 SELECT CRT
8050 RETURN
```

```
8070 ***************************************************************
8080 *                                                            *
8090 *      #44 - THIS SUBROUTINE PRINTS THE SELECTED INVENTORY    *
8100 *            IDENTIFIED IN #43.                               *
8110 *                                                            *
8120 ***************************************************************
8130 DEFFN' 44(Y$)
8140 SELECT PRINTER
8150 FOR P = 1 TO 9
8160 INIT(HEX(20))P1$(P)
8170 STR(P1$(P),1,24) = LABEL$(P)
8180 FOR R = 1 TO 4
8190 CONVERT INVT(P,T15(R)) TO STR(P1$(P),18+9*R,6),PIC(### ##)
8200 NEXT R
8210 NEXT P
8220 IF N$ = HEX(00) THEN JMP5052
8230 PRINT PAGE
8240 PRINT X5$
8250 JMP5052:N$ = N$ XOR HEX(FF)
8260 PRINT SKIP(2),TAB(53),"INVENTORY DISPLAY"
8270 PRINT SKIP(3),TAB(59),"YEARS"
8280 PRINT USING SHP5,"ACTIVITY",T15(1),T15(2),T15(3),T15(4)
8290 SHP5:FMT COL(37),CH(10),COL(59),PIC(##),COL(68),PIC(##),COL(77),
8300 PIC(##),COL(86),PIC(##)
8310 PRINT SKIP(1),TAB(29),P1$(1)
8320 PRINT TAB(29),P1$(2)
8330 PRINT TAB(29),P1$(3)
8340 PRINT TAB(29),P1$(4)
8350 PRINT TAB(29),P1$(5)
8360 PRINT TAB(29),P1$(6)
8370 PRINT TAB(29),P1$(7)
8380 PRINT TAB(29),P1$(8)
8390 PRINT SKIP(1),TAB(20),"**********************************************
8400 *******************************"
8410 PRINT SKIP(1),TAB(29),P1$(9)
8420 PRINT SKIP(1),TAB(20),"**********************************************
8430 *******************************"
8440 PRINT SKIP(2),X5$
8450 SELECT CRT
8460 RETURN
```

```
8480 **********************************************************************
8490 *                                                                    *
8500 *        #45 - THIS SUBROUTINE PRINTS THE REQUIREMENTS               *
8510 *              MATRIX SHOWING THE REQUIREMENTS REMAINING             *
8520 *              TO BE FILLED.                                         *
8530 *                                                                    *
8540 **********************************************************************
8550 DEFFN' 45(Y$)
8560 SELECT PRINTER
8570 FOR P = 1 TO 7
8580 INIT(HEX(20))P1$(P)
8590 STR(P1$(P),1,24) = LABEL$(P)
8600 FOR R = 1 TO 4
8610 CONVERT DO(P,R) TO STR(P1$(P),18+9*R,7),PIC(#### ##)
8620 NEXT R
8630 NEXT P
8640 INIT(HEX(20))P1$(8)
8650 STR(P1$(8),1,24) = "LOWER GRADE FILLS"
8660 FOR R = 1 TO 3
8670 CONVERT Q37(8,R) TO STR(P1$(8),27+3*R,7),PIC(####.##)
8680 NEXT R
8690 IF N$ = HEX(00) THEN JMP5053
8700 PRINT PAGE
8710 PRINT X5$
8720 JMP5053:N$ = N$ XOR HEX(FF)
8730 PRINT SKIP(2),TAB(52),"REQUIREMENTS DISPLAY"
8740 PRINT SKIP(3),TAB(57),"CATEGORY"
8750 PRINT TAB(37),"ACTIVITY                LT     LCDP    CDP     CD!
8760 R+"
8770 PRINT SKIP(1),TAB(22),P1$(1)
8780 PRINT TAB(22),P1$(2)
8790 PRINT TAB(22),P1$(3)
8800 PRINT TAB(22),P1$(4)
8810 PRINT TAB(22),P1$(5)
8820 PRINT TAB(22),P1$(6)
8830 PRINT TAB(22),P1$(7)
8840 PRINT SKIP(1),TAB(20),"***********************************************
8850 ***********************"
8860 PRINT SKIP(1),TAB(22),P1$(8)
8870 PRINT SKIP(1),TAB(20),"***********************************************
8880 ***********************"
8890 PRINT SKIP(2),X5$
8900 SELECT CRT
8910 RETURN
```

```
8930 ***********************************************************
8940 *                                                         *
8950 *       #46 - THIS SUBROUTINE PRINTS THE VALUES IN THE    *
8960 *              ELAPSED TIME MATRIX Q7().                  *
8970 *                                                         *
8980 ***********************************************************
8990 DEFFN' 46(Y$)
9000 SELECT PRINTER
9010 FOR P = 1 TO 7
9020 INIT(HEX(20))P1$(P)
9030 STR(P1$(P),1,24) = LABEL$(P)
9040 FOR R = 1 TO 7
9050 CONVERT ROUND(Q7(P,R),0) TO STR(P1$(P),21+5*R,3),PIC(###)
9060 NEXT R
9070 NEXT P
9080 STR(P1$(8),1,24) = "NON-AVIATION MAN-YEARS"
9090 FOR R = 1 TO 7
9100 CONVERT ROUND(OUTA(R),0) TO STR(P1$(8),21+5*R,3),PIC(###)
9110 NEXT R
9120 IF N$ = HEX(00) THEN JMP5054
9130 PRINT PAGE
9140 PRINT X5$
9150 JMP5054:N$ = N$ XOR HEX(FF)
9160 PRINT SKIP(2),TAB(42),"ELAPSED TIME (Q7) DISPLAY"
9170 PRINT SKIP(3),TAB(72),"TOUR"
9180 PRINT TAB(37),"ACTIVITY          1    2    3    4    5    6
9190 7"
9200 PRINT SKIP(1),TAB(29),P1$(1)
9210 PRINT TAB(29),P1$(2)
9220 PRINT TAB(29),P1$(3)
9230 PRINT TAB(29),P1$(4)
9240 PRINT TAB(29),P1$(5)
9250 PRINT TAB(29),P1$(6)
9260 PRINT TAB(29),P1$(7)
9270 PRINT SKIP(1),TAB(26),"***********************************
9280 *****************"
9290 PRINT SKIP(1),TAB(29),P1$(8)
9300 PRINT SKIP(1),TAB(26),"***********************************
9310 *****************"
9320 PRINT SKIP(2),X5$
9330 SELECT CRT
9340 RETURN
```

```
9360 *********************************************************************
9370 *                                                                   *
9380 *       #47 - THIS SUBROUTINE PRINTS A COMPLETE SET OF              *
9390 *             PRINTS AS SPECIFIED IN #41-#46.   THE RESULT          *
9400 *             ARE LISTED IDENTICALLY TO THE INDIVIDUAL              *
9410 *             PRINTS AT TWO DISPLAYS PER PAGE.                       *
9420 *                                                                   *
9430 *********************************************************************
9440 DEFFN' 47(Y$)
9450 Y2 = 1
9460 GOSUB' 41(Y$)
9470 GOSUB' 42(Y$)
9480 GOSUB' 45(Y$)
9490 GOSUB' 46(Y$)
9500 Y2 = 0
9510 RETURN
```

Basic Cross Reference

Type	Variable												
String Variable (Common)	A$	62								4140	4560	4780	4900
		100	410	3580	3780	3780	4080	4110	4080				
		5810	5910	6940	6640								
Float Array (Common)	A1(15,9)	10	4150										
Float Variable (Common)	ACC1	140	4150	4160	4870	4880							
String Variable (Common)	B$	70											
		120	290	3700	3710	3760	7460	7440	7450	7500			
String Variable (Static)	BGROUP$ 16												
		5830	6460	6590									
String Variable (Common)	C$	70											
		120											
String Variable (Common)	D$ B												
		110	190	200	210	220	230	470	2250	3790	5880		
Float Array (Common)	DO(7,4)	100	350	1630	8610								
Float Variable (Static)	D10												
		6830	6990										
Float Variable (Static)	D3									4550	5740	5420	
		2250	2730	2750	2770	7870	8080	8080	4280	4280			
Float Array (Static)	DB(8)												
		110	370	370	4640	4640	4660	4700					
Float Array (Common)	D3(4)												
		110	330	350	370	370	100	540	560				
String Variable (Static)	DESC$ 30												
		160	4120	4130	4140								
String Variable (Common)	E$ 130												
		130											
String Variable (Static)	F$	70											
		160	3990	4000	4010	4010							
Label	FLOW1												
		7470	7680										

Basic Cross-Reference

Type	Name												
Label	FLOW10	7580	7640										
Label	FLOW?	7690	7710	7730									
Label	FLOW70	7600	7620	7650									
String Variable (Static)	GRAP 16	4730	4740	4750	4760								
Float Variable (Static)	I	5280	5290	5300	5320								
Float Array (Common)	I4(7,7)	110	800	4830	5370	7430							
Float Array (Common)	INVT(3,31)	100	590	1730	2280	2310	2370	2410	2430	2470	2490	2530	2570
		2680	2840	3280	3400	3420	3410	3440	3470	3510	3550	3580
		3620	3630	4150	4720	4880	4830	7600	7620	8100			
Float Variable (Static)	J	5230	5260	5225	5270	5800	5770						
Float Variable (Static)	J1	4140	4140	4150									
Label	JMP1406	4700	4720										
Label	JMP1407	300	2250										
Label	JMP1408	4670	4810										
Label	JMP1409	310	5120										
Label	JMP1410	4300	4970										
Label	JMP1411	4960	5020										
Label	JMP1412	2850	3230										

B-95

Basic Cross-Reference

Label   JMP1420   3830   3830
Label   JMP1421   3880   4050
Label   JMP402   700   760
Label   JMP403   700   1100
Label   JMP404   700   1580
Label   JMP405   700   1910
Label   JMP501   390   710   730
Label   JMP502   1240   1250   1280
Label   JMP5050   7160   7190
Label   JMP5051   7870   7900
Label   JMP5052   8220   8250
Label   JMP5053   8690   8720
Label   JMP5054   9120   9150
Label   JMP5057   7650   7490
Label   JMP5100   700   740
Label   JMP5101   700   720
Label   JMP5102   1070   1080

B-96

Basic Cross-Reference

Label	JMP5103	1240	1260		
Label	JMP5104	1550	1560		
Label	JMP5105	1830	1890		
Label	JMP5106	2200	2210		
Label	JMP5R01	5890	5920	6670	
Label	JMP5R0?	6330	6380		
Label	JMP5R0R	6470	6540		
Label	JMP5R09	6480	6530		
Label	JMP5R10	6590	6620		
Label	JMP5R11	6550	6570		
Label	JMP5B101	5290	5320		
Label	JMP5R10?	5860	5330		
Label	JMP5R103	5350	5430		
Float Variable (Static)	K	6440	6480	6490	6550
Float Variable (Static)	K1	5870	5910	6020	6080	6670
Float Variable (Static)	K2	5870	5910	6140	6150	6670
Float Variable	L				

Basic Cross-Reference

(Static)

String Array
(Common)   LABEL$(9)

Float Variable
(Static)   M$

String Variable
(Common)   MGRDIM$

Float Variable
(Static)   N

String Variable
(Static)   N$

Float Array
(Common)   OUTA(8)

Float Variable
(Static)   P

Float Array
(Common)   PO((0)

String Array
(Common)   P1$(9)

The numeric cross-reference columns are too faded and rotated to transcribe reliably.

B-98

		8370 8380	8380	8410	8580	8590	8610	8640	8660	8770	8780	8790	8800	8810	8820	8830
Float Variable (Common)	P5	100	410	420	430	440										
Float Variable (Common)	P6	100	430	440						6840						
Float Variable (Common)	P9	120	450	2890	2900	2910	6840		6870							
Float Variable (Static)	PR	3220	3230													
Float Variable (Common)	PRD4	140	2270	2330	3270	3710	3430	3510								
Float Variable (Common)	PRD5	140	2330	2390	2330	2450	3310	3390		3570	3570	3610				
Float Array (Common)	PTR(14) 150 6360	5700	5700	5710	5710	5720	5780	5760	5770	5770	5780	5790	6290	6300		
Float Variable (Static)	Q	320 2370 2630 3390 3570 4430 5650 6160														
Float Variable (Common)	Q11	100	430	2910	3690	3830	3900	3960	4040	4150		7440	7450		6670	
Float Array (Common)	Q37(8,4) 130	1690	4590	4600	4620	4620	4640	4640	4660	4660	4700	4700			
Float Array (Common)	Q7(7,7) 120	1960	5360	9050											
Float Variable (Common)	Q74	150	4860												
Float Array (Common)	Q75(5) 150	4930	4930	4340	4340	5870									

B-99

Basic Cross-Reference

Type	Name															
Float Variable (Common)	Q76	150	4890													
Float Array (Static)	Q77(5)	170	4560	4560	4600	4780	4780	4870	5010	5700	5670				
Float Variable (Static)	Q78	4630	4640	4650	4660	4670	4700	4770								
Float Array (Common)	Q79(5)	150	4990	4990	5000	5010	5910	6670								
Float Array (Common)	Q85(5)	150	4560	4790												
Float Array (Common)	Q89(5)	150	4560	4790												
Float Array (Static)	Q9(7,7)	160	3240	3280	3300	3320	3320	3330	3360	3370	3400				
		3410	3460	3460	4490											
Float Variable (Static)	R	790	800	800	1720	1730	1740	1740	1620	1630	1640	1650	1680	1690	1700
		1950	1960	1970	2000	2010	7020	7030	7030	7700	7720	7730	7740	7240	7240
		8190	8180	8200	8610	8670	8670	8670	8670	8670	9040	9060	9060	9060	9060
		9100	9110													
Float Array (Common)	R0(30)	130	5400													
Float Variable (Common)	R02	110	3840	3880												
Float Variable (Static)	S	4020	4020	4040												
Float Array (Common)	S1(15,5)	110	3830	3900	3900	3900	9240								
Label	SHP1	5920	5920	5940	6940	6950	6360								
Label	SHP10	6880	6880	6880												
Label	SHP2	6960	6960	7000	7010											
Label	SHP20															

B-100

Basic Cross-Reference

Label				
SHP3	7340	7360	7010	
SHP30	3850	3870	3940	
SHP31	3860	3950	3970	
SHP33	4160	4170	4350	
SHP34	4190	4200	4780	
SHP35	4270	4260		
SHP4	7950	7960	7980	8000	8040
SHP5	8280	8290		
SHP51	3870	4030	4040	
SHP5R01	5980	6040	6280	6780
SHP5R02	6000	6060	6150	6690
SHP5R03	6020	6080	6170	6200	6700
SHP5R04	6290	6370	6400	6710
SHP5R05	6300	6360	6410	6770
SHP9	7230	7310	7410	

String Variable (Common)   100   240   250   350   470   ...   3800   5800   6200

Basic Cross Reference

Type	Variable															
Float Variable (Static)	T1	5360	5790													
Float Variable (Common)	T11	110	610	7840	7000											
Float Array (Common)	T15(20)	120	1130	1150	1170									8160	8280	
Float Array (Common)	T5(20)	110	2260	2580												
Float Array (Static)	T6(20)	160	5240	5770	5770											
Float Array (Static)	T7(20)	160	5240	5300	5310											
Float Array (Common)	TB(20)	110	2260	2290	2290											
String Array (Common)	T9$(7,7)	130	5260	5270	5300											
Float Array (Common)	TC0(7,5)	120	4150													
String Variable (Static)	TDF$	160	4090	4100	4100											
Float Array (Common)	TDT(8,3)	140	5870	5910	6000											
Float Array (Common)	TDTA(8,2)	140	5570	5570	5520	5870										
Float Array (Common)	TDTN(8,2)	140	5580	5580	5600	5510										
String Array (Common)	TRA$(7)	160	6480	6540												

Basic Cross-Reference

Type	Name														
String Array (Common)	TYPE$(14)	30													
		100	470	2910	3690	7700	6530	7440	7440	7450					
String Variable (Common)	X$	70													
		140	2940												
String Variable (Common)	X4$	130													
		120	270	4680	4800	7560	7660	7740							
Float Variable (Static)	X45														
		2840	3170												
Float Variable (Static)	X46														
		2840	3170	4760											
String Variable (Common)	X5$	130													
		120	280	7810	4050	5060	5040	5080	5030	6180	6710	6450	6560	7020	7180	7400
		7480	7750	7890	8070	8440	8710	8820	7140						
String Variable (Parameter)	Y$	130													
		10	160	460	720	740	1080	1760	1560	1890	7210	3770	5030	6770	6800	6880	7140
		7850	8130	8550	8890	9440	9460	9460	9480						
Float Variable (Parameter)	Y1														
		10	300	310											
Float Variable (Static)	Y2														
		7430	9450	9500											
String Variable (Common)	Z1$														
		130	3200												
String Variable (Common)	Z4$														
		130	2850	3770											

B-103

APPENDIX C

DEFAULT VALUES FOR MODEL VARIABLES

This appendix provides tabulations of all parameters of the
Aviation Officer Requirements Model as they exist in the computer
data base when the program is first called up. These are the
default values to which the model is initially set. The operator
can change any or all of these values for a particular run.

TABLE C1

GRADE STRUCTURE FLEET SQUADRONS AND FLEET READINESS SQUADRON
(Grade Matrix GØ)

| Subcommunity | FLEET SQUADRON | | | | | | FLEET READINESS SQUADRON | | | | | |
| | Aviators | | | NFOs | | | Aviators | | | NFOs | | |
	05	04	03	05	04	03	05	04	03	05	04	03
Light Attack	2	4	11	0	0	0	8	23	85	0	0	0
Fighter	1	2	11	1	2	11	8	23	137	4	15	77
Medium Attack	1	2	13	1	2	13	2	5	44	2	6	31
Early Warning	1	2	7	1	2	12	2	6	34	2	5	33
Electronic Warfare	1	2	3	1	3	14	1	3	38	1	3	26
Carrier ASW	1	3	16	1	3	15	1	8	47	1	5	24
Helicopter ASW	2	4	14	0	0	0	4	17	57	0	0	0
Maritime Patrol	1	3	34	1	3	19	2	15	76	2	9	53
LAMPS MK I	2	4	14	0	0	0	4	17	51	0	0	0
LAMPS MK III	2	17	41	0	0	0	2	13	39	0	0	0
Electronic Warfare	0	0	0	0	0	0	0	0	0	0	0	0
Force Support Jet	0	0	0	0	0	0	0	0	0	0	0	0
Force Support Prop	0	0	0	0	0	0	0	0	0	0	0	0
Force Support Helo	1	3	1	0	0	0	0	0	0	0	0	0
Air Wing Staff	1	3	1	0	0	0	0	0	0	0	0	0

TABLE C2

SQUADRON STRUCTURE
(Squadron Matrix S1)

Subcommunity	Number of Squadrons	Aircraft Per Squadron	Crew Factor	Pilots Per Crew	NFOs Per Crew
Light Attack	24	12	1.42	1	0
Fighter	24	12	1.17	1	1
Medium Attack	12	14	1.14	1	1
Early Warning	12	3	1.66	2	3
Electronic Warfare	9	4	1.5	1	3
Carrier ASW	11	9	1.44	1.5	1.5
Helicopter ASW	11	6	1.66	2	0
Maritime Patrol	24	9	1.33	3	2
LAMPS MK I	6	11	2	2	0
LAMPS MK II	8	15	2	2	0
Electronic Warfare	0	0	0	0	0
Force Support Jet	0	0	0	0	0
Force Support Prop	0	0	0	0	0
Force Support Helo	0	0	0	0	0
Air Wing Staff	12	0	0	0	0

TABLE C3

PIPELINE IDENTIFICATION
Allocation Parameters
(Allocation Matrix-A1)

Subcommunity	Group Identifier Pilot Pipe	Group Identifier NFO Pipe	Pilots Fraction of All Pilots	Pilots Fraction of Community Pilots	Pilots Fraction of Carrier Pilots	NFOs Fraction of All NFOs	NFOs Fraction of Community NFOs	NFOs Fraction of Carrier NFOs	Fraction of All Aviation Officers
Light Attack	A	O	.1068	.2617	.2690	0	0	0	.0729
Fighter	A	D	.0838	.2053	.2110	.1797	1.0	.3101	.1142
Medium Attack	A	E	.0475	.1163	.1195	.1011	.3536	.1744	.0645
Early Warning	B	F	.0311	.0762	.0783	.0929	1.0	.1604	.0507
Electronic Warfare	A	E	.0197	.0483	.0496	.0965	.3375	.1665	.0441
Carrier ASW	A	E	.0508	.1245	.1279	.1092	1.0	.1885	.0694
Helicopter ASW	C	O	.0575	.1883	.1447	0	0	0	.0392
Maritime Patrol	B	G	.2210	.8737	0	.3047	.9170	0	.2476
LAMPS MK I	C	O	.0628	.2057	0	0	0	0	.0430
LAMPS MK III	C	O	.1141	.3741	0	0	0	0	.0780
Electronic Warfare	B	G	.0337	.0826	0	.0883	.3089	0	.0510
Force Support Jet	A	E	.1004	.0852	0	.0276	.0829	0	.0773
Force Support Prop	B	G	.1004	.1263	0	.0276	.0829	0	.0773
Force Support Helo	C	O	.0708	.2919	0	0	0	0	.0483
Air Wing Staff	O	O	.3972	0	1	.5794	0	1	.4550

Pipeline Key
A . Jet Aviator
  B . Prop Aviator
  C . Helo Aviator
  D . RIO NFO
  E . TN NFO
  F . ATDS NFO
  G . NAV NFO

O. Not incl

C-3

TABLE C4

SUPPLEMENTAL FLEET REQUIREMENTS
Grade Table
(Auxilliary Matrix-Aux)

Subcommunity	Pilots			NFOs		
	05	04	03	05	04	03
Light Attack	0	12	18	0	0	0
Fighter	0	6	6	0	4	8
Medium Attack	0	4	0	0	2	0
Early Warning	2	2	2	0	2	0
Electronic Warfare	2	4	21	1	5	29
Carrier ASW	0	0	0	0	0	0
Helicopter ASW	2	10	4	0	0	0
Maritime Patrol	0	56	6	0	17	27
LAMPS MK I	0	6	0	0	0	0
LAMPS MK III	0	0	0	0	0	0
Electronic Warfare	4	20	117	3	12	140
Force Support Jet	25	96	247	6	10	47
Force Support Prop	2	10	38	2	4	23
Force Support Helo	16	25	276	0	0	0
Air Wing Staff	0	0	0	0	0	0

TABLE C5

TRAINING COMMAND REQUIREMENTS
(Training Command Matrix-TCØ)

Pipeline	Input/Output Ratio	05	04	Instructor Planning Factors	
				Pilot	NFO
Jet Aviator	1.405	22	44	.860	0
Prop Aviator	1.291	7	14	.443	0
Helo Aviator	1.347	7	14	.542	0
RIO NFO	1.791	1	2	.180	.255
TN NFO	1.771	1	2	.118	.156
ATDS NFO	1.523	1	2	.070	.079
NAV NFO	1.426	1	2	.030	.088

TABLE C6

RDT&E AFLOAT AND OTHER REQUIREMENTS
(Matrix-OTH)

Activity	AVIATORS				NAVAL FLIGHT OFFICERS			
	Senior 05	05	04	03	Senior 05	05	04	03
RTD&E	26	26	120	189	5	6	31	75
AFLOAT	96	97	130	219	14	9	60	82
OTHER	289	28.	710	634	91	91	243	312

TABLE C-7A

NETWORK DESCRIPTION
ACTIVITY: FLEET SQUADRON TOURS

TOUR	TOUR LENGTH	PRECEDENT NODES						
		FLEET	FRS	TRACOM	RDT&E	ALFOAT	PRODEV	OTHER
1	36	OOO	NNN	NNN	NNN	NNN	NNN	NNN
2	36	NNN	NNN	OOO	NNN	NNN	NNN	NNN
3	36	NNN	OOO	OOO	OOO	NNN	OOO	OOO
4	36	NNN	OOO	OOO	OOO	OOO	OOO	OOO
5	36	NNN	OOO	OOO	OOO	OOO	OOO	OOO
6	24	OOO	OOO	OOO	OOO	OOO	OOO	OOO
7	12	OOO	OOO	OOO	OOO	OOO	OOO	OOO

NNN: PRECEDENT NODE IS BARRED

OOO: TRANSITION FROM PRECEDENT NODE IS PERMITTED

TABLE C-7B

NETWORK DESCRIPTION
ACTIVITY: FLEET READINESS SQUADRON

TOUR	TOUR LENGTH	PRECEDENT NODES						
		FLEET	FRS	TRACOM	RDT&E	ALFOAT	PRODEV	OTHER
1	OO	NNN	NNN	NNN	NNN	NNN	NNN	NNN
2	36	OOO	NNN	NNN	NNN	NNN	NNN	NNN
3	36	OOO	NNN	NNN	NNN	NNN	NNN	NNN
4	36	OOO	NNN	NNN	NNN	NNN	NNN	NNN
5	36	OOO	NNN	NNN	NNN	NNN	NNN	NNN
6	24	OOO	NNN	NNN	OOO	OOO	OOO	OOO
7	24	OOO	NNN	NNN	NNN	NNN	NNN	NNN

NNN: PRECEDENT NODE IS BARRED

OOO: TRANSITION FROM PRECEDENT NODE IS PERMITTED

TABLE C-7C

NETWORK DESCRIPTION
ACTIVITY: TRAINING COMMAND

TOUR	TOUR LENGTH	PRECEDENT NODES						
		FLEET	FRS	TRACOM	RDT&E	ALFOAT	PRODEV	OTHER
1	24	OOO	NNN	NNN	NNN	NNN	NNN	N...
2	36	OOO	NNN	NNN	NNN	NNN	NNN	NNN
3	36	NNN	NNN	NNN	NNN	NNN	OOO	OOO
4	36	OOO	NNN	NNN	NNN	OOO	OOO	OOO
5	36	OOO	NNN	NNN	NNN	OOO	OOO	OOO
6	24	OOO	OOO	OOO	OOO	OOO	OOO	OOO
7	36	NNN	NNN	OOO	OOO	OOO	OOO	OOO

NNN: PRECEDENT NODE IS BARRED

OOO: TRANSITION FROM PRECEDENT NODE IS BARRED

C-9

TABLE C-7D

NETWORK DESCRIPTION
ACTIVITY: RESEARCH AND DEVELOPMENT

TOUR	TOUR LENGTH	PRECEDENT NODES						
		FLEET	FRS	TRACOM	RDT&E	ALFOAT	PRODEV	OTHER
1	00	NNN	NNN	NNN	NNN	NNN	NNN	NNN
2	36	OOO	NNN	NNN	NNN	NNN	NNN	NNN
3	36	OOO	OOO	OOO	NNN	NNN	OOO	NNN
4	36	OOO	OOO	NNN	NNN	OOO	OOO	OOO
5	36	OOO	OOO	OOO	NNN	OOO	OOO	OOO
6	36	OOO	OOO	OOO	NNN	OOO	OOO	OOO
7	36	OOO	OOO	OOO	NNN	OOO	OOO	OOO

NNN: PRECEDENT NODE IS BARRED

OOO: TRANSITION FROM PRECEDENT NODE IS PERMITTED

TABLE C-7E

NETWORK DESCRIPTION
ACTIVITY: AFLOAT ASSIGNMENTS

TOUR	TOUR LENGTH	PRECEDENT NODES						
		FLEET	FRS	TRACOM	RDT&E	ALFOAT	PRODEV	OTHER
1	00	NNN	NNN	NNN	NNN	NNN	NNN	NNN
2	00	NNN	NNN	NNN	NNN	NNN	NNN	NNN
3	24	NNN	OOO	OOO	OOO	NNN	OOO	OOO
4	24	NNN	OOO	OOO	OOO	NNN	OOO	OOO
5	24	NNN	OOO	OOO	OOO	NNN	OOO	OOO
6	24	NNN	OOO	OOO	OOO	NNN	OOO	OOO
7	24	OOO	OOO	OOO	OOO	NNN	OOO	OOO

NNN: PRECEDENT NODE IS BARRED

OOO: TRANSITION FROM PRECEDENT NODE IS PERMITTED

C-11

TABLE C-7F

NETWORK DESCRIPTION
ACTIVITY: PROFESSIONAL DEVELOPMENT

TOUR	TOUR LENGTH	PRECEDENT NODES						
		FLEET	FRS	TRACOM	RDT&E	ALFOAT	PRODEV	OTHER
1	00	NNN	NNN	NNN	NNN	NNN	NNN	NNN
2	24	OOO	NNN	NNN	NNN	NNN	NNN	NNN
3	24	OOO	OOO	OOO	OOO	NNN	NNN	OOO
4	24	OOO	OOO	NNN	OOO	OOO	NNN	OOO
5	12	OOO	OOO	OOO	OOO	OOO	NNN	OOO
6	12	OOO	OOO	OOO	OOO	OOO	NNN	OOO
7	12	OOO	OOO	OOO	OOO	OOO	NNN	OOO

NNN: PRECEDENT NODE IS BARRED

OOO: TRANSITION FROM PRECEDENT NODE IS PERMITTED

C-12

TABLE C-7G

NETWORK DESCRIPTION
ACTIVITY: OTHER

TOUR	TOUR LENGTH	PRECEDENT NODES						
		FLEET	FRS	TRACOM	RDT&E	ALFOAT	PRODEV	OTHER
1	00	NNN	NNN	NNN	NNN	NNN	NNN	NNN
2	36	OOO	NNN	NNN	NNN	NNN	NNN	NNN
3	36	OOO	OOO	OOO	OOO	NNN	NNN	NNN
4	36	OOO	OOO	OOO	NNN	NNN	NNN	NNN
5	36	OOO	OOO	OOO	NNN	NNN	OOO	NNN
6	36	OOO	OOO	OOO	OOO	OOO	OOO	NNN
7	36	OOO	OOO	OOO	OOO	OOO	OOO	NNN

NNN: PRECEDENT NODE IS BARRED

OOO: TRANSITION FROM PRECEDENT NODE IS PERMITTED

Distribution List

(One copy to each addressee except as otherwise noted)

Director Technology Programs
Office of Naval Research (Code 200)
Arlington, VA 22217

Head, Research, Development, and
  Studies Branch
Office of the DCNO(MPT) (Op-115)
G836 Arlington Annex
Washington, D.C. 20350

Director Research Programs
Office of Naval Research (Code 400)
Arlington, VA 22217

Headquarters U.S. Marine Corps
Code MPI-20
Washington, D.C. 20380

Manager, Program in Manpower R&D
  (12 copies)
Office of Naval Research (Code 450)
Arlington, VA 22217

Program Administrator for Manpower,
  Personnel, and Training
678 Crystal Plaza #5
HQ, Naval Material Command (Code 08D22)
Washington, D.C. 20360

Defense Technical Information Center
  (12 copies)
DTIC/DDA-2
Cameron Station, Building 5
Alexandria, VA 22314

Director, Decision Support Systems
  Divisions
Naval Military Personnel Command (N-164)
1818 Arlington Annex
Washington, D.C. 20370

Commanding Officer
Naval Research Laboratory
Code 2627
Washington, D.C. 20375

Assistant for Evaluation, Analysis
  and MIC
Naval Military Personnel Command (N-6C)
4015 Wilson Boulevard
Arlington, VA 22203

Psychologist
Office of Naval Research Branch Office
Building 114, Section D
666 Summer Street
Boston, MA 02210

Technical Director (5 copies)
Navy Personnel R&D Center
San Diego, CA 92152

Head, Manpower, Personnel, Training
  and Reserve Team
Office of the CNO (Op-914D)
4A578, The Pentagon
Washington, D.C. 20350

Principal Civilian Advisor
  on Education and Training
Naval Education and Training Command
NAS Pensacola, FL 32508

Head, Long Range Manpower, Personnel
  and Training Planning Branch
Office of the DCNO(MPT) (Op-110)
1832 Arlington Annex
Washington, D.C. 20350

Department of Administrative Sciences
Naval Postgraduate School
Monterey, CA 93940
Attn: Dr. Richard S. Elster

Technical Director
U.S. Army Research Institute for the
  Behavioral and Social Sciences
5001 Eisenhower Avenue
Alexandria, VA 22333

Department of Operations Research
Naval Postgraduate School
Monterey, CA 93940
Attn: Dr. Kneale T. Marshall

Military Assistant for Training
    and Personnel Technology
Office of the Under Secretary of
    Defense for Research & Engineering
3D129, The Pentagon
Washington, D.C.   20301

Personnel Analysis Division
AF/MPXA
5C360, The Pentagon
Washington, D.C.   20330

Program Director
Manpower Research and Advisory Services
Smithsonian Institution
801 North Pitt Street
Alexandria, VA   22314

END

DATE
FILMED

11 – 83

DTIC